
	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 1(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

APPENDIX B: SAR DISTRIBUTION PLOTS FOR HEAD CONFIGURATION

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 2(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 6:07:56 PM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA800_low_chan_amb_temp_22.8_liq_temp_22.0C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 824.7 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 825$ MHz; $\sigma = 0.861$ mho/m; $\epsilon_r = 43.5$; $\rho = 1000$ kg/m³
Phantom section: Right Section


DASY4 Configuration:


- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.17 mW/g


Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 13.0 V/m; Power Drift = 0.025 dB
Peak SAR (extrapolated) = 1.44 W/kg
SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.758 mW/g

Maximum value of SAR (measured) = 1.14 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 3(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.14mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 4(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 6:22:27 PM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA800_mid_chan_amb_temp_22.9_liq_temp_22.1C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.52$ MHz; $\sigma = 0.856$ mho/m; $\epsilon_r = 43.6$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.886 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 11.6 V/m; Power Drift = -0.090 dB



Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.813 mW/g; SAR(10 g) = 0.581 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.849 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 5(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.849mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 6(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 6:40:42 PM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA800_high_chan_amb_temp_22.9_liq_temp_22.1C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 848.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 848.52$ MHz; $\sigma = 0.841$ mho/m; $\epsilon_r = 43.8$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.05 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 12.5 V/m; Power Drift = 0.204 dB


Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.975 mW/g; SAR(10 g) = 0.697 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.03 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 7(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.03mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 8(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 6:55:29 PM

Test Laboratory: RIM Testing Services

**RightHandSide_Tilt_CDMA800_mid_chan_amb_temp_22.9_liq_temp_22
.1C**

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.52$ MHz; $\sigma = 0.856$ mho/m; $\epsilon_r = 43.6$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.602 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 17.7 V/m; Power Drift = -0.027 dB


Peak SAR (extrapolated) = 0.696 W/kg

SAR(1 g) = 0.571 mW/g; SAR(10 g) = 0.433 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.596 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 9(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.596mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 10(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 7:17:48 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA800_low_chan_amb_temp_22.7_liq_temp_21.9C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E


Communication System: CDMA 800; Frequency: 824.7 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 825$ MHz; $\sigma = 0.861$ mho/m; $\epsilon_r = 43.5$; $\rho = 1000$ kg/m³
Phantom section: Left Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.21 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 13.7 V/m; Power Drift = -0.186 dB
Peak SAR (extrapolated) = 1.39 W/kg
SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.816 mW/g
Maximum value of SAR (measured) = 1.18 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 11(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.18mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 12(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 7:31:18 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA800_mid_chan_amb_temp_22.8_liq_temp_22.0C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.52$ MHz; $\sigma = 0.856$ mho/m; $\epsilon_r = 43.6$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.931 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 11.7 V/m; Power Drift = -0.142 dB


Peak SAR (extrapolated) = 1.08 W/kg

SAR(1 g) = 0.864 mW/g; SAR(10 g) = 0.632 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.902 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 13(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.902mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 14(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 7:44:26 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA800_high_chan_amb_temp_22.8_liq_temp_22.0C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 848.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 848.52$ MHz; $\sigma = 0.841$ mho/m; $\epsilon_r = 43.8$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.16 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 13.4 V/m; Power Drift = 0.034 dB


Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.797 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.16 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 15(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.16mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 16(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 7:59:06 PM

Test Laboratory: RIM Testing Services

LeftHandSide_Tilt_CDMA800_mid_chan_amb_temp_22.9_liq_temp_22.1C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 800; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.52$ MHz; $\sigma = 0.856$ mho/m; $\epsilon_r = 43.6$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.624 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 17.4 V/m; Power Drift = 0.103 dB


Peak SAR (extrapolated) = 0.707 W/kg

SAR(1 g) = 0.585 mW/g; SAR(10 g) = 0.449 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.610 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 17(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.610mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 18(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 4:02:45 PM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA1900_low_chan_amb_temp_23.2_liq_temp_21.4

C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1851.25$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.23 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 12.4 V/m; Power Drift = 0.107 dB


Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.602 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.17 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 19(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.17mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 20(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 10:52:27 AM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA1900_mid_chan_amb_temp_21.3_liq_temp_20.8

C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E


Communication System: CDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³
Phantom section: Right Section
Measurement Standard: DAS4 (High Precision Assessment)


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DAS4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.880 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 10.9 V/m; Power Drift = -0.111 dB
Peak SAR (extrapolated) = 1.12 W/kg
SAR(1 g) = 0.721 mW/g; SAR(10 g) = 0.403 mW/g
Maximum value of SAR (measured) = 0.796 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 21(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.796mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 22(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 1:27:29 AM

Test Laboratory: RIM Testing Services

RightHandSide_CDMA1900_high_chan_amb_temp_22.4_liq_temp_21.8

C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 1900; Frequency: 1908.5 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1908.5$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.962 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 11.5 V/m; Power Drift = -0.019 dB



Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.878 mW/g; SAR(10 g) = 0.498 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.966 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 23(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.966mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 24(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 2:28:59 AM

Test Laboratory: RIM Testing Services

RightHandSide_Tilt_CDMA1900_mid_chan_amb_temp_22.4_liq_temp_2 1.8C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E


Communication System: CDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³
Phantom section: Right Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Touch position -/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.332 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 15.3 V/m; Power Drift = -0.033 dB
Peak SAR (extrapolated) = 0.466 W/kg
SAR(1 g) = 0.290 mW/g; SAR(10 g) = 0.168 mW/g
Maximum value of SAR (measured) = 0.321 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 25(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.321mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 26(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 12:34:31 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA1900_low_chan_amb_temp_21.8_liq_temp_20.9C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1851.25$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.04 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 14.1 V/m; Power Drift = 0.071 dB


Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.937 mW/g; SAR(10 g) = 0.564 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.02 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 27(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 1.02mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 28(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 12:58:57 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA1900_mid_chan_amb_temp_22.1_liq_temp_21.9C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E


Communication System: CDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.44 \text{ mho/m}$; $\epsilon_r = 38.2$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section
Measurement Standard: DAS4 (High Precision Assessment)


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DAS4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Touch position -/Area Scan (51x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.592 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
 $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$
Reference Value = 11.3 V/m; Power Drift = -0.107 dB
Peak SAR (extrapolated) = 0.796 W/kg
SAR(1 g) = 0.531 mW/g; SAR(10 g) = 0.317 mW/g
Maximum value of SAR (measured) = 0.577 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 29(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.577mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 30(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 2:09:24 PM

Test Laboratory: RIM Testing Services

LeftHandSide_CDMA1900_high_chan_amb_temp_22.2_liq_temp_21.0C

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E

Communication System: CDMA 1900; Frequency: 1908.5 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1908.5$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DAS4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DAS4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.599 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 11.8 V/m; Power Drift = -0.339 dB


Peak SAR (extrapolated) = 0.762 W/kg

SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.310 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.557 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 31(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.557mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 32(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 2:34:37 PM

Test Laboratory: RIM Testing Services

**LeftHandSide_Tilt_CDMA1900_mid_chan_amb_temp_22.5_liq_temp_21
.2C**

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 324AD10E


Communication System: CDMA 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³
Phantom section: Left Section
Measurement Standard: DAS4 (High Precision Assessment)


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DAS4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


Touch position -/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.490 mW/g

Touch position -/Zoom Scan (5x5x7) (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 17.2 V/m; Power Drift = -0.341 dB
Peak SAR (extrapolated) = 0.704 W/kg
SAR(1 g) = 0.431 mW/g; SAR(10 g) = 0.241 mW/g
Maximum value of SAR (measured) = 0.477 mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 33(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 0.477mW/g

	Document Appendix B for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 34(34)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Z axis plots for the worst case head worn configuration:

