	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 1(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Annex A: Probe sensitivity and reference signal measurement plots




Figure A1: Probe calibration data for coil and probe




Figure A2: Reference voice 1 kHz signal and noise






Figure A3: Reference voice simulated signal and noise

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 4(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Annex B: Ambient noise and TMFS system validation data and plots

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 5(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 3:59:50 PM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_07_06_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W z (axial) 8 x 8 step 2/ABM Signal(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: 1 kHz Sine
Output Gain: 35
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: -0.0038487 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1 comp = -20.2 dB A/m
BWC Factor = -0.0038487 dB
Location: 0, 2, 3 mm



Document
Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW


Page
6(89)


Author Data
Daoud Attayi

Dates of Test
July 06-Aug 06, 2009

Report No
RTS-1689-0909-02

FCC ID
L6ARCN70UW



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 7(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 4:20:41 PM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_07_06_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Frequency response measurement/z (axial) at center unshielded/ABM

Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_multisine_50-5000_10s.wav

Output Gain: 87

Measure Window Start: 2000ms


Measure Window Length: 5000ms


BWC applied: 12.5 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

Diff = 1.95 dB
 BWC Factor = 12.5 dB
 Location: 0, 0, 3 mm



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 9(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 4:04:51 PM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_07_06_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W x

(longitudinal) 52 x 16 step 4/ABM Signal(x,y,z) (14x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine


Output Gain: 35

Measure Window Start: 0ms

Measure Window Length: 1000ms


BWC applied: -0.0038487 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 10(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1 comp = -25.4 dB A/m
 BWC Factor = -0.0038487 dB
 Location: -18, 0, 3 mm



0 dB = 0.054A/m

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 11(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 4:10:52 PM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_07_06_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W y

(transversal) 16 x 52 step 4/ABM Signal(x,y,z) (5x14x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine

Output Gain: 35

Measure Window Start: 0ms


Measure Window Length: 1000ms

BWC applied: -0.0038487 dB


Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1 comp = -25.7 dB A/m
BWC Factor = -0.0038487 dB
Location: 0, -18, 3 mm



0 dB = 1.00A/m

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 13(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 04/08/2009 9:39:06 AM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_08_04_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Background Noise 10 mm above Grid Reference/z (axial) noise/ABM

Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm


Signal Type: Off

Output Gain: 100

Measure Window Start: 2000ms

Measure Window Length: 5000ms

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 14(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM2 = -52.5 dB A/m
Location: 0, 0, 13 mm

Background Noise 10 mm above Grid Reference/z (axial) noise/ABM Noise Spectrum(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 100
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM = -52.5 dB A/m
Location: 0, 0, 13 mm

Background Noise 10 mm above Grid Reference/x (longitudinal) noise/ABM Noise Spectrum(x,y,z,f) (1x1x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 100
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


ABM = -52.6 dB A/m
Location: 0, 0, 13 mm


Background Noise 10 mm above Grid Reference/y (transversal) noise/ABM Noise Spectrum(x,y,z,f) (1x1x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 100
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0.000, 0.000, -6.30 mm




0 dB = 1.00A/m







	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 18(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 04/08/2009 9:41:54 AM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_08_04_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W z (axial) 8

x 8 step 2/ABM Signal(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine


Output Gain: 35

Measure Window Start: 0ms

Measure Window Length: 1000ms

BWC applied: -0.00306666 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 19(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1 comp = -20.3 dB A/m
 BWC Factor = -0.00306666 dB
 Location: 0, 0, 3 mm

Frequency response measurement/Multisine reference signal/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_multisine_50-5000_10s.wav
 Output Gain: 80
 Measure Window Start: 2000ms
 Measure Window Length: 5000ms
 Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


Diff = 1.97 dB
 Location: 0, 360, -262 mm

Frequency response measurement/z (axial) at center unshielded/ABM Freq Resp(x,y,z,f) (1x1x1):


Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_multisine_50-5000_10s.wav
 Output Gain: 87
 Measure Window Start: 2000ms
 Measure Window Length: 5000ms
 BWC applied: 12.5 dB
 Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

Diff = 1.96 dB
 BWC Factor = 12.5 dB
 Location: 0, 0, 3 mm



0 dB = 1.00A/m



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 22(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 04/08/2009 9:43:50 AM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_08_04_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W x

(longitudinal) 52 x 16 step 4/ABM Signal(x,y,z) (14x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine


Output Gain: 35

Measure Window Start: 0ms

Measure Window Length: 1000ms


BWC applied: -0.00306666 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 23(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1 comp = -25.5 dB A/m
 BWC Factor = -0.00306666 dB
 Location: -18, 0, 3 mm



0 dB = 1.00A/m

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 24(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 04/08/2009 9:50:00 AM

Test Laboratory: RTS

File Name: [TMFS_T_Coil_Validation_08_04_09.da4](#)

DUT: TMFS; Type: Sample ;

Program Name: HAC_Tcoil_ProbeCalibration

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

TMFS Validation Scan with 1kHz/500mVRMS signal level/W y

(transversal) 16 x 52 step 4/ABM Signal(x,y,z) (5x14x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine


Output Gain: 35

Measure Window Start: 0ms

Measure Window Length: 1000ms


BWC applied: -0.00306666 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 25(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:


ABM1 comp = -25.9 dB A/m
 BWC Factor = -0.00306666 dB
 Location: 0, -18, 3 mm



0 dB = 1.00A/m

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 26(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Annex C: Audio Band Magnetic measurement data and plots

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 27(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 8:15:11 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_low_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 28(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 46.6 dB
 ABM1 comp = 11.0 dB A/m
 BWC Factor = 0.15103 dB
 Location: -3, 10, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 29(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 8:46:04 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_low_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 30(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 21.2 dB
 ABM1 comp = 3.18 dB A/m
 BWC Factor = 0.15103 dB
 Location: -11, 13, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 31(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 8:50:23 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_low_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 32(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 43.3 dB
 ABM1 comp = -1.81 dB A/m
 BWC Factor = 0.15103 dB
 Location: -8, 5, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 33(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 8:56:33 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_mid_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 34(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 46.7 dB
 ABM1 comp = 11.1 dB A/m
 BWC Factor = 0.15103 dB
 Location: -3, 10, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 35(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 9:01:04 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_mid_ch.da4](#)

DUT: BlackBerry Smartphone; Type: Not Specified; Serial: Not Specified

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 36(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 21.5 dB
 ABM1 comp = 1.86 dB A/m
 BWC Factor = 0.15103 dB
 Location: -13, 13, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 37(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 9:05:12 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_mid_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 38(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 43.5 dB
 ABM1 comp = -1.79 dB A/m
 BWC Factor = 0.15103 dB
 Location: -8, 5, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 39(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 9:13:11 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_high_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 40(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 46.3 dB
 ABM1 comp = 11.0 dB A/m
 BWC Factor = 0.15103 dB
 Location: -3, 10, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 41(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 9:17:41 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_high_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 42(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 20.9 dB
 ABM1 comp = 1.81 dB A/m
 BWC Factor = 0.15103 dB
 Location: -13, 13, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 43(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 9:21:49 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM850_high_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.15103 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 44(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 43.4 dB
 ABM1 comp = -1.80 dB A/m
 BWC Factor = 0.15103 dB
 Location: -8, 5, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 45(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 07/07/2009 12:00:16 AM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_low_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 46(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 43.2 dB
 ABM1 comp = 8.39 dB A/m
 BWC Factor = 0.150005 dB
 Location: 0, 12, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 47(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 07/07/2009 12:04:48 AM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_low_ch.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 48(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 28.5 dB
 ABM1 comp = 4.85 dB A/m
 BWC Factor = 0.150005 dB
 Location: -8, 10, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 49(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 07/07/2009 12:08:59 AM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_low_ch.da4](#)

DUT: BlackBerry Smartphone

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 50(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 42.9 dB
 ABM1 comp = 7.17 dB A/m
 BWC Factor = 0.150005 dB
 Location: -5, -1, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 51(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:05:48 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_mid_ch_.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1/ABM2 = 42.7 dB
 ABM1 comp = 11.5 dB A/m
 BWC Factor = 0.150005 dB
 Location: 0, 10, 3.7 mm



Document
Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW


Page
52(89)

Author Data
Daoud Attayi


Dates of Test
July 06-Aug 06, 2009

Report No
RTS-1689-0909-02

FCC ID
L6ARCN70UW



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 53(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:10:18 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_mid_ch_.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 54(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 32.7 dB
 ABM1 comp = 4.91 dB A/m
 BWC Factor = 0.150005 dB
 Location: -10, 12, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 55(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:14:27 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_mid_ch_.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 56(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 50.0 dB
 ABM1 comp = 13.8 dB A/m
 BWC Factor = 0.150005 dB
 Location: -5, -3, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 57(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:22:17 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_high_ch_.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 58(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 43.2 dB
 ABM1 comp = 10.2 dB A/m
 BWC Factor = 0.150005 dB
 Location: 0, 12, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 59(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:26:49 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_high_ch_da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM SNR(x,y,z)

(5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 60(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 34.3 dB
 ABM1 comp = 6.83 dB A/m
 BWC Factor = 0.150005 dB
 Location: -8, 12, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 61(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 06/07/2009 11:30:59 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_GSM1900_high_ch_da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms


BWC applied: 0.150005 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 62(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Cursor:

ABM1/ABM2 = 50.0 dB
 ABM1 comp = 13.7 dB A/m
 BWC Factor = 0.150005 dB
 Location: -5, -3, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 63(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:43:04 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_low_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) 5.0mm 50 x 50/ABM SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 64(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

**General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


ABM1/ABM2 = 49.4 dB
ABM1 comp = 8.34 dB A/m
BWC Factor = 0.154017 dB
Location: -5, 12, 3.7 mm

**General Scans/z (axial) wideband at best S/N/ABM Freq
Resp(x,y,z,f) (1x1x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 69.2
Measure Window Start: 2000ms
Measure Window Length: 4000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

Diff = 2.00 dB
BWC Factor = 10.8 dB
Location: -5, 12, 3.7 mm



0 dB = 1.00



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 66(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:54:30 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_low_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 67(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02


General Scans/x (longitudinal) fine 2mm 8 x 8/ABM

SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1/ABM2 = 45.8 dB
ABM1 comp = 1.70 dB A/m
BWC Factor = 0.154017 dB
Location: 5, 13, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 68(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 2:07:43 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_low_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 69(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02


Location: -5, 0, 3.7 mm

**General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1/ABM2 = 48.0 dB
ABM1 comp = -0.875 dB A/m
BWC Factor = 0.154017 dB
Location: -3, 0, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 70(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:43:04 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_mid_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) 5.0mm 50 x 50/ABM SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 71(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

**General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


ABM1/ABM2 = 49.5 dB
ABM1 comp = 8.68 dB A/m
BWC Factor = 0.154017 dB
Location: -5, 10, 3.7 mm

**General Scans/z (axial) wideband at best S/N/ABM Freq
Resp(x,y,z,f) (1x1x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 69.2
Measure Window Start: 2000ms
Measure Window Length: 4000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

Diff = 2.00 dB
BWC Factor = 10.8 dB
Location: -5, 10, 3.7 mm



0 dB = 1.00



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 73(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:54:30 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_mid_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 74(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM

SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

ABM1/ABM2 = 46.0 dB


ABM1 comp = 1.83 dB A/m

BWC Factor = 0.154017 dB

Location: 7, 11, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 75(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 2:07:43 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_mid_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 76(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

**General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:

ABM1/ABM2 = 48.0 dB
ABM1 comp = -1.68 dB A/m
BWC Factor = 0.154017 dB
Location: -3, -2, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 77(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:43:04 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_high_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/z (axial) 5.0mm 50 x 50/ABM SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 78(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

**General Scans/z (axial) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


ABM1/ABM2 = 49.6 dB
ABM1 comp = 8.45 dB A/m
BWC Factor = 0.154017 dB
Location: -5, 12, 3.7 mm

**General Scans/z (axial) wideband at best S/N/ABM Freq
Resp(x,y,z,f) (1x1x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 69.2
Measure Window Start: 2000ms
Measure Window Length: 4000ms
BWC applied: 10.8 dB
Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

Diff = 2.00 dB
BWC Factor = 10.8 dB
Location: -5, 12, 3.7 mm



0 dB = 1.00



	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 80(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 1:54:30 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_high_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/x (longitudinal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 81(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

General Scans/x (longitudinal) fine 2mm 8 x 8/ABM

SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


Cursor:

ABM1/ABM2 = 45.9 dB


ABM1 comp = 1.80 dB A/m

BWC Factor = 0.154017 dB

Location: 7, 11, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 82(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Date/Time: 05/08/2009 2:07:43 PM

Test Laboratory: RTS

File Name: [HAC_TCoil_UMTS_band_IV_high_chan.da4](#)

DUT: BlackBerry Smartphone;

Program Name: HAC_TCoil_WD_Emission

Communication System: WCDMA FDD IV; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

DASY4 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 16/06/2009
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/03/2009
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

General Scans/y (transversal) 5.0mm 50 x 50/ABM SNR(x,y,z)

(11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.154017 dB

Device Reference Point: 0.000, 0.000, -6.30 mm


	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 83(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

**General Scans/y (transversal) fine 2mm 8 x 8/ABM SNR(x,y,z)
(5x5x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 0.154017 dB
Device Reference Point: 0.000, 0.000, -6.30 mm

Cursor:


ABM1/ABM2 = 47.9 dB
ABM1 comp = -1.74 dB A/m
BWC Factor = 0.154017 dB
Location: -3, -2, 3.7 mm



0 dB = 1.00

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 84(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Annex D: Probe certificate and equipment spec

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 85(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland






S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates
 Client **RIM**

Accreditation No.: **SCS 108**

Certificate No: **AM1DV3-3062_Jun09**

CALIBRATION CERTIFICATE																											
Object	AM1DV3 - SN: 3062																										
Calibration procedure(s)	QA CAL-24.v2 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range																										
Calibration date:	June 16, 2009																										
Condition of the calibrated item	In Tolerance																										
<p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p> <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Keithley Multimeter Type 2001</td> <td>SN: 0810278</td> <td>30-Sep-08 (No: 7670)</td> <td>Sep-09</td> </tr> <tr> <td>Reference Probe AM1DV3</td> <td>SN: 3000</td> <td>22-Oct-08 (No. AM1D-3000_Oct08)</td> <td>Oct-09</td> </tr> <tr> <td>DAE4</td> <td>SN: 781</td> <td>20-Feb-09 (No. DAE4-781_Feb09)</td> <td>Feb-10</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>AMCC</td> <td>1050</td> <td>15-Aug-08 (in house check Aug-08)</td> <td>Aug-09</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Keithley Multimeter Type 2001	SN: 0810278	30-Sep-08 (No: 7670)	Sep-09	Reference Probe AM1DV3	SN: 3000	22-Oct-08 (No. AM1D-3000_Oct08)	Oct-09	DAE4	SN: 781	20-Feb-09 (No. DAE4-781_Feb09)	Feb-10	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	AMCC	1050	15-Aug-08 (in house check Aug-08)	Aug-09
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																								
Keithley Multimeter Type 2001	SN: 0810278	30-Sep-08 (No: 7670)	Sep-09																								
Reference Probe AM1DV3	SN: 3000	22-Oct-08 (No. AM1D-3000_Oct08)	Oct-09																								
DAE4	SN: 781	20-Feb-09 (No. DAE4-781_Feb09)	Feb-10																								
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																								
AMCC	1050	15-Aug-08 (in house check Aug-08)	Aug-09																								
Calibrated by:	Name Mike Mehl	Function RF Technician	Signature 																								
Approved by:	Name Fin Bombolt	Function R&D Director	Signature 																								
			Issued: June 16, 2009																								
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.																											

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 86(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

References

- [1] ANSI C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] DASY4 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.


The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [2], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of Noise level
RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected.
Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- *Sensitivity:* With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 87(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

AM1D probe identification and configuration data


Item	AM1DV3 Audio Magnetic 1D Field Probe
Type No	SP AM1 001 BA
Serial No	3062

Overall length	296 mm
Tip diameter	6.0 mm (at the tip)
Sensor offset	3.0 mm (centre of sensor from tip)
Internal Amplifier	20 dB

Manufacturer / Origin	Schmid & Partner Engineering AG, Zürich, Switzerland
Manufacturing date	Oct-2008
Last calibration date	n/a

Calibration data

Connector rotation angle	(in DASY system)	61.1 °	+/- 3.6 ° (k=2)
Sensor angle	(in DASY system)	0.07 °	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	0.00741 V / (A/m)	+/- 2.2 % (k=2)

	Document		Page
	Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		88(89)
Author Data	Dates of Test	Report No	FCC ID
Daoud Attayi	July 06-Aug 06, 2009	RTS-1689-0909-02	L6ARCN70UW

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com

Certificate of conformity

Item	Audio Magnetic Calibration Coil AMCC
Type No	SD HAC P02 A
Series No	1001 ff.
Manufacturer / Origin	Schmid & Partner Engineering AG Zurich, Switzerland

Description of the item

The Audio Magnetic Calibration coil (AMCC) is a Helmholtz Coil designed according to standard [1], section D.9 for calibration of the AM1D probe. Two horizontal coils are positioned above a non-metallic base plate and generate a homogeneous magnetic field in the z direction (normal to it).

Configuration

The AMCC consists of two parallel coils of 20 turns with radius 143 mm connected in parallel in a distance of 143 mm. With this design, a current of 10 mA produces a field of 1 A/m. The DC input resistance at the input BNC socket is adjusted by a series resistor to a DC resistance of approximately 50 Ohm. The voltage required to produce a field of 1 A/m is consequently approx. 500 mV. To current through the coil is monitored via a shunt resistor of 10 Ohm +/- 1%. The voltage is available on a BNO socket with 100 mV corresponding to 1 A/m.

Handling of the item

The coil shall be positioned in a non-metallic environment to avoid distortion of the magnetic field.

Tests

Test	Requirement	Details	Units tested
Number of turns	N = 20 per coil	Resistance measurement	all
Orientation of coils	parallel coils with same direction of windings	Magnetic field variation in the AMCC axis	all
Coil radius	r = 143 mm	mechanical dimension	First article
Coil distance	d = 143 mm distance between coil centers	mechanical dimension	First article
Input resistance	51.7 +/- 2 Ohm	DC resistance at BNC input connector	all
Shunt resistance	R = 10.0 Ohm +/- 1 %	DC resistance at BNO output connector	all
Shunt sensitivity	Hc = 1 A/m per 100 mV according to formula $H_c = (U/R) * N / r / (1.25^{1.5})$	Field measurement compared with Narda ELT400 + BN2300/90.10	First article

Standards

[1] ANSI PC63.19-2006 Draft 3.12


Conformity

Based on the tests above, we certify that this item is in compliance with the requirements of [1].

Date 22.5.2006

Stamp / Signature

s p e a g
 Schmid & Partner Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com

	Document Annex A-C to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RCN71UW		Page 89(89)
	Author Data Daoud Attayi	Dates of Test July 06-Aug 06, 2009	Report No RTS-1689-0909-02

Specifications

Audio Magnetic Field Probe AM1D

The AM1D probe is an active probe with a single sensor according to [1] section D.8. It is fully RF shielded and has a rounded tip of 6 mm diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides.

SPEAG, the manufacturer of the T-Coil system tested the probe frequency response and its dynamic range. The compliance is stated in the Certificate of conformity document 880-SPAM1001A-A. Also the probe frequency has been verified and the response deviation from the ideal differentiator was within +0.05 and - 0.46 dB in the range 100 Hz to 10 kHz on the center frequencies of the third-octave bands. Note that it includes the probe preamplifier and also with the AMMI internal preamplifiers, filters and processing.

Dynamic range:

maximum + 21 dB A/m @ 1 kHz
 Noise level typically -70 dB A/m @ 1 kHz
 ABM2 typically -60 dB A/m

Linearity

Within < 0.1 dB from 5 dB
 below limitation to 16 dB above noise level

Sensitivity

Typically -24 dBV / A/m @ 1 kHz probe output

Audio Magnetic Measurement Instrument (AMMI)

sampling rate 48 kHz / 24 bit
 dynamic range 85 dB
 test signal generation user selectable and predefined (via PC)
 calibration auto-calibration / full system calibration using AMCC
 with monitor output
 dimensions 482 x 65 x 270 mm

Helmholtz Calibration Coil (AMCC)

dimensions 370 x 370 x 196 mm, according to ANSI-PC63.19
 The Audio Magnetic Calibration coil is a Helmholtz Coil designed according to [1], section D.9 for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction.

Shunt sensitivity $H_c = 1$ A/m per 100mV according to formula:

$$H_c = (U / R) * N / r / (1.25 ^ 1.5)$$

Number of turns $N = 20$ per coil
 Coil radius $r = 143$ mm
 Shunt resistance $R = 10.00$ Ohm