


| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 1(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Annex A: Probe sensitivity and reference signal measurement plots

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




Figure A1: Probe calibration data for coil and probe




Figure A2: Reference voice 1 kHz signal and noise

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW






Figure A3: Reference voice simulated signal and noise

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 4(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Annex B: TMFS system validation and ambient data/plots

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 5(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/9/2011 10:27:03 AM

Test Laboratory: RIM Testing Services

HAC T-Coil TMFS_validation

DUT: TMFS; Type: TMFS-1

Communication System: CW; Frequency: 835 MHz; Communication System

PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/Background Noise/z (axial) noise/ABM [HAC-2007] Noise

Spectrum(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm


Signal Type: Off

Output Gain: 0

Measure Window Start: 2000ms

Measure Window Length: 5000ms

Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 6(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM = -48.99 dB A/m
Location: 0, 0, 13 mm

**T-Coil scan/Background Noise/x (longitudinal) noise/ABM
[HAC-2007] Noise Spectrum(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 0
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -49.02 dB A/m
Location: 0, 0, 13 mm

**T-Coil scan/Background Noise/y (transversal) noise/ABM
[HAC-2007] Noise Spectrum(x,y,z,f) (1x1x1):**


Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 0
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -49.00 dB A/m
Location: 0, 0, 13 mm

**T-Coil scan/TMFS Validation/z (axial) 8 x 8 step 2/ABM
[HAC-2007] Interpolated Signal(x,y,z) (41x41x1):**

Measurement grid: dx=10mm, dy=10mm
Signal Type: 1 kHz Sine
Output Gain: 35.05
Measure Window Start: 0ms
Measure Window Length: 1000ms
BWC applied: -0.01 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 7(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1 = -20.63 dB A/m
 BWC Factor = -0.01 dB
 Location: -0.4, 0.8, 3.7 mm

T-Coil scan/TMFS Validation/x (longitudinal) 52 x 16 step 4/ABM [HAC-2007] Interpolated Signal(x,y,z) (131x41x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: 1 kHz Sine
 Output Gain: 35.05
 Measure Window Start: 0ms
 Measure Window Length: 1000ms
 BWC applied: -0.01 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = -26.02 dB A/m
 BWC Factor = -0.01 dB
 Location: -20.4, -0.4, 3.7 mm

T-Coil scan/TMFS Validation/y (transversal) 16 x 52 step 4/ABM [HAC-2007] Interpolated Signal(x,y,z) (41x131x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: 1 kHz Sine
 Output Gain: 35.05
 Measure Window Start: 0ms
 Measure Window Length: 1000ms
 BWC applied: -0.01 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 = -26.30 dB A/m
 BWC Factor = -0.01 dB
 Location: -0.8, -17.2, 3.7 mm

T-Coil scan/TMFS Validation/z (axial) at center 100% gain/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):



Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_multisine_50_10k_10s.wav
 Output Gain: 87.2
 Measure Window Start: 2000ms
 Measure Window Length: 5000ms
 BWC applied: 13.14 dB
 Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi

Dates of Test
**Mar. 18-21, 2011
April 04, 2011**

Report No
RTS-2605-1104-43B

FCC ID
**L6ARDH70CW
L6ARDQ70UW**





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW






Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 11(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 4/4/2011 3:06:55 PM

Test Laboratory: RIM Testing Services

TMFS_noise_04_04_11_validation

DUT: TMFS; Type: TMFS-1;

Communication System: CW; Communication System Band: D1800 (1800.0 MHz); Frequency: 1800 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV2 - 1016; ; Calibrated: 3/7/2011
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/TMFS Validation/z (axial) 8 x 8 step 2/ABM [HAC-2007]

Signal(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm

Signal Type: 1 kHz Sine

Output Gain: 35.05

Measure Window Start: 0ms

Measure Window Length: 1000ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 12(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

BWC applied: -0.00089 dB

Device Reference Point: 0, 0, -6.3 mm

ABM1 comp = -20.07 dB A/m
 BWC Factor = -0.00089 dB
 Location: 0, 2, 3.7 mm

T-Coil scan/TMFS Validation/x (longitudinal) 52 x 16 step 4/ABM [HAC-2007] Signal(x,y,z) (14x5x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: 1 kHz Sine
 Output Gain: 35.05
 Measure Window Start: 0ms
 Measure Window Length: 1000ms
 BWC applied: -0.00089 dB
 Device Reference Point: 0, 0, -6.3 mm



ABM1 comp = -25.11 dB A/m
 BWC Factor = -0.00089 dB
 Location: -18, 4, 3.7 mm


T-Coil scan/TMFS Validation/y (transversal) 16 x 52 step 4/ABM [HAC-2007] Signal(x,y,z) (5x14x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: 1 kHz Sine
 Output Gain: 35.05
 Measure Window Start: 0ms
 Measure Window Length: 1000ms
 BWC applied: -0.00089 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -25.97 dB A/m
 BWC Factor = -0.00089 dB
 Location: 0, -18, 3.7 mm



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 14(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 4/4/2011 3:00:01 PM

Test Laboratory: RIM Testing Services

TMFS_noise_04_04_11_noise

DUT: TMFS; Type: TMFS-1

Communication System: CW

Frequency: 835 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV2 - 1016; ; Calibrated: 3/7/2011
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/Background Noise/z noise in AMCC (no signal should appear)/ABM [HAC-2007] Noise Spectrum(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm


Signal Type: Off

Output Gain: 0

Measure Window Start: 2000ms

Measure Window Length: 5000ms

Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 15(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

ABM = -59.36 dB A/m
Location: 0, 360, -262 mm

T-Coil scan/Background Noise/z noise in AMCC (no signal should appear)/ABM [HAC-2007] Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 0
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM2 = -59.36 dB A/m
Location: 0, 360, -262 mm

T-Coil scan/Background Noise/x (longitudinal) noise/ABM [HAC-2007] Noise Spectrum(x,y,z,f) (1x1x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 0
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -59.47 dB A/m
Location: 0, 0, 13 mm

T-Coil scan/Background Noise/x (longitudinal) noise/ABM [HAC-2007] Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Off
Output Gain: 0
Measure Window Start: 2000ms
Measure Window Length: 5000ms
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 16(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM2 = -59.47 dB A/m
 Location: 0, 0, 13 mm

T-Coil scan/Background Noise/y (transversal) noise/ABM [HAC-2007] Noise Spectrum(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Off
 Output Gain: 0
 Measure Window Start: 2000ms
 Measure Window Length: 5000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM = -59.38 dB A/m
 Location: 0, 0, 13 mm

T-Coil scan/Background Noise/y (transversal) noise/ABM [HAC-2007] Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Off
 Output Gain: 0
 Measure Window Start: 2000ms
 Measure Window Length: 5000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM2 = -59.38 dB A/m
 Location: 0, 0, 13 mm





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011


Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 19(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Annex C: Audio Band Magnetic measurement data and plots

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 20(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/18/2011 12:53:39 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM850_axial

DUT: BlackBerry; Type: Sample

Communication System: GSM 850; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.2 MHz, Frequency: 836.8 MHz, Frequency: 848.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/z (axial) 5.0mm 50 x 50/ABM [HAC-2007]


SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 21(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 26.13 dB
ABM1 comp = 7.04 dB A/m
BWC Factor = 0.14 dB
Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 26.95 dB
ABM1 comp = 7.59 dB A/m
BWC Factor = 0.14 dB
Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 22(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 26.89 dB
 ABM1 comp = 7.65 dB A/m
 BWC Factor = 0.15 dB
 Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.71 dB
 BWC Factor = 10.78 dB
 Location: -5, 10, 3.7 mm

T-Coil scan/General Scans 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.69 dB
 BWC Factor = 10.78 dB
 Location: -5, 10, 3.7 mm

T-Coil scan/General Scans 2 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.79 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



Diff = 1.62 dB
 BWC Factor = 10.79 dB
 Location: -5, 10, 3.7 mm

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




0 dB = 1.000

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 27(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/18/2011 1:10:12 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM850_radial L

DUT: BlackBerry; Type: Sample

Communication System: GSM 850; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.2 MHz, Frequency: 836.8 MHz, Frequency: 848.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/x (longitudinal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 28(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 23.38 dB
ABM1 comp = -1.25 dB A/m
BWC Factor = 0.14 dB
Location: -12, 10, 4.4 mm

T-Coil scan/General Scans 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 29(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 23.85 dB
 ABM1 comp = -1.09 dB A/m
 BWC Factor = 0.14 dB
 Location: -12, 10, 4.4 mm

T-Coil scan/General Scans 2 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 35.28
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.15 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



ABM1/ABM2 = 23.93 dB
 ABM1 comp = -2.98 dB A/m
 BWC Factor = 0.15 dB
 Location: -14, 12, 4.4 mm

Author Data
Daoud Attayi


Dates of Test
**Mar. 18-21, 2011
April 04, 2011**

Report No
RTS-2605-1104-43B

FCC ID
**L6ARDH70CW
L6ARDQ70UW**



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 31(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/18/2011 3:18:57 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM850_radial T

DUT: BlackBerry; Type: Sample

Communication System: GSM 850; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.2 MHz, Frequency: 836.8 MHz, Frequency: 848.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/y (transversal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 32(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 44.35 dB

ABM1 comp = -1.02 dB A/m

BWC Factor = 0.14 dB

Location: 2, 0, 4.4 mm

T-Coil scan/General Scans 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 35.28

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 33(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:


ABM1/ABM2 = 43.74 dB
 ABM1 comp = -1.43 dB A/m
 BWC Factor = 0.14 dB
 Location: 2, 0, 4.4 mm

T-Coil scan/General Scans 2 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 35.28
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.15 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 48.87 dB
 ABM1 comp = 0.13 dB A/m
 BWC Factor = 0.15 dB
 Location: -4, 2, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 34(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 10:50:42 AM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM1900_axial

DUT: BlackBerry; Type: Sample

Communication System: GSM 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1850.2 MHz, Frequency: 1880 MHz, Frequency: 1909.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/z (axial) 5.0mm 50 x 50/ABM [HAC-2007]


SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 35(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 29.81 dB
ABM1 comp = 8.05 dB A/m
BWC Factor = 0.14 dB
Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 29.94 dB
ABM1 comp = 8.27 dB A/m
BWC Factor = 0.14 dB
Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 36(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 30.13 dB
 ABM1 comp = 8.07 dB A/m
 BWC Factor = 0.14 dB
 Location: -3, 10, 4.4 mm

T-Coil scan/General Scans 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.64 dB
 BWC Factor = 10.78 dB
 Location: -5, 10, 3.7 mm

T-Coil scan/General Scans 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.81 dB
 BWC Factor = 10.78 dB
 Location: -5, 10, 3.7 mm

T-Coil scan/General Scans 2 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):



Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




0 dB = 1.000

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 41(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 11:07:16 AM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM1900_radial L

DUT: BlackBerry; Type: Sample;

Communication System: GSM 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1850.2 MHz, Frequency: 1880 MHz, Frequency: 1909.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/x (longitudinal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 42(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 25.60 dB
ABM1 comp = -3.43 dB A/m
BWC Factor = 0.14 dB
Location: -15, 12, 4.4 mm

T-Coil scan/General Scans 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 25.23 dB
ABM1 comp = -3.62 dB A/m
BWC Factor = 0.14 dB
Location: -15, 12, 4.4 mm

T-Coil scan/General Scans 2 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi


Dates of Test
**Mar. 18-21, 2011
 April 04, 2011**

Report No
RTS-2605-1104-43B


FCC ID
**L6ARDH70CW
 L6ARDQ70UW**

Cursor:

ABM1/ABM2 = 25.72 dB
 ABM1 comp = -3.50 dB A/m
 BWC Factor = 0.14 dB
 Location: -15, 12, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 44(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 11:24:33 AM

Test Laboratory: RIM Testing Services

HAC T-Coil_GSM1900_radial T

DUT: BlackBerry; Type: Sample

Communication System: GSM 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1850.2 MHz, Frequency: 1880 MHz, Frequency: 1909.8 MHz; Communication System PAR: 9.191 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/y (transversal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 45(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 43.70 dB
ABM1 comp = -0.59 dB A/m
BWC Factor = 0.14 dB
Location: -3, 3, 4.4 mm

T-Coil scan/General Scans 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 46(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 43.59 dB
 ABM1 comp = -0.60 dB A/m
 BWC Factor = 0.14 dB
 Location: -3, 3, 4.4 mm

T-Coil scan/General Scans 2 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 35.28
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.14 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



ABM1/ABM2 = 43.68 dB
 ABM1 comp = -0.59 dB A/m
 BWC Factor = 0.14 dB
 Location: -3, 3, 4.4 mm

Author Data
Daoud Attayi


Dates of Test
**Mar. 18-21, 2011
April 04, 2011**

Report No
RTS-2605-1104-43B

FCC ID
**L6ARDH70CW
L6ARDQ70UW**



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 48(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 3:55:47 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA800_Axial

DUT: BlackBerry; Type: Sample

Communication System: CDMA 800; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.7 MHz, Frequency: 836.52 MHz, Frequency: 848.52 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/z (axial) 5.0mm 50 x 50/ABM [HAC-2007]


SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 49(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 50.05 dB
ABM1 comp = 3.83 dB A/m
BWC Factor = 0.14 dB
Location: 0, 8, 4.4 mm

T-Coil scan/General Scans 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
Output Gain: 54.9
Measure Window Start: 300ms
Measure Window Length: 2000ms
BWC applied: 10.78 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.38 dB
BWC Factor = 10.78 dB
Location: 0, 10, 3.7 mm

T-Coil scan/General Scans 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 50(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 50.40 dB
 ABM1 comp = 4.73 dB A/m
 BWC Factor = 0.14 dB
 Location: 0, 10, 4.4 mm

T-Coil scan/General Scans 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 54.9
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = 1.39 dB
 BWC Factor = 10.78 dB
 Location: 0, 10, 3.7 mm

T-Coil scan/General Scans 2 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 28
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.14 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 50.57 dB
 ABM1 comp = 5.35 dB A/m
 BWC Factor = 0.14 dB
 Location: -2, 10, 4.4 mm

T-Coil scan/General Scans 2 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 54.9
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



Diff = 0.77 dB
 BWC Factor = 10.78 dB
 Location: 0, 10, 3.7 mm

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




0 dB = 1.000

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 55(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 4:12:21 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA800_Radial_L

DUT: BlackBerry; Type: Sample

Communication System: CDMA 800; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.7 MHz, Frequency: 836.52 MHz, Frequency: 848.52 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/x (longitudinal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 56(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 40.61 dB
ABM1 comp = -4.81 dB A/m
BWC Factor = 0.14 dB
Location: -10, 12, 4.4 mm

T-Coil scan/General Scans 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 40.89 dB
ABM1 comp = -5.29 dB A/m
BWC Factor = 0.14 dB
Location: -12, 12, 4.4 mm

T-Coil scan/General Scans 2 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi


Dates of Test
**Mar. 18-21, 2011
April 04, 2011**

Report No
RTS-2605-1104-43B


FCC ID
**L6ARDH70CW
L6ARDQ70UW**

Cursor:

ABM1/ABM2 = 40.62 dB
ABM1 comp = -4.73 dB A/m
BWC Factor = 0.14 dB
Location: -12, 10, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 58(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 4:29:39 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA800_Radial_T

DUT: BlackBerry; Type: Sample

Communication System: CDMA 800; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 824.7 MHz, Frequency: 836.52 MHz, Frequency: 848.52 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/y (transversal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 59(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 41.32 dB
ABM1 comp = -6.69 dB A/m
BWC Factor = 0.14 dB
Location: -1, -2, 4.4 mm

T-Coil scan/General Scans 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 40.48 dB
ABM1 comp = -8.19 dB A/m
BWC Factor = 0.14 dB
Location: -5, -2, 4.4 mm

T-Coil scan/General Scans 2 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi


Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B


FCC ID
L6ARDH70CW
L6ARDQ70UW

Cursor:

ABM1/ABM2 = 41.19 dB
 ABM1 comp = -5.93 dB A/m
 BWC Factor = 0.14 dB
 Location: -5, 0, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 61(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 5:19:03 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA1900_Axial

DUT: BlackBerry; Type: Sample

Communication System: CDMA 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1851.25 MHz, Frequency: 1880 MHz, Frequency: 1908.5 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/z (axial) 5.0mm 50 x 50/ABM [HAC-2007]


SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 62(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 49.30 dB

ABM1 comp = 4.74 dB A/m

BWC Factor = 0.14 dB

Location: 0, 10, 4.4 mm

T-Coil scan/General Scans 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav

Output Gain: 54.9

Measure Window Start: 300ms

Measure Window Length: 2000ms

BWC applied: 10.78 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = -0.36 dB

BWC Factor = 10.78 dB

Location: 0, 10, 3.7 mm

T-Coil scan/General Scans 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav


Output Gain: 28

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 63(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 49.99 dB
 ABM1 comp = 4.36 dB A/m
 BWC Factor = 0.14 dB
 Location: 0, 8, 4.4 mm

T-Coil scan/General Scans 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 54.9
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.78 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

Diff = -0.04 dB
 BWC Factor = 10.78 dB
 Location: 0, 10, 3.7 mm

T-Coil scan/General Scans 2 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 28
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.14 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 49.27 dB
 ABM1 comp = 3.96 dB A/m
 BWC Factor = 0.14 dB
 Location: 0, 8, 4.4 mm

T-Coil scan/General Scans 2 2 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 54.9
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.79 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



Diff = 1.47 dB
 BWC Factor = 10.79 dB
 Location: 0, 10, 3.7 mm

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



0 dB = 1.000


0 dB = 1.000

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW




Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW





Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 68(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 5:35:38 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA1900_Radial_L

DUT: BlackBerry; Type: Sample

Communication System: CDMA 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1851.25 MHz, Frequency: 1880 MHz, Frequency: 1908.5 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/x (longitudinal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 69(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.48 dB
ABM1 comp = -4.50 dB A/m
BWC Factor = 0.14 dB
Location: -10, 12, 4.4 mm

T-Coil scan/General Scans 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 39.52 dB
ABM1 comp = -5.73 dB A/m
BWC Factor = 0.14 dB
Location: -12, 12, 4.4 mm

T-Coil scan/General Scans 2 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi


Dates of Test
**Mar. 18-21, 2011
 April 04, 2011**

Report No
RTS-2605-1104-43B


FCC ID
**L6ARDH70CW
 L6ARDQ70UW**

Cursor:

ABM1/ABM2 = 40.11 dB
 ABM1 comp = -4.99 dB A/m
 BWC Factor = 0.14 dB
 Location: -12, 12, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 71(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 3/21/2011 5:52:57 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_CDMA1900_Radial_T

DUT: BlackBerry; Type: Sample

Communication System: CDMA 1900; Communication System Band: Exported from older format (data unavailable - please correct).; Frequency: 1851.25 MHz, Frequency: 1880 MHz, Frequency: 1908.5 MHz; Communication System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV3 - 3062; ; Calibrated: 6/8/2010
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn881; Calibrated: 4/19/2010
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/y (transversal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 72(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.14 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 41.23 dB
ABM1 comp = -6.78 dB A/m
BWC Factor = 0.14 dB
Location: -3, -2, 4.4 mm

T-Coil scan/General Scans 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 41.06 dB
ABM1 comp = -6.96 dB A/m
BWC Factor = 0.14 dB
Location: -3, -2, 4.4 mm

T-Coil scan/General Scans 2 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.14 dB
Device Reference Point: 0, 0, -6.3 mm

Author Data
Daoud Attayi


Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B


FCC ID
L6ARDH70CW
L6ARDQ70UW

Cursor:

ABM1/ABM2 = 40.67 dB
 ABM1 comp = -7.00 dB A/m
 BWC Factor = 0.14 dB
 Location: -1, -2, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 74(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 4/4/2011 1:26:14 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_UMTS_band_IV_axial

DUT: BlackBerry; Type: Sample

Communication System: WCDMA FDD IV; Communication System Band:

Exported from older format (data unavailable - please correct).; Frequency:

1712.4 MHz, Frequency: 1732.6 MHz, Frequency: 1752.6 MHz;Communication

System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV2 - 1016; ; Calibrated: 3/7/2011
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/z (axial) 5.0mm 50 x 50/ABM [HAC-2007]


SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 75(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 54.65 dB
ABM1 comp = 6.61 dB A/m
BWC Factor = 0.15 dB
Location: -2, 10, 4.4 mm

T-Coil scan/General Scans 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 55.05 dB
ABM1 comp = 7.05 dB A/m
BWC Factor = 0.15 dB
Location: -2, 10, 4.4 mm

T-Coil scan/General Scans 2 2 2/z (axial) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm


| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 76(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Cursor:

ABM1/ABM2 = 55.21 dB
 ABM1 comp = 7.33 dB A/m
 BWC Factor = 0.15 dB
 Location: -2, 10, 4.4 mm

T-Coil scan/General Scans 2/z (axial) wideband at best S/N/ABM [HAC-2007] Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_300-3000_2s.wav
 Output Gain: 69.12
 Measure Window Start: 300ms
 Measure Window Length: 2000ms
 BWC applied: 10.79 dB
 Device Reference Point: 0, 0, -6.3 mm





0 dB = 1.000

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW






Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW



| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 79(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 4/4/2011 1:42:49 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_UMTS_band_IV_radial L

DUT: BlackBerry; Type: Sample

Communication System: WCDMA FDD IV; Communication System Band:

Exported from older format (data unavailable - please correct).; Frequency:

1712.4 MHz, Frequency: 1732.6 MHz, Frequency: 1752.6 MHz;Communication

System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV2 - 1016; ; Calibrated: 3/7/2011
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/x (longitudinal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 80(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 52.39 dB
ABM1 comp = -2.10 dB A/m
BWC Factor = 0.15 dB
Location: -12, 12, 4.4 mm

T-Coil scan/General Scans 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1/ABM2 = 52.13 dB
ABM1 comp = -2.02 dB A/m
BWC Factor = 0.15 dB
Location: -12, 12, 4.4 mm

T-Coil scan/General Scans 2 2 2/x (longitudinal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 81(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

ABM1/ABM2 = 51.87 dB
 ABM1 comp = -0.79 dB A/m
 BWC Factor = 0.15 dB
 Location: -10, 10, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 82(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Date/Time: 4/4/2011 2:00:09 PM

Test Laboratory: RIM Testing Services

HAC T-Coil_UMTS_band_IV_radial T

DUT: BlackBerry; Type: Sample

Communication System: WCDMA FDD IV; Communication System Band:

Exported from older format (data unavailable - please correct).; Frequency:

1712.4 MHz, Frequency: 1732.6 MHz, Frequency: 1752.6 MHz;Communication

System PAR: 0 dB

Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: AM1DV2 - 1016; ; Calibrated: 3/7/2011
 - Modulation Compensation:
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

T-Coil scan/General Scans 2/y (transversal) 5.0mm 50 x 50/ABM


[HAC-2007] SNR(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 35.28

Measure Window Start: 300ms

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 83(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

T-Coil scan/General Scans 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):

Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1/ABM2 = 51.53 dB
ABM1 comp = -3.10 dB A/m
BWC Factor = 0.15 dB
Location: -3, 0, 4.4 mm

T-Coil scan/General Scans 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1/ABM2 = 52.29 dB
ABM1 comp = -2.89 dB A/m
BWC Factor = 0.15 dB
Location: -3, 2, 4.4 mm

T-Coil scan/General Scans 2 2 2/y (transversal) 2mm 8 x 8/ABM [HAC-2007] SNR(x,y,z) (5x5x1):


Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 35.28
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.15 dB
Device Reference Point: 0, 0, -6.3 mm

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 84(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |


ABM1/ABM2 = 52.22 dB
 ABM1 comp = -3.20 dB A/m
 BWC Factor = 0.15 dB
 Location: -3, 0, 4.4 mm



0 dB = 1.000

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 85(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Annex D: Probe/TMFS calibration certificate and equipment specification

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 86(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates
 Client **RTS (RIM Testing Service)**

Accreditation No.: **SCS 108**

Certificate No: **AM1DV3-3062_Jun10**

CALIBRATION CERTIFICATE

Object AM1DV3 - SN: 3062
Calibration procedure(s) **QA CAL-24.v2**
Calibration procedure for AM1D magnetic field probes and TMFS in the audio range
Calibration date: **June 8, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.


Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-------------------------------|-------------|-----------------------------------|-----------------------|
| Keithley Multimeter Type 2001 | SN: 0810278 | 1-Oct-09 (No: 9055) | Oct-10 |
| Reference Probe AM1DV3 | SN: 3000 | 17-Aug-09 (No: AM1D-3000_Aug09) | Aug-10 |
| DAE4 | SN: 781 | 22-Jan-10 (No: DAE4-781_Jan10) | Jan-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| AMCC | 1050 | 15-Oct-09 (in house check Oct-09) | Oct-10 |

Calibrated by: Name **Mike Meli** Function **Laboratory Technician** Signature *[Signature]*
Approved by: Name **Fin Bomholt** Function **R&D Director** Signature *[Signature]*

Issued: June 9, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 87(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

References

- [1] ANSI C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] DASY4 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.


The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- **Coordinate System:** The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [2], with the tip pointing to "southwest" orientation.
- **Functional Test:** The functional test preceding calibration includes test of Noise level RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- **Connector Rotation:** The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- **Sensor Angle:** The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- **Sensitivity:** With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 88(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

AM1D probe identification and configuration data


| | |
|-----------|---|
| Item | AM1DV3 Audio Magnetic 1D Field Probe |
| Type No | SP AM1 001 BA |
| Serial No | 3062 |

| | |
|--------------------|------------------------------------|
| Overall length | 296 mm |
| Tip diameter | 6.0 mm (at the tip) |
| Sensor offset | 3.0 mm (centre of sensor from tip) |
| Internal Amplifier | 20 dB |

| | |
|-----------------------|--|
| Manufacturer / Origin | Schmid & Partner Engineering AG, Zürich, Switzerland |
| Manufacturing date | Oct-2008 |
| Last calibration date | June 16, 2009 |

Calibration data

| | | | |
|--------------------------|------------------|--------------------------|-----------------|
| Connector rotation angle | (in DASY system) | 62.6 ° | +/- 3.6 ° (k=2) |
| Sensor angle | (in DASY system) | 0.00 ° | +/- 0.5 ° (k=2) |
| Sensitivity at 1 kHz | (in DASY system) | 0.00741 V / (A/m) | +/- 2.2 % (k=2) |

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 89(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland






S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates
 Client **RTS (RIM Testing Services)**

Accreditation No.: **SCS 108**

Certificate No: **AM1DV2- 1016_Mar11**

| CALIBRATION CERTIFICATE | | | |
|--|--|--|--|
| Object | AM1DV2 - SN: 1016 | | |
| Calibration procedure(s) | QA CAL-24.v2 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range | | |
| Calibration date: | March 7, 2011 | | |
| <p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p> | | | |
| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
| Keithley Multimeter Type 2001 | SN: 0810278 | 28-Sep-10 (No:10376) | Sep-11 |
| Reference Probe AM1DV2 | SN: 1008 | 18-Jan-11 (No. AM1D-1008_Jan11) | Jan-12 |
| DAE4 | SN: 781 | 20-Oct-10 (No. DAE4-781_Oct10) | Oct-11 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| AMCC | 1050 | 15-Oct-09 (in house check Oct-09) | Oct-11 |
| Calibrated by: | Name Mike Meili | Function Laboratory Technician | Signature  |
| Approved by: | Name Fin Bornholt | Function R&D Director | Signature  |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. | | | Issued: March 9, 2011 |

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 90(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

References

- [1] ANSI C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] DASY4 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.


The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [2], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of Noise level
RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected.
Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- *Sensitivity:* With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 91(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

AM1D probe identification and configuration data


| | |
|-----------|---|
| Item | AM1DV2 Audio Magnetic 1D Field Probe |
| Type No | SP AM1 001 AC |
| Serial No | 1016 |

| | |
|--------------------|------------------------------------|
| Overall length | 296 mm |
| Tip diameter | 6.0 mm (at the tip) |
| Sensor offset | 3.0 mm (centre of sensor from tip) |
| Internal Amplifier | 40 dB |

| | |
|-----------------------|--|
| Manufacturer / Origin | Schmid & Partner Engineering AG, Zurich, Switzerland |
| Manufacturing date | Apr-2006 |
| Last calibration date | March 17, 2010 |

Calibration data

| | | | |
|--------------------------|------------------|-------------------------|-----------------|
| Connector rotation angle | (in DASY system) | 251.5 ° | +/- 3.6 ° (k=2) |
| Sensor angle | (in DASY system) | 3.69 ° | +/- 0.5 ° (k=2) |
| Sensitivity at 1 kHz | (in DASY system) | 0.0652 V / (A/m) | +/- 2.2 % (k=2) |

| | | | |
|---|---|---|---------------------------------------|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 92(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Calibration Laboratory of Schmid & Partner Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **RTS (RIM Testing Services)**

Certificate No: **TMFS_1003_Jan10**

CALIBRATION CERTIFICATE

Object / Identification: **TMFS-1 - SN: 1003**
Calibration procedure(s): **QA CAL-24 v2**
Calibration procedure for AM1D magnetic field probes and TMFS in the audio range
Calibration date: **January 22, 2010**
Condition of the calibrated item: **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The calibrations have been conducted in the R&D laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.


Calibration Equipment used (M&TE critical for calibration)


| Primary Standards | ID # | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|---------------------------------|-------------|---|-----------------------------|
| Keithley Multimeter Type 2001 | SN: 0810278 | 1-Oct-09 (No: 9055) | Oct-10 |
| Secondary Standards | ID # | Cal / Check Date | Scheduled Calibration Check |
| AMCC | 1050 | 15-Oct-09 (in house check Oct-09) | Oct-11 |
| Reference Probe AM1DV2 | SN: 1008 | 21-Jan-10 (No: AM1D-1008_Jan10) | Jan-11 |
| AMMI Audio Measuring Instrument | 1062 | 14-Jul-09 (in house check Jul-09) | Jul-11 |
| Agilent WF Generator 33120A | MY40005266 | 13-Oct-09 (in house check Oct-09) | Oct-11 |

Calibrated by: Name **Mike Meili** Function **Laboratory Technician** Signature *[Signature]*
Approved by: Name **Fin Bormholt** Function **R&D Director** Signature *[Signature]*

Issued: January 25, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

| | | | |
|---|--|--|---|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 93(100) |
| Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B | FCC ID L6ARDH70CW L6ARDQ70UW |

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 94(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

References

- [1] ANSI-PC63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] DASY4 manual, Chapter 29: Hearing Aid Compatibility (HAC) T-Coil Extension (April 2008)

Methods Applied and Interpretation of Parameters

- **Coordinate System:** The TMFS is mounted underneath the HAC Test Arch touching equivalently to a wireless device according to [2] 29.2.2.: In "North" orientation, the TMFS signal connector is directed to the north, with x and y axes of TMFS and Test arch coinciding (see fig. 1). The rotational symmetry axis of the TMFS is aligned to the center of the HAC test Arch. For East, South and West configuration, the TMFS has been rotated clockwise in steps of 90°, so the connector looks into the specified direction. The evaluation of the radial direction is referenced to the device orientation (x equivalent to South direction).





Fig. 1 TMFS scanning measurement configurations

- **Measurement Plane:** In coincidence with standard [1], the measurement plane (probe sensor center) is selected to be at a distance of 10 mm above the the surface of the TMFS touching the frame. The 50 x 50 mm scan area is aligned to the center of the unit. The scanning plane is verified to be parallel to the phantom frame before the measurements using the predefined "Geometry and signal check" procedure according to the predefined procedures described in [2].

- **Measurement Conditions:** Calibration of AM1D probe and AMMI are according to [2]. The 1 kHz sine signal for the level measurement is supplied from an external, independent generator via a BNC cable to TMFS IN and monitored at TMFS OUT with an independent RMS voltmeter or Audio Analyzer. The level is set to 0.5 Vrms and monitored during the scans.
- For the *frequency response*, a higher suppression of the background ambient magnetic field over the full frequency range was achieved by placing the TMFS in a magnetically shielded box. The AM1D probe was fixed without robot positioner near the axial maximum for this measurement. The background noise suppression was typ. 30 dB at 100 Hz (minimum) and 42 dB at 1 kHz. The predefined multisine signal (48k_multisine_50-10000_10s.wav) was used and evaluated in the third-octave bands from 100 Hz to 10000 Hz.

| | | | |
|---|---|---|---------------------------------------|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 95(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

1 Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|---|------------------------|--|
| DASY Version | DASY5 | V5.2 B162 |
| DASY PP Version | SEMCAD | V14.0 B59 |
| Phantom | HAC Test Arch | SD HAC P01 BA, #1002 |
| Distance TMFS Top - Probe Centre | 10 mm | |
| Scan resolution | dx, dy = 5 mm | area = 50 x 50 mm |
| Frequency | for field scans | 1 kHz |
| Signal level to TMFS | for field scans | 500 mV RMS |
| Signal | for frequency response | multisine signal 50-10000 Hz, each third-octave band |

Table 1: System configuration

2 Axial Maximum Field

| Configuration | East | South | West | North | Subset Average | Average |
|-----------------------------|---------------|---------------|---------------|---------------|----------------|---------------|
| Axial Max | -20.17 | -20.17 | -20.16 | -20.17 | | -20.17 |
| TMFS Y Axis 1st Max | -25.74 | -25.74 | -25.70 | -25.70 | | |
| TMFS Y Axis 2nd Max | -25.92 | -25.66 | -26.02 | -25.7 | | |
| Longitudinal Max Avg | -25.83 | -25.70 | -25.86 | -25.70 | -25.77 | |
| TMFS X Axis 1st Max | -25.73 | -25.71 | -25.73 | -25.67 | | |
| TMFS X Axis 2nd Max | -25.68 | -25.91 | -25.67 | -25.96 | | |
| Transversal Max Avg | -25.71 | -25.81 | -25.70 | -25.82 | -25.76 | |
| Radial Max | | | | | | -25.77 |

Table 2: Axial and radial field maxima measured with probe center at 10mm distance in dB A/m

The maximum was calculated as the average from the values measured in the 4 orientations listed in table 2.

Axial Maximum -20.17 dB A/m (+/- 0.33dB, k=2)

3 Radial Maximum Field

In addition, the average from the 16 maxima of the radial field listed in table 2 (measured at 10mm) was calculated:

Radial Maximum **-25.77 dB A/m**

Author Data
Daoud Attayi

Dates of Test
Mar. 18-21, 2011
April 04, 2011

Report No
RTS-2605-1104-43B

FCC ID
L6ARDH70CW
L6ARDQ70UW

4 Appendix

4.1 Frequency response

Max. deviation measured, relative to 1 kHz: **min. -0.03, max. +0.02 dB**

| Frequency [Hz] | Response [dB] |
|----------------|---------------|
| 100 | 0.02 |
| 125 | 0.00 |
| 160 | -0.01 |
| 200 | 0.00 |
| 250 | 0.02 |
| 315 | -0.01 |
| 400 | 0.00 |
| 500 | 0.00 |
| 630 | 0.00 |
| 800 | 0.00 |
| 1000 | 0.00 |
| 1250 | -0.01 |
| 1600 | -0.01 |
| 2000 | -0.01 |
| 2500 | -0.01 |
| 3150 | -0.01 |
| 4000 | -0.02 |
| 5000 | -0.02 |
| 6300 | -0.03 |
| 8000 | -0.03 |
| 10000 | -0.03 |

Table 3: Frequency response




Fig. 2 Frequency response 100 to 10'000 Hz

4.2 Field plots




Fig. 3: Typical 2D field plots for x (red), y (green) and z (blue) components






Fig. 4: Superposed field plots of z (axial), x and y radial magnetic field, 50 x 50 mm, individual scaling: white = max. field level, black = -4dB below max. The lines show the position of the 2D field plot of figure 3.

| | | | |
|---|--|--|---|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 98(100) |
| Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B | FCC ID L6ARDH70CW L6ARDQ70UW |

| | | | |
|---|---|--------------------------|--|
|  | Document | | Page |
| | Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | 99(100) |
| Author Data | Dates of Test | Report No | FCC ID |
| Daoud Attayi | Mar. 18-21, 2011 April 04, 2011 | RTS-2605-1104-43B | L6ARDH70CW L6ARDQ70UW |

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com

Certificate of conformity

| | |
|-----------------------|--|
| Item | Audio Magnetic Calibration Coil AMCC |
| Type No | SD HAC P02 A |
| Series No | 1001 ff. |
| Manufacturer / Origin | Schmid & Partner Engineering AG Zurich, Switzerland |

Description of the item

The Audio Magnetic Calibration coil (AMCC) is a Helmholtz Coil designed according to standard [1], section D.9 for calibration of the AM1D probe. Two horizontal coils are positioned above a non-metallic base plate and generate a homogeneous magnetic field in the z direction (normal to it).

Configuration

The AMCC consists of two parallel coils of 20 turns with radius 143 mm connected in parallel in a distance of 143 mm. With this design, a current of 10 mA produces a field of 1 A/m. The DC input resistance at the input BNC socket is adjusted by a series resistor to a DC resistance of approximately 50 Ohm. The voltage required to produce a field of 1 A/m is consequently approx. 500 mV. To current through the coil is monitored via a shunt resistor of 10 Ohm +/- 1%. The voltage is available on a BNO socket with 100 mV corresponding to 1 A/m.

Handling of the item

The coil shall be positioned in a non-metallic environment to avoid distortion of the magnetic field.

Tests

| Test | Requirement | Details | Units tested |
|----------------------|---|---|---------------|
| Number of turns | N = 20 per coil | Resistance measurement | all |
| Orientation of coils | parallel coils with same direction of windings | Magnetic field variation in the AMCC axis | all |
| Coil radius | r = 143 mm | mechanical dimension | First article |
| Coil distance | d = 143 mm distance between coil centers | mechanical dimension | First article |
| Input resistance | 51.7 +/- 2 Ohm | DC resistance at BNC input connector | all |
| Shunt resistance | R = 10.0 Ohm +/- 1 % | DC resistance at BNO output connector | all |
| Shunt sensitivity | Hc = 1 A/m per 100 mV according to formula $H_c = (U/R) * N / r / (1.25^{*1.5})$ | Field measurement compared with Narda ELT400 + BN2300/90.10 | First article |

Standards

[1] ANSI PC63.19-2006 Draft 3.12


Conformity

Based on the tests above, we certify that this item is in compliance with the requirements of [1].

Date 22.5.2006

Stamp / Signature

s p e a g
 Schmid & Partner Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 1 245 9700, Fax +41 1 245 9779
 info@speag.com, http://www.speag.com

| | | | |
|---|--|--|--|
|  | Document Annex A-D to Hearing Aid Compatibility Audio Band Magnetic (ABM) T-Coil Test Report for BlackBerry® Smartphone model RDH71CW/RDQ71UW | | Page 100(100) |
| | Author Data Daoud Attayi | Dates of Test Mar. 18-21, 2011 April 04, 2011 | Report No RTS-2605-1104-43B |

Specifications

Audio Magnetic Field Probe AM1D

The AM1D probe is an active probe with a single sensor according to [1] section D.8. It is fully RF shielded and has a rounded tip of 6 mm diameter incorporating a pickup coil with its center offset 3mm from the tip and the sides.

SPEAG, the manufacturer of the T-Coil system tested the probe frequency response and its dynamic range. The compliance is stated in the Certificate of conformity document 880-SPAM1001A-A. Also the probe frequency has been verified and the response deviation from the ideal differentiator was within +0.05 and - 0.46 dB in the range 100 Hz to 10 kHz on the center frequencies of the third-octave bands. Note that it includes the probe preamplifier and also with the AMMI internal preamplifiers, filters and processing.

Dynamic range:

maximum + 21 dB A/m @ 1 kHz
 Noise level typically -70 dB A/m @ 1 kHz
 ABM2 typically -60 dB A/m

Linearity

Within < 0.1 dB from 5 dB
 below limitation to 16 dB above noise level

Sensitivity

Typically -24 dBV / A/m @ 1 kHz probe output

Audio Magnetic Measurement Instrument (AMMI)

sampling rate 48 kHz / 24 bit
 dynamic range 85 dB
 test signal generation user selectable and predefined (via PC)
 calibration auto-calibration / full system calibration using AMCC
 with monitor output
 dimensions 482 x 65 x 270 mm

Helmholtz Calibration Coil (AMCC)

dimensions 370 x 370 x 196 mm, according to ANSI-PC63.19
 The Audio Magnetic Calibration coil is a Helmholtz Coil designed according to [1], section D.9 for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction.

Shunt sensitivity $H_c = 1$ A/m per 100mV according to formula:

$$H_c = (U / R) * N / r / (1.25 \wedge 1.5)$$

Number of turns $N = 20$ per coil
 Coil radius $r = 143$ mm
 Shunt resistance $R = 10.00$ Ohm