## **EMI Test Report**

Tested in accordance with Federal Communications Commission (FCC) Personal Communications Services CFR 47, Part 15 Subpart C & Industry Canada (IC) RSS-210, RSS-GEN



# A division of Research In Motion Limited

REPORT NO.: RTS-6036-1304-60B

PRODUCT MODEL NO.:RFS121LW, RFR101LWTYPE NAME:BlackBerry® smartphoneFCC ID:L6ARFS120LW, L6ARFR100LWIC:2503A-RFS120LW, 2503A-RFR100LW

DATE: May 30, 2013

RTS is accredited according to EN ISO/IEC 17025 by:



592

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

#### **Statement of Performance:**

The BlackBerry® smartphone, model RFS121LW, part number CER-54731-001 Rev3-x09-01, and its accessories perform within the requirements of the test standards when configured and operated under RIM's operation instructions.

The BlackBerry<sup>®</sup> smartphone, model RFR101LW, part number HWD\_CER-54730-001-Rev2-x09-04 and accessories perform within the requirements of the test standards when configured and operated per RIM's instructions.

#### **Declaration:**

We hereby certify that:

The test data reported herein is an accurate record of the performance of the sample(s) tested.

The test results are valid for the tested unit (s) only.

The test equipment used was suitable for the tests performed and within manufacturer's published specifications and operating parameters.

The test methods were consistent with the methods described in the relevant standards.

Documented by:

Reviewed by:

Feras Obeid Regulatory Compliance Associate

Heng Lin Regulatory Compliance Specialist

Reviewed and Approved by:

Masud S. Attayi, P.Eng. Manager, Regulatory Compliance

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### **Table of Contents**

Α.	Scope4
В.	Associated Documents
C.	Product Identification
D.	Support Equipment Used for the Testing of the EUT
E.	Test Results Chart7
F.	Summary of Results9
G.	Compliance Test Equipment Used 15
APPE	NDIX 1 – AC CONDUCTED EMISSIONS TEST DATA/PLOTS
APPE EMIS	NDIX 2 – BLUETOOTH, BLUETOOTH LOW ENERGY AND 802.11b/g/n RADIATED SIONS TEST DATA
APPE DATA	NDIX 3 – BLUETOOTH AND BLUETOOTH LOW ENERGY CONDUCTED EMISSIONS TEST /PLOTS
APPE	NDIX 4 – 802.11b/g/n CONDUCTED EMISSIONS TEST DATA/PLOTS
APPE	NDIX 5 – NEAR FIELD COMMUNICATIONS TEST DATA/PLOTS

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry $^{ extsf{B}}$ smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### A. Scope

This report details the results of compliance tests which were performed in accordance to the requirements of:

- FCC CFR 47 Part 15, Subpart C, October, 2012
- Industry Canada, RSS-210, Issue 8, December 2010, License-exempt Radio Apparatus

• Industry Canada, RSS-GEN, Issue 3, December 2010, General Requirements and Information for the Certification of Radio Apparatus

### B. Associated Documents

- 1) MultiSourceDeclaration\_RFS121LW\_b3901
- 2) MultiSourceDeclaration\_RFS121LW\_b4081
- 3) RFS121LW\_HW\_Declaration\_CER-54731-001\_Rev3-x09-01
- 4) BlackBerrySystemSimilarity\_Declaration\_RFS121LW\_RFR101LW

#### C. Product Identification

Manufactured by Research In Motion Limited whose headquarters is located at: 295 Phillip Street Waterloo, Ontario Canada, N2L 3W8 Phone: 519 888 7465 Fax: 519 888 6906

The equipment under test (EUT) was tested at the following locations:

<b>RIM Tes</b>	ting Services EMI test	facilities			
305 Phillip Street 440 Phillip Street			ip Street		
Waterloo, Ontario		Waterloo	Waterloo, Ontario		
Canada, N2L 3W8		Canada,	N2L 5R9		
Phone:	519 888 7465	Phone:	519 888 7465		
Fax:	519 888 6906	Fax:	519 888 6906		

The testing was performed from March 06 to May 03, 2013

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

The sample EUT included:

SAMPLE	MODEL	CER NUMBER	PIN	SOFTWARE
1	RFS121LW	CER-54731-001Rev1- 906-00	2AB02A48	OS Version: 127.0.1.4081 Bundle 4081
2	RFS121LW	CER-54731-001Rev1- 906-00	2AB02A58	OS Version: 127.0.1.4081 Bundle 4081
3	RFS121LW	CER-54731-001Rev1- 906-00	2AB02A65	OS Version: 127.0.1.4081 Bundle 4081
4	RFS121LW	CER-54731-001Rev1- 906-00	2AB02A5A	OS Version: 127.0.1.3901 Bundle 3901
5	5 RFS121LW CER-54731-001Rev2- 906-00		2AB04CFB	OS Version: 127.0.1.3901 Bundle 3901
6	RFS121LW CER-54731-001Rev3- x09-01		2FFF9A73	OS Version: 127.0.1.4081 Bundle 4081
7 RFS121LW CER-54		CER-54731-001Rev3- x09-01	2FFF9A74	OS Version: 127.0.1.4081 Bundle 4081

AC Line Conducted Emissions testing was performed on sample 3 and 4 Radiated Emissions testing was performed on samples 1, 2, 3, 4, and 5 Conducted Emissions testing was performed on sample 7 Near Field Communications testing was performed on sample 5 AND 7

Only the characteristics that may have been affected by the changes from RFS121LW Rev2 to Rev3 were re-tested.

For more details, refer to RFS121LW\_HW\_Declaration\_ CER-54731-001\_Rev3-x09-01

Only the characteristics that may have been affected by the changes from RFS121LW to RFR100LW were re-tested.

For more information, see

BlackBerrySystemSimilarity\_Declaration\_RFS121LW\_RFR101LW.

To view the differences between software bundles 127.0.1.3901 to 127.0.1.4081 for RFS121LW, see document MultiSourceDeclaration\_RFS121LW\_b3901 and MultiSourceDeclaration\_RFS121LW\_b4081

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### BlackBerry<sup>®</sup> smartphone Accessories Tested

- 1) Fixed Blade Charger, part number HDW-47725-001, with an output voltage of 5.0 volts dc, 850 mA
- 2) Alt. Fixed Blade Charger, part number HDW-46445-001, with an output voltage 5.0 volts dc, 850mA
- 3) Folding Blade Charger, part number HDW 34724-001, with an output voltage 5 volts dc, 1.8A
- 4) Wired Headset, part number HDW-44306-003, with a lead length of 1.1 metres.
- 5) Alt. Wired Headset, part number HDW-44306-003, with a lead length of 1.1 metres.
- 6) Alt.2 Wired Headset, part number HDW-49299-001, with a lead length of 1.1 metres.
- 7) Alt.3 Wired Headset, part number HDW-55351-001, with a lead length of 1.1 metres
- 8) USB Data Cable, part number HDW-51800-001, 1.0 metres long.
- 9) Alt. USB Data Cable, part number HDW-51800-001, 1.0 metres long.

### D. Support Equipment Used for the Testing of the EUT

N/A

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry $^{ extsf{B}}$ smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### E. Test Results Chart

SPECIFICATION			Meets	TEST DATA
FCC CFR 47	IC	TEST TPE	Requirements	APPENDIX
Part 15.207	RSS-GEN, 7.2.4	Conducted AC Line Emission	Pass	1
Part 15.209 Part 15.247	RSS-210, A8.5 RSS-GEN, 7.2.2	BT/BLE Radiated Spurious Emissions	Pass	2
Part 15.209 Part 15.247	RSS-210, A8.5 RSS-GEN, 7.2.2	BT/BLE Radiated Band Edge Compliance	Pass	2
Part 15.209 Part 15.247	RSS-210, A8.5 RSS-GEN, 7.2.2	802.11b/g/n Radiated Spurious Emissions	Pass	2
Part 15.209 Part 15.247	RSS-210 RSS-GEN, 7.2.2	802.11b/g/n Radiated Band Edge Compliance	Pass	2
Part 15.247(a)	RSS-210 A8.1(a)	BT, 20 dB Bandwidth	Pass	3
Part 15.247(a)	RSS-210 A8.1(b)	BT, Carrier Frequency Separation	Pass	3
Part 15.247(a)	RSS-210 A8.1(d)	BT, Number of Hopping Frequencies	Pass	3
Part 15.247(a)	RSS-210 A8.1(d)	BT, Time of Occupancy (Dwell Time)	Pass	3
Part 15.247(b)	RSS-210 A8.4(4)	BT, Maximum Peak Conducted Output Power	Pass	3
Part 15.247(d)	RSS-210, A8.5	BT, Band-Edge Compliance of RF Conducted Emissions	Pass	3
Part 15.247(d)	RSS-210, A8.5	BT, Spurious RF Conducted Emissions	Pass	3
Part 15.247(a)	RSS-210, A8.2(a)	BLE, 6 dB Bandwidth	Pass	3
Part 15.247(b)	RSS-210, A8.4(4)	BLE, Maximum Conducted Output Power	Pass	3
Part 15.247(d)	RSS-210, A8.5	BLE, Band-Edge	Pass	3
Part 15.247(e)	RSS-210, A8.2(b)	BLE, Peak Power Spectral Density	Pass	3
Part 15.247(d)	RSS-210, A8.5	BLE, Spurious RF Conducted Emissions	Pass	3

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### Test Results Chart cont'd

SPECIFICATION		TEST TYPE	Meets Requirements	TEST DATA
FCC CFR 47	IC		Meeta Requirementa	APPENDIX
Part 15.247(a)	RSS-210, A8.2(a)	802.11b/g/n, 6 dB Bandwidth	Pass	4
Part 15.247(b)	RSS-210, A8.4(4)	802.11b/g/n, Maximum Conducted Output Power	Pass	4
Part 15.247(b)	RSS-210, A8.5	802.11b/g/n, Band-Edge	Pass	4
Part 15.247(e)	RSS-210, A8.2(b)	802.11b/g/n, Peak Power Spectral Density	Pass	4
Part 15.247(d)	RSS-210, A8.5	802.11b/g/n, Spurious RF Conducted Emissions	Pass	4
Part 15.209 Part 15.225(a)	RSS-210, A2.6	Near Field Communications, Radiated Emissions	Pass	5
Part 15.225(e)	RSS-210, A2.6	Near Field Communications, Occupied Bandwidth	Pass	5
Part 15.225(e)	RSS-210, A2.6	Near Field Communications, Frequency Stability	Pass	5

Testing Services™	EMI Test Report for the BlackBerry $^{ extsf{B}}$ smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### F. Summary of Results

The Following Tests were performed on model RFS121LW

1) AC LINE CONDUCTED EMISSIONS

The conducted emissions were measured using the test procedure outlined in CISPR Recommendation 22 through a 50 Ohm Line Impedance Stabilization Network (LISN), which was inserted in the power line to the equipment to provide the specified impedance for measurements. The EUT was placed on a nonconductive wooden table, 80 cm high that was positioned 40 cm from a vertical ground plane. The RF output of the network was connected to an EMI receiver system with characteristics that duplicate those of the receiver specified in CISPR Publication 16. BlackBerry<sup>®</sup> smartphone was in battery charging mode. The input voltage was 120 V, 60 Hz.

Test Configuration	Operating Mode(s)	Charger + Accessories		
1	Bluetooth Tx + Audio Playing	Fixed Blade Charger + Alt.2 Wired Headset + 1.0m USB Cable		
2	802.11b Tx + Video Playing	Alt. Fixed Blade Charger + Wired Headset +Alt.1.0m USB Cable		
3	NFC Tx	Folding Blade Charger + Alt. Wired Headset		
4	NFC Tx	Folding Blade Charger + Alt.3 Wired Headset		

The following test configurations were measured:

The sample EUT's conducted emissions were compared with respect to the FCC CFR 47 Part 15, Subpart C and IC RSS-210 limits. The sample EUT had a worst case test margin of 9.11 dB below the QP limit at 0.411 MHz in Test Configuration 4 and 6.12 dB below the AV limit at 0.420 MHz with the Folding Blade Charger in Test **Configuration 3** 

See APPENDIX 1 for the test data.

### Measurement Uncertainty ±3.2 dB

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

- 2) BLUETOOTH, BLUETOOTH LOW ENERGY AND 802.11b/g/n RADIATED EMISSIONS
- a) Radiated Spurious and Harmonic Emissions

The EUT was placed on a nonconductive styrofoam table, 80 cm high that was positioned on a remotely controlled turntable. The test distance used between the EUT and the receiving antenna was three metres. The turntable was rotated to determine the azimuth of the peak emissions. Then the emissions were maximized by elevating the antenna in the range of 1 to 4 metres. The maximum emission level was recorded. The frequency range measured was from 30 MHz to 25.0 GHz. Both the horizontal and vertical polarizations of the emissions were measured.

The measurements were done in a semi-anechoic chamber (SAC) below 1 GHz and a semi-anechoic chamber (SAC) with floor absorbers above 1 GHz. The SAC's FCC registration number is **778487** and the Industry Canada (IC) file number is **2503B-1**. The SAC with floor absorber's FCC registration number is **959115** and the IC file number is **2503C-1**.

The EUT was configured and operated to produce the maximum radiated emissions while still keeping within RIM's specifications.

The BlackBerry<sup>®</sup> smartphone was measured in standalone configuration with Bluetooth transmitting in single frequency mode at low channel (0), middle channel (39) and high channel (78) for packet type "DH5", "2-DH5" and "3-DH5". The system's radiated emission levels were compared with respect to the FCC CFR 47 Part 15, Subpart C, 15.247 and RSS-210.

The BlackBerry<sup>®</sup> smartphone was measured in standalone configuration with Bluetooth Low Energy transmitting in single frequency mode at low channel (0), middle channel (20) and high channel (39). The system's radiated emission levels were compared with respect to the FCC CFR 47 Part 15, Subpart C, 15.247 and RSS-210.

The BlackBerry<sup>®</sup> smartphone was measured in standalone configuration transmitting on channels 1, 6 & 11 at 1 Mbps for 802.11b mode, at 6 Mbps for 802.11g mode, and at MCS 0 for 802.11n mode. The system's radiated emission levels were compared with respect to the FCC CFR 47 Part 15 Subpart C, 15.247 and RSS-210.

The Bluetooth harmonics were investigated up to the 10th harmonic. The sample EUT emissions were in the noise floor (NF).

The Bluetooth Low Energy harmonics were investigated up to the 10th harmonic. The worst case test margin was 20.68 dB below the accepted limit at 1891.46MHz

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

The 802.11b/g/n harmonics were investigated up to the 10th harmonic. The worst case test margin was 5.41 dB below the accepted limit at 2396.54MHz. See APPENDIX 2 for the test data.

b) Band-Edge Compliance of RF Radiated Emissions

The BlackBerry<sup>®</sup> smartphone met the requirements for band-edge compliance of RF radiated emissions for Bluetooth, Bluetooth Low Energy and 802.11b/g/n as per the requirements of 15.247, 15.209, and RSS-210/RSS-GEN.

#### Measurement Uncertainty ±4.5 dB

See APPENDIX 2 for the test data

3) i) BLUETOOTH RF CONDUCTED EMISSIONS

The Bluetooth conducted RF emissions from the BlackBerry<sup>®</sup> smartphone were measured using the methods outlined in FCC CFR 47 Part 15, Subpart C.

a) 20 dB Bandwidth

The BlackBerry<sup>®</sup> smartphone met the requirements of the 20 dB bandwidth as per 47 CFR 15.247(a) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured. The result includes both normal data rate and EDR. The worst case 20 dB Bandwidth was 0.922 MHz for channels 39 and 78 in normal data rate mode and 1.332MHz for channel 39 in EDR mode. See APPENDIX 3 for the test data.

b) Carrier Frequency Separation

The BlackBerry<sup>®</sup> smartphone met the requirements of the carrier frequency separation as per 47 CFR 15.247(a) and RSS-210. Channel 38 to 39 was measured. The result includes both normal data rate and EDR. See APPENDIX 3 for the test data.

- Number of Hopping Frequencies The BlackBerry<sup>®</sup> smartphone met the requirements of the number of hopping frequencies as per 47 CFR 15.247(a) and RSS-210. The number of hopping channels measured was 79. See APPENDIX 3 for the test data.
- d) Time of Occupancy (Dwell Time) The EUT met the requirements of the dwell time as per 47 CFR 15.247(a) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured in DH1, DH3 and DH5 modes. Bluetooth was operating in frequency hopping (Euro/US) mode during the measurements. See APPENDIX 3 for the test data.

Testing Services™	EMI Test Report for the BlackBerry $^{ extsf{B}}$ smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

- e) Maximum Peak Conducted Output Power The BlackBerry<sup>®</sup> smartphone met the requirements of the maximum peak conducted output power as per 47 CFR 15.247(b) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured. The result includes both normal data rate and EDR. The worst case Conducted Output Power level was 10.00 dBm (0.010 W) for Channel 39 in normal data rate mode and 9.00 dBm (0.00794 W) for channel 39 in EDR mode. See APPENDIX 3 for the test data.
- f) Band-Edge Compliance of RF Conducted Emissions The BlackBerry® smartphone met the requirements of the band-edge compliance of RF conducted emissions as per 47 CFR 15.247(d) and RSS-210. Channels 0 and 78 were measured in frequency hopping (Euro/US) mode and single frequency mode. The result includes both normal data rate and EDR. See APPENDIX 3 for the test data.
- g) Spurious RF Conducted Emissions The BlackBerry<sup>®</sup> smartphone met the requirements of the spurious RF conducted emissions as per 47 CFR 15.247(d) and RSS-210. The frequency range measured was 10 MHz to 26 GHz. Low channel (0), middle channel (39) and high channel (78) were measured in single frequency mode and frequency hopping (Euro/US) mode. The result includes both normal data rate and EDR. See APPENDIX 3 for the test data.
- 4) ii) BLUETOOTH LOW ENERGY RF CONDUCTED EMISSIONS

The Bluetooth Low Energy conducted RF emissions from the BlackBerry<sup>™</sup> smartphone were measured using the methods outlined in FCC CFR 47 Part 15, Subpart C.

a) 6dB Bandwidth

The EUT met the requirements of the 6 dB bandwidth as per 47 CFR 15.247(a) and RSS-210. Low channel (0), middle channel (20) and high channel (39) were measured. The worst case 6 dB Bandwidth was 0.705 MHz for channes 0 and 39.

See APPENDIX 3 for the test data.

b) Maximum Conducted Output Power

The EUT met the requirements of the maximum conducted output power as per 47 CFR 15.247(b) and RSS-210. Low channel (0), middle channel (20) and high channel (39) were measured. The worst case Conducted Output Power level was 3.94 dBm (0.00248W) for channel 20.

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

See APPENDIX 3 for the test data

- c) Band-Edge Compliance of RF Conducted Emissions The EUT met the requirements of band-edge compliance of RF conducted emissions as per 47 CFR 15.247(d) and RSS-210. Low channel (0) and high channel (39) were measured. See APPENDIX 3 for the test data.
- d) Peak Power Spectral Density The EUT met the requirements of peak power spectral density as per 47 CFR 15.247(e) and RSS-210. Low channel (0), middle channel (20) and high channel (39) were measured. See APPENDIX 3 for the test data.
- e) Spurious RF Conducted Emissions The EUT met the requirements of the spurious RF conducted emissions as per 47 CFR 15.247(d) and RSS-210. The frequency range measured was 30 MHz to 26 GHz. Low channel (0), middle channel (20) and high channel (39) were measured.

See APPENDIX 3 for the test data.

4) 802.11b/g/n RF CONDUCTED EMISSIONS

The 802.11b/g/n conducted RF emissions from the BlackBerry<sup>®</sup> smartphone were measured using the methods outlined in FCC CFR 47 Part 15, Subpart C.

a) 6dB Bandwidth

The EUT met the requirements of the 6 dB bandwidth as per 47 CFR 15.247(a) and RSS-210. Low channel (1), middle channel (6) and high channel (11) were measured. The worst case 6 dB Bandwidth was 8.39 MHz for channels 1 and 6 in 802.11b mode, 16.35 MHz for channels 1 and 6 in 802.11g mode, and 17.44 MHz for channels 6 and 11 in 802.11n mode. See APPENDIX 5 for the test data.

b) Maximum Conducted Output Power

The EUT met the requirements of the maximum conducted output power as per 47 CFR 15.247(b) and RSS-210. Low channel (1), middle channel (6) and high channel (11) were measured. The worst case Conducted Output Power level was 19.19 dBm (0.083W) for channel 11 in 802.11b mode, 18.65 dBm (0.073W) for channel 11 in 802.11g mode, and 18.67 dBm (0.074W) for channel 11 in 802.11n mode.

See APPENDIX 5 for the test data

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

- c) Band-Edge Compliance of RF Conducted Emissions The EUT met the requirements of band-edge compliance of RF conducted emissions as per 47 CFR 15.247(b) and RSS-210. Low channel (1) and high channel (11) were measured. See APPENDIX 5 for the test data
- d) Peak Power Spectral Density The EUT met the requirements of peak power spectral density as per 47 CFR 15.247(e) and RSS-210. Low channel (1), middle channel (6) and high channel (11) were measured. See APPENDIX 5 for the test data.
- e) Spurious RF Conducted Emissions The EUT met the requirements of the spurious RF conducted emissions as per 47 CFR 15.247(d) and RSS-210. The frequency range measured was 30 MHz to 26 GHz. Low channel (1), middle channel (6) and high channel (11) were measured.

See APPENDIX 5 for the test data.

7) Near Field Communications (NFC)

The Near Field Communications emissions from the BlackBerry<sup>®</sup> smartphone were measured using the methods outlined in FCC CFR 47 Part 15, Subpart C.

a) Radiated Emissions

The BlackBerry<sup>®</sup> smartphone was measured in standalone configuration transmitting at 13.56 MHz. The system's radiated emission levels were compared with respect to the FCC CFR 47 Part 15 Subpart C, 15.209, 15.225(a) and RSS-210/RSS-GEN.

The NFC emissions were investigated from 9 kHz to 1 GHz. The sample EUT has a field strength measurement of 50.46 dBuV/m. See APPENDIX 5 for the test data.

b) Occupied Bandwidth

The EUT met the requirements of the Occupied bandwidth as per 47 CFR 15 C 15.225(e) and RSS-210. The EUT was measured in test mode with modulation on and transmitting at 13.56 MHz. See APPENDIX 5 for the test data.

c) Frequency Stability

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

The EUT met the requirements of the Frequency Stability as per 47 CFR 15.225(e) and RSS-210. The EUT was measured in test mode with modulation on and transmitting at 13.56 MHz. See APPENDIX 5 for the test data.

### G. Compliance Test Equipment Used

<u>UNIT</u>	MANUFACTURER	MODEL	<u>SERIAL</u> NUMBER	CAL DUE DATE (YY MM DD)	<u>USE</u>	
EMI Test Receiver	Rohde & Schwarz	ESIB 40	100255	13-11-30	Conducted/Radiated Emissions	
EMI Test Receiver	Rohde & Schwarz	ESU 40	100162	13-11-30	Conducted/Radiated Emissions	
Hybrid Log Antenna	EMC Automation	HLP-3003C	017301	13-08-23	Radiated Emissions	
Horn Antenna	СМТ	3116	R52734-001	14-08-02	Radiated Emissions	
Horn Antenna	ETS-Lindgren	3117	2538	13-08-04	Radiated Emissions	
Preamplifier	Rohde & Schwarz	TS-ANA4-SP	001	13-09-01	Radiated Emissions	
Preamplifier	Sonoma	310N/11909A	185831	13-10-10	Radiated Emissions	
Preamplifier	Rohde & Schwarz	TS-ANA-SP	001	13-09-01	Radiated Emissions	
L.I.S.N.	Rohde & Schwarz	ENV216	100060	13-10-25	Conducted Emissions	
Environment Monitor	Omega	iTHX-SD	0380561	13-10-30	Radiated Emissions	
EMC Analyzer	Agilent	E7405A	US40240226	14-01-15	Radiated Emissions	
Spectrum Analyzer	HP	8563E	3745A08113	13-10-05	RF Conducted Emissions	
DC Power Supply	HP	6632B	US37472178	13-09-25	RF Conducted Emissions	
Environment Monitor	Omega	iTHX-SD	0340060	13-10-30	RF Conducted Emissions	
Environmental Chamber	Test Equity	107	0900246	N/R	Frequency Stability	
Bluetooth Tester	Rohde & Schwarz	СВТ	119549	13-12-04	RF Conducted Emissions	
Bluetooth Tester	Rohde & Schwarz	CBT35	100368	13-12-04	Radiated Emissions	
Bluetooth Tester	Rohde & Schwarz	CBT35	100370	13-12-04	Radiated Emissions	
Power Meter	Agilent	N1911A	MY45100951	13-08-16	RF Conducted / Frequency Stability	
Power Sensor	Agilent	N1921A	MY45241383	13-09-11	RF Conducted / Frequency Stability	
Digital Multimeter	Hewlett Packard	34401A	US36042324	13-11-13	Conducted/Radiated Emissions	
Environment Monitor	Omega	iTHX-SD	0380567	13-10-30	Radiated Emissions	

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services**	APPENDIX 1		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### **APPENDIX 1 – AC CONDUCTED EMISSIONS TEST DATA/PLOTS**

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 1		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

#### AC Conducted Emission Test Results

The following tests were performed by Mahmood Ahmed

The tests were performed on model RFS121LW

#### Test Configuration 1

The BlackBerry<sup>®</sup> smartphone was tested on March 08, 2013

The environmental test conditions were: Temperature: 24.8 °C Relative Humidity: 21.9 %

Frequency	Line	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit (QP)	Limit (AV)	Margin (QP) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)
0.182	L1	23.44	10.99	34.43	57.40	47.40	-22.97
0.209	Ν	24.73	10.82	35.55	56.00	46.00	-20.45
0.420	L1	27.81	9.98	37.80	56.00	46.00	-18.21
1.370	L1	31.59	9.80	41.39	57.30	47.30	-15.91
1.379	Ν	27.66	9.81	37.47	56.00	46.00	-18.53
2.738	Ν	23.04	9.87	32.91	56.00	46.00	-23.09

All other emission levels were at least 25 dB below the limit.

Measurements were done with the quasi-peak detector.

See figure 1-1 and figure 1-2 for the measurement plot of the L1 and N lines of AC power line conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	<b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emissions Test Graphs

#### Test Configuration 1

#### Figure 1-1: L1 lines



Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emission Test Results cont'd

Test Configuration 2

The BlackBerry<sup>®</sup> smartphone was tested on March 08, 2013

The environmental test conditions were: Temperature: 25.1°C 23 % Relative Humidity:

Frequency	Line	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit (QP)	Limit (AV)	Margin (QP) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)
0.168	L1	30.85	11.08	41.93	65.10	55.10	-23.17
0.726	L1	25.80	9.83	35.63	56.00	46.00	-20.38
0.794	Ν	25.17	9.82	35.00	56.00	46.00	-21.01
0.938	L1	30.24	9.81	40.05	56.00	46.00	-15.96
0.951	Ν	25.42	9.81	35.23	56.00	46.00	-20.77
1.104	Ν	25.23	9.81	35.04	56.00	46.00	-20.96
1.190	Ν	25.89	9.80	35.69	56.00	46.00	-20.31
1.194	L1	30.91	9.80	40.71	56.00	46.00	-15.29
1.320	L1	30.76	9.80	40.56	56.00	46.00	-15.44
1.383	Ν	24.77	9.81	34.58	56.00	46.00	-21.42
2.099	Ν	28.27	9.83	38.10	56.00	46.00	-17.90
2.112	L1	33.17	9.83	43.00	56.00	46.00	-13.00
2.148	Ν	28.12	9.83	37.95	56.00	46.00	-18.05
2.211	Ν	27.47	9.84	37.30	56.00	46.00	-18.70
2.270	L1	33.70	9.84	43.53	56.00	46.00	-12.47
3.764	L1	25.29	9.90	35.18	56.00	46.00	-20.82

All other emission levels were at least 25 dB below the limit.

Measurements were done with the quasi-peak detector

See figure 1-3 and figure 1-4 for the measurement plot of the L1 and N lines of AC power line conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	<b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emissions Test Graphs

### Test Configuration 2

#### Figure 1-3: L1 lines



Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emissions Test Results cont'd

Test Configuration 3

The BlackBerry<sup>®</sup> smartphone was tested on March 08, 2013

The environmental test conditions were: Temperature:25.1°CRelative Humidity:23 %

Frequency	Line	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit (QP)	Margin (QP) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dB)
0.186	L1	37.01	10.95	47.97	64.20	-16.23
0.420	L1	36.59	9.98	46.57	57.40	-10.83
0.425	Ν	36.89	9.98	46.88	57.40	-10.53
0.434	L1	35.51	9.96	45.47	57.20	-11.73
0.515	Ν	36.66	9.91	46.57	56.00	-9.43
0.614	L1	31.67	9.85	41.53	56.00	-14.47
0.969	Ν	34.13	9.81	43.94	56.00	-12.06
0.974	L1	32.82	9.80	42.62	56.00	-13.38
1.064	Ν	33.45	9.81	43.26	56.00	-12.74
1.199	L1	33.43	9.80	43.23	56.00	-12.77
2.108	Ν	32.79	9.83	42.62	56.00	-13.38
2.117	L1	33.11	9.83	42.94	56.00	-13.06
2.351	Ν	34.17	9.84	44.02	56.00	-11.98
2.423	L1	33.35	9.85	43.20	56.00	-12.80
3.539	L1	31.08	9.89	40.97	56.00	-15.03
3.656	Ν	31.91	9.90	41.80	56.00	-14.20
3.732	L1	30.36	9.89	40.25	56.00	-15.75
4.695	Ν	31.18	9.91	41.09	56.00	-14.91

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services™	<b>APPENDIX 1</b>			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emissions Test Results cont'd

### Test Configuration 3 cont'd

Frequency	Line	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit (AV)	Margin (AV) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dB)
0.186	L1	27.21	10.95	38.16	44.20	-16.04
0.420	L1	31.30	9.98	41.28	37.40	-6.12
0.425	Ν	31.08	9.98	41.07	37.40	-6.34
0.434	L1	26.93	9.96	36.90	37.20	-10.31
0.515	Ν	29.15	9.91	39.06	36.00	-6.95
0.614	L1	23.88	9.85	33.73	36.00	-12.27
0.969	Ν	20.32	9.81	30.13	36.00	-15.87
0.974	L1	19.02	9.80	28.83	36.00	-17.17
1.064	Ν	20.71	9.81	30.52	36.00	-15.48
1.199	L1	26.99	9.80	36.79	36.00	-9.21
2.108	Ν	26.02	9.83	35.85	36.00	-10.15
2.117	L1	26.56	9.83	36.39	36.00	-9.61
2.351	Ν	28.43	9.84	38.27	36.00	-7.73
2.423	L1	27.28	9.85	37.13	36.00	-8.88
3.539	L1	25.49	9.89	35.38	36.00	-10.62
3.656	N	26.20	9.90	36.10	36.00	-9.90
3.732	L1	24.77	9.89	34.67	36.00	-11.34
4.695	N	25.42	9.91	35.33	36.00	-10.67

All other emission levels were at least 25 dB below the limit.

Measurements were done with the quasi-peak and average detectors

See figure 1-5 for the measurement plot of the L1 and N lines of AC power line conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	<b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emissions Test Graphs

#### **Test Configuration 3**

#### Figure 1-5: L1 Lines







Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 1</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### AC Conducted Emission Test Results cont'd

### Test Configuration 4

The BlackBerry<sup>®</sup> smartphone was tested on April 25, 2013

The environmental test conditions were: Temperature:26.8 °CRelative Humidity:34.2 %

Frequency	Line	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit (QP)	Margin (QP) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dB)
0.173	L1	37.25	11.05	48.30	64.80	-16.50
0.177	Ν	33.58	11.05	44.63	57.60	-12.97
0.411	L1	36.28	9.99	46.28	56.00	-9.72
0.411	Ν	36.88	10.01	46.89	56.00	-9.11
0.510	L1	36.24	9.90	46.14	56.00	-9.86
0.519	Ν	36.56	9.91	46.46	56.00	-9.54
0.960	Ν	34.69	9.81	44.51	56.00	-11.49
0.965	L1	33.59	9.81	43.40	56.00	-12.61
1.064	L1	32.27	9.80	42.07	56.00	-13.93
1.185	Ν	34.86	9.80	44.67	60.00	-15.33
1.397	Ν	32.41	9.81	42.22	64.60	-22.39
2.085	L1	33.39	9.83	43.21	57.60	-14.39
2.328	L1	33.99	9.84	43.83	56.00	-12.17
2.346	Ν	34.02	9.84	43.87	56.00	-12.13
3.692	Ν	31.56	9.90	41.45	56.00	-14.55
3.696	L1	30.70	9.89	40.60	56.00	-15.41
4.565	Ν	31.17	9.91	41.08	56.00	-14.92
4.754	L1	29.45	9.90	39.35	56.00	-16.65
16.040	Ν	24.81	10.12	34.93	56.00	-21.07

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	<b>APPENDIX 1</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Frequency	Line	Reading (AV	Correction Factor	Corrected Reading (AV)	Limit (AV)	Margin (AV) Limits
(MHz)		(dBµV)	(dB)	(dB)	(dBµV)	(dB)
0.173	L1	25.78	11.05	36.83	44.80	-17.97
0.177	Ν	26.81	11.05	37.86	37.60	-9.74
0.411	L1	28.43	9.99	38.42	36.00	-7.58
0.411	Ν	29.66	10.01	39.66	36.00	-6.34
0.510	L1	29.10	9.90	39.00	36.00	-7.00
0.519	Ν	27.25	9.91	37.16	36.00	-8.84
0.960	Ν	21.57	9.81	31.38	36.00	-14.62
0.965	L1	20.35	9.81	30.16	36.00	-15.84
1.064	L1	19.70	9.80	29.50	36.00	-16.50
1.185	Ν	28.07	9.80	37.87	40.00	-12.13
1.397	Ν	23.07	9.81	32.87	44.60	-21.73
2.085	L1	26.26	9.83	36.08	37.60	-11.52
2.328	L1	28.39	9.84	38.23	36.00	-7.77
2.346	Ν	28.33	9.84	38.17	36.00	-7.83
3.692	Ν	25.87	9.90	35.76	36.00	-10.24
3.696	L1	25.12	9.89	35.01	36.00	-10.99
4.565	Ν	25.43	9.91	35.34	36.00	-10.66
4.754	L1	23.88	9.90	33.79	36.00	-12.22
16.040	Ν	17.59	10.12	27.71	36.00	-18.29

All other emission levels were at least 25 dB below the limit.

Measurements were done with the quasi-peak and the average detectors.

See figure 1-6 and figure 1-7 for the measurement plot of the L1 and N lines of AC power line conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services™	APPENDIX 1				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

### AC Conducted Emissions Test Graphs

#### Test Configuration 4

#### Figure 1-7: L1 lines



Figure 1-8: N Lines



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LV			
Services <sup>**</sup>	APPENDIX 2			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

### APPENDIX 2 – BLUETOOTH, BLUETOOTH LOW ENERGY AND 802.11b/g/n **RADIATED EMISSIONS TEST DATA**

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services**	<b>APPENDIX 2</b>				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

# **Radiated Emissions Test Results**

### Bluetooth Band

The tests were performed on model RFS121LW

Date of Test: March 07, 2013 Measurements were performed by Savtej Sandhu

25.9 °C The environmental test conditions were: Temperature: Relative Humidity: 18.1 %

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 30 MHz to 1 GHz.

The BlackBerry<sup>®</sup> smartphone in Bluetooth Tx mode was in horizontal position.

The frequency sweep measurements were performed in single frequency mode on channels 0, 39 and 78 using packet types "DH5", "2-DH5" and "3-DH5".

All emission levels were at least 25 dB below the limit.

Radiated Emissions Test Results cont'd Bluetooth Band cont'd

Date of Test: March 11-15, 27, 2013 Measurements were performed by Mahmood Ahmed

The environmental test conditions were	: Temperature:	24.8-25.8⁰C
	Relative Humidity:	17.5-31.1 %

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 1GHz to 25GHz.

The BlackBerry<sup>®</sup> smartphone in Bluetooth Tx mode was in horizontal down position.

The frequency sweep measurements were performed in single frequency mode on channels 0, 39 and 78 using packet types "DH5", "2-DH5" and "3-DH5".

All emission levels were at least 25 dB below the limit.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services <sup>**</sup>	<b>APPENDIX 2</b>				
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

#### Band-Edge Compliance of RF Radiated Emissions Test Results Bluetooth Band

Date of test: March 12, 2013 Measurements were performed by Feras Obeid

The environmental test conditions were: Temperature:	25.0 º C
Relative Humidity:	17.8%

The BlackBerry<sup>®</sup> smartphone was in standalone, horizontal position and pattern type "Static PBRS" in "<u>DH5</u>", "<u>2-DH5</u>" and "<u>3-DH5</u>" modulation during the measurements.

The test distance was 3.0 metres.

Channel	Freq.	Rx Ante	enna	Detector	VBW	Corrected Reading	Delta Marker	Corrected Band edge	Limit	Diff. To Limit
	(MHz)	Туре	POL.			(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
Low Cha	nnel, Pac	ket Type I	DH5				1		1	
0	2402	Horn	V	PK	1 MHz	96.27	51.49	44.78	74	-29.22
0	2402	Horn	н	PK	1 MHz	108.03	63.25	44.78	74	-29.22
0	2402	Horn	V	AVE.	10 Hz	90.29	51.49	38.8	54	-15.2
0	2402	Horn	Н	AVE.	10 Hz	101.1	63.25	37.85	54	-16.15
High Cha	annel, Pac	ket Type	DH5				-			
78	2480	Horn	V	PK	1 MHz	99.04	53.87	45.17	74	-28.83
78	2480	Horn	Н	PK	1 MHz	108.79	63.81	44.98	74	-29.02
78	2480	Horn	V	AVE.	10 Hz	92.04	53.87	38.17	54	-15.83
78	2480	Horn	н	AVE.	10 Hz	101.74	63.81	37.93	54	-16.07
Low Cha	nnel, Pac	ket Type 2	2-DH5			1				
0	2402	Horn	V	PK	1 MHz	95.41	50.64	44.77	74	-29.23
0	2402	Horn	н	PK	1 MHz	107.22	62.48	44.74	74	-29.26
0	2402	Horn	V	AVE.	10 Hz	81.59	50.64	30.95	54	-23.05
0	2402	Horn	Н	AVE.	10 Hz	92.14	62.48	29.66	54	-24.34
High Cha	High Channel, Packet Type 2-DH5									
78	2480	Horn	V	PK	1 MHz	97.93	52.68	45.25	74	-28.75
78	2480	Horn	н	PK	1 MHz	107.65	61.21	46.44	74	-27.56
78	2480	Horn	V	AVE.	10 Hz	82.83	52.68	30.15	54	-23.85
78	2480	Horn	Н	AVE.	10 Hz	92.45	61.21	31.24	54	-22.76

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services <sup>**</sup>	<b>APPENDIX 2</b>				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

### Band-Edge Compliance of RF Radiated Emissions Test Results cont'd Bluetooth Band

Channel	Freq.	Rx Ante	enna	Detector	VBW	Corrected Reading	Delta Marker	Corrected Band edge	Limit	Diff. To Limit
	(MHz)	Туре	POL.			(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
Low Cha	innel, Pac	ket Type :	3-DH5	-		-	-	-	-	
0	2402	Horn	V	PK	1 MHz	95.53	50.94	44.59	74	-29.41
0	2402	Horn	н	PK	1 MHz	107.31	61.97	45.34	74	-28.66
0	2402	Horn	V	AVE.	10 Hz	87.04	50.94	36.1	54	-17.9
0	2402	Horn	Н	AVE.	10 Hz	97.45	61.97	35.48	54	-18.52
High Cha	annel, Pac	ket Type	3-DH5							
78	2480	Horn	V	PK	1 MHz	98.19	52.91	45.28	74	-28.72
78	2480	Horn	н	PK	1 MHz	107.82	60.14	47.68	74	-26.32
78	2480	Horn	V	AVE.	10 Hz	88.24	52.91	35.33	54	-18.67
78	2480	Horn	н	AVE.	10 Hz	97.87	60.14	37.73	54	-16.27

See figures 2-1 to 2-12 for the plots of the Bluetooth band-edge compliance.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services™	<b>APPENDIX 2</b>				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

#### Bluetooth Band-Edge Compliance of RF Radiated Emissions cont'd

Figure 2-1: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, DH5, Channel 0, Pol: V, Detector: PK



Figure 2-3: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, DH5, Channel 78, Pol: V, Detector: PK









Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services**	<b>APPENDIX 2</b>				
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

#### Bluetooth Band-Edge Compliance of RF Radiated Emissions cont'd

Figure 2-5: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, 2-DH5, Channel 0, Pol: V, Detector: PK









Figure 2-8: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, 2-DH5, Channel 78, Pol: H, Detector: PK



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW					
Services™	<b>APPENDIX 2</b>					
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW				
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW				

#### Bluetooth Band-Edge Compliance of RF Radiated Emissions cont'd

Figure 2-9: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, 3-DH5, Channel 0, Pol: V, Detector: PK









Figure 2-12: Band-Edge Compliance of RF Rad. Emissions. Bluetooth, Single freq., Static PBRS, 3-DH5, Channel 78, Pol: H, Detector: PK



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW					
Services**	<b>APPENDIX 2</b>					
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW				
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW				

#### Radiated Emissions Test Results cont'd Bluetooth Low Energy Band

Date of Test: March 07, 2013 Measurements were performed by Feras Obeid.

The environmental test conditions were: Temperature:	25.9 ⁰C
Relative Humidity:	18.1 %

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 30 MHz to 1 GHz.

The BlackBerry<sup>®</sup> smartphone in Bluetooth Low Energy Tx mode was in horizontal position.

The frequency sweep measurements were performed in single frequency mode on channels 0, 20 and 39.

All emissions had a test margin of greater than 25.0 dB.

Date of Test: March 12-27, 2013

Measurements were performed by Mahmood Ahmed

The environmental test conditions were: Temperature:	25.0-25.8°C
Relative Humidit	y: 21.3-31.1%

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 1GHz to 25GHz.

The BlackBerry<sup>®</sup> smartphone in Bluetooth Low Energy Tx mode was in horizontal down position.

The frequency sweep measurements were performed in single frequency mode on channels 0, 20 and 39.

Frequency	Channel	Ant	tenna	Test	Detector	Detector Measured Corr		Field Strength Level	Limit @	Test
	Occurrenc	Pol.	Height	Angle		Levei	preamp/antenna/	(reading+corr)	3.0 m	Margin
(MHz)	е	(V/H)	(meters)	(Deg.)	(PK or QP)	(dBµV)	(dB)	(dBm)	(dBm)	(dB)
1891.46	0	V	100	326	QP	14.207	19.11	33.317	54	-20.68
1885.14		V	250	169	QP	11.893	21.11	33.003	54	-20.99

All other emission levels were at least 25 dB below the limit.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW					
Services <sup>**</sup>	<b>APPENDIX 2</b>					
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW				
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW				

### Band-Edge Compliance of RF Radiated Emissions Test Results Bluetooth Low Energy Band

Date of test: March 12, 2013 Measurements were performed by Feras Obeid.

The environmental test conditions were: Temperature:					
Relative Humi	idity: 17.8 %				

The BlackBerry<sup>®</sup> smartphone was in horizontal position.

The test distance was 3.0 metres.

Channel	Freq.	Rx Ante	enna	Detector	VBW	Corrected Reading	Delta Marker	Corrected Band edge	Limit	Diff. To Limit
	(MHz)	Туре	POL.			(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
Low Cha	nnel, LE	-				-				
0	2402	Horn	V	PK	1 MHz	92.79	48	44.79	74	-29.21
0	2402	Horn	н	PK	1 MHz	104.04	60.51	43.53	74	-30.47
0	2402	Horn	V	AVE.	10 Hz	75.64	48	27.64	54	-26.36
0	2402	Horn	н	AVE.	10 Hz	86.84	60.51	26.33	54	-27.67
High Cha	annel, LE		_							
78	2480	Horn	V	PK	1 MHz	92.47	47.53	44.94	74	-29.06
78	2480	Horn	н	PK	1 MHz	104.17	59.34	44.83	74	-29.17
78	2480	Horn	V	AVE.	10 Hz	75.1	47.53	27.57	54	-26.43
78	2480	Horn	Н	AVE.	10 Hz	87.08	59.34	27.74	54	-26.26

See figures 2-13 to 2-16 for the plots of the Bluetooth Low Energy band-edge compliance.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW					
Services™	<b>APPENDIX 2</b>					
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW				
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW				

#### Bluetooth Low Energy Band-Edge Compliance of RF Radiated Emissions cont'd

Figure 2-13: Band-Edge Compliance of RF Rad. Emissions. Bluetooth Low Energy, Single freq., LE, Channel 0, Pol: V, Detector: PK



Figure 2-15: Band-Edge Compliance of RF Rad. Emissions. Bluetooth Low Energy, Single freq.,










Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 2</b>							
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW						
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW						

# Radiated Emissions Test Results cont'd 802.11b/g/n Band

Date of Test: March 06, 2013 Measurements performed by Berkin Can

The environmental test conditions were: Temperature:25.5 °CRelative Humidity:16.2%

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 30 MHz to 1 GHz.

The BlackBerry<sup>®</sup> smartphone was in USB up position.

The frequency sweep measurements were performed in 802.11b Tx mode at 1 Mbps on channels 1, 6 and 11, in 802.11g Tx mode at 6 Mbps on channels 1, 6 and 11, and in 802.11n Tx mode at MCS 0 on channels 1, 6 and 11.

All other emission levels were at least 25 dB below the limit

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 2							
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW						
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW						

# Radiated Emissions Test Results cont'd 802.11b/g/n Band

Date of Test: March 12-15, 28, 2013 Measurements performed by Mahmood Ahmed

The environmental test conditions were:	Temperature:	24.1-25.7 °C
I	Relative Humidity:	17.1-23.3%

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 1GHz to 25GHz.

The BlackBerry<sup>®</sup> smartphone was in horizontal position.

The frequency sweep measurements were performed in 802.11b Tx mode at 1 Mbps on channels 1, 6 and 11, in 802.11g Tx mode at 6 Mbps on channels 1, 6 and 11, and in 802.11n Tx mode at MCS 0 on channels 1, 6 and 11.

All emissions levels were at least 25dB below the limits.

Frequency	Channel Of	Ant Pol.	tenna Height	Test Angle	Detector	Measured Level	Correction Factor for preamp/antenna/	Field Strength Level (reading+corr)	Limit @ 3.0 m	Test Margin
(MHz)	e	(V/H)	(meters)	(Deg.)	(PK or QP)	(dBµV)	cables/ filter (dB)	(dBm)	(dBm)	(dB)
2394.90	6B	Н	1.00	0	PK	53.88	9.03	62.91	74.00	-11.09
2398.82	6B	H	1.00	352	PK	34.01	9.01	43.02	54.00	-10.98
2399.50	11B	Н	1.00	0	PK	50.62	9.00	59.63	74.00	-14.37
2397.99	11B	H	1.00	0	PK	29.71	9.01	38.72	54.00	-15.28
2397.81	6G	Н	1.00	349	PK	52.70	9.01	61.71	74.00	-12.29
2396.54	6G	Н	3.00	224	PK	39.57	9.02	48.59	54.00	-5.41
2400.14	11G	Н	3.00	228	PK	50.51	9.00	59.51	74.00	-14.49
2399.37	11G	Н	3.00	219	PK	32.13	9.00	41.13	54.00	-12.87
4809.21	1N	V	4.00	202	PK	42.55	19.24	61.79	74.00	-12.21
4809.46	1N	V	4.00	201	PK	28.17	19.24	47.41	54.00	-6.59
2400.69	6N	Η	1.00	226	PK	53.22	9.00	62.22	74.00	-11.78
2396.80	6N	Н	3.00	218	PK	39.13	9.02	48.14	54.00	-5.86

All other emission levels were at least 25 dB below the limit.

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 2</b>							
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW						
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW						

# 802.11b/g/n Band-Edge Compliance of RF Radiated Emissions

Date of Tests: February 25, 2013 Measurements performed by Savtej Sandhu.

The environmental test conditions were: Temperature:	24 °C
Relative Humidity:	34 %

#### 802.11b Band

The measurements were performed on BlackBerry® smartphone in standalone, USB up configuration on channels 1 and 11 for 802.11b mode at 1 Mbps.

The test distance was 3 metres.

						Carrier	Peak				
				Detec		Freq	Corrected	Delta	Corrected		Diff. To
Channel	Freq.	Rx An	tenna	tor	VBW	Reading	Reading	Marker	Band edge	Limit	Limit
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
1	2412.00	Horn	V	PK	1 MHz	98.52	108.34	54.57	53.77	74.00	-20.23
1	2412.00	Horn	Н	PK	1 MHz	100.25	110.07	54.97	55.10	74.00	-18.90
1	2412.00	Horn	V	AV	10 Hz	95.21	105.03	65.71	39.32	54.00	-14.68
1	2412.00	Horn	Н	AV	10 Hz	96.16	105.98	66.66	39.32	54.00	-14.68

						Carrier	Peak				
Channel	Freq	Rv Δn	tonna	Detec	\/R\//	Freq Reading	Corrected Reading	Delta Marker	Corrected	Limit	Diff. To
Channel	rieq.		lenna	101	VDVV	Reduing	Reading	Marker	Danu euge	LIIIII	LIIIII
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
11	2462.00	Horn	V	PK	1MHz	94.14	103.89	48.11	55.78	74.00	-18.22
11	2462.00	Horn	Н	PK	1MHz	98.49	109.51	49.34	60.17	74.00	-13.83
11	2462.00	Horn	V	AV	10 Hz	90.78	100.73	57.55	43.18	54.00	-10.82
11	2462.00	Horn	Н	AV	10 Hz	95.3	106.27	57.07	49.20	54.00	-4.80

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW							
Services™	<b>APPENDIX 2</b>							
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW						
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW						

# 802.11g Band

The measurements were performed on the BlackBerry<sup>®</sup> smartphone in standalone, USB up configuration on channels 1 and 11 for 802.11g mode at 6 Mbps.

The test distance was 3 metres.

						Carrier	Peak				
Channel	Freq.	Rx An	tenna	Detec tor	VBW	Freq Reading	Corrected Reading	Delta Marker	Corrected Band edge	Limit	Diff. To Limit
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
1	2412.00	Horn	V	PK	1 MHz	101.73	111.55	47.59	63.96	74.00	-10.04
1	2412.00	Horn	Н	PK	1 MHz	100.93	110.75	48.52	62.23	74.00	-11.77
1	2412.00	Horn	V	AV	10 Hz	90.54	100.36	56.83	43.53	54.00	-10.47
1	2412.00	Horn	Н	AV	10 Hz	89.69	99.51	56.67	42.84	54.00	-11.16

						Carrier	Peak				
				Detec		Freq	Corrected	Delta	Corrected		Diff. To
Channel	Freq.	Rx An	tenna	tor	VBW	Reading	Reading	Marker	Band edge	Limit	Limit
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
11	2462.00	Horn	V	PK	1 MHz	96.13	107.05	47.76	59.29	74.00	-14.71
11	2462.00	Horn	Н	PK	1 MHz	102.46	113.38	47.84	65.54	74.00	-8.46
11	2462.00	Horn	V	AV	10 Hz	88.53	99.45	55.51	43.94	54.00	-10.06
11	2462.00	Horn	Н	AV	10 Hz	90.91	101.83	52.63	49.20	54.00	-4.80

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 2</b>							
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW						
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW						

# 802.11n Band

The measurements were performed on the BlackBerry<sup>®</sup> smartphone in standalone, USB up configuration on channels 1 and 11 for 802.11n mode at MCS 0.

The test distance was 3 metres.

Channel	Freq.	Rx An	tenna	Detec tor	VBW	Carrier Freq Reading	Peak Corrected Reading	Delta Marker	Corrected Band edge	Limit	Diff. To Limit
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
1	2412.00	Horn	V	PK	1MHz	92.17	101.99	48.56	53.43	74.00	-20.57
1	2412.00	Horn	Н	PK	1MHz	98	107.82	48.96	58.86	74.00	-15.14
1	2412.00	Horn	V	AV	10 Hz	82.59	92.41	54.25	38.16	54.00	-15.84
1	2412.00	Horn	Н	AV	10 Hz	88.12	97.94	55.86	42.08	54.00	-11.92

						Carrier	Peak				
Channel	Гтал		toono	Detec		Freq	Corrected	Delta	Corrected	Linsit	Diff. To
Channel	Freq.	KX AII	lenna	loi	VDVV	Reading	Reading	warker	banu euge	LITTIL	LIMIL
	(MHz)	Туре	POL.			(dBuV)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
11	2462.00	Horn	V	PK	1 MHz	93.43	104.35	46.65	57.70	74.00	-16.30
11	2462.00	Horn	Н	PK	1 MHz	97.66	108.58	47.18	61.40	74.00	-12.60
11	2462.00	Horn	V	AV	10 Hz	82.94	93.86	51.51	42.35	54.00	-11.65
11	2462.00	Horn	Н	AV	10 Hz	87.32	98.24	52.96	45.28	54.00	-8.72

See figures 2-17 to 2-20 for the plots of the 802.11b band-edge compliance. See figures 2-21 to 2-24 for the plots of the 802.11g band-edge compliance. See figures 2-25 to 2-28 for the plots of the 802.11n band-edge compliance.

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 2</b>		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

## 802.11b/g/n Band-Edge Compliance of RF Radiated Emissions cont'd





Figure 2-18: Band-Edge Compliance of RF Radiated Emission 802.11b, Channel 1, 2412 MHz, Max Pol: H,



Figure 2-19: Band-Edge Compliance of RF Radiated Emission 802.11b, Channel 11, 2462 MHz, Max Pol: V, **Detector: PK** 

Figure 2-20: Band-Edge Compliance of RF Radiated Emission 802.11b, Channel 11, 2462 MHz, Max Pol: H, **Detector: PK** 



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	<b>APPENDIX 2</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	



# Figure 2-23: Band-Edge Compliance of RF Radiated Emission 802.11g, Channel 11, 2462 MHz, Max Pol: V,





Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 2</b>			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		



Figure 2-26: Band-Edge Compliance of RF Radiated Emission 802.11n, Channel 1, 2412 MHz, Max Pol: H, Detector: PK



Figure 2-27: Band-Edge Compliance of RF Radiated Emission 802.11n, Channel 11, 2462 MHz, Max Pol: V,



Figure 2-28: Band-Edge Compliance of RF Radiated Emission 802.11n, Channel 11, 2462 MHz, Max Pol: H,



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services**	APPENDIX 3		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW,	
RTS-6036-1304-60B	March 06 to May 03, 2012	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW,	

# **APPENDIX 3 – BLUETOOTH AND BLUETOOTH LOW ENERGY CONDUCTED EMISSIONS TEST DATA/PLOTS**

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services <sup>**</sup>	APPENDIX 3		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Bluetooth power output from BlackBerry<sup>®</sup> smartphone was at maximum for all the recorded measurements shown below.

The measurements were performed by Berkin Can The tests were performed on model RFS121LW

Date of test: April 29, 2013

# **Test Setup Diagram**

HP P/S 6632B 3.7 volts		HP Spectrum Analyzer		
EUT	Mini Circuit Attenuator (6 dB)	Weinschel Splitter (6 dB)	Mini Circuit Attenuator (6 dB)	R&S Model CBT Bluetooth Tester

UNIT	MANUFACTURER	MODEL	<u>SERIAL</u> <u>NUMBER</u>
Attenuator 1	Mini-Circuits	BW-S6W2+	0647
Attenuator 2	Mini-Circuits	BW-S6W2+	0648
Attenuator 3	Mini-Circuits	BW-S20-2W263+	1234
Splitter 1	Weinschel	1515	MES 92

A reference offset of 12.4 dB was applied to the spectrum analyzer reference level for the attenuators and coaxial cable loss in the test circuit.

The environmental test conditions were:	Temperature:	22.8 °C
	Relative Humidity:	25.8 %

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services**	APPENDIX 3			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

#### 20 dB Bandwidth

The EUT met the requirements of the 20 dB bandwidth as per 47 CFR 15.247(a) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured. Bluetooth was operating in single frequency mode.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Bluetooth Channel	Limit (MHz)	Measured Level (MHz)
0	≤1.0	0.918
39	≤1.0	0.922
78	≤1.0	0.922

See figures 4-1 to 4-3 for the plots of the 20 dB bandwidth measurements.



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	<b>APPENDIX 3</b>			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

# Figure 4-3: 20 dB Bandwidth Single freq., Static PBRS, DH5



Using Pattern type "Static PBRS" and packet type "2-DH5" during the measurements.

Bluetooth Channel	Limit (MHz)	Measured Level (MHz)
0	≤1.5	1.318
39	≤1.5	1.316
78	≤1.5	1.318

See figures 4-4 to 4-6 for the plots of the 20 dB bandwidth measurements.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	<b>APPENDIX 3</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	



Figure 4-6: 20 dB Bandwidth Single freq., Static PBRS, 2-DH5



Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

Using Pattern type "Static PBRS" and packet type "<u>3-DH5</u>" during the measurements.

Bluetooth Channel	Limit (MHz)	Measured Level (MHz)
0	≤1.5	1.328
39	≤1.5	1.332
78	≤1.5	1.290

See figures 4-7 to 4-9 for the plots of the 20 dB bandwidth measurements.

#### Figure 4-7: 20 dB Bandwidth

Figure 4-8: 20 dB Bandwidth



Figure 4-9: 20 dB Bandwidth Single freq., Static PBRS, 3-DH5

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 3		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services™	APPENDIX 3			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## **Carrier Frequency Separation**

The EUT met the requirements of the Carrier Frequency Separation as per 47 CFR 15.247(a) and RSS-210. Channel 38 to 39 was measured. Bluetooth was operating in frequency hopping (Euro/US) mode.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Bluetooth Channels	Limit (MHz)	Measured Level (MHz)
38 to 39	$\ge$ 0.025 or 20 dB bandwidth	0.9986

See figure 4-10 for the plot of the Carrier Frequency Separation measurement.

Figure 4-10: Carrier Frequency Separation, Freq. Hopping, Static PBRS, DH5, Channels 38 to 39



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services™	APPENDIX 3			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

Using Pattern type "Static PBRS" and packet type "2-DH5" during the measurements.

Bluetooth Channels	Limit (MHz)	Measured Level (MHz)
38 to 39	≥ 0.025 or 20 dB bandwidth	0.9986

See figure 4-11 for the plot of the Carrier Frequency Separation measurement.

#### Figure 4-11: Carrier Frequency Separation, Freq. Hopping, Static PBRS, 2-DH5, Channels 38 to 39

Spectrum	n								
Ref Level	20.00 dBm	Offset 1	2.10 dB 😑 🛛	<b>RBW</b> 20 kH	z				
Att	25 dB	SWT	1.1 ms 😑 🖣	<b>∕BW</b> 100 k⊢	z Mode	Sweep			
Hopping Fre	quency Sepa	aration 😑 1R	m Max						
					M	1[1]			3.01 dBm
					_			2.441	17320 GHz
10 dBm			5.4.1		D	1[1]			0.62 dB
			X			1			998.00 KHZ
0 dBm	~~~	- and -	A.		<u></u>		$\frac{1}{2}$	A	^
www.	$\sim \sim$	~~···	$\sim \sim$	$\sim \sim \sim$	m	$\sim \sim$	VV VI	w w	$\sim \sim$
-10 dBm				×	•••				V
00 d0m									
-20 uBiii									
-30 dBm									
-40 dBm									
-50 dBm									
-60 d8m									
-00 0011									
-70 dBm									
CF 2.4414	8 GHz		I	691	pts	I	I	Spa	n 2.0 MHz
	)[				Mea	suring		<b>4/4</b> 1	9.03.2013 10:04:48

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services™	APPENDIX 3			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

Using Pattern type "Static PBRS" and packet type "<u>3-DH5</u>" during the measurements.

Bluetooth Channels	Limit (MHz)	Measured Level (MHz)
38 to 39	≥ 0.025 or 20 dB bandwidth	0.9986

See figure 4-12 for the plot of the Carrier Frequency Separation measurement.

#### Figure 4-12: Carrier Frequency Separation, Freq. Hopping, Static PBRS, 3-DH5, Channels 38 to 39



Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>		
<b>Test Report No.</b> RTS-6036-1304-60B	Dates of TestFCC ID: L6ARFS120LW IC: 2503A-RFS120LWMarch 06 to May 03, 2013FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## Number of Hopping Frequencies

The EUT met the requirements of the number of hopping frequencies as per 47 CFR 15.247(a) and RSS-210. Bluetooth was operating in frequency hopping (Euro/US) mode.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Limit	Number of Hopping Frequencies
(CH)	(CH)
≥75	79

See figures 4-13 to 4-16 for the plots of the number of hopping frequencies.



Figure 4-14: Number of Hopping Frequencies Static PBRS, DH5



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 3		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

#### Figure 4-15: Number of Hopping Frequencies Static PBRS, DH5

#### Figure 4-16: Number of Hopping Frequencies Static PBRS, DH5



# Time of Occupancy (Dwell Time)

The EUT met the requirements of the time of occupancy (dwell time) as per 47 CFR 15.247(a) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured in packet types DH1, DH3 and DH5. Bluetooth was operating in frequency hopping (Euro/US) mode during the measurements. The frequency hopping is 1600 hops per second for a dwell time of 625 µsec for 79 channels.

A DH1 packet needs one time slot for transmitting and one time slot for receiving. The frequency hopping is 800 hops per second with 79 channels which is 10.127 times per second. As per 15.247(a) (iii) "The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed". Therefore for 31.6 seconds (79x0.4) there are 320.0 times of appearance.

A DH3 packet needs one time slot for transmitting and one time slot for receiving. The frequency hopping is 400 hops per second with 79 channels which is 5.06 times per second. Therefore for 31.6 seconds there are 159.9 times of appearance.

A DH5 packet needs one time slot for transmitting and one time slot for receiving. The frequency hopping is 266.7 hops per second with 79 channels which is 3.38 times per second. Therefore for 31.6 seconds there are 106.8 times of appearance.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	<b>APPENDIX 3</b>		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Bluetooth Channel	Mode	Tx Time (ms)	Dwell Time/31.6 sec. (msec.)	Limit (msec.)	Margin (msec.)
0	DH1	0.3910	0.405 x 320.0 = 129.60	400	274.88
39	DH1	0.3880	0.403 x 320.0 = 128.96	400	275.84
78	DH1	0.3880	0.403 x 320.0 = 128.96	400	275.84
0	DH3	1.6410	1.653 x 159.9 = 264.31	400	137.60
39	DH3	1.6430	1.653 x 159.9 = 264.31	400	137.28
78	DH3	1.6430	1.653 x 159.9 = 264.31	400	137.28
0	DH5	2.8920	2.914 x 106.8 = 311.22	400	91.13
39	DH5	2.8940	2.923 x 106.8 = 312.18	400	90.92
78	DH5	2.9110	2.923 x 106.8 = 312.18	400	89.11

See figures 4-17 to 4-25 for the plots of the dwell time.

#### Bluetooth RF Conducted Emission Test Results cont'd



Figure 4-18: Time of Occupancy (Dwell Time)



Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

## Figure 4-19: Time of Occupancy (Dwell Time) Freq. Hopping, Static PBRS, DH1

Figure 4-20: Time of Occupancy (Dwell Time) Freq. Hopping, Static PBRS, DH3



Figure 4-21: Time of Occupancy (Dwell Time) Freq. Hopping, Static PBRS, DH3

Figure 4-22: Time of Occupancy (Dwell Time) Freq. Hopping, Static PBRS, DH3



Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 3	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW



#### Figure 4-25: Time of Occupancy (Dwell Time) Freq. Hopping, Static PBRS, DH5



Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>		
<b>Test Report No.</b> RTS-6036-1304-60B	Dates of TestFCC ID: L6ARFS120LW IC: 2503A-RFS120LWMarch 06 to May 03, 2013FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

#### Maximum Peak Conducted Output Power

The EUT met the requirements of the maximum peak conducted output power of class 1 as per 47 CFR 15.247(b) and RSS-210. Low channel (0), middle channel (39) and high channel (78) were measured. Bluetooth was operating in single frequency mode during the measurements. A reference offset of 12.4 dB was applied to the spectrum analyzer reference level for the coaxial cable loss and attenuators in the test circuit.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Bluetooth Channel	Measured Level (dBm)	Measured Level (W)	Class 1 Limit (dBm)
0	9.30	0.00851	0.0 to 20.0
39	10.00	0.01000	0.0 to 20.0
78	9.50	0.00891	0.0 to 20.0

Using Pattern type "Static PBRS" and packet type "2-DH5" during the measurements.

Bluetooth Channel	Measured Level (dBm)	Measured Level (W)	Class 1 Limit (dBm)
0	7.80	0.00603	0.0 to 20.0
39	8.60	0.00724	0.0 to 20.0
78	8.00	0.00631	0.0 to 20.0

Using Pattern type "Static PBRS" and packet type "<u>3-DH5</u>" during the measurements.

Bluetooth Channel	Measured Level (dBm)	Measured Level (W)	Class 1 Limit (dBm)
0	8.30	0.00676	0.0 to 20.0
39	9.00	0.00794	0.0 to 20.0
78	8.50	0.00708	0.0 to 20.0

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### Band Edge Compliance

The EUT met the requirements of the band edge compliance as per 47 CFR 15.247(c) and RSS-210. Low channel (0) and high channel (78) were measured. Bluetooth was operating in single frequency and hopping mode.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Bluetooth Channel	Operating Mode	Measured Level (dBc)	Limit (dBc)	Margin (dB)
0	Single Frequency	-58.15	-20	-38.15
78	Single Frequency	-58.05	-20	-38.05
0	Hopping	-61.81	-20	-41.81
78	Hopping	-61.24	-20	-41.24

See figures 4-35 to 4-38 for the plots of the band edge compliance measurements.

Figure 4-35: Band Edge Compliance Figure 4-36: Band Edge Compliance Single Freq., Static PBRS, DH5 Single Freq., Static PBRS, DH5 Spectrum Spectrum Ref Level 20.00 dBm Att 25 dB Ref Level 20.00 25 dB Att Mode Sweep Mode Sweep Band Edge 😑 1Pk Max and Edge 🔵 1Pk Max -2.2 8.86 dB 2.4021710 G м1[1] 10 dBr 41[1] 10 dBr 8.55 di 0 dBn -10 dBr -10 dBr -20 dBr 20 dB -30 dBr 30 dBr 40 dBr 40 dBr -50 dBm -50ndBm -60 dBr -60 dB -70 dBm 70 dBr CE 2 4 GH CE 2 482 GH 10.0 MU 10.0 MU 9.03.2013 9.03.2013

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services™	APPENDIX 3	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW



Using pattern type "Static PBRS" and packet type "2-DH5" during the measurements.

Bluetooth Channel	Operating Mode	Measured Level (dBc)	Limit (dBc)	Margin (dB)
0	Single Frequency	-56.32	-20	-36.32
78	Single Frequency	-57.81	-20	-37.81
0	Hopping	-59.26	-20	-39.26
78	Hopping	-59.02	-20	-39.02

See figures 4-39 to 4-42 for the plots of the band edge compliance measurements.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services**	APPENDIX 3	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW





Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Using pattern type "Static PBRS" and packet type "3-DH5" during the measurements.

Bluetooth Channel	Operating Mode	Measured Level (dBc)	Limit (dBc)	Margin (dB)
0	Single Frequency	-57.28	-20	-37.28
78	Single Frequency	-56.05	-20	-36.05
0	Hopping	-57.69	-20	-37.69
78	Hopping	-59.71	-20	-39.71

See figures 4-43 to 4-46 for the plots of the band edge compliance measurements.



Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services <sup>**</sup>	<b>APPENDIX 3</b>	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

## **Spurious RF Conducted Emissions**

The EUT met the requirements of the spurious RF conducted emissions as per 47 CFR 15.247(c) and RSS-210. Low channel (0), mid channel (39) and high channel (78) were measured. Bluetooth was operating in single frequency and hopping mode. A reference offset of 12.4 dB was applied to the spectrum analyzer reference level for the attenuators and coaxial cable loss in the test circuit.

Using pattern type "Static PBRS" and packet type "DH5" during the measurements.

Bluetooth Channel	Channel Power (dBm)	Max. Measured Level (dBm)	Max. Measured Level from carrier (dBc)	Limit (dBc)
0	9.80	-31.06	-40.86	-20.00
39	10.20	-31.91	-42.11	-20.00
78	9.90	-31.88	-41.78	-20.00
Hopping mode	9.80	-31.12	-40.92	-20.00

See figures 4-47 to 4-50 for the plots of the spurious RF conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services™	APPENDIX 3	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Figure 4-47: Spurious RF Conducted Emissions Single Freq., Static PBRS, DH5,





Date: 8.JAN.2013 16:09:57

Date: 8.JAN.2013 16:18:05





Date: 8.JAN.2013 16:11:17

Date: 8.JAN.2013 16:18:54

#### Figure 4-48: Spurious RF Conducted Emissions Single Freq., Static PBRS, DH5

Page 67 of 107

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Figure 4-49: Spurious RF Conducted Emissions Single Freq., Static PBRS, DH5





Date: 8.JAN.2013 16:12:06

Date: 8.JAN.2013 16:19:48





Date: 8.JAN.2013 16:13:55

Date: 8.JAN.2013 16:20:38

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services <sup>™</sup>	APPENDIX 3		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Using pattern type "Static PBRS" and packet type "2-DH5" during the measurements.

Bluetooth Channel	Channel Power (dBm)	Max. Measured Level (dBm)	Max. Measured Level from carrier (dBc)	Limit (dBc)
0	6.40	-31.49	-37.89	-20.00
39	6.60	-32.08	-38.68	-20.00
78	6.50	-32.16	-38.66	-20.00
Hopping mode	6.40	-31.24	-37.64	-20.00

See figures 4-51 to 4-54 for the plots of the spurious RF conducted emissions.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 3		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Figure 4-51: Spurious RF Conducted Emissions Single Freq., Static PBRS, 2-DH5





Date: 8.JAN.2013 17:09:13

Date: 8.JAN.2013 16:25:30



# \*RBW 1 MHz \*VBW 3 MHz SWT 300 ms Marker 1 [T1 ] -31.22 Þ Ref 20 dBm 0 dE Att 1 PR MAXH rear

Date: 8.JAN.2013 17:08:00

Date: 8.JAN.2013 16:54:55

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 3		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Figure 4-53: Spurious RF Conducted Emissions Single Freq., Static PBRS, 2-DH5





Date: 8.JAN.2013 17:07:18

Date: 8.JAN.2013 16:59:08





Date: 8.JAN.2013 17:06:37

Date: 8.JAN.2013 17:06:37

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services <sup>™</sup>	APPENDIX 3		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Using pattern type "Static PBRS" and packet type "<u>3-DH5</u>" during the measurements.

Bluetooth Channel	Channel Power (dBm)	Max. Measured Level (dBm)	Max. Measured Level from carrier (dBc)	Limit (dBc)
0	6.50	-30.68	-37.18	-20.00
39	6.70	-31.61	-38.31	-20.00
78	6.50	-31.26	-37.76	-20.00
Hopping mode	6.50	-30.83	-37.33	-20.00

See figures 4-55 to 4-58 for the plots of the spurious RF conducted emissions.
Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services™	APPENDIX 3				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

Figure 4-55: Spurious RF Conducted Emissions Single Freq., Static PBRS, 3-DH5





Date: 9.JAN.2013 10:52:25

Date: 9.JAN.2013 11:07:28





Date: 9.JAN.2013 10:53:18

Date: 9.JAN.2013 11:06:47

#### Figure 4-56: Spurious RF Conducted Emissions Single Freq., Static PBRS, 3-DH5

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW				
Services™	APPENDIX 3				
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW			
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW			

Figure 4-57: Spurious RF Conducted Emissions Single Freq., Static PBRS, 3-DH5





Date: 9.JAN.2013 10:54:23

Date: 9.JAN.2013 11:03:17





Date: 9.JAN.2013 10:59:39

Date: 9.JAN.2013 11:01:59

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

#### 6 dB Bandwidth

The EUT met the requirements of the 6 dB bandwidth as per 47 CFR 15.247(a)(2) and RSS-210. Channels 0, 20 and 39 were measured.

Channel	Limit (kHz)	Measured Level (MHz)
0	≥ 500	705.00
20	≥ 500	695.00
39	≥ 500	705.00

See figures 4-59 to 4-61 for the plots of the 6 dB bandwidth measurements for Channels 0, 20, and 39.



Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

# Figure 4-61: 6 dB Bandwidth

		,		ann		,				
Spectrum										
Ref Level 2	0.00 dB	m Offset 1	2.40 dB (	RBW	100 kHz					
Att	25 c	B SWT	1 ms (	VBW	300 kHz	Mode	Sweep			
6dBc Bandwi	dth 🔵 1 🖡	9k Max								
						M	1[1]			3.62 dBm
10 d0m									2	.47999750 GH
TO GBM					M1	n	dB			6.00 dB
0 dBm				T1	$\sim$	~~T2 BI	w		705.	000000000 kH;
U UBIII						र् २	factor			3517.7
-10 dBm				X			h			
-10 00111				7			$ \rangle$			
-20 dam							$  \rangle$			
-20 00111							$  \rangle$			
-30 dBm							<u> </u>			
So abili										
-40 dBm		1		_				$\rightarrow$		
	1	and the second sec								
-50 dBm	Jack N			_			L		~~	
mound.									1	man
-60 dBm				_					_	
-70 dBm				_			<u> </u>		_	
CF 2.48 GHz					1000 p	ts				Span 5.0 MHz
larker										
Type Ref	Trc	Stimulu	s	Res	ponse	Fund	tion	F	unction R	esult
M1	1	2.47999	75 GHz		3.62 dBm	ndB	down			705.0 kHz
T1	1	2.47963	25 GHz	-	2.38 dBm		ndB			6.00 dB
T2	1	2.48033	75 GHz	-	2.31 dBm	Q	factor			3517.7
	1					Mea	surina			29.04.2013

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## Maximum Conducted Output Power

The EUT met the requirements of the maximum conducted output power of class 2 as per 47 CFR 15.247(b)(3) and RSS-210. Channels 0, 20 and 39 were measured using an Agilent power meter, model N1911A with model N1921A power sensor. A reference offset of 6.4 dB was applied to the power meter reference level for the coaxial cable loss and attenuators in the test circuit.

Channel	Class 2 Limit (W)	Measured Level (dBm)	Measured Level (W)
0	< 1.00	3.21	0.00209
20	< 1.00	3.94	0.00248
39	< 1.00	3.17	0.00207

Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## **Band Edge Compliance**

The EUT met the requirements of the band edge compliance as per 47 CFR 15.247(c) and RSS-210. Channels 0 and 39 were measured.

Channel	Limit (dBc)	Measured Level (dBc)	Margin (dBc)
0	< -20	-55.77	-35.77
39	< -20	-54.52	-34.52

See figures 4-62 to 4-63 for the plots of the band edge compliance measurements for Channels 0 and 39.



Testing Services <sup>**</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 3</b>			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## **Peak Power Spectral Density**

The EUT met the requirements of the peak power spectral density as per 47 CFR 15.247(d) and RSS-210. Channels 0, 20 and 39 were measured.

Channel	Limit (dBm)	Measured Level (dBm)	Margin (dBm)
0	< 8.00	-7.71	-15.71
20	< 8.00	-8.19	-16.19
39	< 8.00	-8.52	-16.52

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services <sup>**</sup>	APPENDIX 3		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

See figures 4-64 to 4-66 for the plots of the peak power spectral density for Channels 0, 20 and 39.

#### Figure 4-64: Peak Power Spectral Density LE, Channel 0

#### Figure 4-65: Peak Power Spectral Density LE, Channel 20



### Figure 4-66: Peak Power Spectral Density



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services**	<b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

## APPENDIX 4 – 802.11b/g/n CONDUCTED EMISSIONS TEST DATA/PLOTS

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

## **Test Setup Diagram**



UNIT	MANUFACTURER	MODEL	<u>SERIAL</u> <u>NUMBER</u>
Attenuator 1	Mini-Circuits	BW-S6W2+	0647
Attenuator 2	Mini-Circuits	BW-S6W2+	0648
Attenuator 3	Mini-Circuits	BW-S20-2W263+	1234
Splitter 1	Weinschel	1515	MES 92

A reference offset of 20.4 dB was applied to the spectrum analyzer and 6.6 dB was applied to the Power Meter reference level for the attenuators and coaxial cable loss in the test circuit.

Date of test: April 29, 2013

The measurements on the BlackBerry<sup>®</sup> smartphone were performed by Berkin Can The tests were performed on model RFS121LW

The environmental test conditions were:	Temperature:	22.8ºC
	Relative Humidity:	25.8 %

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

#### 6 dB Bandwidth

The EUT met the requirements of the 6 dB bandwidth as per 47 CFR 15.247(a)(2) and RSS-210. Channels 1, 6 and 11 were measured at 1 Mbps, 5.5 Mbps, and 11 Mbps each for 802.11b mode, 6 Mbps, 24 Mbps, and 54 Mbps each for 802.11g mode, and MCS 0, 4, and 7 for 802.11n mode.

Channel	Data Rate	Limit (kHz)	Measured Level (MHz)
	1 Mbps	≥ 500	8.05
	5.5 Mbps	≥ 500	8.39
	11 Mbps	≥ 500	8.25
	6 Mbps	≥ 500	15.66
1	24 Mbps	≥ 500	16.35
	54 Mbps	≥ 500	16.35
	MCS 0	≥ 500	15.37
	MCS 4	≥ 500	17.28
	MCS 7	≥ 500	16.67
	1 Mbps	≥ 500	7.55
	5.5 Mbps	≥ 500	8.22
	11 Mbps	≥ 500	8.39
	6 Mbps	≥ 500	15.31
6	24 Mbps	≥ 500	16.35
	54 Mbps	≥ 500	16.35
	MCS 0	≥ 500	16.87
	MCS 4	≥ 500	17.21
	MCS 7	≥ 500	17.44
	1 Mbps	≥ 500	8.05
	5.5 Mbps	≥ 500	7.12
	11 Mbps	≥ 500	7.50
	6 Mbps	≥ 500	15.34
11	24 Mbps	≥ 500	15.75
	54 Mbps	≥ 500	15.75
	MCS 0	≥ 500	16.06
	MCS 4	≥ 500	17.35
	MCS 7	≥ 500	17.44

Testing Services <sup>***</sup>	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

See figures 5-1 to 5-9 for the plots of the 6 dB bandwidth measurements for Channels 1, 6, and 11, at 1 Mbps each for 802.11b mode, 6 Mbps each for 802.11g mode, and MCS 0 each for 802.11n mode.





This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 84 of 107

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	<b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	





Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services™	APPENDIX 4		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

#### Figure 5-9: 6 dB Bandwidth 802.11n, Channel 11, MCS 0



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services <sup>**</sup>	APPENDIX 4		
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

### Maximum Conducted Output Power

The EUT met the requirements of the maximum conducted output power of class 2 as per 47 CFR 15.247(b)(3) and RSS-210. Channels 1, 6 and 11 were measured at 1 Mbps, 5.5 Mbps, and 11 Mbps each for 802.11b mode, 6 Mbps, 24 Mbps, and 54 Mbps each for 802.11g mode, and MCS 0, 4 and 7 for 802.11n mode using an Aglient power meter, model N1911A with model N1921A power sensor. A reference offset of 18.4 dB was applied to the power meter reference level for the coaxial cable loss and attenuators in the test circuit.

Channel	Data Rate	Class 2 Limit (W)	Measured Level (dBm)	Measured Level (W)
	1 Mbps	< 1.00	18.92	0.0780
	5.5 Mbps	< 1.00	18.90	0.0775
	11 Mbps	< 1.00	18.76	0.0752
	6 Mbps	< 1.00	18.57	0.0720
1	24 Mbps	< 1.00	18.22	0.0664
	54 Mbps	< 1.00	17.63	0.0579
	MCS 0	< 1.00	18.60	0.0725
	MCS 4	< 1.00	17.97	0.0626
	MCS 7	< 1.00	17.59	0.0574
	1 Mbps	< 1.00	18.90	0.0775
	5.5 Mbps	< 1.00	18.80	0.0758
	11 Mbps	< 1.00	18.61	0.0725
	6 Mbps	< 1.00	18.46	0.0701
6	24 Mbps	< 1.00	18.08	0.0643
	54 Mbps	< 1.00	17.58	0.0572
	MCS 0	< 1.00	18.55	0.0716
	MCS 4	< 1.00	17.85	0.0609
	MCS 7	< 1.00	17.53	0.0567

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services <sup>**</sup>	APPENDIX 4	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Channel	Data Rate	Class 2 Limit (W)	Measured Level (dBm)	Measured Level (W)
	1 Mbps	< 1.00	19.19	0.0830
	5.5 Mbps	< 1.00	19.05	0.0803
11	11 Mbps	< 1.00	18.91	0.0778
	6 Mbps	< 1.00	18.65	0.0732
	24 Mbps	< 1.00	18.26	0.0670
	54 Mbps	< 1.00	17.70	0.0589
	MCS 0	< 1.00	18.67	0.0736
	MCS 4	< 1.00	18.03	0.0636
	MCS 7	< 1.00	17.65	0.0582

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services <sup>**</sup>	APPENDIX 4	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### **Band Edge Compliance**

The EUT met the requirements of the band edge compliance as per 47 CFR 15.247(c) and RSS-210. Channels 1 and 11 were measured at 1 Mbps, 5.5 Mbps, and 11 Mbps each for 802.11b mode, 6 Mbps, 24 Mbps, and 54 Mbps each for 802.11g mode, and MCS 0, 4 and 7 for 802.11n mode.

Channel	Data Rate	Limit (dBc)	Measured Level (dBc)	Margin (dBc)
	1 Mbps	< -20	-50.11	-30.11
	5.5 Mbps	< -20	-50.83	-30.83
	11 Mbps	< -20	-50.47	-30.47
	6 Mbps	< -20	-37.23	-17.23
1	24 Mbps	< -20	-41.44	-21.44
	54 Mbps	< -20	-41.62	-21.62
	MCS 0	< -20	-41.35	-21.35
	MCS 4	< -20	-44.87	-24.87
	MCS 7	< -20	-44.24	-24.24
	1 Mbps	< -20	-49.71	-29.71
	5.5 Mbps	< -20	-51.72	-31.72
	11 Mbps	< -20	-53.14	-33.14
	6 Mbps	< -20	-40.60	-20.60
11	24 Mbps	< -20	-43.84	-23.84
	54 Mbps	< -20	-43.51	-23.51
	MCS 0	< -20	-41.74	-21.74
	MCS 4	< -20	-44.37	-24.37
	MCS 7	< -20	-46.88	-26.88

See figures 5-10 to 5-15 for the plots of the band edge compliance measurements for Channels 1 and 11, at 1 Mbps each for 802.11b mode, 6 Mbps each for 802.11g mode, and MCS 0 each for 802.11n mode.

This report shall NOT be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW





Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services**	APPENDIX 4	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

## Figure 5-14: Band Edge Compliance 802.11n, Channel 1, MCS 0

Figure 5-15: Band Edge Compliance 802.11n, Channel 11, MCS 0



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services <sup>**</sup>	APPENDIX 4	
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### Peak Power Spectral Density

The EUT met the requirements of the peak power spectral density as per 47 CFR 15.247(d) and RSS-210. Channels 1, 6 and 11 were measured at 1 Mbps, 5.5 Mbps, and 11 Mbps each for 802.11b mode, 6 Mbps, 24 Mbps, and 54 Mbps each for 802.11g mode, and MCS 0, 4, and 7 for 802.11n mode.

Channel	Data Rate	Limit (dBm)	Measured Level (dBm)	Margin (dBm)
	1 Mbps	< 8.00	-3.63	-11.63
	5.5 Mbps	< 8.00	-5.36	-13.36
	11 Mbps	< 8.00	-5.72	-13.72
	6 Mbps	< 8.00	-8.82	-16.82
1	24 Mbps	< 8.00	-10.36	-18.36
	54 Mbps	< 8.00	-12.39	-20.39
	MCS 0	< 8.00	-10.02	-18.02
	MCS 4	< 8.00	-13.38	-21.38
	MCS 7	< 8.00	-14.35	-22.35
	1 Mbps	< 8.00	-3.07	-11.07
	5.5 Mbps	< 8.00	-4.87	-12.87
6	11 Mbps	< 8.00	-5.43	-13.43
	6 Mbps	< 8.00	-8.06	-16.06
	24 Mbps	< 8.00	-10.13	-18.13
	54 Mbps	< 8.00	-11.63	-19.63
	MCS 0	< 8.00	-10.28	-18.28
	MCS 4	< 8.00	-13.14	-21.14
	MCS 7	< 8.00	-13.70	-21.70
	1 Mbps	< 8.00	-3.35	-11.35
11	5.5 Mbps	< 8.00	-5.05	-13.05
	11 Mbps	< 8.00	-5.30	-13.30
	6 Mbps	< 8.00	-8.49	-16.49
	24 Mbps	< 8.00	-10.19	-18.19
	54 Mbps	< 8.00	-11.13	-19.13
	MCS 0	< 8.00	-11.19	-19.19
	MCS 4	< 8.00	-13.34	-21.34
	MCS 7	< 8.00	-13.59	-21.59

Testing Services**	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

See figures 5-16 to 5-24 for the plots of the peak power spectral density for Channels 1, 6 and 11, at 1 Mbps each for 802.11b mode, 6 Mbps each for 802.11g mode, and MCS 0 for 802.11n mode.

#### Figure 5-16: Peak Power Spectral Density 802.11b, Channel 1, 1 Mbps

#### Figure 5-17: Peak Power Spectral Density 802.11b, Channel 6, 1 Mbps



### Figure 5-18: Peak Power Spectral Density 802.11b, Channel 11, 1 Mbps



#### This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 93 of 107

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services**	APPENDIX 4	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### Figure 5-19: Peak Power Spectral Density 802.11g, Channel 1, 6 Mbps

#### Figure 5-20: Peak Power Spectral Density 802.11g, Channel 6, 6 Mbps



#### Figure 5-21: Peak Power Spectral Density 802.11g, Channel 11, 6 Mbps



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services**	APPENDIX 4	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### Figure 5-22: Peak Power Spectral Density 802.11n, Channel 1, MCS 0

#### Figure 5-23: Peak Power Spectral Density 802.11n, Channel 6, MCS 0



#### Figure 5-24: Peak Power Spectral Density 802.11n, Channel 11, MCS 0



Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW	
Services <sup>**</sup>	<b>APPENDIX 4</b>	
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

#### **Spurious RF Conducted Emissions**

The EUT met the requirements of the spurious RF conducted emissions as per 47 CFR 15.247(c) and RSS-210. Channels 1, 6 and 11 were measured at 1 Mbps, 5.5 Mbps, and 11 Mbps each for 802.11b mode, 6 Mbps, 24 Mbps, and 54 Mbps each for 802.11g mode, and MCS 0, 4, and 7 for 802.11n mode. Peak power was measured using an Agilent power meter, model N1911A with model N1921A power sensor. A reference offset of 18.4 dB was applied to the power meter reference level for the coaxial cable loss and attenuators in the test circuit.

Channel	Data Rate	Power (dBm)	Max. Measured Level (dBm)	Max. Measured Level from Carrier (dBc)	Limit (dBc)
	1 Mbps	18.21	-32.24	-51.1625821	-20
	5.5 Mbps	18.01	-31.41	-50.3059992	-20
	11 Mbps	18	-32.27	-51.0358082	-20
	6 Mbps	17.72	-25.46	-44.0345367	-20
1	24 Mbps	14.91	-27.81	-46.0330567	-20
	54 Mbps	13.46	-27.15	-44.7783856	-20
	MCS 0	17.7	-32.71	-51.3130863	-20
	MCS 4	14.7	-33.06	-51.0283053	-20
	MCS 7	13.28	-32.89	-50.4766323	-20
	1 Mbps	18.88	-32.82	-51.7154311	-20
	5.5 Mbps	18.663	-32.41	-51.2072146	-20
	11 Mbps	18.61	-32.58	-51.18559	-20
	6 Mbps	17.88	-19.54	-37.9974988	-20
6	24 Mbps	15.12	-31.46	-49.5388429	-20
	54 Mbps	13.49	-21.62	-39.196791	-20
	MCS 0	17.95	-32.73	-51.2784451	-20
	MCS 4	14.94	-31.64	-49.4912561	-20
	MCS 7	13.51	-32.55	-50.0833897	-20

This report shall NOT be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013

Testing Services™	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Channel	Data Rate	Power (dBm)	Max. Measured Level (dBm)	Max. Measured Level from Carrier (dBc)	Limit (dBc)
	18.85	-44.00	-32.56	-51.7499113	-20
	18.62	-44.23	-32.88	-51.9261802	-20
	18.57	-48.21	-32.41	-51.3222962	-20
11	17.85	-48.43	-24.60	-43.2450575	-20
	15.12	-48.11	-31.76	-50.0217632	-20
	13.52	-48.42	-31.51	-49.2117658	-20
	17.93	-48.37	-32.94	-51.6076632	-20
	14.9	-48.28	-32.65	-50.682683	-20
	13.5	-48.34	-32.59	-50.2411595	-20

The emissions were in the NF.

See figures 5-25 to 5-33 for the plots of the spurious RF conducted emissions for Channels 1, 6 and 11, at 1 Mbps each for 802.11b mode, 6 Mbps each for 802.11g mode, and MCS 0 each for 802.11n mode.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW		
Services**	<b>APPENDIX 4</b>		
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW	
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW	

Figure 5-25: Spurious Conducted RF Emissions



#### Figure 5-26 : Spurious Conducted RF Emissions 802.11b, Channel 6, 1 Mbps



This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 98 of 107

Testing Services <sup>™</sup>	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 4
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Figure 5-27: Spurious Conducted RF Emissions 802.11b. Channel 11. 1 Mbps



#### Figure 5-28: Spurious Conducted RF Emissions 802.11g, Channel 1, 6 Mbps



This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 99 of 107

Testing Services <sup>™</sup>	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Figure 5-29: Spurious Conducted RF Emissions 802.11g, Channel 6, 6 Mbps \*RBW 1 MHz \*VBW 3 MHz SWT 40 ms \*RBW 1 MHz [T1 ] Marker 1 [T1 ] -19.54 dBm 2.424562500 GHz \*VBW 3 MHz SWT 440 ms -32.66 dBm 24.268500000 GHz 17 dBm \*Att 20 dB 17 dBm \* Att 10 dB Ref Ref Offset 20.4 dB Offset 20.4 dB A A l pr View l pr View 7 المان براية فهر بالأعمر فاسليه الحايدة والمسالي ومعالية ويساله a house 297 MHz/ Start 30 MHz Stop 3 GHz Start 3 GHz 2.2 GHz/ Stop 25 GHz



This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 100 of 107

Testing Services**	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW <b>APPENDIX 4</b>
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

Figure 5-31: Spurious Conducted RF Emissions 802.11n, Channel 1, MCS 0



![](_page_100_Figure_4.jpeg)

![](_page_100_Figure_5.jpeg)

This report shall <u>NOT</u> be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013 Page 101 of 107

Testing Services**	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 4
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

![](_page_101_Figure_2.jpeg)

Testing Services**	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 5
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

## **APPENDIX 5 – NEAR FIELD COMMUNICATIONS TEST DATA/PLOTS**

Testing Services <sup>**</sup>	EMI Test Report for the Blac	kBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW APPENDIX 5
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW

## Near Field Communications (NFC) Test Results

Radiated Emissions

Date of Test: April 25, 2013 Measurements were performed by Savtej Sandhu. The tests were performed on model RFS121LW

The environmental test conditions were: Temperature:	25.4⁰C
Relative Humidity:	18.1 %

The test distance was 3.0 metres with a EUT height of 0.8 metres, and sweep frequency of 9 kHz to 1 GHz.

The BlackBerry<sup>®</sup> smartphone was in vertical position.

The frequency sweep measurements were performed in Near Field Communications Tx mode at 13.56 MHz.

Frequency	Reading (QP)	Correction Factor	Corrected Reading (QP)	Limit	Test Margin
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
13.558	32.56	18.13	50.69	124.00	-73.31
14.408	24.56	13.19	42.72	69.50	-26.78

All other emissions had a test margin of greater than 25.0 dB.

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	APPENDIX 5			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## Near Field Communications (NFC) Test Results cont'd

**Occupied Bandwidth** 

Date of test: May 03, 2013 The measurements were performed by Berkin Can. The tests were performed on model RFS121LW

The environmental test conditions were:	Temperature:	24.2 °C
	Relative Humidity:	23.6 %

Operation mode (TX ON)	Occupied Bandwidth (kHz)		
NFC, modulated	424		

![](_page_104_Figure_6.jpeg)

Figure 7-1: Occupied Bandwidth, NFC TX Frequency = 13.56 MHz

This report shall NOT be reproduced except in full without the written consent of RIM Testing Services - A division of Research in Motion Limited. Copyright 2005-2013

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	APPENDIX 5			
<b>Test Report No.</b>	<b>Dates of Test</b>	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## Near Field Communications (NFC) Test Results cont'd

## **Frequency Stability**

Date of test: May 03, 2013. The measurements were performed by Berkin Can. The tests were performed on model RFS121LW

The environmental test conditions were:	Temperature:	24.2 °C
	Relative Humidity:	23.6 %

Test Temperature (Celsius)	Nominal Freq. (MHz)	Measured Freq. (MHz)	Input Voltage (Volts)	Max Freq Error (Hz)	% Deviation (Limit .01%)	РРМ
-20	13.56	13.559622	3.6	-0.000378	-378	-0.00279
-20	13.56	13.559686	3.8	-0.000314	-314	-0.00232
-20	13.56	13.559692	4.35	-0.000308	-308	-0.00227
-10	13.56	13.559570	3.6	-0.000430	-430	-0.00317
-10	13.56	13.559492	3.8	-0.000508	-508	-0.00375
-10	13.56	13.559519	4.35	-0.000481	-481	-0.00355
0	13.56	13.559516	3.6	-0.000484	-484	-0.00357
0	13.56	13.559478	3.8	-0.000522	-522	-0.00385
0	13.56	13.559712	4.35	-0.000288	-288	-0.00212
10	13.56	13.559557	3.6	-0.000443	-443	-0.00327
10	13.56	13.559578	3.8	-0.000422	-422	-0.00311
10	13.56	13.559581	4.35	-0.000419	-419	-0.00309
20	13.56	13.559584	3.6	-0.000416	-416	-0.00307
20	13.56	13.559652	3.8	-0.000348	-348	-0.00257
20	13.56	13.559316	4.35	-0.000684	-684	-0.00504

Testing	EMI Test Report for the BlackBerry <sup>®</sup> smartphone Model RFS121LW, RFR101LW			
Services <sup>**</sup>	APPENDIX 5			
<b>Test Report No.</b>	Dates of Test	FCC ID: L6ARFS120LW IC: 2503A-RFS120LW		
RTS-6036-1304-60B	March 06 to May 03, 2013	FCC ID: L6ARFR100LW IC: 2503A-RFR100LW		

## Near Field Communications (NFC) Test Results cont'd

## Frequency Stability cont'd

Test Temperature (Celsius)	Nominal Freq. (MHz)	Measured Freq. (MHz)	Input Voltage (Volts)	Max Freq Error (Hz)	% Deviation (Limit .01%)	РРМ
30	13.56	13.559355	3.6	-0.000645	-645	-0.00476
30	13.56	13.559747	3.8	-0.000253	-253	-0.00187
30	13.56	13.559482	4.35	-0.000518	-518	-0.00382
40	13.56	13.559512	3.6	-0.000488	-488	-0.00360
40	13.56	13.559643	3.8	-0.000357	-357	-0.00263
40	13.56	13.559451	4.35	-0.000549	-549	-0.00405
50	13.56	13.559496	3.6	-0.000504	-504	-0.00372
50	13.56	13.559630	3.8	-0.000370	-370	-0.00273
50	13.56	13.559594	4.35	-0.000406	-406	-0.00299
60	13.56	13.559485	3.6	-0.000515	-515	-0.00380
60	13.56	13.559654	3.8	-0.000346	-346	-0.00255
60	13.56	13.559307	4.35	-0.000693	-693	-0.00511