



440 Phillip Street, Waterloo,
Ontario, Canada
Tel: (519) 888-7465 ; Fax: (519)
888-6906

Date: December 3, 2014

Declaration - MIF for HAC RF Interference Evaluation

To whom it may concern:

This device, with FCC ID: L6ARHF140LW, Hearing Aid Compatibility Requirement is going to be certified under ANSI C63.19 2011 version per Part 20.19.

For Radio Frequency Interference, SPEAG's Audio Interference Analyzer (AIA) or other indirect or direct measurement was not used to determine the M rating.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) or average antenna input power as documented in HAC test report exhibit, and adding the MIF value in dB. The MIF values below for the worst-case operation mode for all air interfaces are pre-determined values provided by SPEAG.

UID	Communication System Name	MIF(dB)
10021	GSM-FDD(TDMA,GMSK)	3.63
10011	UMTS-FDD(WCDMA)	-27.23
10039	CDMA2000 (1xRTT, RC1)	-19.77
10081	CDMA2000 (1xRTT, RC3)	-19.71
10295	CDMA2000 (1xRTT, RC1 SO3, 1/8th Rate 25 fr.)	3.26

Sincerely,

Masud S. Attayi, P. Eng.
Manager, Regulatory Certification
Email: mattayi@blackberry.com