RF Exposure Evaluation

Page: A4 1

No. 11, Lane 41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C. TEL.: 886-2-25984542 FAX.: 886-2-25984546

RF Exposure Evaluation

Report No.: RF-C450-0912-419

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions f this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to TCB Exclusion list, no SAR required if power is lower than the flowing threshold:

Frequency Range		Center	60/f
Low Frequency	Low Frequency	frequency	SAR Limitation
(MHz)	(MHz)	(MHz)	(mw)
2415	2465	2442	24.57

Maximum measured transmitter power:

Conducted Average	Max Antenna Gain	EIRP
Power	(dBi)	(dBm/mW)
(dBm)		
12.03	1.1	13.1 3 / 20.56

The averaging power was measured using average power meter with duty cycle set to 22% we declared that which is the maximum duty cycle in end user operating condition.

Threshold at which no SAR required is 24.57mw

Conclusion: No SAR is required.

CENTRAL RESEARCH TECHNOLOGY CO.

No. 11, Lane 41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.

TEL.: 886-2-25984542 FAX.: 886-2-25984546