

| | | | | | | | | |
|--|-------------------|-----------------------------|------------------|----------------------|----------------------|---------------------|----------------------|----------------------|
| RETLIF TESTING LABORATORIES | | | | | | | | |
| TABULAR DATA SHEET | | | | | | | | |
| TEST METHOD: Field Strength of Fundamental | | | | | | | | |
| CUSTOMER: Global Data, Inc. | | | | JOB NO: R-3676N1 | | | | |
| TEST SAMPLE: 13.56 MHz Portable RF ID Read/Write Terminal | | | | | | | | |
| MODEL NO: NOVAS-120 | | | | SERIAL NO: 450146 | | | | |
| TEST SPECIFICATION: FCC Part 15, Subpart C Paragraph: 15.225 & 15.31 | | | | | | | | |
| OPERATING MODE: Continuously Transceiving | | | | | | | | |
| TECHNICIAN: T. Firkowski | | | | DATE: 10/19/00 | | | | |
| NOTES: Detector Function: Quasi-Peak @ 3m | | | | | | | | |
| TRANSMIT FREQUENCY | TEST FREQUENCY | ANTENNA/ EUT POSITION | METER READING | CORRECTION FACTOR | CORRECTED READING | CONVERTED TO 30m | CONVERTED READING | LIMIT @ 30 METERS |
| MHz | MHz | Polarization/ Axis | dBuV | dB | dBuV/m | dBuV/m | uV/m | uV/m |
| 13.56 | 13.56 | C/Y | 53.08 | 10.53 | 63.61 | 23.61 | 15.15 | 10,000 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| DATA SHEET 1 of 1 | | | | | | R-3676N1 | | |

