



A Test Lab Techno Corp.


Changan Lab : No. 140 -1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.
Tel : 886-3-271-0188 / Fax : 886-3-271-0190

MPE Report



Test Report No.	: 1007FS16
Applicant	: Comtrend Corporation
Manufacturer	: Comtrend Corporation
Product Type	: Wireless ADSL2+Router
Trade Name	: COMTREND
Model Number	: CT-5367
FCC ID	: L9V-5367
Dates of Test	: Jul. 26, 2010
Test Specification	: 47 CFR § 2.1091 47 CFR §1.1310 ANSI / IEEE Std.C95.1-1999
Location of Test Lab.	: Chang-an Lab.

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.



Sam Chuang **20100726**
Approve Signer



Alex Wu **20100726**
Testing Engineer



Contents

1. Description of Equipment under Test (EUT).....	3
1.2 RF Output Power	4
2. Human Exposure Assessment	5
2.1 Test Result	6



1. Description of Equipment under Test (EUT)

Applicant	Comtrend Corporation
Applicant Address	3F-1, 10 Lane 609, Chung Hsin Road, Section 5 San Chung City, Taipei Hsien, Taiwan 241
Manufacturer	Comtrend Corporation
Manufacturer Address	3F-1, 10 Lane 609, Chung Hsin Road, Section 5 San Chung City, Taipei Hsien, Taiwan 241
Product Type	Wireless ADSL2+Router
Trade Name	COMTREND
Model Number	CT-5367
FCC ID	L9V-5367
Frequency Range	2412 - 2462 MHz (IEEE 802.11b / IEEE 802.11g)
Transmit Power (Peak conducted power)	IEEE 802.11b: 0.044 W / 14.48 dBm IEEE 802.11g: 0.075 W / 16.74 dBm
Modulation Technique	IEEE 802.11b:DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g:DSSS(CCK, DQPSK, DBPSK)+ OFDM(QPSK, BPSK, 16-QAM, 64-QAM)
Hardware Ver.	CTU-1
Software Ver.	A111-312CTU-C01_R01
Antenna Specification	2 dBi
Temperature Range	-30 ~ +70°C

The above equipment was tested by Compliance Certification Services Inc. For compliance with the requirements set forth in 47 CFR § 2.1091 & 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



1.1 RF Output Power

Band	Data Rate	Frequency (MHz)	Average Power (dBm)	Peak Power (dBm)	Worst Case
IEEE 802.11b	1M	2412	9.69	14.29	<input type="checkbox"/>
		2437	9.69	14.42	<input type="checkbox"/>
		2462	9.44	14.16	<input type="checkbox"/>
	2M	2412	9.63	14.31	<input type="checkbox"/>
		2437	9.74	14.42	<input type="checkbox"/>
		2462	9.49	14.22	<input type="checkbox"/>
	5.5M	2412	9.41	14.33	<input type="checkbox"/>
		2437	9.36	14.44	<input type="checkbox"/>
		2412	9.33	14.30	<input type="checkbox"/>
	11M	2437	8.88	14.36	<input type="checkbox"/>
		2462	8.81	14.48	<input checked="" type="checkbox"/>
		2462	8.77	14.40	<input type="checkbox"/>
IEEE 802.11g	6M	2412	9.12	16.70	<input type="checkbox"/>
		2437	9.24	16.74	<input checked="" type="checkbox"/>
		2462	9.10	16.56	<input type="checkbox"/>
	9M	2412	8.88	16.31	<input type="checkbox"/>
		2437	9.01	16.42	<input type="checkbox"/>
		2462	8.80	16.45	<input type="checkbox"/>
	12M	2412	8.60	16.54	<input type="checkbox"/>
		2437	8.74	16.72	<input type="checkbox"/>
		2462	8.41	16.42	<input type="checkbox"/>
	18M	2412	8.30	16.46	<input type="checkbox"/>
		2437	8.35	16.56	<input type="checkbox"/>
		2462	8.10	16.50	<input type="checkbox"/>
	24M	2412	7.77	16.66	<input type="checkbox"/>
		2437	7.71	16.73	<input type="checkbox"/>
		2462	7.63	16.52	<input type="checkbox"/>
	36M	2412	7.20	16.63	<input type="checkbox"/>
		2437	7.10	16.67	<input type="checkbox"/>
		2462	7.02	16.48	<input type="checkbox"/>
	48M	2412	6.52	16.50	<input type="checkbox"/>
		2437	6.65	16.61	<input type="checkbox"/>
		2462	6.51	16.54	<input type="checkbox"/>
	54M	2412	6.31	16.31	<input type="checkbox"/>
		2437	6.30	16.45	<input type="checkbox"/>
		2462	6.32	16.36	<input type="checkbox"/>



2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR §1.1310 titled “Radiofrequency radiation exposure limits”, generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as “a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter’s radiating structure(s) and the body of the user or nearby persons. ” This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: “IMPORTANT: To meet the FCC’s RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna”. Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a “mobile device” as defined in section § 2.1091 paragraph (b).

Exposure evaluation

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.



2.1 Test Result

Band	Data Rate	Frequency (MHz)	Limit (mw)	Distance (cm) [R]	Power (dBm) [P]	ANT Gain (dBi) [G]	[P]+ [G] (W) [TP]	Power Density [S]	Min. distance (cm)
IEEE 802.11b	11	2412.0	1.000	20	14.36	2.00	0.043	0.009	20cm
		2437.0	1.000	20	14.48	2.00	0.044	0.009	20cm
		2462.0	1.000	20	14.40	2.00	0.044	0.009	20cm
IEEE 802.11g	6	2412.0	1.000	20	16.70	2.00	0.074	0.015	20cm
		2437.0	1.000	20	16.74	2.00	0.075	0.015	20cm
		2462.0	1.000	20	16.56	2.00	0.072	0.014	20cm