

# FCC Part 15 EMI TEST REPORT

of

E.U.T. : 11N Wireless ADSL2+Router  
FCC ID. : L9V-CT-5364A  
Model No. : CT-5364A  
Serial Model : CT-5364A NA

for

APPLICANT : Comtrend Corporation  
ADDRESS : 3F-1, 10 Lane 609, Chung Hsin Road, Section 5  
San Chung City, Tapei Hsien, Taiwan, 241

Test Performed by

**ELECTRONICS TESTING CENTER, TAIWAN**

NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG

TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

Tel : (02)26023052 Fax : (02)26010910

<http://www.etc.org.tw> ; e-mail: [emc@etc.org.tw](mailto:emc@etc.org.tw)

Report Number : 10-03-RBF-009-01

# TEST REPORT CERTIFICATION

Applicant : Comtrend Corporation  
3F-1, 10 Lane 609, Chung Hsin Road, Section 5 San Chung City, Tapei Hsien, Taiwan, 241

Manufacturer : Comtrend Corporation  
3F-1, 10 Lane 609, Chung Hsin Road, Section 5 San Chung City, Tapei Hsien, Taiwan, 241

## Description of EUT


- a) Type of EUT : 11N Wireless ADSL2+Router
- b) Trade Name : Comtrend
- c) Model No. : CT-5364A
- d) Serial Model : CT-5364A NA
- e) Power Supply : Adaptor Model No.: AMS9-1201000FU2-VP  
I/P: 100-240Vac 50/60Hz 0.5A;  
O/P: 12V---1.0A


Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (2008)


I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

- Note: 1. The result of the testing report relate only to the item tested.  
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Date Test Item Received : Mar. 02, 2010  
Date Test Campaign Completed : Mar. 22, 2010  
Date of Issue : Apr. 19, 2010

Test Engineer :   
( Falcon Shi, Engineer )

Check By :   
( Charles Wang, Supervisor )

Approve & Authorized Signer :   
Will Yauo, Manager  
EMC Dept. II of ELECTRONICS  
TESTING CENTER, TAIWAN

<b>Table of Contents</b>	<b>Page</b>
<b>1 GENERAL INFORMATION .....</b>	<b>1</b>
1.1 Product Description.....	1
1.2 Characteristics of Device.....	1
1.3 Test Methodology .....	1
1.4 Test Facility.....	1
<b>2 PROVISIONS APPLICABLE.....</b>	<b>2</b>
2.1 Definition.....	2
2.2 Requirement for Compliance.....	3
2.3 Restricted Bands of Operation.....	5
2.4 Labeling Requirement .....	5
2.5 User Information .....	6
<b>3. SYSTEM TEST CONFIGURATION .....</b>	<b>7</b>
3.1 Justification.....	7
3.2 Devices for Tested System.....	7
<b>4 RADIATED EMISSION MEASUREMENT.....</b>	<b>8</b>
4.1 Applicable Standard.....	8
4.2 Measurement Procedure.....	8
4.3 Measuring Instrument .....	10
4.4 Radiated Emission Data.....	11
4.5 Field Strength Calculation.....	28
4.6 Photos of Radiation Measuring Setup.....	29
<b>5 CONDUCTED EMISSION MEASUREMENT.....</b>	<b>30</b>
5.1 Standard Applicable .....	30
5.2 Measurement Procedure.....	30
5.3 Conducted Emission Data.....	31
5.4 Result Data Calculation.....	33
5.5 Conducted Measurement Equipment.....	33
5.6 Photos of Conduction Measuring Setup .....	34
<b>6 ANTENNA REQUIREMENT.....</b>	<b>35</b>
6.1 Standard Applicable.....	35
6.2 Antenna Construction and Directional Gain .....	35
<b>7 EMISSION BANDWIDTH MEASUREMENT.....</b>	<b>36</b>
7.1 Standard Applicable .....	36
7.2 Measurement Procedure.....	36

7.3 Measurement Equipment ..... 36

7.4 Measurement Data ..... 37

**8 OUTPUT POWER MEASUREMENT..... 56**

8.1 Standard Applicable ..... 56

8.2 Measurement Procedure..... 56

8.3 Measurement Equipment ..... 56

8.4 Measurement Data ..... 57

**9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT..... 59**

9.1 Standard Applicable ..... 59

9.2 Measurement Procedure..... 59

9.3 Measurement Equipment ..... 59

9.4 Measurement Data ..... 60

**10 POWER DENSITY MEASUREMENT ..... 73**

10.1 Standard Applicable ..... 73

10.2 Measurement Procedure..... 73

10.3 Measurement Equipment ..... 73

10.4 Measurement Data ..... 74

**11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT ..... 100**

11.1 Standard Applicable ..... 100

11.2 Measurement Procedure..... 100

11.3 Measurement Equipment ..... 100

11.4 Measurement Data ..... 101

# 1 GENERAL INFORMATION

## 1.1 Product Description

- a) Type of EUT : 11N Wireless ADSL2+Router
- b) Trade Name : Comtrend
- c) Model No. : CT-5364A
- d) Serial Model : CT-5364A NA
- e) Power Supply : Adaptor Model No.: AMS9-1201000FU2-VP  
I/P: 100-240Vac 50/60Hz 0.5A;  
O/P: 12V---1.0A

## 1.2 Characteristics of Device

802.11N(provide a mini-PCI interface glue with wireless AP module)  
WEP 64/128-bit encryption  
WAP, WAP2, WAP-PSK  
Support multiple SSID  
Hide SSID  
MAC Address Filtering

## 1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details.

## 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Aug. 05, 2008

## 2 PROVISIONS APPLICABLE

### 2.1 Definition

**Unintentional radiator:**

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

**Class A Digital Device:**

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

**Class B Digital Device :**

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

**Intentional radiator:**

A device that intentionally generates and emits radio frequency energy by radiation or induction.

## 2.2 Requirement for Compliance

### (1) Conducted Emission Requirement

Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB $\mu$ V	Average dB $\mu$ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

\* Decreases with the logarithm of the frequency

### (2) Radiated Emission Requirement

For unintentional device, according to §5.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB $\mu$ V/m	Radiated $\mu$ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §5.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

### (3) Antenna Requirement

For intentional device, according to §5.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



**(4) Bandwidth Requirement**

For direct sequence system, according to 15.247(a)(2), the minimum 6dB bandwidth shall be at least 500 kHz.

**(5) Output Power Requirement**

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**(6) 100 kHz Bandwidth of Frequency Band Edges Requirement**

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §5.209(a), whichever results in the lesser attenuation.

**(7) Power Density Requirement**

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

## 2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

\*\* : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

## 2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## 2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
  
- Increase the separation between the equipment and receiver.
  
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
  
- Consult the dealer or an experienced radio / TV technician for help.

### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification

For both radiated and conducted emissions below 1 GHz, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the cables connected to EUT to maximize the emission from EUT.

For conducted and radiated spurious emissions, whichever RF channel is operated, the digital circuits function identically. As the reason, measurement of radiated emissions from digital circuits is only performed with channel 7 by transmitting mode.

#### 3.2 Devices for Tested System

<b>Device</b>	<b>Manufacture</b>	<b>Model</b>	<b>Cable Description</b>
11N Wireless ADSL2+Router *	Comtrend Corporation	CT-5364A	1.8m Unshielded AC Adaptor Power Cord

Remark “\*” means equipment under test.

## 4 RADIATED EMISSION MEASUREMENT

### 4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §5.109(a).

For intentional radiators, according to §5.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §5.247 (c)

### 4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



### 4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum	Rohde & Schwarz	FSP40	2009/09/10	2010/09/09
EMI Test Receiver	Rohde & Schwarz	ESCI	2010/02/03	2011/02/02
Test Receiver	Rohde & Schwarz	ESVS30	2009/05/07	2010/05/06
Double Ridged Antenna	EMCO	3115	2009/05/12	2010/05/11
Log-periodic Antenna	EMCO	3146	2009/09/11	2010/09/10
Biconical Antenna	EMCO	3110B	2009/09/22	2010/09/21
Amplifier	HP	8449B	2009/12/16	2010/12/15
Amplifier	HP	8447D	2009/05/07	2010/05/06
Amplifier	HP	83051A	2009/05/11	2010/05/10

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

## 4.4 Radiated Emission Data

### 4.4.1 RF Portion

#### A. Channel Low(802.11b)

Operation Mode : Transmitting

Fundamental Frequency : 2412.000 MHz

Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave			
4824.028	46.3	***	48.7	***	-1.3	47.4	***	74.0	54.0	-6.6	67	1.2
7236.199	45.1	***	49.0	***	2.7	51.7	***	74.0	54.0	-2.3	93	1.4
9648.370	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12060.541	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14472.712	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16884.883	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19297.054	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21709.225	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24121.396	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : Receiving

Fundamental Frequency : Local Frequency : 2412.000 MHz

Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave			
* 2412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4824.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7236.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9648.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12060.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.



**B. Channel Middle(802.11b)**Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4874.168	47.0	***	47.9	***	-1.1	46.8	***	74.0	54.0	-7.2	79	1.2
7311.216	46.1	***	48.3	***	2.9	51.2	***	74.0	54.0	-2.8	83	1.5
9748.264	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12185.312	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14622.360	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17059.408	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19496.456	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21933.504	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24370.552	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**C. Channel High(802.11b)**Operation Mode : TransmittingFundamental Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4923.952	47.6	***	48.1	***	-1.0	47.1	***	74.0	54.0	-6.9	66	1.1
7385.888	48.1	***	50.2	***	3.2	53.4	***	74.0	54.0	-0.6	39	1.4
9847.824	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12309.760	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14771.696	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17233.632	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19695.568	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22157.504	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24619.440	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2462.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4924.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7386.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9848.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12310.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**D. Channel Low(802.11g)**Operation Mode : TransmittingFundamental Frequency : 2412.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4823.962	47.3	***	49.0	***	-1.3	47.7	***	74.0	54.0	-6.3	33	1.1
7236.098	47.1	***	47.8	***	2.7	50.5	***	74.0	54.0	-3.5	65	1.2
9648.234	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12060.370	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14472.506	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16884.642	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19296.778	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21708.914	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24121.050	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2412.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4824.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7236.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9648.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12060.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**E. Channel Middle(802.11g)**Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4874.369	47.6	***	48.2	***	-1.1	47.1	***	74.0	54.0	-6.9	67	1.1
7311.514	45.9	***	47.0	***	2.9	49.9	***	74.0	54.0	-4.1	59	1.3
9748.659	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12185.804	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14622.949	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17060.094	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19497.239	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21934.384	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24371.529	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**F. Channel High(802.11g)**Operation Mode : TransmittingFundamental Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4923.936	48.3	***	49.1	***	-1.0	48.1	***	74.0	54.0	-5.9	69	1.1
7380.263	46.7	***	47.9	***	3.2	51.1	***	74.0	54.0	-2.9	78	1.4
9836.590	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12292.917	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14749.244	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17205.571	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19661.898	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22118.225	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24574.552	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2462.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4924.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7386.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9848.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12310.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**G. Channel Low(802.11n HT-20)**Operation Mode : TransmittingFundamental Frequency : 2412.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4823.155	47.3	***	48.7	***	-1.3	47.4	***	74.0	54.0	-6.6	16	1.2
7234.733	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9646.310	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12057.888	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14469.465	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16881.043	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19292.620	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21704.198	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24115.775	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2412.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2412.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4824.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7236.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9648.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12060.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**H. Channel Middle(802.11n HT-20)**Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4872.116	47.9	***	49.0	***	-1.1	47.9	***	74.0	54.0	-6.1	67	1.4
7308.174	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9744.232	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12180.290	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14616.348	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17052.406	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19488.464	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21924.522	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24360.580	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**I. Channel High(802.11n HT-20)**Operation Mode : TransmittingFundamental Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4925.111	47.0	***	48.3	***	-1.0	47.3	***	74.0	54.0	-6.7	39	1.2
7387.667	---	---	---	---	-1.1	---	---	74.0	54.0	---	---	---
9850.223	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
12312.779	---	---	---	---	-1.0	---	---	74.0	54.0	---	---	---
14775.335	---	---	---	---	3.2	---	---	74.0	54.0	---	---	---
17237.891	---	---	---	---	-1.3	---	---	74.0	54.0	---	---	---
19700.447	---	---	---	---	2.7	---	---	74.0	54.0	---	---	---
22163.003	---	---	---	---	-1.1	---	---	74.0	54.0	---	---	---
24625.559	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2462.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2462.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4924.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7386.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9848.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12310.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.



**J. Channel Low(802.11n HT-40)**Operation Mode : TransmittingFundamental Frequency : 2422 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4843.958	47.2	***	48.3	***	-1.2	47.1	***	74.0	54.0	-6.9	33	1.1
7265.937	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9687.916	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12109.895	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14531.874	---	---	---	---	---	---	---	74.0	54.0	---	---	---
16953.853	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19375.832	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21797.811	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24219.790	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2422.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2422.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4844.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7266.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9688.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12110.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**K. Channel Middle(802.11n HT-40)**Operation Mode : TransmittingFundamental Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4873.514	46.9	***	48.2	***	-1.1	47.1	***	74.0	54.0	-6.9	38	1.4
7310.271	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9747.028	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12183.785	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14620.542	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17057.299	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19494.056	---	---	---	---	---	---	---	74.0	54.0	---	---	---
21930.813	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24367.570	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2437.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2437.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4874.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7311.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9748.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12185.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**L. Channel High(802.11n HT-40)**Operation Mode : TransmittingFundamental Frequency : 2452.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
4903.688	47.5	***	48.0	***	-1.0	47.0	***	74.0	54.0	-7.0	39	1.4
7355.532	---	---	---	---	---	---	---	74.0	54.0	---	---	---
9807.376	---	---	---	---	---	---	---	74.0	54.0	---	---	---
12259.220	---	---	---	---	---	---	---	74.0	54.0	---	---	---
14711.064	---	---	---	---	---	---	---	74.0	54.0	---	---	---
17162.908	---	---	---	---	---	---	---	74.0	54.0	---	---	---
19614.752	---	---	---	---	---	---	---	74.0	54.0	---	---	---
22066.596	---	---	---	---	---	---	---	74.0	54.0	---	---	---
24518.440	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Operation Mode : ReceivingFundamental Frequency : Local Frequency : 2452.000 MHzTest Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
	Peak	Ave	Peak	Ave								
* 2452.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 4904.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 7356.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 9808.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---
* 12260.000	---	---	---	---	---	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Remark "\*" means the local oscillator frequency and its harmonics.
5. Item "Margin" referred to Average limit while there is only peak result.
6. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**4.4.2 Radiated Emission of Restricted bands****Mode: 802.11b**Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %**Operation Mode : CH 01****Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2378.240	31.6	17.6	32.3	18.3	30.2	62.5	48.5	74.0	54.0	-5.5	58	1.2
2389.980	30.5	17.5	32.8	19.3	30.2	63.0	49.5	74.0	54.0	-4.5	66	1.2

**Operation Mode : CH 11****Restricted Frequency band: 2483.5MHz – 2500MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2483.620	29.6	17.6	31.8	18.8	30.4	62.2	49.2	74.0	54.0	-4.8	77	1.2
2484.410	28.8	17.2	30.0	18.5	30.4	60.4	48.9	74.0	54.0	-5.1	83	1.1

*Note :*

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “\*\*\*” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**Mode: 802.11g**Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %**Operation Mode : CH 01 Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2387.680	33.2	19.0	35.6	19.8	30.2	65.8	50.0	74.0	54.0	-4.0	27	1.2
2389.200	33.8	19.5	37.0	20.5	30.2	67.2	50.7	74.0	54.0	-3.3	90	1.4

**Operation Mode : CH 11 Restricted Frequency band: 2483.5MHz – 2500MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2483.580	37.8	19.8	40.3	22.1	30.4	70.7	52.5	74.0	54.0	-1.5	67	1.2
2483.800	38.0	19.5	40.0	21.8	30.4	70.4	52.2	74.0	54.0	-1.8	73	1.2

*Note :*

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “\*\*\*” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**Mode: 802.11n HT-20**Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %**Operation Mode : CH 01 Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave	Peak	Ave.			
2388.640	33.6	18.8	36.0	20.5	30.2	66.2	50.7	74.0	54.0	-3.3	33	1.2
2389.680	33.8	19.0	37.6	21.2	30.2	67.8	51.4	74.0	54.0	-2.6	54	1.3

**Operation Mode : CH 11 Restricted Frequency band: 2483.5MHz – 2500MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	Ave	V Peak	Ave		Peak	Ave	Peak	Ave.			
2484.010	30.6	20.3	32.1	21.9	30.4	62.5	52.3	74.0	54.0	-1.7	71	1.4
2485.530	30.1	19.8	32.3	21.5	30.4	62.7	51.9	74.0	54.0	-2.1	70	1.1

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “\*\*\*\*” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**Mode: 802.11n HT-40**Test Date : Mar. 02, 2010 Temperature : 19 °C Humidity : 63 %**Operation Mode : CH 01 Restricted Frequency band: 2310MHz – 2390MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2388.640	38.6	17.6	40.3	18.8	30.2	70.5	49.0	74.0	54.0	-3.5	35	1.1
2389.650	37.9	17.8	39.8	18.9	30.2	70.0	49.1	74.0	54.0	-4.0	37	1.2

**Operation Mode : CH 9 Restricted Frequency band: 2483.5MHz – 2500MHz**

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave.			
2484.460	37.8	17.2	39.3	18.8	30.4	69.7	49.2	74.0	54.0	-4.3	41	1.4
2488.710	37.0	17.1	39.2	18.5	30.4	69.6	48.9	74.0	54.0	-4.4	48	1.3

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark “\*\*\*” means that Peak result is meet average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. Item “Margin” referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**4.4.3 Other Emission**

a) Emission frequencies below 1 GHz

Operation Mode : full load on line

Test Date : Mar. 16, 2010 Temperature : 21 °C Humidity : 64 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
133.52	H	23.8	13.7	37.5	43.5	-6.0	66	2.5
222.41	H	22.2	18.8	41.0	46.0	-5.0	74	2.7
233.52	V	23.3	19.3	42.6	46.0	-3.4	65	1.2
249.78	H	15.6	20.3	35.9	46.0	-10.1	45	1.8
349.50	H	24.0	17.8	41.8	46.0	-4.2	24	1.5
400.04	H	25.2	19.1	44.3	46.0	-1.7	78	1.6

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

Operation Mode : full load on line (adap on table)

Test Date : Mar. 16, 2010 Temperature : 21 °C Humidity : 64 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
133.52	H	23.7	13.7	37.4	43.5	-6.1	67	2.5
222.41	H	22.2	18.8	41.0	46.0	-5.0	71	2.6
233.52	V	23.2	19.3	42.5	46.0	-3.5	64	1.2
249.78	H	15.7	20.3	36.0	46.0	-10.0	44	1.8
349.50	H	24.0	17.8	41.8	46.0	-4.2	29	1.5
400.04	H	25.0	19.1	44.1	46.0	-1.9	74	1.6

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.



## 4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna FACTOR} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

## 4.6 Photos of Radiation Measuring Setup



## 5 CONDUCTED EMISSION MEASUREMENT


### 5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and §5.207(a) respectively. Both Limits are identical specification.

### 5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



### 5.3 Conducted Emission Data

Operation Mode : Operation Link

Test Date : Mar. 16, 2010      Temperature : 21 °C      Humidity : 64 %

Mode: Operation Link

N1

Frequency (MHz)	Meter Reading (dB $\mu$ V)		Factor (dB)	Result (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB $\mu$ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.172	47.2		----	0.4	47.6	----	64.9	54.9
0.231	40.2	----	0.4	40.6	----	62.4	52.4	-21.8	----
0.361	38.2	----	0.4	38.6	----	58.7	48.7	-20.1	----
0.456	39.6	----	0.4	40.0	----	56.8	46.8	-16.8	----
3.173	39.9	----	0.5	40.4	----	56.0	46.0	-15.6	----
8.963	38.2	----	0.7	38.9	----	60.0	50.0	-21.1	----

Mode: Operation Link


L1

Frequency (MHz)	Meter Reading (dB $\mu$ V)		Factor (dB)	Result (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB $\mu$ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
	0.365	39.5		----	0.4	39.9	----	58.6	48.6
0.423	40.1	----	0.4	40.5	----	57.4	47.4	-16.9	----
1.990	39.4	----	0.4	39.8	----	56.0	46.0	-16.2	----
2.308	40.6	----	0.4	41.0	----	56.0	46.0	-15.0	----
2.567	41.5	----	0.5	42.0	----	56.0	46.0	-14.0	----
8.963	38.6	----	0.8	39.4	----	60.0	50.0	-20.6	----

Note : The expanded uncertainty of the conducted emission tests is 2.45 dB

Mode: Operation Link


N1



Date: 16.MAR.2010 12:30:23

Mode: Operation Link

L1



Date: 16.MAR.2010 12:33:14

## 5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{RESULT = READING + LISN FACTOR}$$

Assume a receiver reading of 22.5 dB  $\mu$  V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB  $\mu$  V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

## 5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2010/02/03	2011/02/02
LISN	EMCO	3625/2	2010/02/08	2011/02/07
LISN	Rohde & Schwarz	ESH2-Z5	2009/07/16	2010/07/15

## 5.6 Photos of Conduction Measuring Setup



## **6 ANTENNA REQUIREMENT**

### **6.1 Standard Applicable**

For intentional device, according to §5.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to §5.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **6.2 Antenna Construction and Directional Gain**

Please see photos submitted in Exhibit B.

An external omni-directional antenna with IPEX connector was employed. The antenna gain is 2.72dBi. No need to reduce the peak output power.

Please see construction Photos of Exhibit B for details.



## 7 EMISSION BANDWIDTH MEASUREMENT


### 7.1 Standard Applicable

According to 15.247(a)(2), for direct sequence system, the minimum 6dB bandwidth shall be at least 500 kHz.

### 7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



### 7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2009/09/10	2010/09/09

## 7.4 Measurement Data

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

### A 802.11b

- a) Channel Low: 6 dB Emission Bandwidth is 10.256 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 10.256 MHz
- c) Channel High: 6 dB Emission Bandwidth is 10.256 MHz

### B 802.11g

- a) Channel Low: 6 dB Emission Bandwidth is 16.506 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 16.506 MHz
- c) Channel High: 6 dB Emission Bandwidth is 16.506 MHz

### C 802.11n HT-20-Antenna 1

- a) Channel Low: 6 dB Emission Bandwidth is 17.644 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 17.660 MHz
- c) Channel High: 6 dB Emission Bandwidth is 17.708 MHz

### D 802.11n HT-20-Antenna 2

- a) Channel Low: 6 dB Emission Bandwidth is 17.692 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 17.804 MHz
- c) Channel High: 6 dB Emission Bandwidth is 17.692 MHz

### E 802.11n HT-40-Antenna 1


- a) Channel Low: 6 dB Emission Bandwidth is 36.490 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 36.362 MHz
- c) Channel High: 6 dB Emission Bandwidth is 35.288 MHz

### F 802.11n HT-40-Antenna 2

- a) Channel Low: 6 dB Emission Bandwidth is 35.801 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 36.185 MHz
- c) Channel High: 6 dB Emission Bandwidth is 36.330 MHz

*Note : The expanded uncertainty of the emission bandwidth tests is 1500Hz.*

### 802.11b






\*RBW 100 kHz      Delta 1 [T1 ]  
VBW 300 kHz      -0.26 dB  
SWT 20 ms      10.256410256 MHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Delta 1 [T1 ]  
VBW 300 kHz      -1.86 dB  
SWT 20 ms      10.256410256 MHz


Ref 20 dBm      Offset 31 dB


Att 15 dB


1 PK  
VIEW



### 802.11g












### 802.11n HT-20-Antenna 1










### 802.11n HT-20-Antenna 2




\*RBW 100 kHz      Delta 1 [T1 ]  
\*VBW 100 kHz      1.03 dB  
Ref 20 dBm      \*Att 10 dB      SWT 20 ms      17.692307692 MHz







### 802.11n HT-40-Antenna 1






\*RBW 100 kHz      Delta 1 [T1 ]  
\*VBW 100 kHz      -0.25 dB  
SWT 20 ms          36.362179487 MHz


Ref 20 dBm

\*Att 15 dB


1 PK  
VIEW







### 802.11n HT-40-Antenna 2







\*RBW 100 kHz      Delta 1 [T1 ]  
\*VBW 100 kHz      1.63 dB  
SWT 20 ms      36.185897436 MHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW





Date: 10.MAR.2010 16:55:19

## 8 OUTPUT POWER MEASUREMENT


### 8.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz.
4. Use channel power function and record the level displayed.
5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



### 8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
POWER METER+SENSOR	ANRITSU	ML2487A+ MA2491A	2009/12/15	2010/12/14

## 8.4 Measurement Data

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

The antenna gain is 12.06dBi so the power should be reduced by 6.06dB. The maximum peak output power limit is 23.94dBm.

### A 802.11b

- a) Channel Low:    Output Peak Power is    19.7    dBm    **93.325**    mW
- b) Channel Mid:    Output Peak Power is    19.6    dBm    **91.201**    mW
- c) Channel High:    Output Peak Power is    19.8    dBm    **95.499**    mW

### B 802.11g

- a) Channel Low:    Output Peak Power is    22.4    dBm    **173.78**    mW
- b) Channel Mid:    Output Peak Power is    22.3    dBm    **169.82**    mW
- c) Channel High:    Output Peak Power is    22.5    dBm    **177.83**    mW

### C.1 802.11n HT-20-Antenna 1

- a) Channel Low:    Output Peak Power is    22.7    dBm    **186.21**    mW
- b) Channel Mid:    Output Peak Power is    22.8    dBm    **190.55**    mW
- c) Channel High:    Output Peak Power is    22.9    dBm    **194.98**    mW

### C.2 802.11n HT-20-Antenna 2

- a) Channel Low:    Output Peak Power is    22.6    dBm    **181.97**    mW
- b) Channel Mid:    Output Peak Power is    22.5    dBm    **177.83**    mW
- c) Channel High:    Output Peak Power is    22.6    dBm    **181.97**    mW

### C.3 802.11n 20M Combined peak out power

- a) Channel Low      Output Peak Power is  $22.7 + 22.6 = 368.1788$  mW (25.660 dBm).
- b) Channel Middle    Output Peak Power is  $22.8 + 22.5 = 368.374$  mW (25.662dBm).
- c) Channel High      Output Peak Power is  $22.9 + 22.6 = 376.954$  mW (25.762 dBm)

**D.1 802.11n HT-40-Antenna 1**

- a) Channel Low: Output Peak Power is 21 dBm **125.89** mW
- b) Channel Mid: Output Peak Power is 21 dBm **125.89** mW
- c) Channel High: Output Peak Power is 21.3 dBm **134.9** mW

**D.2 802.11n HT-40-Antenna 2**

- a) Channel Low: Output Peak Power is 21 dBm **125.89** mW
- b) Channel Mid: Output Peak Power is 21.1 dBm **128.82** mW
- c) Channel High: Output Peak Power is 21.3 dBm **134.9** mW

**D.3 802.11n HT-40 Combined peak out power**

- a) Channel Low Output Peak Power is  $21 + 21 = 251.785$  mW (24.010 dBm)。
- b) Channel Middle Output Peak Power is  $21 + 21.1 = 254.717$  mW (24.060 dBm)。
- c) Channel High Output Peak Power is  $21.3 + 21.3 = 269.792$  mW (24.310 dBm)

**Note : The expanded uncertainty of the output power tests is 2dB.**

## 9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

### 9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

### 9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW of spectrum analyzer to 100kHz and VBW to 1 MHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### 9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2009/09/10	2010/09/09



## 9.4 Measurement Data

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

### A 802.11b

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

### B 802.11g

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

### C 802.11n HT-20-Antenna 1

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

### D 802.11n HT-20-Antenna 2

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

### E 802.11n HT-40-Antenna 1

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

### E 802.11n HT-40-Antenna 2

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.


**Note : The expanded uncertainty of the 100 khz bandwidth of band edges tests is 2dB.**

### 802.11b



1 PK  
VIEW

\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -32.24 dBm  
SWT 10 ms          2.397038462 GHz






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -43.74 dBm  
SWT 10 ms          2.484730769 GHz


Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW



### 802.11g






### 802.11n 20M-Antenna 1




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -23.88 dBm  
SWT 10 ms          2.399500000 GHz





\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -40.50 dBm  
SWT 10 ms          2.485500000 GHz




### 802.11n 20M-Antenna 2



\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -24.76 dBm  
SWT 10 ms          2.399403846 GHz

Ref 20 dBm      \*Att 10 dB


1 PK  
VIEW







\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -43.28 dBm  
SWT 10 ms          2.485019231 GHz



### 802.11n 40M-Antenna 1




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -32.04 dBm  
SWT 10 ms          2.399769231 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -36.98 dBm  
SWT 10 ms          2.484512821 GHz

Ref 20 dBm

\*Att 15 dB


1 PK  
VIEW



### 802.11n 40M-Antenna 2




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -32.01 dBm  
SWT 10 ms          2.399769231 GHz





\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -38.48 dBm  
SWT 10 ms          2.489538462 GHz



## 10 POWER DENSITY MEASUREMENT

### 10.1 Standard Applicable

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

### 10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on highest level appearing on spectral display within a 300 kHz frequency span.
4. Set the spectrum analyzer on a 3 kHz resolution bandwidth and 300 kHz video bandwidth as well as max hold function.
5. Repeat above procedures until all measured frequencies were complete.

### 10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2009/09/10	2010/09/09

## 10.4 Measurement Data

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

### A 802.11b

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -6.58 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -6.55 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -6.52 dBm

### B 802.11g

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -10.62 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -10.20 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is - 9.64 dBm

### C 802.11n HT-20-Antenna 1

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -8.42 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -8.95 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -9.61 dBm

### D 802.11n HT-20-Antenna 2

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -9.06 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -7.47 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -8.44 dBm

### E 802.11n HT-20 Combined

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -6.23 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -6.64 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -5.32 dBm

### F 802.11n HT-40-Antenna 1

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -13.12 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -13.88 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -14.63 dBm

### G 802.11n HT-40-Antenna 2

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -14.02 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -15.49 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -15.21 dBm

*Note : The expanded uncertainty of the power density tests is 2dB.*

**H 802.11n HT-40-Combined**

- a) Channel Low: Maximun Power Density of 3 kHz Bandwidth is -12.05 dBm
- b) Channel Mid: Maximun Power Density of 3 kHz Bandwidth is -12.89 dBm
- c) Channel High: Maximun Power Density of 3 kHz Bandwidth is -11.31 dBm

***Note : The expanded uncertainty of the power density tests is 2dB.***




### 802.11b



\* RBW 3 kHz                      Marker 1 [T1 ]  
\* VBW 100 kHz                      -6.58 dBm  
\* SWT 100 s                      2.414751923 GHz

Ref 20 dBm

Att 15 dB






\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -6.55 dBm  
\* SWT 100 s      2.434190865 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW



Center 2.434169231 GHz      30 kHz/      Span 300 kHz




\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -6.52 dBm  
\* SWT 100 s      2.459191186 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW



Center 2.459309455 GHz      30 kHz/      Span 300 kHz

### 802.11g




\* RBW 3 kHz                      Marker 1 [T1 ]  
\* VBW 100 kHz                      -10.62 dBm  
\* SWT 100 s                      2.414471955 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW



Center 2.414471955 GHz

30 kHz/

Span 300 kHz




\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -10.20 dBm  
\* SWT 100 s      2.439463782 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW






\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -9.64 dBm  
\* SWT 100 s      2.463220994 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW



Center 2.463188301 GHz      30 kHz/      Span 300 kHz

### 802.11n 20M-Antenna 1




\*RBW 3 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -8.42 dBm  
\*SWT 100 s      2.413223878 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW





\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -8.95 dBm  
\* Att 10 dB      \* SWT 100 s      2.442008333 GHz

Ref 20 dBm

\* Att 10 dB


\* RBW 3 kHz

Marker 1 [ T1 ]

-8.95 dBm

2.442008333 GHz

1 PK  
VIEW







\*RBW 3 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -9.61 dBm  
\*Att 10 dB      \*SWT 100 s      2.465721474 GHz


Ref 20 dBm

\*Att 10 dB

\*SWT 100 s

2.465721474 GHz

1 PK  
VIEW



### 802.11n 20M-Antenna 2




\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -9.06 dBm  
\* SWT 100 s      2.407596795 GHz

Ref 20 dBm

\* Att 10 dB

1 PK  
VIEW



Center 2.407597276 GHz      30 kHz/      Span 300 kHz




\*RBW 3 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -7.47 dBm  
\*SWT 100 s      2.439470833 GHz

Ref 20 dBm

\*Att 15 dB

2.439470833 GHz

1 PK  
VIEW






\*RBW 3 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -8.44 dBm  
\*SWT 100 s      2.465470673 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW



### 802.11n 20M Combined




\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -6.23 dBm  
\* SWT 100 s      2.414470513 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



Center 2.414485417 GHz

30 kHz/

Span 300 kHz




\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -6.64 dBm  
\* SWT 100 s      2.439470513 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



Center 2.439477724 GHz      30 kHz/      Span 300 kHz




\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -5.32 dBm  
\* SWT 100 s      2.458269071 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



### 802.11n 40M-Antenna 1




\* RBW 3 kHz                    Marker 1 [T1 ]  
\* VBW 100 kHz                    -13.12 dBm  
\* SWT 100 s                    2.424497756 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



Center 2.424501122 GHz

30 kHz/

Span 300 kHz






\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -13.88 dBm  
\* SWT 100 s      2.441957853 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW






\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -14.63 dBm  
\* SWT 100 s      2.446908013 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



### 802.11n 40M-Antenna 2




\* RBW 3 kHz                      Marker 1 [T1 ]  
\* VBW 100 kHz                      -14.02 dBm  
\* SWT 100 s                      2.428164904 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



Center 2.428258654 GHz

30 kHz/

Span 300 kHz




\*RBW 3 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -15.49 dBm  
\*SWT 100 s      2.438858814 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW



Center 2.438871795 GHz      30 kHz/      Span 300 kHz




\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -15.21 dBm  
\* SWT 100 s      2.458809295 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



### 802.11n 40M Combined




\* RBW 3 kHz                      Marker 1 [T1 ]  
\* VBW 100 kHz                    -12.05 dBm  
\* SWT 100 s                        2.412378045 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



Center 2.41231891 GHz                      30 kHz/                      Span 300 kHz




\* RBW 3 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -12.89 dBm  
\* Att 15 dB      2.434487179 GHz  
\* SWT 100 s

Ref 20 dBm

\* Att 15 dB

2.434487179 GHz

1 PK  
VIEW



Center 2.434485737 GHz      30 kHz/      Span 300 kHz




\* RBW 3 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -11.31 dBm  
\* Att 15 dB      \* SWT 100 s      2.448220513 GHz

Ref 20 dBm

\* Att 15 dB

2.448220513 GHz

1 PK  
VIEW





## 11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT

### 11.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

### 11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold.

4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

### 11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2009/09/10	2010/09/09

## 11.4 Measurement Data

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

### A 802.11b

#### Model : Channel Low

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

#### Model : Channel Mid

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

#### Model : Channel High

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**B 802.11g**

**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**C 802.11n HT-20-Antenna 1**

**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**D 802.11n HT-20-Antenna 2**

**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**E 802.11n HT-20 Combined**

**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**F 802.11n HT-40-Antenna 1**

**Model : Channel Low**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- a) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- b) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

**G 802.11n HT-40-Antenna 2**

**Model : Channel Low**

- c) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- d) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel Mid**

- c) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- d) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

**Model : Channel High**

- c) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- d) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.



Test Date : Mar. 02, 2010      Temperature : 19 °C      Humidity : 63 %

### **H 802.11n HT-40 Combined**

#### **Model : Channel Low**

- e) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- f) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

#### **Model : Channel Mid**

- e) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- f) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

#### **Model : Channel High**

- e) 1 GHz to 3 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- f) 3 GHz to 25 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.

***Note : The expanded uncertainty of the out-of-band conducted emission tests is 2dB.***


**802.11b**



\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      4.12 dBm  
SWT 200 ms      2.416666667 GHz


Ref 20 dBm      Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      -38.89 dBm  
SWT 2.2 s      3.387820513 GHz





\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      4.08 dBm  
SWT 200 ms      2.432692308 GHz






\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      -39.09 dBm  
SWT 2.2 s      3.105769231 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      4.08 dBm  
SWT 200 ms      2.458333333 GHz

Ref 20 dBm

Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
VBW 300 kHz      -38.49 dBm  
SWT 2.2 s      3.564102564 GHz

Ref 20 dBm

Att 15 dB


1 PK  
VIEW



### 802.11g



\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -0.19 dBm  
SWT 200 ms      2.416666667 GHz








\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -45.29 dBm  
SWT 2.2 s            3.564102564 GHz

Ref 10 dBm

Att 10 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      2.19 dBm  
SWT 200 ms      2.442307692 GHz

Ref 10 dBm

Att 10 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -44.93 dBm  
SWT 2.2 s            3.493589744 GHz

Ref 10 dBm

Att 10 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      0.44 dBm  
SWT 200 ms      2.471153846 GHz

Ref 10 dBm

Att 10 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -45.64 dBm  
SWT 2.2 s            3.458333333 GHz

Ref 10 dBm

Att 10 dB

1 PK  
VIEW



### 802.11n 20M-Antenna 1




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      2.67 dBm  
SWT 200 ms      2.419871795 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -43.89 dBm  
SWT 2.2 s          3.035256410 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      2.51 dBm  
SWT 200 ms      2.442307692 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW








\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -45.30 dBm  
SWT 2.2 s          22.320512821 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      1.80 dBm  
SWT 200 ms      2.458333333 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -44.88 dBm  
SWT 2.2 s          19.288461538 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW



### 802.11n 20M-Antenna 2




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      0.99 dBm  
SWT 200 ms      2.407051282 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -40.13 dBm  
SWT 2.2 s            19.817307692 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      1.98 dBm  
SWT 200 ms      2.442307692 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -40.53 dBm  
SWT 2.2 s          23.025641026 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      1.82 dBm  
SWT 200 ms      2.458333333 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW








\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -44.68 dBm  
SWT 2.2 s          24.647435897 GHz

Ref 20 dBm

\*Att 10 dB

1 PK  
VIEW




### 802.11n 20M Combined peak out power



\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      3.98 dBm  
SWT 200 ms      2.410256410 GHz

Ref 20 dBm

\*Att 15 dB






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -35.90 dBm  
SWT 2.2 s          25.000000000 GHz

Ref 20 dBm


\*Att 15 dB

1 PK  
VIEW





\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      7.85 dBm  
\* Att 15 dB      SWT 200 ms      2.464743590 GHz






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -35.75 dBm  
SWT 2.2 s          24.647435897 GHz

Ref 20 dBm


\*Att 15 dB

1 PK  
VIEW





\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      7.85 dBm  
\* Att 15 dB      2.464743590 GHz  
SWT 200 ms






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -36.00 dBm  
SWT 2.2 s          23.342948718 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW



### 802.11n 40M-Antenna 1




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -1.88 dBm  
SWT 200 ms      2.429487179 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW








\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -39.62 dBm  
SWT 2.2 s          21.756410256 GHz

Ref 20 dBm


\* Att 15 dB

1 PK  
VIEW





\* RBW 100 kHz      Marker 1 [ T1 ]  
\* VBW 100 kHz      -2.11 dBm  
\* Att 15 dB      SWT 200 ms      2.432692308 GHz






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -39.88 dBm  
SWT 2.2 s      25.000000000 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -1.74 dBm  
SWT 200 ms      2.448717949 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -38.78 dBm  
SWT 2.2 s            24.400641026 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



### 802.11n 40M-Antenna 2




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -2.25 dBm  
SWT 200 ms      2.407051282 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -40.43 dBm  
SWT 2.2 s          19.852564103 GHz

Ref 20 dBm


\*Att 15 dB

1 PK  
VIEW





\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -0.46 dBm  
SWT 200 ms      2.455128205 GHz








\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -40.07 dBm  
SWT 2.2 s          20.416666667 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -0.39 dBm  
SWT 200 ms      2.445512821 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      -40.50 dBm  
SWT 2.2 s            24.224358974 GHz

Ref 20 dBm

\* Att 15 dB

1 PK  
VIEW



### 802.11n 40M Combined peak out power




\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      3.31 dBm  
SWT 200 ms      2.432692308 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -36.30 dBm  
SWT 2.2 s          24.612179487 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      2.47 dBm  
SWT 200 ms      2.432692308 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW






\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -34.98 dBm  
SWT 2.2 s          24.012820513 GHz

Ref 20 dBm


\*Att 15 dB

1 PK  
VIEW





\* RBW 100 kHz      Marker 1 [T1 ]  
\* VBW 100 kHz      2.22 dBm  
\* Att 15 dB      2.464743590 GHz  
SWT 200 ms







\*RBW 100 kHz      Marker 1 [T1 ]  
\*VBW 100 kHz      -34.80 dBm  
SWT 2.2 s          24.506410256 GHz

Ref 20 dBm

\*Att 15 dB

1 PK  
VIEW

