



# A Test Lab Techno Corp.

Changan Lab : N o. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)  
Tel : 886-3-271-0188 / Fax : 886-3-271-0190



## MPE Report

Test Report No.	: 1606FS15-01
Applicant	: Comtrend Corporation
Product Type	: Wireless Gateway
Trade Name	: COMTREND
Model Number	: VR-3060u, VR-3060
Date of Received	: Apr. 19, 2016
Test Period	: Apr. 29, 2016
Date of Issued	: Sep. 27, 2016
Test Specification	: ANSI / IEEE Std.C95.1-1992 / IEEE Std. 1528-2013 47 CFR § 2.1091 47 CFR § 1.1310
Location of Test Lab.	: Chang-an Lab.

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By

: Bill Hu  
(Bill Hu)

Tested By

: Mark Duan  
(Mark Duan)



# Contents

1. Description of Equipment under Test (EUT).....	3
2. Human Exposure Assessment.....	4
3. RF Output Power .....	5
4. Test Result .....	8



## 1. Description of Equipment under Test (EUT)

Applicant	Comtrend Corporation 3F-1, No. 10, Lane 609, Chung Hsin Road, Section 5, San Chung Dist, New Taipei City 24159, Taiwan				
Manufacturer	Comtrend Corporation 3F-1, No. 10, Lane 609, Chung Hsin Road, Section 5, San Chung Dist, New Taipei City 24159, Taiwan				
Product Type	Wireless Gateway				
Trade Name	COMTREND				
Model Number	VR-3060u, VR-3060				
Model Different Description	Those model numbers differ from each other in selling region.				
FCC ID	L9VVR3060U				
Frequency Range	IEEE 802.11b / 802.11g / 802.11n 2.4GHz 20MHz : 2412 - 2462 MHz IEEE 802.11n 2.4GHz 40MHz : 2422 - 2452 MHz IEEE 802.11a U-NII Band I : 5180 - 5240 MHz IEEE 802.11a U-NII Band III : 5745 - 5825 MHz IEEE 802.11n 5GHz 20MHz U-NII Band I : 5180 - 5240 MHz IEEE 802.11ac 20MHz U-NII Band I : 5180 - 5240 MHz IEEE 802.11n 5GHz 20MHz U-NII Band III : 5745 - 5825 MHz IEEE 802.11ac 20MHz U-NII Band III : 5745 - 5825 MHz IEEE 802.11n 5GHz 40MHz U-NII Band I : 5190 - 5230 MHz IEEE 802.11ac 40MHz U-NII Band I : 5190 - 5230 MHz IEEE 802.11n 5GHz 40MHz U-NII Band III : 5755 - 5795 MHz IEEE 802.11ac 40MHz U-NII Band III : 5755 - 5795 MHz IEEE 802.11ac 80MHz U-NII Band I : 5210 MHz IEEE 802.11ac 80MHz U-NII Band III : 5775 MHz				
Antenna information	ANT	Trade Name	Model Number	Type	Max. Gain (dBi)
	2.4GHz ANT-0	Cortec	AN2450-64D02BBO	External antenna	2.5
	2.4GHz ANT-1	Cortec	AN2450-64D03BBO	External antenna	1.2
	5GHz ANT-0	Cortec	AN2450-64D02BBO	External antenna	2.5
	5GHz ANT-1	Cortec	NBO351-C70BO	Embedded antenna	4.0
	5GHz ANT-2	Cortec	AN2450-64D03BBO	External antenna	2.5
Directional Gain	Band				
	2.4GHz	4.88 dBi (please refer to RF report)			
	5GHz	7.80 dBi (please refer to RF report)			
Temperature Range	0 ~ +40°C				
RF Evaluation	0.895 mW/cm <sup>2</sup>				

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



## 2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.



### 3. RF Output Power

The conducted power turn-up tolerance reference manufacturer specification.

Band	Data Rate	CH	Frequency (MHz)	Average Conducted power (dBm)		
				ANT-0	ANT-1	ANT-0+1
IEEE 802.11b ANT-0	1M	1	2412.0	25.75	---	---
		6	2437.0	25.45	---	---
		11	2462.0	25.37	---	---
	2M	6	2437.0	25.44	---	---
	5.5M	6	2437.0	25.42	---	---
	11M	6	2437.0	25.41	---	---
IEEE 802.11g ANT-0	6M	1	2412.0	21.03	---	---
		6	2437.0	20.85	---	---
		11	2462.0	20.55	---	---
	9M	6	2437.0	20.83	---	---
	12M	6	2437.0	20.82	---	---
	18M	6	2437.0	20.79	---	---
	24M	6	2437.0	20.78	---	---
	36M	6	2437.0	20.76	---	---
	48M	6	2437.0	20.75	---	---
	54M	6	2437.0	20.72	---	---
IEEE 802.11n 2.4GHz 20MHz	13M	1	2412.0	16.88	16.62	19.76
		6	2437.0	16.85	16.83	19.85
		11	2462.0	16.67	16.41	19.55
	26M	6	2437.0	16.82	16.79	19.82
	39M	6	2437.0	16.79	16.78	19.80
	52M	6	2437.0	16.76	16.75	19.77
	78M	6	2437.0	16.74	16.70	19.73
	104M	6	2437.0	16.71	16.66	19.70
	117M	6	2437.0	16.66	16.61	19.65
	130M	6	2437.0	16.63	16.59	19.62
IEEE 802.11n 2.4GHz 40MHz	27M	3	2422.0	16.42	16.34	19.39
		6	2437.0	16.95	17.22	20.10
		9	2452.0	16.35	16.27	19.32
	54M	6	2437.0	16.91	17.18	20.06
	81M	6	2437.0	16.88	17.17	20.04
	108M	6	2437.0	16.85	17.12	20.00
	162M	6	2437.0	16.82	17.08	19.96
	216M	6	2437.0	16.78	17.00	19.90
	243M	6	2437.0	16.75	16.93	19.85
	135M	6	2437.0	16.71	16.88	19.81



Band	Data Rate	CH	Frequency (MHz)	Average Conducted power (dBm)			
				ANT-0	ANT-1	ANT-2	ANT-0+1+2
IEEE 802.11a	6M	36	5180.0	20.49	20.16	20.24	25.07
		40	5200.0	19.45	18.77	19.18	23.91
		44	5220.0	19.26	18.68	18.86	23.71
		48	5240.0	19.13	18.74	18.82	23.67
		149	5745.0	23.05	22.34	23.41	27.73
		153	5765.0	22.87	22.09	23.22	27.52
		157	5785.0	22.65	22.17	23.37	27.53
		161	5805.0	22.66	22.34	23.31	27.56
	165	5825.0	21.19	20.80	20.85	25.72	
	54M	36	5180.0	20.38	20.06	20.14	24.97
		40	5200.0	19.28	18.67	19.01	23.77
		44	5220.0	19.14	18.52	18.74	23.58
		48	5240.0	19.05	18.58	18.64	23.53
		149	5745.0	22.95	22.24	23.21	27.59
		153	5765.0	22.71	21.98	23.12	27.40
		157	5785.0	22.48	22.07	23.18	27.37
161		5805.0	22.58	22.25	23.17	27.45	
165	5825.0	21.01	20.69	20.71	25.58		
IEEE 802.11ac 20MHz	19.5M	36	5180.0	21.46	20.65	20.78	25.75
		40	5200.0	21.37	20.88	20.76	25.78
		44	5220.0	21.41	20.71	20.65	25.71
		48	5240.0	21.31	20.76	20.64	25.68
		149	5745.0	22.68	22.08	23.18	27.44
		153	5765.0	22.53	21.92	22.76	27.19
		157	5785.0	22.64	22.01	23.42	27.50
		161	5805.0	22.55	22.06	23.47	27.50
	165	5825.0	22.79	22.11	23.27	27.52	
	234M	36	5180.0	20.51	19.62	19.85	24.78
		40	5200.0	20.36	19.92	19.72	24.78
		44	5220.0	20.44	19.71	19.65	24.72
		48	5240.0	20.31	19.75	19.61	24.67
		149	5745.0	21.74	21.14	22.25	26.50
		153	5765.0	21.51	20.91	21.82	26.20
		157	5785.0	21.61	21.05	22.41	26.50
161		5805.0	21.55	21.13	22.55	26.56	
165	5825.0	21.88	21.16	22.31	26.58		



Band	DataRate	CH	Frequency (MHz)	Average Conducted power (dBm)			
				ANT-0	ANT-1	ANT-2	ANT-0+1+2
IEEE 802.11ac 40MHz	40.5M	38	5190.0	19.79	19.04	19.46	24.21
		46	5230.0	23.01	21.91	22.61	27.30
		151	5755.0	22.97	22.53	23.51	27.79
		159	5795.0	23.01	22.48	23.65	27.84
	540M	38	5190.0	18.82	17.72	18.52	23.15
		46	5230.0	21.82	21.05	21.51	26.24
		151	5755.0	21.81	21.66	22.48	26.77
		159	5795.0	22.09	21.51	22.68	26.89
IEEE 802.11ac 80MHz	87.9M	42	5210.0	18.92	18.55	18.31	23.37
		155	5775.0	21.22	21.00	21.13	25.89
	1170M	42	5210.0	17.38	17.09	16.94	21.91
		155	5775.0	19.68	19.41	19.62	24.34



#### 4. Test Result

Band	Data Rate	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	[P] x [G] with Duty cycle [TP] (mW)	Power Density [S] (mw)/cm <sup>2</sup>
IEEE 802.11b ANT-0	1M	2412	1.000	20	25.90	2.50	1.78	1	692.500	0.138
		2437	1.000	20	25.60	2.50	1.78	1	646.280	0.129
		2462	1.000	20	25.50	2.50	1.78	1	631.570	0.126
IEEE 802.11g ANT-0	6M	2412	1.000	20	21.20	2.50	1.78	1	234.650	0.047
		2437	1.000	20	21.00	2.50	1.78	1	224.090	0.045
		2462	1.000	20	20.70	2.50	1.78	1	209.130	0.042
IEEE 802.11n 2.4GHz 20MHz MIMO	13M	2412	1.000	20	19.90	4.88	3.08	1	300.990	0.060
		2437	1.000	20	20.00	4.88	3.08	1	308.000	0.061
		2462	1.000	20	19.70	4.88	3.08	1	287.440	0.057
IEEE 802.11n 2.4GHz 40MHz MIMO	27M	2422	1.000	20	19.50	4.88	3.08	1	274.510	0.055
		2437	1.000	20	20.20	4.88	3.08	1	322.520	0.064
		2452	1.000	20	19.50	4.88	3.08	1	274.510	0.055





Band	Data Rate	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	[P] x [G] with Duty cycle [TP] (mW)	Power Density [S] (mw)/cm <sup>2</sup>
IEEE 802.11a MIMO	6M	5180	1.000	20	25.20	7.80	6.03	1	1996.720	0.397
		5200	1.000	20	24.10	7.80	6.03	1	1549.950	0.308
		5220	1.000	20	23.90	7.80	6.03	1	1480.190	0.294
		5240	1.000	20	23.80	7.80	6.03	1	1446.500	0.288
		5745	1.000	20	27.90	7.80	6.03	1	3718.070	0.740
		5765	1.000	20	27.70	7.80	6.03	1	3550.730	0.706
		5785	1.000	20	27.70	7.80	6.03	1	3550.730	0.706
		5805	1.000	20	27.70	7.80	6.03	1	3550.730	0.706
IEEE 802.11ac 20MHz MIMO	19.5M	5180	1.000	20	25.90	7.80	6.03	1	2345.940	0.467
		5200	1.000	20	25.90	7.80	6.03	1	2345.940	0.467
		5220	1.000	20	25.90	7.80	6.03	1	2345.940	0.467
		5240	1.000	20	25.80	7.80	6.03	1	2292.540	0.456
		5745	1.000	20	27.60	7.80	6.03	1	3469.900	0.690
		5765	1.000	20	27.30	7.80	6.03	1	3238.300	0.644
		5785	1.000	20	27.60	7.80	6.03	1	3469.900	0.690
		5805	1.000	20	27.70	7.80	6.03	1	3550.730	0.706
IEEE 802.11ac 40MHz MIMO	40.5M	5190	1.000	20	24.40	7.80	6.03	1	1660.800	0.330
		5230	1.000	20	27.50	7.80	6.03	1	3390.920	0.675
		5755	1.000	20	27.90	7.80	6.03	1	3718.070	0.740
		5795	1.000	20	28.00	7.80	6.03	1	3804.670	0.757
IEEE 802.11ac 80MHz MIMO	87.9M	5210	1.000	20	23.50	7.80	6.03	1	1349.950	0.269
		5775	1.000	20	26.00	7.80	6.03	1	2400.590	0.478

Note:

1. The Numeric Gain calculated by  $10^{(\text{ant. Gain(dBi)} / 10)}$ .
2. Each band max power which perform MPE of any configurations.
3. The device operating IEEE 802.11b / g mode is Diversity with transmit signals to 1 TX.
4. The device operating IEEE 802.11a / n / ac mode is MIMO with transmit signals to 3 TX.
5. In WLAN 2.4G and WLAN 5G functions, they can be chosen to simultaneously transmitted.

**Simultaneous Transmitting:**

Total MPE = WLAN 2.4GHz MPE + WLAN 5GHz MPE = 0.138 + 0.757 = 0.895 mW/cm<sup>2</sup> < 1mW/cm<sup>2</sup>