

Model:FF2115TE

TECHNICAL DESCRIPTION

Content

HANDSET

1.RF/Audio Sections

- 1.1Receiver
- 1.2Transmitter
- 1.3Duplexer
- 1.4Alerter
- 1.5 microphone
- 1.6 CID

2.MCU

- 2.1Battery Detect
- 2.2Carrier Detection

BASE

3. RF/Audio Sections

4.Telephone Network

- 4.1 Telephone Interface
- 4.2 Ring Detect
- 4.3 Sidetone Cancellation Network
- 4.4 The CID decode

5.MCU

- 5.1Charging Network
- 5.2Carrier Detection

HANDSET

1.RF/Audio Section

The radio link Handset and Base is full duplex at 902/928 MHz with the 40 channels. FM modulation is used for the link. The 1st IF frequency is 10.7MHz and the 2nd IF frequency is 450KHz. The operating frequency for the cordless phone is selected from one of the following channels and controlled by the synthesizer IC1 which is programmed by the MCU. Please refer to Table 1 for the Channel Frequency Table.

This section is common to both handset and base as the same ICs are used: LMX1602(IC1),KA3361(IC2 is made up of dual serial input PLL frequency synthesizer with 1000MHz prescaler. KA3361 is a narrow-band IF detector IC.

1.1 Receiver

The receiver section is made of double conversion with 10.7MHz as the first and second IF. Rx signal from the duplexer circuit is amplified by a Low Noise RF transistor and passed to a Mixer (Q501), and it is converted to 10.7MHz IF and it is then double converted to 450kHz IF in the internal mixer of IC2. Voice/data signal is demodulated and output from pin 9 of IC2. The demodulated signal is then divided into two paths, a path is fed into the data amplifier Q202,Q203. The recovered data signal RX-DATA is extracted from the output of Q203. The other path will go through a de-emphasized amplifier and an expander in U201. Recovered signal can be muted by the pin 13 of U201, the 3 volume levels of the signal can be controlled by the switch SW201.

1.2 Transmitter

Audio signal(from Microphone for handset/Tip & Ring for base) is first fed into the amplifier and compressor inside U201. The signal will pass through a limiter. The AGC and the limiter has the property to limit the maximum signal which feed into the transmitter so that the RF deviation is limited. The transmitter section mainly divided into two parts. They are the voice/data modulator and the Tx power amplifier. The voltage controlled oscillator VCO operated at the Tx frequency controlled by the synthesizer is modulated by the audio and data signals. Modulated signal is amplified by the RF amplifier and sending the signal to the dupliexer for radiation by the antenna.

1.3 Duplexer

Two band-pass filter are matched to use as duplexer. The function of the duplexer is to multiplex the transmitting and receiving signals to a common antenna while providing isolation and rejection of interference and other spurious signals.

1.4 Alerter

The alerting signals include the following: Ringing, Paging, Key Beep and Low battery warning tone. These tones are generated by the MCU to the alert or through the driving circuit formed Q103 and the associated components.

1.5 microphone

The condenser microphone is in the headset and it biased by the resistor R313. The signal is applied to the amplifier inside U201.

1.6 CID

The CID receive and display section is made of MCU and LCD. The telephone can receive Type I and Type II (call waiting). When the telephone receive CID information. MCU will decode the information and display with LCD. The CID information will stored in EEPROM(U102--24LC16)

2.MCU

2.1 Battery Detect

The voltage detector is composed of Q101 which is used to detect battery low condition. The detecting accuracy of the voltage detector is $\pm 0.2V$. The detect pin BAT-LOW is connected to the pin 18 of the MCU.

2.2 Carrier Detection

This 40 channels cordless has the features of auto-scanning. This is done by the detection of the RSSI at pin 39 of MCU of handset. During PHONE on or CHANNEL changing, the MCU will select the clearest channel for the RF communication.

BASE

3.RF/Audio sections

The operation of the RF/Audio section are similar to that of the handset.

4.Telephone Network

4.1 Telephone Interface

Fuse FUSE1 is for over-voltage protection. Relay RL101 controls the on/off hook state and pulse dialing. The Tip&Ring are isolated from the base circuit by the transformer

T101, relay RL101.

4.2 Ring Detect

When ring signal is present on the Tip/ Ring, and envelope waveform of the ring pattern will transfer to pin 69 of MCU by the Q102. The MCU will read this waveform and determine whether it will send ringer command.

4.3 Sidetone Cancellation Network

The sidetone cancellation is a hybrid circuit of the Tx and Rx paths of the telephone circuit formed by the Q103、R115、R116、C109、C60、R113、R114.

4.4 CID decode

The CID decode section is made of the NW6006 (Type I and Type II decoder). When the telephone line send the CID information, the NW6006 will decode it and send result to the MCU. The MCU code it then transmit to the handset with RF. and display on the LCD which is on the handset.

5.MCU

5.1 Charging Network

Base charging circuit provides a DC current for handset batter. Resistor R303 controls the current flow.

5.2 Carrier Detection

This is similar to the handset counterpart.

TAIFENG RF MODULE FREQUENCY TABLE FOR USA

1st IF : 10.7MHZ 2nd IF : 450KHz

CH SPACE : 75KHz

REF. OSC. : 10.25MHz ER : 25KHz

CH	BASE TX	BASE LOCAL	HAND TX	HAND LOCAL
1	902.175	935.575	924.875	891.475
2	902.25	935.65	924.95	891.55
3	902.325	935.725	925.025	891.625
4	902.4	935.8	925.1	891.7
5	902.475	935.875	925.175	891.775
6	902.55	935.95	925.25	891.85
7	902.625	936.025	925.325	891.925
8	902.7	936.1	925.4	892
9	902.775	936.175	925.475	892.075
10	902.85	936.25	925.55	892.15
11	902.925	936.325	925.625	892.225
12	903	936.4	925.7	892.3
13	903.075	936.475	925.775	892.375
14	903.15	936.55	925.85	892.45
15	903.225	936.625	925.925	892.525
16	903.3	936.7	926	892.6
17	903.375	936.775	926.075	892.675
18	903.45	936.85	926.15	892.75
19	903.525	936.925	926.225	892.825
20	903.6	937	926.3	892.9
21	903.675	937.075	926.375	892.975
22	903.75	937.15	926.45	893.05
23	903.825	937.225	926.525	893.125
24	903.9	937.3	926.6	893.2
25	903.975	937.375	926.675	893.275
26	904.05	937.45	926.75	893.35
27	904.125	937.525	926.825	893.425
28	904.2	937.6	926.9	893.5
29	904.275	937.675	926.975	893.575
30	904.35	937.75	927.05	893.65
31	904.425	937.825	927.125	893.725
32	904.5	937.9	927.2	893.8
33	904.575	937.975	927.275	893.875
34	904.65	938.05	927.35	893.95
35	904.725	938.125	927.425	894.025
36	904.8	938.2	927.5	894.1
37	904.875	938.275	927.575	894.175
38	904.95	938.35	927.65	894.25
39	905.025	938.425	927.725	894.325
40	905.1	938.5	927.8	894.4