FCC ID: LCG-FG-FXA52X-32X

Prediction of MPE limit at given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$
 where: S = power density
P = power input to the antenna
G = power gain of the antenna in the direction of interest
relative to an isotropic radiator
R = distance to the center of radiation of the antenna

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 – 1500	f/1500	30
1500 – 100.000	1.0	30

where f = frequency in MHz

Prediction GSM 1900

Antenna Type: 0dBi Antenna / 2dBi Antenna

Maximum peak output power at antenna input terminal:	29.8	dBm
Maximum peak output power at antenna input terminal:	954,99	mW

Antenna gain(typical): Maximum antenna gain: Prediction distance: Prediction frequency: MPE limit for uncontrolled exposure at prediction frequency:	2 1,58 20 1880 1	dBi numeric cm MHz $\frac{mW}{cm^2}$
Power density at prediction frequency: with Antenna Gain of 0dBi	0,190	$\frac{mW}{cm^2}$
Power density at prediction frequency: with Antenna Gain of 2 dBi	0,301	$\frac{mW}{cm^2}$

The MPE limit specified above will not be reached with the specified configuration of the product with the specified antenna gain of 2 dBi.

The product satifies RF Exposure compliance requirements.