




FMR10-CA...


Made in Germany, 79689 Maulburg
Micropilot

Endress+Hauser 

Order code: FMR10-CAX/XXX
Ser. no.: MMMM6VY0335
Ext. ord. cd.: FMR10-CAQBMVCEVEE2




IP68 TYPE 6P Encl.



10.5...30 V DC / 2-wire
4...20 mA HART 



MODEL FMR10 IC:2519A-2K
FCC ID LCGFMR2XK

MWP: 3 bar / 43 psi
Ta: -40...+60°C Tp max: 60°C
DeviceID: 452B481005-A91234010AB
FW: 01.00.00 Dev.Rev.: 1 ex works


Mat.: PVDF, PBT-PC, EPDM, PVC
Ms/Ni

 X = if modification see sep. label Date: 2016-03 



FMR20-CA...


Made in Germany, 79689 Maulburg
Micropilot

Endress+Hauser 

Order code: FMR20-CAX/XXX
Ser. no.: MMMM6VY0335
Ext. ord. cd.: FMR20-CAPBMVCEVEE2




IP68 TYPE 6P Encl.



10.5...30 V DC / 2-wire
4...20 mA HART 



MODEL FMR20 IC:2519A-2K
FCC ID LCGFMR2XK

MWP: 3 bar / 43 psi
Ta: -40...+80°C Tp max: 80°C
DeviceID: 452B481005-A91234010AB
FW: 01.00.00 Dev.Rev.: 1 ex works


Mat.: PVDF, PBT-PC, EPDM, PVC
Ms/Ni

 X = if modification see sep. label Date: 2016-03 



FMR20-CB...


Made in Germany, 79689 Maulburg
Micropilot

Endress+Hauser 

Order code: FMR20-CBX/XXX
Ser. no.: MMMM6VY0335
Ext. ord. cd.: FMR20-CBPBMVCEVEE2




IP68 TYPE 6P Encl.

  151079 CSA 16.70105943
AEx/Ex ia IIC T4, CL, Zone 0, Ga



10.5...30 V DC / 2-wire
4...20 mA HART 



MODEL FMR20 IC:2519A-2K
FCC ID LCGFMR2XK
Ui / Vmax = 30 V, li / Imax = 100 mA
Pi / Pmax = 750 mW, Ci = 15nF, Li = 35µH
intrinsically safe / Sécurité intrinsèque
WARNING - Potential electrostatic charging hazard - see instructions
AVERTISSEMENT: Risque potentiel de décharges électrostatiques - voir consignes

MWP: 1 bar / 14,5 psi
Ta: -40...+80°C Tp max: 80°C
DeviceID: 452B481005-A91234010AB
FW: 01.00.00 Dev.Rev.: 1 ex works

Mat.: PVDF, PBT-PC, EPDM, PVC
Ms/Ni


 X = if modification see sep. label Date: 2016-03 

Agency controlled drawing
No changes without prior
Agency approval.

Endress+Hauser 

Endress+Hauser GmbH+Co. KG
D-79689 Maulburg Germany

Refer to protection notice ISO 16016
Classification



Scale

1:1

Tolerance

-

Title

Funkzulassung FMR10/20
FCC ID LCGFMR2XK

Notif. no.

73336

Designed 13.10.2016 KOPPD

Drawing chng. 18.12.2016 LENZM

Number of changes

- 

Welding contr. - -

Approval contr. - -

Status

released

Pressure contr. - -

Released 19.12.2016 KOPPD

No. of document

960018454

Version

C

Doc. part

000

Weight

kg

Volume

cm³

Material

-

SAP material no.

Format

DIN A4

Sheet

1/1