



Product Service

Choose certainty.
Add value.

March 29, 2013

Page 1 of 55

Prüfbericht / Test Report

Nr. / No. 20351-08912-6 (Edition 3)

Applicant: Endress & Hauser GmbH
Type of equipment: C-Band Radar
Type designation: FMR53, FMR54 (C-Band)
Order No.: 106/12063546
Test standards: FCC Code of Federal Regulations,
CFR 47, Part 15,
Sections 15.205, 15.207 and 15.209

Industry Canada Radio Standards Specifications
RSS-GEN Issue 3, Sections 7.2.2, 7.2.4 and 7.2.5(Category I Equipment)

Note:

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.



Table of Contents

1	Description of the Equipment Under Test (EUT)	3
2	Administrative Data	4
3	Identification of the Test Laboratory	5
4	Summary	6
5	Operation Mode and Configuration of EUT	7
6	Measurement Procedures	9
6.1	Conducted Output Power	9
6.2	Bandwidth Measurements	11
6.3	Pulse Train Measurement	13
6.4	Conducted AC Powerline Emission	15
6.5	Radiated Emission Measurement 9 kHz to 30 MHz	17
6.6	Radiated Emission in Fully or Semi Anechoic Room	19
6.7	Radiated Emission at Alternative Test Site	21
7	Photographs Taken During Testing	23
8	Test Results	28
8.1	Occupied Bandwidth	29
8.2	Bandwidth of the Emission	33
8.3	Designation of Emissions	35
8.4	Pulse Train Measurement	36
8.5	Desensitization of pulsed Emissions	38
8.6	Restricted Bands of Operation	39
8.7	Conducted Powerline Emission Measurement 150 kHz to 30 MHz	40
8.8	Radiated Emission Measurement 9 kHz to 30 MHz	41
8.9	Radiated Emission Measurement 30 MHz to 40 GHz	43
8.10	Exposure of Humans to RF Fields	50
9	Referenced Regulations	52
10	Test Equipment List with Calibration Data	54
11	Revision History	55

1 Description of the Equipment Under Test (EUT)

General data of EUT	
Type designation ¹ :	FMR53, FMR54 (C-Band)
Parts ² :	<ul style="list-style-type: none"> - Base module - Housing GT 19 - FMR53 Stab 390 mm / 15", PTFE vollisoliert - FMR54 Horn 80 mm / 3" - FMR54 Horn 250 mm / 10" - FMR 54 Planar 150 mm / 6"
Serial number(s):	Test Samples
Manufacturer:	Endress & Hauser GmbH
Type of equipment:	C-Band Radar
Version:	As received
FCC ID:	
Additional parts/accessories:	

Technical data of EUT	
Application frequency range:	4.5 GHz - 7 GHz
Frequency range:	4.5 - 7 GHz
Operating frequency:	6.05 GHz (nominal)
Type of modulation:	1G50P0NAN
Pulse train:	558.54 ns
Pulse width:	7.04 ns
Number of RF-channels:	1
Channel spacing:	N/A
Designation of emissions ³ :	1G50P0NAN
Type of antenna:	See table of configuration of EUTs for details
Size/length of antenna:	See table of configuration of EUTs for details
Connection of antenna:	<input type="checkbox"/> detachable <input checked="" type="checkbox"/> not detachable
Type of power supply:	DC supply
Specifications for power supply:	nominal voltage: 24.0 V Primary voltage 115 V AC

¹ Type designation of the system if EUT consists of more than one part.

² Type designations of the parts of the system, if applicable.

³ Also known as "Class of Emission".



2 Administrative Data

Application details

Applicant (full address):	Endress & Hauser GmbH Hauptstraße 1 D-79689 Maulburg
Contact person:	Mr. Ralf Reimelt
Order number:	106/12063546
Receipt of EUT:	June 19, 2012; July 3, 2012
Date(s) of test:	June 29, 2012 to July 20, 2012
Note(s):	The applicant provided three different configurations for tests. In order to simplify tests the configuration were numbered. Mr. Reimelt attended tests on June 19, 2012 and July 3, 2012.

Report details

Report number:	20351-08912-6
Edition:	3
Issue date:	March 29, 2013



3 Identification of the Test Laboratory

Details of the Test Laboratory

Company name:	TÜV SÜD Product Service GmbH
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
FCC test site registration number	90926
Industry Canada test site registration:	3050A-2
Contact person:	Mr. Johann Roidt
	Phone: +49 9421 5522-0 Fax: +49 9421 5522-99



4 Summary

Summary of test results

The tested sample complies with the requirements set forth in the
Code of Federal Regulations CFR 47, Part 15, Sections 15.205, 15.207 and 15.209
of the Federal Communication Commission (FCC) and the
Radio Standards Specifications
RSS-GEN Issue 3, Sections 7.2.2, 7.2.4 and 7.2.5 (Category I Equipment)
of Industry Canada (IC).

Personnel involved in this report

Laboratory Manager:

A blue ink signature of Johann Roidt.

Mr. Johann Roidt

Responsible for testing:

A blue ink signature of Martin Steindl.

Mr. Martin Steindl

Responsible for test report:

Mr. Martin Steindl



5 Operation Mode and Configuration of EUT

Operation Mode(s)

Normal operation mode: Measurement with pulsed signal

Configuration(s) of EUT

FCC test setup, DC 24 V power supply, EUT in vertical position. Conducted emissions were performed with a transmitter head without antenna and 50 Ω termination.

List of ports and cables

<i>Port</i>	<i>Description</i>	<i>Classification⁴</i>	<i>Cable type</i>	<i>Cable length</i>
1	DC supply with HART communication	dc power	Unshielded	2 m

List of devices connected to EUT

<i>Item</i>	<i>Description</i>	<i>Type Designation</i>	<i>Serial no. or ID</i>	<i>Manufacturer</i>

List of support devices

<i>Item</i>	<i>Description</i>	<i>Type Designation</i>	<i>Serial no. or ID</i>	<i>Manufacturer</i>

⁴ Ports shall be classified as ac power, dc power or signal/control port



Configuration of test samples

<i>Configuration</i>	<i>Module</i>	<i>Antenna</i>	<i>Flange</i>	<i>Housing</i>
C1	FMR 53	FMR 53 Stab 390 mm / 15" (11.5 dBi)	Flange DN 150	GT 19
C2	FMR 54	FMR 54 Horn 250 mm / 10" (15.0 dBi)	Flange DN 250	GT 19
C2 small antenna	FMR 54	FMR 54 Horn 80 mm / 6" (4.5 dBi)	Flange DN 250	GT 19
C3	FMR 54	FMR 54 Planar 150 mm / 6"	DN 150	GT 19

6 Measurement Procedures

6.1 Conducted Output Power


Measurement Procedure:

Rules and specifications: CFR 47 Part 2, section 2.1046(a)
 IC RSS-Gen Issue 3, section 4.8

Guide: CFR 47 Part 2, section 2.1046 / IC RSS-Gen Issue 3

Conducted output power is measured at the RF output terminals (e.g. antenna connector if antenna is detachable) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer and/or a power meter with appropriate sensor. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.

If a spectrum analyzer is used and no other settings are specified resolution bandwidth shall be selected according to the carrier frequency f_c and set to 10 kHz ($150 \text{ kHz} \leq f_c < 30 \text{ MHz}$), 100 kHz ($30 \text{ MHz} \leq f_c < 1 \text{ GHz}$) or 1 MHz ($f_c \geq 1 \text{ GHz}$). The video bandwidth shall be at least three times greater than the resolution bandwidth. The settings used have to be indicated within the appropriate test record(s).






Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESPI7	1711	836914/0002	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input type="checkbox"/> Power meter	NRVS	1264	836856/015	Rohde & Schwarz
<input type="checkbox"/> Peak power sensor	NRV-Z31	1701	8579604.03	Rohde & Schwarz
<input type="checkbox"/> Power sensor	NRV-Z52	1499	837901/030	Rohde & Schwarz
<input type="checkbox"/> Power sensor	NRV-Z4	1034	863828/015	Rohde & Schwarz
<input checked="" type="checkbox"/> DC-block	7006	1636	A2798	Weinschel
<input type="checkbox"/> Attenuator	4776-10	1638	9412	Narda
<input type="checkbox"/> Attenuator	4776-20	1639	9503	Narda

6.2 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 3, sections 4.6.1 and 4.6.2 IC RSS-210 Issue 8, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 3, sections 4.6.1 and 4.6.2
Measurement setup:	<input checked="" type="checkbox"/> Conducted: See below <input type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.6)
<p>If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range.</p> <p>The analyzer settings are specified by the test description of the appropriate test record(s).</p>	




Test instruments used for conducted measurements:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESPI7	1711	836914/0002	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input type="checkbox"/> Power meter	NRVS	1264	836856/015	Rohde & Schwarz
<input type="checkbox"/> Peak power sensor	NRV-Z31	1701	8579604.03	Rohde & Schwarz
<input type="checkbox"/> Power sensor	NRV-Z52	1499	837901/030	Rohde & Schwarz
<input type="checkbox"/> Power sensor	NRV-Z4	1034	863828/015	Rohde & Schwarz
<input checked="" type="checkbox"/> DC-block	7006	1636	A2798	Weinschel
<input type="checkbox"/> Attenuator	4776-10	1638	9412	Narda
<input type="checkbox"/> Attenuator	4776-20	1639	9503	Narda

6.3 Pulse Train Measurement

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.35(c) IC RSS-Gen Issue 3, section 4.5
Guide:	ANSI C63.4
Measurement setup:	<input checked="" type="checkbox"/> Conducted: See below (direct connection or via test fixture) <input type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.6)
<p>If antenna is detachable pulse train measurements shall be performed at the antenna connector (conducted measurement). The RF output terminals are connected to a spectrum analyzer or to a diode detector in combination with an oscilloscope. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If antenna is not detachable a test fixture may be used instead of direct connection to RF output terminals.</p> <p>If radiated measurements are performed similar test setups and instruments are used as with radiated emission measurements for the appropriate frequency range. However, the spectrum analyzer may be replaced by a diode detector connected to an oscilloscope.</p>	





Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESPI7	1711	836914/0002	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/> Diode detector negative	8473D	1581	01492	Hewlett Packard
<input type="checkbox"/> Oscilloscope	54602B	1535	US35060304	Hewlett Packard
<input checked="" type="checkbox"/> Digital oscilloscope	Wave Surfer 452	1796	LCRY0301J11938	LeCroy
<input type="checkbox"/> Test probe	TP 01	1628	001	TÜV SÜD PS
<input type="checkbox"/> DC-block	7006	1636	A2798	Weinschel
<input type="checkbox"/> Attenuator	4776-10	1638	9412	Narda
<input type="checkbox"/> Attenuator	4776-20	1639	9503	Narda

6.4 Conducted AC Powerline Emission

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, section 15.207
 IC RSS-GEN Issue 3, section 7.2.4

Guide: ANSI C63.4 / CISPR 22


Conducted emission tests in the frequency range 150 kHz to 30 MHz are performed using Line Impedance Stabilization Networks (LISNs). To simplify testing with quasi-peak and average detector the following procedure is used:

First the whole spectrum of emission caused by the equipment under test (EUT) is recorded with detector set to peak using CISPR bandwidth of 10 kHz. After that all emission levels having less margin than 10 dB to or exceeding the average limit are retested with detector set to quasi-peak.

If average limit is kept with quasi-peak levels no additional scan with average detector is necessary. In cases of emission levels between quasi-peak and average limit an additional scan with detector set to average is performed.

According to ANSI C63.4, section 13.1.3.1, testing of intentional radiators with detachable antenna shall be performed using a suitable dummy load connected to the antenna output terminals. Otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended.

Testing with dummy load may be necessary to distinguish (unintentional) conducted emissions on the supply lines from (intentional) emissions radiated by the antenna and coupling directly to supply lines and/or LISN. Usage of dummy load has to be stated in the appropriate test record(s) and notes should be added to clarify the test setup.





Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Test receiver	ESHS 10	1028	860043/016	Rohde & Schwarz
<input checked="" type="checkbox"/> V-network	ESH 3-Z5	1059	894785/005	Rohde & Schwarz
<input type="checkbox"/> V-network	ESH 3-Z5	1218	830952/025	Rohde & Schwarz
<input type="checkbox"/> Artificial mains network	ESH 2-Z5	1536	842966/004	Rohde & Schwarz
<input checked="" type="checkbox"/> Shielded room	No. 1	1451	---	Albatross
<input type="checkbox"/> Shielded room	No. 4	1454	3FD 100 544	Euroshield

6.5 Radiated Emission Measurement 9 kHz to 30 MHz

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.205 and 15.209
 IC RSS-GEN Issue 3, sections 7.2.2 and 7.2.5

Guide: ANSI C63.4

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.


Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.





Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input type="checkbox"/> Test receiver	ESHS 10	1028	860043/016	Rohde & Schwarz
<input checked="" type="checkbox"/> Preampifier	CPA9231A	1716	3557	Schaffner
<input checked="" type="checkbox"/> Loop antenna	HFH2-Z2	1016	882964/1	Rohde & Schwarz
<input checked="" type="checkbox"/> Fully anechoic room	No. 2	1452	---	Albatross
<input type="checkbox"/> Semi anechoic room	No. 3	1453	---	Siemens
<input type="checkbox"/> Semi anechoic room	No. 8	2057	---	Albatross

6.6 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, section 15.209
 IC RSS-GEN Issue 3, section 7.2.5

Guide: ANSI C63.4

Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.


All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz a semi anechoic room complying with the NSA requirements of ANSI C63.4 for alternative test sites is used (see 6.7). If prescans are recorded in fully anechoic room they are indicated appropriately.




Test instruments used:

Type		Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/>	Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	Cabin no. 3 ESPI7	2010	101018	Rohde & Schwarz
<input type="checkbox"/>	EMI test receiver	ESU8	2044	100232	Rohde & Schwarz
<input checked="" type="checkbox"/>	EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/>	Preamplifier	Cabin no. 2 CPA9231A	1716	3557	Schaffner
<input type="checkbox"/>	Preamplifier	R14601	1142	13120026	Advantest
<input checked="" type="checkbox"/>	Preamplifier (1 - 8 GHz)	AFS3-00100800-32-LN	1684	847743	Miteq
<input type="checkbox"/>	Preamplifier (0.5 - 8 GHz)	AMF-4D-005080-25-13P	1685	860149	Miteq
<input checked="" type="checkbox"/>	Preamplifier (8 - 18 GHz)	ACO/180-3530	1484	32641	CTT
<input checked="" type="checkbox"/>	External Mixer	WM782A	1576	845881/005	Tektronix
<input checked="" type="checkbox"/>	Harmonic Mixer Accessories	FS-Z30	1577	624413/003	Rohde & Schwarz
<input checked="" type="checkbox"/>	Trilog antenna	Cabin no. 2 VULB 9163	1722	9163-188	Schwarzbeck
<input type="checkbox"/>	Trilog antenna	Cabin no. 3 VULB 9163	1802	9163-214	Schwarzbeck
<input type="checkbox"/>	Trilog antenna	Cabin no. 8 VULB 9163	2058	9163-408	Schwarzbeck
<input checked="" type="checkbox"/>	Horn antenna	3115	1516	9508-4553	EMCO
<input type="checkbox"/>	Horn antenna	3160-03	1010	9112-1003	EMCO
<input type="checkbox"/>	Horn antenna	3160-04	1011	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-05	1012	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-06	1013	9112-1001	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-07	1014	9112-1008	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-08	1015	9112-1002	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-09	1265	9403-1025	EMCO
<input checked="" type="checkbox"/>	Horn antenna	3160-10	1575	399185	EMCO
<input checked="" type="checkbox"/>	Fully anechoic room	No. 2	1452	---	Albatross
<input type="checkbox"/>	Semi anechoic room	No. 3	1453	---	Siemens
<input type="checkbox"/>	Semi anechoic room	No. 8	2057	---	Albatross

6.7 Radiated Emission at Alternative Test Site

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.209 IC RSS-GEN Issue 3, section 7.2.5
Guide:	ANSI C63.4
<p>Radiated emission in the frequency range 30 MHz to 1 GHz is measured within a semi-anechoic room with groundplane complying with the NSA requirements of ANSI C63.4 for alternative test sites. A linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna") is used. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p> <p>Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in fully anechoic room.</p> <p>If no prescan in a fully anechoic room is used first a peak scan is performed in four positions to get the whole spectrum of emission caused by EUT with the measuring antenna raised and lowered from 1 to 4 m to find table position, antenna height and antenna polarization for the maximum emission levels.</p> <p>Data reduction is applied to these results to select those levels having less margin than 10 dB to or exceeding the limit using subranges and limited number of maximums. Further maximization is following.</p> <p>With detector of the test receiver set to quasi-peak final measurements are performed immediately after frequency zoom (for drifting disturbances) and maximum adjustment.</p> <p>Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>In cases where prescans in a fully anechoic room are taken (e. g. if EUT is operating for a short time only or battery is discharged quickly) final measurements with quasi-peak detector are performed manually at frequencies indicated by prescan with EUT rotating all around and receiving antenna raising and lowering within 1 meter to 4 meters to find the maximum levels of emission.</p> <p>Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.</p>	




Alternate test site (semi anechoic room)

Test instruments used:



Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> EMI test receiver	ESU8	2044	100232	Rohde & Schwarz
<input checked="" type="checkbox"/> Trilog antenna	Cabin no. 8 VULB 9163	2058	9163-408	Schwarzbeck
<input checked="" type="checkbox"/> Semi anechoic room	No. 8	2057	---	Albatross

7 Photographs Taken During Testing

Test setup for conducted DC powerline emission measurement



Test setup for radiated emission measurement 9 kHz – 30 MHz



Test setup for radiated emission measurement (fully anechoic room)



Note: This setup has been considered to represent the “Worst-case” scenario and was used to demonstrate compliance with the FCC Rules without any additional shielding effect of an enclosure.



Test setup for radiated emission measurement (fully anechoic room) - continued -



Test setup for radiated emission measurement (alternate test site)



8 Test Results

FCC CFR 47 Parts 2 and 15			
Section(s)	Test	Page	Result
2.1046(a)	Conducted output power		Recorded
2.202(a)	Occupied bandwidth	29	Recorded
2.201, 2.202	Class of emission	35	Calculated
15.35(c)	Pulse train measurement for pulsed operation	36	Recorded
15.205(a)	Restricted bands of operation	39	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz	40	Test passed
15.205(b) 15.209	Radiated emission 9 kHz to 30 MHz	41	Test passed
15.205(b) 15.209	Radiated emission 30 MHz to 40 GHz	43	Test passed

IC RSS-GEN Issue 3			
Section(s)	Test	Page	Result
4.8	Transmitter output power (conducted)		Not applicable
4.6.1	Occupied Bandwidth	29	Recorded
8	Designation of emissions	35	Calculated
4.5	Pulsed operation	36	Recorded
7.2.4	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz	40	Test passed
7.2.2	Restricted bands and unwanted emission frequencies	39	Test passed
7.2.2(b)(c) 7.2.5	Unwanted emissions 9 kHz to 30 MHz	41	Test passed
7.2.2(b)(c) 7.2.5	Unwanted emissions 30 MHz to 40 GHz	43	Test passed
5.6	Exposure of Humans to RF Fields	50	Exempted from SAR and RF evaluation



8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6	
Guide:	ANSI C63.4	
Description:	<p>The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.</p> <p>The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p>	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
	The video bandwidth shall be at least three times greater than the resolution bandwidth.	
Measurement procedure:	Bandwidth Measurements (6.2)	

Comment:	
Date of test:	July 20, 2012
Test site:	Fully anechoic room, cabin no. 2


Occupied Bandwidth (99 %):



MARKER 1
 6.048 GHz
 Ref -20 dBm Att 10 dB

*RBW 100 kHz Marker 1 [T1]
 VBW 300 kHz -43.97 dBm
 SWT 400 ms 6.048000000 GHz

1 PK
 VIEW



Center 6 GHz 400 MHz/ Span 4 GHz

Date: 20.JUL.2012 15:09:25

Occupied Bandwidth (99 %): **1.984 GHz**



Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 3, section 4.6.1
Guide:	IC RSS-Gen Issue 3, section 4.6.1
Description:	<p>If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth.</p> <p>The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.</p> <p>The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.</p>
Measurement procedure:	Bandwidth Measurements (6.2)

Comment:	---
Date of test:	July 20, 2012
Test site:	Fully anechoic room, cabin no. 2


Occupied Bandwidth (99 %):



MARKER 1
 6.048 GHz
 Ref -20 dBm Att 10 dB

*RBW 100 kHz Marker 1 [T1]
 VBW 300 kHz -43.97 dBm
 SWT 400 ms 6.048000000 GHz

1 PK
 VIEW



Center 6 GHz 400 MHz/ Span 4 GHz

Date: 20.JUL.2012 15:09:25

Occupied Bandwidth (99 %): **1.984 GHz**

8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.209 IC RSS-GEN Issue 3, section 7.2.5	
Guide:	ANSI C63.4	
Description:	<p>The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier.</p> <p>For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p>	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
The video bandwidth shall be at least three times greater than the resolution bandwidth.		
Measurement procedure:	Bandwidth Measurements (6.2)	


Comment:	
Date of test:	July 20, 2012
Test site:	Fully anechoic room, cabin no. 2



MARKER 3
 7.096 GHz
 Ref -20 dBm Att 10 dB

*RBW 100 kHz Marker 3 [T1]
 VBW 300 kHz -65.84 dBm
 SWT 400 ms 7.096000000 GHz

1 PK
 VIEW



Center 6 GHz 400 MHz/ Span 4 GHz

Date: 20.JUL.2012 15:06:54

Bandwidth of the emission: **2.048 GHz**



8.3 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 3, sections 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Unmodulated Pulse Emission
---------------------	----------------------------

B_n = Necessary Bandwidth	$B_n = 2K/t$
t = Pulse duration at half amplitude	$t = 2 \text{ ns}$
K = Overall numerical factor	$K = 1.5$
Calculation:	$B_n = 2 \cdot 1.5 / 2 \text{ ns} = 1.5 \text{ GHz}$


Designation of Emissions:	1G50P0NAN
---------------------------	------------------


8.4 Pulse Train Measurement

Rules and specifications:	CFR 47 Part 15, section 15.35(c) IC RSS-Gen Issue 3, section 4.5
Guide:	ANSI C63.4
Measurement procedure:	Pulse Train Measurement (6.3)

Comment:	
Date of test:	June 29, 2012
Test site:	Fully anechoic room, cabin no. 2

Total Pulse Train:





Calculation of pulse train correction:

TX-On-Time (worst case):	T_{on}	=	2.04 ns
Pulse Train Time:	T_{pt}	=	558.54 ns
Period Time:	T_{period}	=	558.54 ns
Pulse Train Correction:	C_{pt}	=	$20 \cdot \text{Log}(T_{on} / T_{period})$ dB
		=	-48.74 dB

8.5 Desensitization of pulsed Emissions

Since the EUT transmits pulsed energy, the desensitization factor α has been calculated and included in the calculation for the final peak value. The provisions of Public Notice DA 04-3946: have been applied.

In the HP Application Note 150-2 the analyzer settings to measure a line spectrum are defined as follows:

- a) Bandwidth $B < 0.3 \times \text{PRF}$
- J. Scan time $T_s > F_s / B^2$

With the pulse repetition frequency (PRF) of the EUT of 1.8 MHz and the selected measuring bandwidth of $B = 0.3$ MHz the requirement a) was observed.

The scan width of $F_s = 3$ GHz and Bandwidth of $B = 0.3$ MHz leads to following values:

$$F_s/B^2 = 3 \text{ GHz} / (0.3 \text{ MHz})^2 = 0.033 \text{ s}$$

The selected scan time of $T_s = 85$ ms meets requirement b). Hence, a line spectrum was measured, which could be seen, when the Pseudo-Noise-mode of the EUT was switched off (no influence on the measured amplitudes) and the frequency scale of the analyser zoomed.

The desensitization factor α_i was calculated according to HP Application note 150-2:

$$\alpha_i = 20 \log (\tau_{\text{eff}} / T) = - 48.74 \text{ dB}$$

The calculation based on the pulse width $\tau_{\text{eff}} = 2.04$ ns and the pulse period $T = 558.54$ ns, which have been supplied by the applicant.

To avoid overloading the spectrum analyzer the internal preselector has been activated during final testing. A linearity check by adding a 3 dB attenuator to the input was used to ensure integrity of the test data.


Sample Calculation of Field Strength values for pulsed systems:

- 1) Measure Peak value with analyzer RBW set to 0.3 MHz, VBW set to 1 MHz, T_s set to 85 ms
- 2) Calculate Field Strength by adding antenna correction factor
- 3) Calculate True Peak Field Strength by adding Desensitization Factor
Apply provisions according to section 15.35 (b) of the FCC Rules for limiting peak emissions
- 4) Calculate Average value by subtracting Duty Cycle Correction Factor from True Peak Field Strength Value

8.6 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 8, section 7.2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 7, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.6)

Comment:	Plot shown for test setup C1 which has worst case spurious emissions
Date of test:	July 20, 2012
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters




Test Result:	Test passed
--------------	-------------

8.7 Conducted Powerline Emission Measurement 150 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, section 15.207 IC RSS-GEN Issue 3, section 7.2.4		
Guide:	ANSI C63.4 / CISPR 22		
Limit:	Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
		Quasi-peak	Average
	0.15 - 0.5	66 to 56	56 to 46
	0.5 - 5	56	46
	5 - 30	60	50
Measurement procedure:	Conducted AC Powerline Emission (6.4)		

Comment:	Test performed with 50 Ω termination on antenna port. Tested configuration C1 $U_{AC} = 115 V$ Conducted emissions have been tested at the DC terminals of the test sample since a dedicated AC-DC adapter has not been assigned. This represents worst-case emissions.
Date of test:	July 18, 2012
Test site:	Shielded room, cabin no. 4

Test Result:	Test passed
--------------	-------------




Sample calculation of final values:

$$\text{Final Value (dB}\mu\text{V)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB)}$$

8.8 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.205 and 15.209 IC RSS-GEN Issue 3, sections 7.2.2 and 7.2.5			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance d (meters)
	0.009 - 0.490	$2400/F(\text{kHz})$	$67.6 - 20 \cdot \log(F(\text{kHz}))$	300
	0.490 - 1.705	$24000/F(\text{kHz})$	$87.6 - 20 \cdot \log(F(\text{kHz}))$	30
	1.705 - 30.000	30	29.5	30
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.5)			

Test Result:	Test passed
--------------	-------------





Comment:	Test performed for configuration C1, 3 m test distance
Date of test:	July 10, 2012
Test site:	Open field test site

Test Result:	Test passed
--------------	-------------

No emissions above noise level detected

Sample calculation of final values:

$$\begin{aligned} \text{Extrapolation Factor (dB)} &= (\text{Log}(d) - \text{Log}(d_1)) \cdot \text{Extrapolation Factor (dB/decade)} \\ \text{Final Value (dB}\mu\text{V/m)} &= \text{Reading Value } d_1 \text{ (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ &\quad + \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)} \end{aligned}$$

Note: Extrapolation factor (dB) and final value (dB μ V/m) are relating to distance d.

8.9 Radiated Emission Measurement 30 MHz to 40 GHz

Rules and specifications:	CFR 47 Part 15, section 15.209 IC RSS-GEN Issue 3, section 7.2.5		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.		
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.6) Radiated Emission at Alternative Test Site (6.7)		

Test Result:	Test passed
--------------	-------------

Comment:	Test performed for configuration C1
Date of test:	July 10, 2012; July 18, 2012; July 19, 2012
Test site:	Frequencies ≤ 1 GHz: Semi-anechoic room, cabin no. 8 Frequencies > 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	Frequencies ≤ 1 GHz: 3 meters Frequencies ≤ 8.2 GHz: 1 meters Frequencies > 8.2 GHz and ≤ 18 GHz: 1 meters Frequencies > 18 GHz: 0.5 meters

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Polarization	Detector	Reading (dBµV)	Distance correction (dB)	Preamplifier Gain (dB)	Antenna Correction (dB/m)	Pulse Desensitization Factor (dB)	Peak-Field Strength (dBµV/m)
5682,800	hor	Peak	9,0	10	20	35.3	48.74	63.04
5850,000	ver	Peak	8.1	10	20	35.3	48.74	62.14
5953,400	ver	Peak	10.4	10	20	37.9	48.74	67.04

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Limit (dB)	Margin (dB)
5682,800	hor	Peak	63.04	74.0	10.96
5850,000	ver	Peak	62.14	74.0	11.86
5953,400	ver	Peak	67.04	74.0	6.96

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Duty Cycle Correction Factor (dB)	Average-Field Strength (dBµV/m)	Limit dBµV/m	Margin (dB)
5682,800	hor	Average	63.04	-48.74	14.3	54.0	39.7
5850,000	ver	Average	62.14	-48.74	13.4	54.0	40.6
5953,400	ver	Average	67.04	-48.74	18.3	54.0	35.7
30 M – 40 GHz	hor/ver	Peak / Average	***				







*** = No emissions above noise floor detected.


Sample Calculation of Field Strength values for pulsed systems:


- 1) Measure Peak value with analyzer RBW set to 0.3 MHz, VBW set to 1 MHz, Ts set to 85 ms
- 2) Calculate Field Strength by adding antenna correction factor
- 3) Calculate True Peak Field Strength by adding Desensitization Factor
 Apply provisions according to section 15.35 (b) of the FCC Rules for limiting peak emissions
- 4) Calculate Average value by subtracting Duty Cycle Correction Factor from True Peak Field Strength Value

Horizontal Polarisation

Vertical Polarisation







Comment:	Test performed for configuration C2 Spurious emission measurement in the frequency range 30 MHz to 40 GHz performed with configuration C1 representing worst case configuration.		
Date of test:	July 10, 2012; July 11, 2012; July 18, 2012; July 19, 2012; July 20, 2012		
Test site:	Frequencies ≤ 1 GHz: Semi-anechoic room, cabin no. 8 Frequencies > 1 GHz: Fully anechoic room, cabin no. 2		
Test distance:	Frequencies ≤ 1 GHz:	3 meters	
	Frequencies ≤ 8.2 GHz:	1 meters	
	Frequencies > 8.2 GHz and ≤ 18 GHz:	1 meters	
	Frequencies > 18 GHz:	0.5 meters	

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Polarization	Detector	Reading (dBµV)	Distance correction (dB)	Preamplifier Gain (dB)	Antenna Correction (dB/m)	Pulse Desensitization Factor (dB)	Peak-Field Strength (dBµV/m)
6023.900	ver	Peak	9,1	10	20	37.9	48.74	65.74

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Limit (dB)	Margin (dB)
6023,900	hor	Peak	65.74	74.0	8.26

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Duty Cycle Correction Factor (dB)	Average-Field Strength (dBµV/m)	Limit dBµV/m	Margin (dB)
6023.900	hor	Average	65.74	-48.74	17	54.0	37.0
30 M – 40 GHz	hor/ver	Peak / Average	***				

*** = No emissions above noise floor detected.

Sample Calculation of Field Strength values for pulsed systems:

- 1) Measure Peak value with analyzer RBW set to 0.3 MHz, VBW set to 1 MHz, Ts set to 85 ms
- 2) Calculate Field Strength by adding antenna correction factor
- 3) Calculate True Peak Field Strength by adding Desensitization Factor
Apply provisions according to section 15.35 (b) of the FCC Rules for limiting peak emissions
- 4) Calculate Average value by subtracting Duty Cycle Correction Factor from True Peak Field Strength Value

Comment:	Test performed for configuration C3 Spurious emission measurement in the frequency range 30 MHz to 40 GHz performed with configuration C1 representing worst case configuration.
Date of test:	July 9, 2012; July 18, 2012; July 19, 2012
Test site:	Frequencies ≤ 1 GHz: Semi-anechoic room, cabin no. 8 Frequencies > 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	Frequencies ≤ 1 GHz: 3 meters Frequencies ≤ 8.2 GHz: 1 meters Frequencies > 8.2 GHz and ≤ 18 GHz: 1 meters Frequencies > 18 GHz: 0.5 meters

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Polarization	Detector	Reading (dBµV)	Distance correction (dB)	Preamplifier Gain (dB)	Antenna Correction (dB/m)	Pulse Desensitization Factor (dB)	Peak-Field Strength (dBµV/m)
6038.000	ver	Peak	8,0	10	20	38.3	48.74	65.04

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Limit (dB)	Margin (dB)
6038.000	ver	Peak	65.04	74.0	8.96

Frequency (MHz)	Polarization	Detector	Peak-Field Strength (dBµV/m)	Duty Cycle Correction Factor (dB)	Average-Field Strength (dBµV/m)	Limit dBµV/m	Margin (dB)
6038.000	ver	Average	65.04	-48.74	16.3	54.0	37.7
30 M – 40 GHz	hor/ver	Peak / Average	***				

*** = No emissions above noise floor detected.

Sample Calculation of Field Strength values for pulsed systems:

- 1) Measure Peak value with analyzer RBW set to 0.3 MHz, VBW set to 1 MHz, Ts set to 85 ms
- 2) Calculate Field Strength by adding antenna correction factor
- 3) Calculate True Peak Field Strength by adding Desensitization Factor
Apply provisions according to section 15.35 (b) of the FCC Rules for limiting peak emissions
- 4) Calculate Average value by subtracting Duty Cycle Correction Factor from True Peak Field Strength Value

8.10 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 3, section 5.6
Guide:	IC RSS-102 Issue 4, section 2.5

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
<input type="checkbox"/> detachable				
<p>The conducted output power (CP in watts) is measured at the antenna connector:</p> $CP = \dots\dots\dots \text{ W}$ <p>The effective isotropic radiated power (EIRP in watts) is calculated using</p> <p><input type="checkbox"/> the numerical antenna gain: $G = \dots\dots\dots$</p> $EIRP = G \cdot CP \Rightarrow EIRP = \dots\dots\dots \text{ W}$ <p><input type="checkbox"/> the field strength⁵ in V/m: $FS = \dots\dots\dots \text{ V/m}$</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots\dots\dots \text{ W}$ <p>with:</p> <p>Distance between the antennas in m: $D = \dots\dots\dots \text{ m}$</p>			<input type="checkbox"/>	
<input checked="" type="checkbox"/> not detachable				
<p>A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by⁵:</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \mathbf{116.7 \text{ nW}}$ <p>with:</p> <p>Field strength in V/m: $FS = \mathbf{55.9 \text{ dB}\mu\text{V/m}}$ $= \mathbf{623.7 \text{ }\mu\text{V/m}}$</p> <p>Distance between the two antennas in m: $D = \mathbf{3 \text{ m}}$</p>			<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Selection of output power				
<p>The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):</p> $TP = \mathbf{116.7 \text{ nW}}$				

⁵ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

9 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

<input checked="" type="checkbox"/>	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 1, 2012
<input checked="" type="checkbox"/>	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	October 1, 2012
<input checked="" type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
<input type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	June 7, 2009 (published on September 15, 2009)
<input checked="" type="checkbox"/>	RSS-Gen	Radio Standards Specification RSS-Gen Issue 3 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	December 2010
<input checked="" type="checkbox"/>	RSS-210	Radio Standards Specification RSS-210 Issue 8 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	December 2010
<input type="checkbox"/>	RSS-310	Radio Standards Specification RSS-310 Issue 3 for Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	December 2010
<input checked="" type="checkbox"/>	RSS-102	Radio Standards Specification RSS-102 Issue 4: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), published by Industry Canada	March 2010, footnote 13 updated December 2010
<input type="checkbox"/>	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
<input checked="" type="checkbox"/>	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997



<input type="checkbox"/>	CAN/CSA- CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002
		CAN/CSA CISPR 22-10 Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement (Adopted IEC CISPR 22:2008, sixth edition, 2008-09)	
<input type="checkbox"/>	CAN/CSA CISPR 22-10	Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement (Adopted IEC CISPR 22:2008, sixth edition, 2008-09)	2010
<input checked="" type="checkbox"/>	TRC-43	Notes Regarding Designation of Emissions (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada	October, 2008
<input checked="" type="checkbox"/>	150-2	HP Application Note "Spectrum Analysis ... Pulsed RF	November 1971



10 Test Equipment List with Calibration Data

Type	Inv.-No.	Type Designation	Serial Number	Manufacturer	Calibration Organization	Last Calibration	Next Calibration
EMI test receiver	1569	ESMI	839379/013	Rohde & Schwarz	Rohde & Schwarz	10/2009	10/2012
EMI test receiver	2044	ESU8	100232	Rohde & Schwarz	Rohde & Schwarz	07/2012	01/2014
Spectrum analyser	1666	FSP30	100036	Rohde & Schwarz	Rohde & Schwarz	05/2011	11/2012
Preamplifier	1484	ACO/180-3530	32641	CTT	TÜV SÜD PS-EMC-STR	06/2011	12/2012
Preamplifier	1684	AFS3-00100800-32-LN	847743	MITEQ	TÜV SÜD PS-EMC-STR	10/2011	04/2013
Preamplifier	1716	CPA9231A	3557	Schaffner EMC Systems	TÜV SÜD PS-EMC-STR	07/2012	01/2014
V-network	1059	ESH3-Z5	894785/005	Rohde & Schwarz	Rohde & Schwarz	08/2011	08/2013
Loop antenna	1016	HFH2-Z2	882964/0001	Rohde & Schwarz	Rohde & Schwarz	05/2011	11/2012
TRILOG broadband antenna	1722	VULB 9163	9163-188	Schwarzbeck	Rohde & Schwarz	03/2012	09/2013
TRILOG Broadband Antenna	2058	VULB 9163	9163-408	Schwarzbeck	Rohde & Schwarz	05/2011	11/2012
Double ridged waveguide horn antenna	1516	3115	9508-4553	EMCO Elektronik	Seibersdorf Laboratories	10/2010	10/2012
Horn Antenna	1012	3160-05	9112-1001	EMCO	---	No calibration required	
Horn Antenna	1013	3160-06	9112-1001	EMCO	---	No calibration required	
Horn Antenna	1014	3160-07	9112-1008	EMCO	---	No calibration required	
Horn Antenna	1015	3160-08	9112-1002	EMCO	---	No calibration required	
Horn Antenna	1265	3160-09	9403-1025	EMCO	---	No calibration required	



11 Revision History

Revision History			
<i>Edition</i>	<i>Date</i>	<i>Issued by</i>	<i>Modifications</i>
1	02.11.2012	Martin Steindl (gz)	First Edition
2	28.03.2013	J. Roidt	Pulse desentization factor calculation detailed.
3	29.03.2013	J. Roidt	Equipment list revised