

# RADIO FREQUENCY ADDENDUM EXPOSURE REPORT TO 95599-18

FOR THE  
IR509 915MHz WPAN Router w/2 Serial, 1 FE LAN  
IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Single Antenna  
IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Dual Antenna  
Models:  
IR509UWP-915/K9, IR529UBWP-915S/K9 and IR529UBWP-915D/K9

Report No.: 95599-18A

Date of issue: November 4, 2014

**PREPARED FOR:**

Cisco Systems, Inc.  
170 W. Tasman Dr.  
San Jose, CA 95134-1706

**PREPARED BY:**

Eddie Mariscal  
CKC Laboratories, Inc.  
5046 Sierra Pines Drive  
Mariposa, CA 95338

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.



**Steve Behm**  
*Director of Quality Assurance & Engineering Services*  
CKC Laboratories, Inc.

## Revision History

**Original:** Testing of the Devices: IR509 915MHz WPAN Router w/2 Serial, 1 FE LAN, IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Single Antenna, IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Dual Antenna, Models: IR509UWP-915/K9, IR529UBWP-915S/K9 and IR529UBWP-915D/K9 to FCC Part 2.1091 and RSS-102.

**Addendum A:** 1) Changed the limits from “Occupational / Controlled Exposure” to “General Population / Uncontrolled Exposure”, 2) Added notes and manufacturer declarations to the “Device and Antenna Operating Configuration” section and 3) Recalculated the Power Density and exposure limits.

### Purpose:

To demonstrate compliance with United States, Canada and/or European Union RF Exposure requirements for Portable equipment (devices used  $\leq 20$ cm from the body) or Mobile equipment (devices used  $> 20$ cm from the body) with power output below exemption levels and Mobile equipment, where Maximum Permissible Exposure (MPE) Calculations apply.

### United States Compliance Requirements (1.1310):

#### *RF Exposure Evaluation Limits Occupational / Controlled Exposure*

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5.0	6

#### *RF Exposure Evaluation Limits General Population / Uncontrolled Exposure*

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1.0	30

\* Plane wave equivalent power density

Limit is calculated based on the mid-band frequency used in the operating frequency range.

**Exemption Level:** Power output  $< 60/f_{GHz}$  (mW)

**Canadian Compliance Requirements (RSS-102):**

**RF Exposure Evaluation Limits  
Occupational / Controlled Exposure:**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1.0	600	4.9	---	6
1.0-10	600/f	4.9/f	---	6
10-30	60	4.9/f	---	6
30-300	60	0.163	10	6
300-1500	3.54 f <sup>0.5</sup>	0.0094*f <sup>0.5</sup>	f/3	6
1500-15,000	137	0.364	50	6
15,000-150,000	137	0.364	50	616000/f <sup>1.2</sup>

**RF Exposure Evaluation Limits  
General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1.0	280	2.19	---	6
1.0-10	280/f	2.19/f	---	6
10-30	28	2.19/f	---	6
30-300	28	0.073	2	6
300-1500	1.585 * f <sup>0.5</sup>	0.0042 * f <sup>0.5</sup>	f/150	6
1500-15,000	61.4	0.163	10	6
15,000-150,000	61.4	0.163	10	616000/f <sup>1.2</sup>

\*Power density limit applicable >100MHz

**Exemption Level:**

Frequency Range (MHz)	Maximum Output Power (Conducted or EIRP)
0.003-1000	≤ 200 mW
1000-2200	≤ 100 mW
2200-3000	≤ 20 mW
3000-6000	≤ 10 mW

**European Union Compliance Requirements (ICNIRP):**

***RF Exposure Evaluation Limits  
Occupational / Controlled Exposure:***

<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (W/m<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.00082-0.065	610	24.4	---	6
0.065-1.0	610	1.6/f	---	
1.0-10	610/f	1.6/f	---	6
10-400	61	0.16	10	6
400-2000	3.0 * f <sup>0.5</sup>	0.008 * f <sup>0.5</sup>	f/40	6
2000-300,000	137	0.36	50	6

***RF Exposure Evaluation Limits  
General Population / Uncontrolled Exposure***

<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (W/m<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.003-0.150	87	5.0	---	6
0.150-1.0	87	0.73/f	--	6
1.0-10	87/f <sup>0.5</sup>	0.73/f	---	6
10-400	28	0.073	2	6
400-2000	1.375 f <sup>0.5</sup>	0.0037*f <sup>0.5</sup>	f/200	6
2000-300,000	61	0.16	10	6

*\*Power density limit applicable >100MHz*

**Exemption Level:** Power output < 20mW<sup>1</sup>

---

<sup>1</sup> May vary by product type

**Device and Antenna Operating Configuration:**

Devices operating at maximum output power with continuous transmission of modulated data. EUTs employed removable antennas so data was gathered via conducted measurements. The manufacturer declares that the gains of the antennas of each EUT will not exceed the following:

IR509 915MHz WPAN router w/2 serial, 1 FE LAN: 5dBi

IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Single Antenna: 5dBi

IR529 915MHz WPAN IP67 Range Ext. BBU Adv PS Dual Antenna: 9dBi

The manufacturer declares that the maximum transmit duty cycle of the EUTs listed above is 50%; therefore the average power is the product of the duty cycle and the peak maximum power.

\*NOTE: The manufacturer declares that the model IR529 915D/K9 listed above employs a single transmitter that directs power through an internal splitter into two output ports transmitting identical data. This device will have Yagi antennas installed in opposite directions so that field interaction of the two antennas will not be present. The manufacturer also declares that this model will always be installed with a lightning arrestor and cable with insertion loss totaling 1.1dB. The measured power in the report was 26.6dBm at the antenna port. Accounting for this 1.1dB of insertion loss produces 25.5dB. This value of 25.5dBm is used to calculate the Power Density below.

**Test Procedure:**

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65 & ANSI C95.1 for the US and Health Canada Safety Code 6 & RSS 102 for Canada.

## MPE Calculations

**Applicability:**

<i>Limit Used</i>	<b>X</b>	General Population / Uncontrolled Exposure
		Occupational / Controlled Exposure
<i>RF Exposure Exemption</i>	No	United States
	No	Canada
	NC	Europe

NC: Not contracted

**Equipment operational details:**

<i>Config #</i>	<i>Operating Frequency (MHz)</i>	<i>Measured Output Power (dBm)</i>	<i>Antenna Gain (dBi)</i>	<i>Antenna Type / Configuration</i>	<i>EIRP (dBm)</i>
1	902	29.9	5	External Omni-stick Antenna	34.9
2	902	29.9	5	External Omni-stick Antenna	34.9
3	902	25.5	9	External Yagi Antenna	34.8

Measurements based from EMC Test Reports: 95599-10, 95599-13

**MPE Calculation:**

$$PowerDensity = \frac{EIRP * DutyCycle}{4\pi d^2}$$

Given: **EIRP** in mW or W and **d** in cm or m

<i>Config #</i>	<i>Distance (cm)</i>	<i>US (1.1310)</i>		<i>Canada (RSS-102)</i>	
		<i>Power Density (mW/cm<sup>2</sup>)</i>	<i>Limit (mW/cm<sup>2</sup>)</i>	<i>Power Density (W/m<sup>2</sup>)</i>	<i>Limit (W/m<sup>2</sup>)</i>
1	20	0.31	0.61	3.07	6.1
2	20	0.31	0.61	3.07	6.1
3	20	0.28	0.61	2.80	6.1

**Summary:***Exemptions:*

In the case the equipment meets compliance requirements by exemption the product is approved for use under mobile or portable conditions without further testing under the condition that any additional collocation or simultaneous transmission requirements (including necessary separation distances) have been met.

*MPE Calculation Results:*

In the case the equipment meets compliance by MPE Calculations the product is approved for use under mobile conditions without further testing under the condition that any additional collocation or simultaneous transmission requirements (including necessary separation distances) have been met. It is assumed that the manufacturer shall design the equipment such that the minimum separation distance of 20cm (or greater, as listed above) is met or that the manufacturer provides a protection guide (or installation instructions) to the end user such that the antenna(s) may be installed in accordance with the manufacturer's instructions in such a manor to maintain the minimum separation distance.

The Absorption and distribution of Electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape and physiological condition of the body; the orientation of the body with respect to the fields; and, the electrical properties of the body and the environment. Variables that may play a substantial role in possible biological effects are those that characterize the environment (including but not limited to: ambient temperature, air velocity, relative humidity and body insulation); and those that characterize the individual (including but not limited to: age, gender, activity level and existing debilitation or disease). Because innumerable factors may interact to determine specific biological effects of exposure to electromagnetic fields, any protection guide should consider both intended and unintended operational environments and provide guidance for installation and use of the product such that proper separation distances can be maintained. (ANSI C95.1)

## References

Federal Communications Commission Knowledge Database (KDB) Publication 447498, "What are the RF exposure requirements and procedures for mobile and portable devices?" As in effect on the issue date of this report.

Federal Communications Commission Bulletin OET 65 Supplement C, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields" June 2001

Title 47 Code of Federal Regulations, Part 1.1310, "Radiofrequency radiation exposure limits." As in effect on the issue date of this report.

Title 47 Code of Federal Regulations, Part 2.1091, "Radiofrequency radiation exposure evaluation: mobile devices." As in effect on the issue date of this report.

Health Canada Safety Code 6 Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz, 2009

Health Canada Safety Code 6 Technical Guide, 2009

Industry Canada RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010 (including update December, 2010)

International Commission on Non-Ionizing Radiation Protection. Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). Health Physics 74 (4): 494-522; 1998.

International Commission on Non-Ionizing Radiation Protection Statement on the "Guidelines for limiting exposure to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz). Health Physics 97(3):257-259; 2009.

European Committee for Electrotechnical Standardization. European Normative, EN 50371 Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz) 2002.