Cisco Systems, Inc. FCC ID: LDK102074P

4 FCC §2.1091 & §15.407(f) - RF Exposure

4.1 Applicable Standard

According to FCC §15.407(f) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

^{* =} Plane-wave equivalent power density

Cisco Systems, Inc. FCC ID: LDK102074P

4.3 MPE Results

5.8 GHz Band:

Antenna gain = 4 dBi HT20 Dual Antenna (Data Rate: M8)

Maximum peak output power at antenna input terminal (dBm): 26.04

Maximum peak output power at antenna input terminal (mW): 401.79

Prediction distance (cm): 20

Prediction frequency (MHz): 5825

Maximum Antenna Gain, typical (dBi): 4

Maximum Antenna Gain (numeric): 2.512

Power density of prediction frequency at 20.0 cm (mW/cm²): 0.2

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.2 mW/cm². Limit is 1.0 mW/cm².

Antenna gain = 7 dBi HT20 Dual Antenna (Data Rate: M8)

<u>Maximum peak output power at antenna input terminal (dBm):</u> 26.04 <u>Maximum peak output power at antenna input terminal (mW):</u> 401.79

Prediction distance (cm): 20

Prediction frequency (MHz): 5825

Maximum Antenna Gain, typical (dBi): 7

Maximum Antenna Gain (numeric): 5.012

Power density of prediction frequency at 20.0 cm (mW/cm²): 0.4

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.4 mW/cm². Limit is 1.0 mW/cm².

Antenna gain = 8 dBi Non HT20 Dual Antenna

Maximum peak output power at antenna input terminal (dBm): 24.61

Maximum peak output power at antenna input terminal (mW): 289.07

Prediction distance (cm): 20

<u>Prediction frequency (MHz):</u> 5825

Maximum Antenna Gain, typical (dBi): 8

Maximum Antenna Gain (numeric): 6.31
Power density of prediction frequency at 20.0 cm (mW/cm²): 0.363

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.363 mW/cm². Limit is 1.0 mW/cm².

Cisco Systems, Inc. FCC ID: LDK102074P

Antenna gain = 14 dBi HT20 Dual Antenna (Data Rate: M0)

Maximum peak output power at antenna input terminal (dBm): 18.81

Maximum peak output power at antenna input terminal (mW): 76.033

Prediction distance (cm): 20

Prediction frequency (MHz): 5745

Maximum Antenna Gain, typical (dBi): 14

Maximum Antenna Gain (numeric): 25.119

Power density of prediction frequency at 20.0 cm (mW/cm²): 0.38

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.38 mW/cm^2 . Limit is 1.0 mW/cm^2 .