

Test Report

AIR-AP1815I-x-K9

Where (x=A,B,D,N,T,Z)

Cisco Aironet 802.11ac Dual Band Access Points

FCC ID: LDK102108

IC: 2461B-102108

2400-2483.5 MHz

Against the following Specifications:

CFR47 Part 15.247

RSS-247

RSS-Gen

AS/NZS 4268

LP0002



G.S.R 45 (E)



Cisco Systems

170 West Tasman Drive

San Jose, CA 95134

	
Author: Jose Aguirre Tested By:	Approved By: Jim Nicholson Title: Technical Leader, Engineering Revision: 1

This report replaces any previously entered test report under EDCS – **1570570**. This test report has been electronically authorized and archived using the CISCO Engineering Document Control system.

This test report has been electronically authorized and archived using the CISCO Engineering Document Control system.

SECTION 1: OVERVIEW	3
SECTION 2: ASSESSMENT INFORMATION	4
2.1 GENERAL	4
2.2 DATE OF TESTING	6
2.3 REPORT ISSUE DATE	6
2.4 TESTING FACILITIES	6
2.5 EQUIPMENT ASSESSED (EUT)	6
2.6 EUT DESCRIPTION	7
SECTION 3: RESULT SUMMARY	8
SECTION 4: SAMPLE DETAILS	10
4.1 SAMPLE DETAILS	10
4.2 SYSTEM DETAILS	10
4.3 MODE OF OPERATION DETAILS	10
APPENDIX A: EMISSION TEST RESULTS	11
CONDUCTED TEST SETUP DIAGRAM	11
TARGET MAXIMUM CHANNEL POWER	11
A.1 6dB BANDWIDTH	12
A.2 99% AND 26dB BANDWIDTH	19
A.3 MAXIMUM CONDUCTED OUTPUT POWER	26
A.4 POWER SPECTRAL DENSITY	29
A.5 CONDUCTED SPURIOUS EMISSIONS	36
A.6 CONDUCTED BANDEDGE	42
APPENDIX B: EMISSION TEST RESULTS	50
RADIATED EMISSION SETUP DIAGRAM-BELOW 1G	50
B.1 RADIATED SPURIOUS EMISSIONS	51
B.2 RECEIVER SPURIOUS EMISSIONS	52
B.3 RADIATED EMISSIONS 30MHZ TO 1GHZ	65
B.4 AC CONDUCTED EMISSIONS	67
APPENDIX C: LIST OF TEST EQUIPMENT USED TO PERFORM THE TEST	68
APPENDIX E: ABBREVIATION KEY AND DEFINITIONS	75

Section 1: Overview

The samples were assessed against the tests under the requirements of the following specifications:

Emission
CFR47 Part 15.247 RSS247 Issue 1: May 2015 RSS-Gen Issue 4: Nov 2014

Measurements were made in accordance with

- ANSI C63.10:2013
- FCC KDB 662911 D01 v02r01
- KDB 558074 D01 Meas Guidance v03r05

Section 2: Assessment Information

2.1 General

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on the samples submitted. The testing was performed by and for the use of Cisco systems Inc:

With regard to this assessment, the following points should be noted:

- a) The results contained in this report relate only to the items tested and were obtained in the period between the date of the initial assessment and the date of issue of the report. Manufactured products will not necessarily give identical results due to production and measurement tolerances.
- b) The apparatus was set up and exercised using the configuration and modes of operation defined in this report only.
- c) Where relevant, the apparatus was only assessed using the susceptibility criteria defined in this report and the Test Assessment Plan (TAP).
- d) All testing was performed under the following environmental conditions:

Temperature	15°C to 35°C (54°F to 95°F)
Atmospheric Pressure	860mbar to 1060mbar (25.4" to 31.3")
Humidity	10% to 75*%

*[Where applicable] For ESD testing the humidity limits used were 30% to 60% and for EFT/B tests the humidity limits used were 25% to 75%.
- e) All AC testing was performed at one or more of the following supply voltages:
110V 60 Hz (+/-20%)

Units of Measurement

The units of measurements defined in the appendices are reported in specific terms, which are test dependent. Where radiated measurements are concerned these are defined at a particular distance. Basic voltage measurements are defined in units of [dBuV]

As an example, the basic calculation for all measurements is as follows:

$$\text{Emission level [dBuV]} = \text{Indicated voltage level [dBuV]} + \text{Cable Loss [dB]} + \text{Other correction factors [dB]}$$

The combinations of correction factors are dependent upon the exact test configurations [see test equipment lists for further details] and may include:-

Antenna Factors, Pre Amplifier Gain, LISN Loss, Pulse Limiter Loss and Filter Insertion Loss..

Note: to convert the results from dBuV/m to uV/m use the following formula:-

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(X \text{ dBuV/m})/20] = Y \text{ uV/m}$$

Measurement Uncertainty Values

voltage and power measurements	± 2 dB
conducted EIRP measurements	± 1.4 dB
radiated measurements	± 3.2 dB
frequency measurements	$\pm 2.4 \cdot 10^{-7}$
temperature measurements	$\pm 0.54^{\circ}$
humidity measurements	$\pm 2.3\%$
DC and low frequency measurements	$\pm 2.5\%$

Where relevant measurement uncertainty levels have been estimated for tests performed on the apparatus. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Radiated emissions (expanded uncertainty, confidence interval 95%)

30 MHz - 300 MHz	+/- 3.8 dB
300 MHz - 1000 MHz	+/- 4.3 dB
1 GHz - 10 GHz	+/- 4.0 dB
10 GHz - 18GHz	+/- 8.2 dB
18GHz - 26.5GHz	+/- 4.1 dB
26.5GHz - 40GHz	+/- 3.9 dB

Conducted emissions (expanded uncertainty, confidence interval 95%)

30 MHz – 40GHz	+/- 0.38 dB
----------------	-------------

A product is considered to comply with a requirement if the nominal measured value is below the limit line. The product is considered to not be in compliance in case the nominal measured value is above the limit line.

This report must not be reproduced except in full, without written approval of Cisco Systems.

2.2 Date of testing

01-Jun-16 to 26-Jun-16

2.3 Report Issue Date

28-Jun-16

Cisco uses an electronic system to issue, store and control the revision of test reports. This system is called the Engineering Document Control System (EDCS). The actual report issue date is embedded into the original file on EDCS. Any copies of this report, either electronic or paper, that are not on EDCS must be considered uncontrolled.

2.4 Testing facilities

This assessment was performed by:

Testing Laboratory

Cisco Systems, Inc.,
125 West Tasman Drive
San Jose, CA 95134, USA

Registration Numbers for Industry Canada

Cisco System Site	Address	Site Identifier
Building P, 10m Chamber	125 West Tasman Dr San Jose, CA 95134	Company #: 2461N-2
Building P, 5m Chamber	125 West Tasman Dr San Jose, CA 95134	Company #: 2461N-1
Building I, 5m Chamber	285 W. Tasman Drive San Jose, California 95134	Company #: 2461M-1

Test Engineers

Jose Aguirre

2.5 Equipment Assessed (EUT)

AIR-AP1815I-A-K9

2.6 EUT Description

The Cisco Aironet 802.11ac Dual Band Access Points support the following modes of operation. The modes are further defined in the radio Theory of Operation. The modes included in this report represent the worst case data for all modes. Data is recorded at the lowest supported data rate for each mode. This report covers operation on channel 1-11.

802.11n/ac - Legacy CCK, One Antenna, 1 to 11 Mbps
802.11n/ac - Legacy CCK, Two Antennas, 1 to 11 Mbps

802.11n/ac - Non HT20, One Antenna, 6 to 54 Mbps
802.11n/ac - Non HT20, Two Antennas, 6 to 54 Mbps

802.11n/ac - HT/VHT20, One Antenna, M0 to M7
802.11n/ac - HT/VHT20, Two Antennas, M0 to M7
802.11n/ac - HT/VHT20, Two Antennas, M8 to M15

802.11n/ac - HT/VHT20 Beam Forming, Two Antennas, M0 to M7
802.11n/ac - HT/VHT20 Beam Forming, Two Antennas, M8 to M15

802.11n/ac - HT/VHT20 STBC, Two Antennas, M0 to M7

The following antennas are supported by this product series.
The data included in this report represent the worst case data for all antennas.

Frequency	Part Number	Antenna Type	Antenna Gain (dBi)
2.4 / 5 GHz	2x2 Internal	Omni	2 / 4

Section 3: Result Summary

3.1 Results Summary Table

Conducted emissions

Basic Standard	Technical Requirements / Details	Result
FCC 15.247 RSS-247 LP0002:3.10.1(6.2.1)	6dB Bandwidth: Systems using digital modulation techniques may operate in the 2400-2483.5MHz band. The minimum 6dB bandwidth shall be at least 500 kHz.	Pass
FCC 15.247 RSS-247	99% & 26 dB Bandwidth: The 99% occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. There is no limit for 99% OBW. The 26 dB emission is the width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.	Pass
FCC 15.247 RSS-247 LP0002:3.10.1(2.3)	Output Power: 15.247 The maximum conducted output power of the intentional radiator for systems using digital modulation in the 2400-2483.5 MHz band shall not exceed 1 Watt (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-247 For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.	Pass
FCC 15.247 RSS-247 LP0002:3.10.1(6.2.2)	Power Spectral Density: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	Pass
FCC 15.247 RSS-247 LP0002:3.10.1(5)/2.8	Conducted Spurious Emissions / Band-Edge: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required	Pass
FCC 15.247 RSS-247 FCC 15.205 RSS-Gen	Restricted band: Unwanted emissions falling within the restricted bands, as defined in FCC 15.205 (a) and RSS-Gen 8.10 must also comply with the radiated emission limits specified in FCC 15.209 (a) and RSS-Gen 8.9.	Pass

Radiated Emissions (General requirements)

Basic Standard	Technical Requirements / Details	Result
FCC 15.209 RSS-Gen LP0002:3.10.1(5)/2.8	TX Spurious Emissions: Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the filed strength limits table in this section. Unwanted emissions falling within the restricted bands, as defined in FCC 15.205 (a) and RSS-Gen 8.10 must also comply with the radiated emission limits specified in FCC 15.209 (a) and RSS-Gen 8.9.	Pass
RSS-Gen LP0002:3.10.1(5)2.8	RX Spurious Emissions: RSS-Gen 8.9 Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 4 and Table 5 below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission. RSS-Gen 8.10 Unwanted emissions that fall into restricted bands of Table 6 shall comply with the limits specified in RSS-Gen; and (c) Unwanted emissions that do not fall within the restricted frequency bands of Table 6 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.	Pass
FCC 15.207 RSS-Gen LP0002:2.3	AC conducted Emissions: Except when the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply, either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table in these sections. The more stringent limit applies at the frequency range boundaries.	Pass

* MPE calculation is recorded in a separate report

Section 4: Sample Details

Note: Each sample was evaluated to ensure that its condition was suitable to be used as a test sample prior to the commencement of testing.

4.1 Sample Details

Sample No.	Equipment Details	Manufacturer	Hardware Rev.	Firmware Rev.	Software Rev.	Serial Number
S01	AIR-AP1815I-A-K9	Cisco Systems	P2	8.3.15.124	AP1G5	FOC20041PJB
S02*	Catalyst 3750E-24PD-E	Cisco Systems	A0	12.2(50)SE2	C3750E-UNIVERSALK9-M	FDO15422DE4

(*) is support equipment Power supply for EUT

4.2 System Details

System #	Description	Samples
1	AIR-AP1815I-A-K9	S01
2	POE	S02

4.3 Mode of Operation Details


Mode#	Description	Comments
1	Continuous Transmitting	Continuous Transmitting \geq 98% duty cycle

Measurements were made in accordance with

- ANSI C63.10:2013
- FCC KDB 662911 D01 v02r01
- KDB 558074 D01 Meas Guidance v03r05

Appendix A: Emission Test Results

Conducted Test Setup Diagram



Target Maximum Channel Power

The following table details the maximum supported Total Channel Power for all operating modes.

Operating Mode	Maximum Channel Power (dBm EIRP)		
	Frequency (MHz)		
	2412	2437	2462
Legacy CCK, 1 to 11 Mbps	21	21	21
Non HT20, 6 to 54 Mbps	21	22	21
Non HT20 Beam Forming, 6 to 54 Mbps	23	25	23
HT/VHT20, M0 to M15	21	22	21
HT/VHT20 Beam Forming, M0 to M15	23	25	21
HT/VHT20 STBC, M0 to M7	21	22	21



A.1 6dB Bandwidth

15.247 / RSS-247 / LP0002:3.10.1(6.2.1) Systems using digital modulation techniques may operate in the 2400-2483.5MHz band. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Procedure

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013

<p>6 BW Test Procedure</p> <ol style="list-style-type: none"> 1. Set the radio in the continuous transmitting mode. 2. Allow the trace to stabilize. 3. Setting the x-dB bandwidth mode to -6dB within the measurement set up function. 4. Select the automatic OBW measurement function of an instrument to perform bandwidth measurement. 5. Capture graphs and record pertinent measurement data.
--

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013 section 11.8.2 Option 2

<p>6 BW Test parameters</p> <p>X dB BW = 6dB (using the OBW function of the spectrum analyzer) Span = Large enough to capture the entire EBW RBW = 100 KHz VBW ≥ 3 x RBW Sweep = Auto couple Detector = Peak or where practical sample shall be used Trace = Max. Hold</p>

System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

<p>Tested By : Jose Aguirre</p>	<p>Date of testing: 01-Jun-16 to 26-Jun-16</p>
<p>Test Result : PASS</p>	


See Appendix C for list of test equipment

Frequency (MHz)	Mode	Data Rate (Mbps)	6dB BW (MHz)	Limit (kHz)	Margin (MHz)
2412	CCK, 1 to 11 Mbps	11	7.6	>500	7.1
	Non HT20, 6 to 54 Mbps	6	16.4	>500	15.9
	HT/VHT20, M0 to M15	m0	17.6	>500	17.1
2437	CCK, 1 to 11 Mbps	11	8.1	>500	7.6
	Non HT20, 6 to 54 Mbps	6	16.3	>500	15.8
	HT/VHT20, M0 to M15	m0	17.6	>500	17.1
2462	CCK, 1 to 11 Mbps	11	8.1	>500	7.6
	Non HT20, 6 to 54 Mbps	6	16.4	>500	15.9
	HT/VHT20, M0 to M15	m0	17.6	>500	17.1


6dB Bandwidth, 2412 MHz, CCK, 1 to 11 Mbps



6dB Bandwidth, 2412 MHz, Non HT20, 6 to 54 Mbps




6dB Bandwidth, 2412 MHz, HT/VHT20, M0 to M15




6dB Bandwidth, 2437 MHz, CCK, 1 to 11 Mbps




6dB Bandwidth, 2437 MHz, Non HT20, 6 to 54 Mbps




6dB Bandwidth, 2437 MHz, HT/VHT20, M0 to M15




6dB Bandwidth, 2462 MHz, CCK, 1 to 11 Mbps



6dB Bandwidth, 2462 MHz, Non HT20, 6 to 54 Mbps



6dB Bandwidth, 2462 MHz, HT/VHT20, M0 to M15



A.2 99% and 26dB Bandwidth

The 99% occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. There is no limit for 99% OBW.

The 26 dB emission is the width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

Test Procedure

Ref. ANSI C63.10: 2013

26 BW & 99% BW

Test Procedure

1. Set the radio in the continuous transmitting mode.
2. Allow the trace to stabilize.
3. Setting the x-dB bandwidth mode to -26dB & OBW to 99% within the measurement set up function.
4. Select the automatic OBW measurement function of an instrument to perform bandwidth measurement.
5. Capture graphs and record pertinent measurement data.

Ref. ANSI C63.10: 2013 section 6.9.3

26 BW & 99% BW

Test parameters

X dB BW = -26dB (using the OBW function of the spectrum analyzer)

OBW = 99%

Span = 1.5 to 5 times the OBW

RBW = 1% to 5% of the OBW

VBW \geq 3 x RBW

Sweep = Auto couple

Detector = Peak or where practical sample shall be used

Trace = Max. Hold

System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By :

Jose Aguirre

Date of testing:

01-Jun-16 to 26-Jun-16


Test Result : PASS

See Appendix C for list of test equipment


Frequency (MHz)	Mode	Data Rate (Mbps)	26dB BW (MHz)	99% BW (MHz)
2412	CCK, 1 to 11 Mbps	11	16.9	12.815
	Non HT20, 6 to 54 Mbps	6	20.7	17.233
	HT/VHT20, M0 to M15	m0	21.6	18.215
2437	CCK, 1 to 11 Mbps	11	16.9	12.812
	Non HT20, 6 to 54 Mbps	6	20.8	17.317
	HT/VHT20, M0 to M15	m0	21.8	18.269
2462	CCK, 1 to 11 Mbps	11	16.9	12.841
	Non HT20, 6 to 54 Mbps	6	20.7	17.242
	HT/VHT20, M0 to M15	m0	21.7	18.246



26dB / 99% Bandwidth, 2412 MHz, CCK, 1 to 11 Mbps




26dB / 99% Bandwidth, 2412 MHz, Non HT20, 6 to 54 Mbps




26dB / 99% Bandwidth, 2412 MHz, HT/VHT20, M0 to M15




26dB / 99% Bandwidth, 2437 MHz, CCK, 1 to 11 Mbps




26dB / 99% Bandwidth, 2437 MHz, Non HT20, 6 to 54 Mbps




26dB / 99% Bandwidth, 2437 MHz, HT/VHT20, M0 to M15




26dB / 99% Bandwidth, 2462 MHz, CCK, 1 to 11 Mbps



26dB / 99% Bandwidth, 2462 MHz, Non HT20, 6 to 54 Mbps



26dB / 99% Bandwidth, 2462 MHz, HT/VHT20, M0 to M15



A.3 Maximum Conducted Output Power

15.247 / RSS-247 section 5.4 / LP0002:3.10.1(2.3) The maximum conducted output power of the intentional radiator for systems using digital modulation in the 2400-2483.5 MHz band shall not exceed 1 Watt (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

The maximum supported antenna gain is 2dBi.

Test Procedure

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013

Maximum Conducted Output power

Test Procedure

1. Set the radio in the continuous transmitting mode at full power
2. Compute power by integrating the spectrum across the EBW (or alternatively entire 99% OBW) of the signal using the instrument's band power measurement function. The integration shall be performed using the spectrum analyzer band-power measurement function with band limits set equal to the EBW or the OBW band edges.
3. Capture graphs and record pertinent measurement data.

Ref. 558074 D01 DTS Meas Guidance v03r05 section 9.2 Method AVGSA-1
ANSI C63.10: 2013 section 11.9.2 Method AVGSA-1

Maximum Conducted Output power

Test parameters

Span = >1.5 times the OBW
RBW = 1MHz
VBW ≥ 3 x RBW
Sweep = Auto couple
Detector = Sample, (RMS or where practical sample shall be used)
Trace = Trace Average 100

The "measure-and-sum technique" is used for measuring in-band transmit power of a device. In the measure-and-sum approach, the conducted emission level is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in linear power units. (See ANSI C63.10 section 14.3 for Guidance)

System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By :

Jose Aguirre

Date of testing:

01-Jun-16 to 26-Jun-16

Test Result : PASS

See Appendix C for list of test equipment


Note: Limit is modified to ensure complying with both conducted power limit of 30dBm and eirp limit of 36 dBm. For antenna gains <6dBi, a product could comply with the 36dBm eirp limit, and still exceed the 30 dBm conducted limit. As a result, for gains <6dBi, we calculate the limit as 36dBm –(6dBi – Actual gain)

Frequency (MHz)	Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Max Power (dBm)	Tx 2 Max Power (dBm)	Total Tx Channel Power (dBm EIRP)	Limit (dBm) EIRP	Margin (dB)
2412	CCK, 1 to 11 Mbps	1	2	16.2		18.2	32.0	13.8
	CCK, 1 to 11 Mbps	2	2	16.2	16.3	21.3	32.0	10.7
	Non HT20, 6 to 54 Mbps	1	2	16.2		18.2	32.0	13.8
	Non HT20, 6 to 54 Mbps	2	2	16.2	16.5	21.4	32.0	10.6
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	15.3	15.5	23.4	35.0	11.6
	HT/VHT20, M0 to M7	1	2	16.3		18.3	32.0	13.7
	HT/VHT20, M0 to M7	2	2	16.3	16.5	21.4	32.0	10.6
	HT/VHT20, M8 to M15	2	2	16.3	16.5	21.4	32.0	10.6
	HT/VHT20 Beam Forming, M0 to M7	2	5	15.3	15.5	23.4	35.0	11.6
	HT/VHT20 Beam Forming, M8 to M15	2	2	16.3	16.5	21.4	32.0	10.6
	HT/VHT20 STBC, M0 to M7	2	2	16.3	16.5	21.4	32.0	10.6
2437	CCK, 1 to 11 Mbps	1	2	16.6		18.6	32.0	13.4
	CCK, 1 to 11 Mbps	2	2	16.6	16.3	21.5	32.0	10.5
	Non HT20, 6 to 54 Mbps	1	2	16.8		18.8	32.0	13.2
	Non HT20, 6 to 54 Mbps	2	2	16.8	16.4	21.6	32.0	10.4
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	16.8	16.4	24.6	35.0	10.4
	HT/VHT20, M0 to M7	1	2	16.7		18.7	32.0	13.3
	HT/VHT20, M0 to M7	2	2	16.7	16.4	21.6	32.0	10.4
	HT/VHT20, M8 to M15	2	2	16.7	16.4	21.6	32.0	10.4
	HT/VHT20 Beam Forming, M0 to M7	2	5	16.7	16.4	24.6	35.0	10.4
	HT/VHT20 Beam Forming, M8 to M15	2	2	16.7	16.4	21.6	32.0	10.4
	HT/VHT20 STBC, M0 to M7	2	2	16.7	16.4	21.6	32.0	10.4
2462	CCK, 1 to 11 Mbps	1	2	16.7		18.7	32.0	13.3
	CCK, 1 to 11 Mbps	2	2	16.7	16.1	21.4	32.0	10.6
	Non HT20, 6 to 54 Mbps	1	2	16.6		18.6	32.0	13.4
	Non HT20, 6 to 54 Mbps	2	2	16.6	16.2	21.4	32.0	10.6
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	15.6	15.3	23.5	35.0	11.5
	HT/VHT20, M0 to M7	1	2	16.7		18.7	32.0	13.3
	HT/VHT20, M0 to M7	2	2	15.9	15.3	20.6	32.0	11.4
	HT/VHT20, M8 to M15	2	2	15.9	15.3	20.6	32.0	11.4
	HT/VHT20 Beam Forming, M0 to M7	2	5	12.9	12.4	20.7	35.0	14.3


HT/VHT20 Beam Forming, M8 to M15	2	2	15.9	15.3	20.6	32.0	11.4
HT/VHT20 STBC, M0 to M7	2	2	15.9	15.3	20.6	32.0	11.4

(*) Limit is modified to ensure complying with both conducted power limit of 30dBm and eirp limit of 36 dBm

Peak Output Power, 2437 MHz, Non HT20, 6 to 54 Mbps



Antenna A



Antenna B

A.4 Power Spectral Density

15.247 / RSS-247 / LP0002:3.10.1(6.2.2) For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013

Power Spectral Density Test Procedure
1. Set the radio in the continuous transmitting mode at full power 2. Configure Spectrum analyzer as per test parameters below and Peak search marker 3. Capture graphs and record pertinent measurement data.

Ref. 558074 D01 DTS Meas Guidance v03r05 section 10.2 Peak PSD
ANSI C63.10: 2013 section 11.10.2 Peak PSD

Power Spectral Density Test parameters
Span = >1.5 times the OBW RBW = 3 kHz ≤ RBW ≤ 100 kHz. VBW ≥ 3 x RBW Sweep = Auto couple Detector = Peak Trace = Trace Average 100

The "Measure and add 10 log(N) dB technique", where N is the number of outputs, is used for measuring in-band Power Spectral Density. With this technique, spectrum measurements are performed at each output of the device, and the quantity 10 log(2) (or 3dB) is added to the worst case spectrum value before comparing to the emission limit. (See ANSI C63.10 section 14.3.2.3)


System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	


See Appendix C for list of test equipment

Frequency (MHz)	Mode	Data Rate (Mbps)	PSD / Antenna (dBm/3kHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
2412	CCK, 1 to 11 Mbps	11	-7.1	-4	8	12
	Non HT20, 6 to 54 Mbps	6	-12.0	-8.9	8	16.9
	HT/VHT20, M0 to M15	m0	-12.0	-8.9	8	16.9
2437	CCK, 1 to 11 Mbps	11	-4.6	-1.5	8	9.5
	Non HT20, 6 to 54 Mbps	6	-10.8	-7.7	8	15.7
	HT/VHT20, M0 to M15	m0	-11.5	-8.4	8	16.4
2462	CCK, 1 to 11 Mbps	11	-6.7	-3.6	8	11.6
	Non HT20, 6 to 54 Mbps	6	-11.3	-8.2	8	16.2
	HT/VHT20, M0 to M15	m0	-11.1	-8	8	16


Power Spectral Density, 2412 MHz, CCK, 1 to 11 Mbps




Power Spectral Density, 2412 MHz, Non HT20, 6 to 54 Mbps




Power Spectral Density, 2412 MHz, HT/VHT20, M0 to M15




Power Spectral Density, 2437 MHz, CCK, 1 to 11 Mbps




Power Spectral Density, 2437 MHz, Non HT20, 6 to 54 Mbps




Power Spectral Density, 2437 MHz, HT/VHT20, M0 to M15




Power Spectral Density, 2462 MHz, CCK, 1 to 11 Mbps



Power Spectral Density, 2462 MHz, Non HT20, 6 to 54 Mbps



Power Spectral Density, 2462 MHz, HT/VHT20, M0 to M15



A.5 Conducted Spurious Emissions

15.205 / 15.209 / LP0002 - Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

RSS-Gen 8.9: Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 4 and Table 5 below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

RSS-Gen 8.10 (b) Unwanted emissions that fall into restricted bands of Table 6 shall comply with the limits specified in RSS-Gen; and **(c)** Unwanted emissions that do not fall within the restricted frequency bands of Table 6 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Use formula below to substitute conducted measurements in place of radiated measurements

$$E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77, \text{ where } E = \text{field strength and } d = 3 \text{ meter}$$

- 1) Average Plot, Limit= -41.25 dBm eirp
- 2) Peak plot, Limit = -21.25 dBm eirp

Test Procedure

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013

Conducted Spurious Emissions

Test Procedure

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Place the radio in continuous transmit mode
3. Configure Spectrum analyzer as per test parameters below (be sure to enter all losses between the transmitter output and the spectrum analyzer).
4. Use the peak marker function to determine the maximum spurs amplitude level.
5. The "measure-and-sum technique" is used for measuring in-band transmit power of a device. In the measure-and-sum approach, the conducted emission level is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in linear power units. The worst case output is recorded. (see ANSI C63.10 2013 section 14.3.2.2)
6. Capture graphs and record pertinent measurement data.

Ref. 558074 D01 DTS Meas Guidance v03r05 section 11.1b, 11.2-3, 12.2.4 & 12.2.5.3
ANSI C63.10: 2013 section 11.10.3 & 11.12.2.4 & 11.12.2.5.3

Conducted Spurious Emissions

Test parameters

Span = 30 MHz-26 GHz
RBW = 100 kHz.
VBW ≥ 3 x RBW
Sweep = Auto couple
Detector = Peak
Trace = Max Hold

KDB: 558074 D01 DTS Meas Guidance v03r05 section 12.2.2 © add the max antenna gain + ground reflection factor (4.7 dB for frequencies between 30 MHz and 1000 MHz, and 0 dB for frequencies > 1000 MHz).

System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	

See Appendix C for list of test equipment

Frequency (MHz)	Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Spur Power (dBm)	Tx 2 Spur Power (dBm)	Total Conducted Spur (dBm)	Limit (dBm)	Margin (dB)
2412	CCK, 1 to 11 Mbps	1	2	-53.0		-51.0	-41.25	9.8
	CCK, 1 to 11 Mbps	2	2	-53.0	-63.2	-50.6	-41.25	9.4
	Non HT20, 6 to 54 Mbps	1	2	-50.4		-48.4	-41.25	7.2
	Non HT20, 6 to 54 Mbps	2	2	-50.4	-56.8	-47.5	-41.25	6.3
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-50.3	-56.6	-44.4	-41.25	3.1
	HT/VHT20, M0 to M7	1	2	-50.5		-48.5	-41.25	7.3
	HT/VHT20, M0 to M7	2	2	-50.5	-56.9	-47.6	-41.25	6.4
	HT/VHT20, M8 to M15	2	2	-50.5	-56.9	-47.6	-41.25	6.4
	HT/VHT20 Beam Forming, M0 to M7	2	5	-50.3	-57.3	-44.5	-41.25	3.3
	HT/VHT20 Beam Forming, M8 to M15	2	2	-50.5	-56.9	-47.6	-41.25	6.4
	HT/VHT20 STBC, M0 to M7	2	2	-50.5	-56.9	-47.6	-41.25	6.4
2437	CCK, 1 to 11 Mbps	1	2	-51.2		-49.2	-41.25	8.0
	CCK, 1 to 11 Mbps	2	2	-51.2	-67.9	-49.1	-41.25	7.9
	Non HT20, 6 to 54 Mbps	1	2	-49.4		-47.4	-41.25	6.2
	Non HT20, 6 to 54 Mbps	2	2	-49.4	-69.7	-47.4	-41.25	6.1
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-49.4	-69.7	-44.4	-41.25	3.1
	HT/VHT20, M0 to M7	1	2	-49.3		-47.3	-41.25	6.1
	HT/VHT20, M0 to M7	2	2	-49.3	-69.3	-47.3	-41.25	6.0
	HT/VHT20, M8 to M15	2	2	-49.3	-69.3	-47.3	-41.25	6.0
	HT/VHT20 Beam Forming, M0 to M7	2	5	-49.3	-69.3	-44.3	-41.25	3.0
	HT/VHT20 Beam Forming, M8 to M15	2	2	-49.3	-69.3	-47.3	-41.25	6.0
	HT/VHT20 STBC, M0 to M7	2	2	-49.3	-69.3	-47.3	-41.25	6.0
2462	CCK, 1 to 11 Mbps	1	2	-50.7		-48.7	-41.25	7.5
	CCK, 1 to 11 Mbps	2	2	-50.7	-68.4	-48.6	-41.25	7.4
	Non HT20, 6 to 54 Mbps	1	2	-47.5		-45.5	-41.25	4.3
	Non HT20, 6 to 54 Mbps	2	2	-47.5	-54.9	-44.8	-41.25	3.5
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-47.0	-54.3	-41.3	-41.25	0.0
	HT/VHT20, M0 to M7	1	2	-47.2		-45.2	-41.25	4.0
	HT/VHT20, M0 to M7	2	2	-47.0	-54.2	-44.2	-41.25	3.0
	HT/VHT20, M8 to M15	2	2	-47.0	-54.2	-44.2	-41.25	3.0
	HT/VHT20 Beam Forming, M0 to M7	2	5	-48.7	-56.3	-43.0	-41.25	1.8
	HT/VHT20 Beam Forming, M8 to M15	2	2	-47.0	-54.2	-44.2	-41.25	3.0
	HT/VHT20 STBC, M0 to M7	2	2	-47.0	-54.2	-44.2	-41.25	3.0

Frequency (MHz)	Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Spur Power (dBm)	Tx 2 Spur Power (dBm)	Total Conducted Spur (dBm)	Limit (dBm)	Margin (dB)
2412	CCK, 1 to 11 Mbps	1	2	-63.5		-61.5	-21.25	40.3
	CCK, 1 to 11 Mbps	2	2	-63.5	-64.0	-58.7	-21.25	37.5
	Non HT20, 6 to 54 Mbps	1	2	-63.1		-61.1	-21.25	39.9
	Non HT20, 6 to 54 Mbps	2	2	-63.1	-63.3	-58.2	-21.25	36.9
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-63.8	-63.0	-55.4	-21.25	34.1
	HT/VHT20, M0 to M7	1	2	-62.8		-60.8	-21.25	39.6
	HT/VHT20, M0 to M7	2	2	-62.8	-62.2	-57.5	-21.25	36.2
	HT/VHT20, M8 to M15	2	2	-62.8	-62.2	-57.5	-21.25	36.2
	HT/VHT20 Beam Forming, M0 to M7	2	5	-62.5	-61.8	-54.1	-21.25	32.9
	HT/VHT20 Beam Forming, M8 to M15	2	2	-62.8	-62.2	-57.5	-21.25	36.2
	HT/VHT20 STBC, M0 to M7	2	2	-62.8	-62.2	-57.5	-21.25	36.2
2437	CCK, 1 to 11 Mbps	1	2	-63.2		-61.2	-21.25	40.0
	CCK, 1 to 11 Mbps	2	2	-63.2	-64.5	-58.8	-21.25	37.5
	Non HT20, 6 to 54 Mbps	1	2	-63.9		-61.9	-21.25	40.7
	Non HT20, 6 to 54 Mbps	2	2	-63.9	-61.3	-57.4	-21.25	36.1
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-63.9	-61.3	-54.4	-21.25	33.1
	HT/VHT20, M0 to M7	1	2	-63.0		-61.0	-21.25	39.8
	HT/VHT20, M0 to M7	2	2	-63.0	-63.7	-58.3	-21.25	37.1
	HT/VHT20, M8 to M15	2	2	-63.0	-63.7	-58.3	-21.25	37.1
	HT/VHT20 Beam Forming, M0 to M7	2	5	-63.0	-63.7	-55.3	-21.25	34.1
	HT/VHT20 Beam Forming, M8 to M15	2	2	-63.0	-63.7	-58.3	-21.25	37.1
	HT/VHT20 STBC, M0 to M7	2	2	-63.0	-63.7	-58.3	-21.25	37.1
2462	CCK, 1 to 11 Mbps	1	2	-63.5		-61.5	-21.25	40.3
	CCK, 1 to 11 Mbps	2	2	-63.5	-63.6	-58.5	-21.25	37.3
	Non HT20, 6 to 54 Mbps	1	2	-63.0		-61.0	-21.25	39.8
	Non HT20, 6 to 54 Mbps	2	2	-63.0	-63.8	-58.4	-21.25	37.1
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-64.3	-63.6	-55.9	-21.25	34.7
	HT/VHT20, M0 to M7	1	2	-62.9		-60.9	-21.25	39.7
	HT/VHT20, M0 to M7	2	2	-64.7	-62.7	-58.6	-21.25	37.3
	HT/VHT20, M8 to M15	2	2	-64.7	-62.7	-58.6	-21.25	37.3
	HT/VHT20 Beam Forming, M0 to M7	2	5	-46.4	-64.2	-41.3	-21.25	20.1
	HT/VHT20 Beam Forming, M8 to M15	2	2	-64.7	-62.7	-58.6	-21.25	37.3
	HT/VHT20 STBC, M0 to M7	2	2	-64.7	-62.7	-58.6	-21.25	37.3


Conducted Spurs Average, All Antennas




Conducted Spurs Peak, All Antennas



Conducted Spurs Average, 2462 MHz, Non HT20 Beam Forming, 6 to 54 Mbps




Antenna A




Antenna B

Conducted Spurs Peak, 2462 MHz, HT/VHT20 Beam Forming, M0 to M7



Antenna A



Antenna B

A.6 Conducted Band

15.205 / 15.209 / LP0002 - Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

RSS-Gen 8.9: Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 4 and Table 5 below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

RSS-Gen 8.10 (b) Unwanted emissions that fall into restricted bands of Table 6 shall comply with the limits specified in RSS-Gen; and **(c)** Unwanted emissions that do not fall within the restricted frequency bands of Table 6 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Use formula below to substitute conducted measurements in place of radiated measurements

$$E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77, \text{ where } E = \text{field strength and } d = 3 \text{ meter}$$

- 1) Average Plot, Limit= -41.25 dBm eirp
- 2) Peak plot, Limit = -21.25 dBm eirp

Test Procedure

Ref. KDB 558074 D01 DTS Meas Guidance v03r05
ANSI C63.10: 2013

Conducted Band edge	
Test Procedure	
<ol style="list-style-type: none"> 1. Connect the antenna port(s) to the spectrum analyzer input. 2. Place the radio in continuous transmit mode. Use the procedures in KDB 558074 D01 DTS Meas Guidance v03r05 to substitute conducted measurements in place of radiated measurements. 3. Configure Spectrum analyzer as per test parameters below (be sure to enter all losses between the transmitter output and the spectrum analyzer). 4. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands.. 5. The "measure-and-sum technique" is used for measuring in-band transmit power of a device. In the measure-and-sum approach, the conducted emission level is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in linear power units. The worst case output is recorded. 6. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands 7. Capture graphs and record pertinent measurement data. 	
Conducted Bandedge	Conducted Bandedge
Test parameters non-restricted Band KDB 558074 D01 v03r05 section 11.1b, 11.2-3, also see ANSI C63.10: 2013 section 11.10.3	Test parameters restricted Band KDB 558074 D01 v03r05 section 12.2.4 & 12.2.5.3 also see ANSI C63.10: 2013 section 11.12.4 & 11.12.5.3
RBW = 100 kHz VBW ≥ 3 x RBW Sweep = Auto couple Detector = Peak Trace = Max Hold.	RBW = 1 MHz VBW ≥ 3 x RBW for Peak, 100Hz for Average Sweep = Auto couple Detector = Peak Trace = Max Hold.

System Number	Description	Samples	System under test	Support equipment
1	EUT	S01	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S02	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	


See Appendix C for list of test equipment

Conducted Bandedge (Restricted Band)


Frequency (MHz)	Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Bandedge Level (dBm)	Tx 2 Bandedge Level (dBm)	Total Tx Bandedge Level (dBm)	Limit (dBm)	Margin (dB)
2412	CCK, 1 to 11 Mbps	1	2	-61.6		-59.6	-41.25	18.4
	CCK, 1 to 11 Mbps	2	2	-61.6	-59.4	-55.4	-41.25	14.1
	Non HT20, 6 to 54 Mbps	1	2	-48.8		-46.8	-41.25	5.6
	Non HT20, 6 to 54 Mbps	2	2	-48.8	-48.8	-43.8	-41.25	2.5
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-52.5	-51.3	-43.8	-41.25	2.6
	HT/VHT20, M0 to M7	1	2	-47.4		-45.4	-41.25	4.2
	HT/VHT20, M0 to M7	2	2	-47.4	-48.2	-42.8	-41.25	1.5
	HT/VHT20, M8 to M15	2	2	-47.4	-48.2	-42.8	-41.25	1.5
	HT/VHT20 Beam Forming, M0 to M7	2	5	-50.9	-49.8	-42.3	-41.25	1.1
	HT/VHT20 Beam Forming, M8 to M15	2	2	-47.4	-48.2	-42.8	-41.25	1.5
	HT/VHT20 STBC, M0 to M7	2	2	-47.4	-48.2	-42.8	-41.25	1.5
2462	CCK, 1 to 11 Mbps	1	2	-58.3		-56.3	-41.25	15.1
	CCK, 1 to 11 Mbps	2	2	-58.3	-57.7	-53.0	-41.25	11.7
	Non HT20, 6 to 54 Mbps	1	2	-45.9		-43.9	-41.25	2.7
	Non HT20, 6 to 54 Mbps	2	2	-45.9	-48.4	-42.0	-41.25	0.7
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-49.2	-52.0	-42.4	-41.25	1.1
	HT/VHT20, M0 to M7	1	2	-43.5		-41.5	-41.25	0.3
	HT/VHT20, M0 to M7	2	2	-46.6	-52.5	-43.6	-41.25	2.4
	HT/VHT20, M8 to M15	2	2	-46.6	-52.5	-43.6	-41.25	2.4
	HT/VHT20 Beam Forming, M0 to M7	2	5	-52.4	-55.3	-45.6	-41.25	4.4
	HT/VHT20 Beam Forming, M8 to M15	2	2	-46.6	-52.5	-43.6	-41.25	2.4
	HT/VHT20 STBC, M0 to M7	2	2	-46.6	-52.5	-43.6	-41.25	2.4

Frequency (MHz)	Mode	Tx Paths	Correlated Antenna Gain (dBi)	Tx 1 Bandedge Level (dBm)	Tx 2 Bandedge Level (dBm)	Total Tx Bandedge Level (dBm)	Limit (dBm)	Margin (dB)
2412	CCK, 1 to 11 Mbps	1	2	-50.1		-48.1	-21.25	26.9
	CCK, 1 to 11 Mbps	2	2	-50.1	-48.1	-44.0	-21.25	22.7
	Non HT20, 6 to 54 Mbps	1	2	-30.7		-28.7	-21.25	7.5
	Non HT20, 6 to 54 Mbps	2	2	-30.7	-31.8	-26.2	-21.25	5.0
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-36.7	-34.8	-27.6	-21.25	6.4
	HT/VHT20, M0 to M7	1	2	-32.3		-30.3	-21.25	9.1
	HT/VHT20, M0 to M7	2	2	-32.3	-32.2	-27.2	-21.25	6.0
	HT/VHT20, M8 to M15	2	2	-32.3	-32.2	-27.2	-21.25	6.0
	HT/VHT20 Beam Forming, M0 to M7	2	5	-34.4	-36.0	-27.1	-21.25	5.9
	HT/VHT20 Beam Forming, M8 to M15	2	2	-32.3	-32.2	-27.2	-21.25	6.0
	HT/VHT20 STBC, M0 to M7	2	2	-32.3	-32.2	-27.2	-21.25	6.0
2462	CCK, 1 to 11 Mbps	1	2	-48.0		-46.0	-21.25	24.8
	CCK, 1 to 11 Mbps	2	2	-48.0	-48.1	-43.0	-21.25	21.8
	Non HT20, 6 to 54 Mbps	1	2	-29.2		-27.2	-21.25	6.0
	Non HT20, 6 to 54 Mbps	2	2	-29.2	-31.3	-25.1	-21.25	3.9
	Non HT20 Beam Forming, 6 to 54 Mbps	2	5	-33.4	-36.2	-26.6	-21.25	5.3
	HT/VHT20, M0 to M7	1	2	-28.2		-26.2	-21.25	5.0
	HT/VHT20, M0 to M7	2	2	-33.0	-37.5	-29.7	-21.25	8.4
	HT/VHT20, M8 to M15	2	2	-33.0	-37.5	-29.7	-21.25	8.4
	HT/VHT20 Beam Forming, M0 to M7	2	5	-39.3	-44.2	-33.1	-21.25	11.8
	HT/VHT20 Beam Forming, M8 to M15	2	2	-33.0	-37.5	-29.7	-21.25	8.4
	HT/VHT20 STBC, M0 to M7	2	2	-33.0	-37.5	-29.7	-21.25	8.4

Conducted Bandedge Average, 2412 MHz, HT/VHT20 Beam Forming, M0 to M7




Antenna A




Antenna B

Conducted Bandedge Average, 2462 MHz, HT/VHT20, M0 to M7




Antenna A

Conducted Bandedge Peak, 2412 MHz, Non HT20, 6 to 54 Mbps



Antenna A



Antenna B

Conducted Bandedge Peak, 2462 MHz, Non HT20, 6 to 54 Mbps



Antenna A



Antenna B




Conducted Bandedge (Non-Restricted Band)

Frequency (MHz)	Mode	Data Rate (Mbps)	Conducted Bandedge Delta (dB)	Limit (dBc)	Margin (dB)
2412	CCK, 1 to 11 Mbps	11	56.2	>30	26.2
	Non HT20, 6 to 54 Mbps	6	39.7	>30	9.7
	HT/VHT20, M0 to M15	m0	40.3	>30	10.3

Conducted Bandedge Delta, 2412 MHz, CCK, 1 to 11 Mbps



Conducted Bandedge Delta, 2412 MHz, Non HT20, 6 to 54 Mbps




Conducted Bandedge Delta, 2412 MHz, HT/VHT20, M0 to M15




Appendix B: Emission Test Results

Testing Laboratory: Cisco Systems, Inc., 125 West Tasman Drive, San Jose, CA 95134, USA

Radiated Emission Setup Diagram-Below 1G



Radiated Emission Setup Diagram-Above 1G





B.1 Radiated Spurious Emissions

15.205 / RSS-Gen / LP0002:3.10.1(5)/2.8 Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)) and RSS-Gen 8.9.

Ref. ANSI C63.10: 2013 section 4.1.4.2.2, 4.1.4.2.3, 6.6.4 & 11.12.2

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span: 1GHz – 18 GHz
 Reference Level: 80 dBuV
 Attenuation: 10 dB
 Sweep Time: Coupled
 Resolution Bandwidth: 1MHz
 Video Bandwidth: 3 MHz for peak, 1 KHz for average
 Detector: Peak

Terminate the access Point RF ports with 50 ohm loads.

Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)

Save 2 plots: 1) Average plot, Limit= 54dBuV/m @3m
 2) Peak plot, Limit = 74dBuV/m @3m

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands.

This report represents the worst case data for all supported operating modes and antennas. There are no measurable emissions above 18 GHz.

System Number	Description	Samples	System under test	Support equipment
2	EUT	S03	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S04	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	

See Appendix C for list of test equipment

B.1.A Transmitter Radiated Spurious Emissions-Average Worst Case

Frequency (MHz)	Mode	Data Rate (Mbps)	Spurious Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2412	Legacy CCK, 1 to 11 Mbps	11	51.2	54	2.8
	Non HT-20, 6 to 54 Mbps	6	51.5	54	2.5
	HT-20, m0-15	M0	51.5	54	2.5
2437	Legacy CCK, 1 to 11 Mbps	11	51.6	54	2.4
	Non HT-20, 6 to 54 Mbps	6	51.3	54	2.7
	HT-20, m0-15	M0	51.2	54	2.8
2462	Legacy CCK, 1 to 11 Mbps	11	51.4	54	2.6
	Non HT-20, 6 to 54 Mbps	6	51.2	54	2.8
	HT-20, m0-15	M0	51.2	54	2.8




Average Radiated Transmitter Spurs, 2412 MHz, 1-11 Mbps, (1-18GHz) Worst Case 20MHz BW



Average Radiated Transmitter Spurs, 2437 MHz, 1-11 Mbps, (1-18GHz) Worst Case 20MHz BW




Average Radiated Transmitter Spurs, 2462 MHz, 1-11 Mbps, (1-18GHz) Worst Case 20MHz BW




Average Radiated Transmitter Spurs, 2412 MHz, non HT20 6-54 Mbps, (1-18GHz) Worst Case 20MHz BW



Average Radiated Transmitter Spurs, 2437 MHz, non HT20 6-54 Mbps, (1-18GHz) Worst Case 20MHz BW




Average Radiated Transmitter Spurs, 2462 MHz, non HT20 6-54 Mbps, (1-18GHz) Worst Case 20MHz BW






Average Radiated Transmitter Spurs, 2412 MHz, HT20 M0-M15 Mbps, (1-18GHz) Worst Case 20MHz BW



Average Radiated Transmitter Spurs, 2437 MHz, HT20 M0-M15 Mbps, (1-18GHz) Worst Case 20MHz BW



Average Radiated Transmitter Spurs, 2462 MHz, HT20 M0-M15 Mbps, (1-18GHz) Worst Case 20MHz BW



Average Radiated Transmitter Spurs, All modes, (18-26.5GHz) Worst Case



No emissions seen above 18GHz. The plot above is representative of all modes tested

B.1.P Transmitter Radiated Spurious Emissions-Peak Worst Case

Frequency (MHz)	Mode	Data Rate (Mbps)	Spurious Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2412	Legacy CCK, 1 to 11 Mbps	11	64.2	74	9.8
	Non HT-20, 6 to 54 Mbps	6	64.1	74	9.9
	HT-20, m0-15	M0	63.4	74	10.6
2437	Legacy CCK, 1 to 11 Mbps	11	63.4	74	10.6
	Non HT-20, 6 to 54 Mbps	6	64.6	74	9.4
	HT-20, m0-15	M0	63.3	74	10.7
2462	Legacy CCK, 1 to 11 Mbps	11	64.4	74	9.6
	Non HT-20, 6 to 54 Mbps	6	63.9	74	10.1
	HT-20, m0-15	M0	64.0	74	10.0

Peak Radiated Transmitter Spurs, 2412 MHz, Legacy CCK 1 to 11 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, 2437 MHz, Legacy CCK 1 to 11 Mbps, (1-18GHz) Worst Case 20MHz BW




Peak Radiated Transmitter Spurs, 2462 MHz, Legacy CCK 1 to 11 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, 2412 MHz, non HT20 6 to 54 Mbps, (1-18GHz) Worst Case 20MHz BW




Peak Radiated Transmitter Spurs, 2437 MHz, non HT20 6 to 54 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, 2462 MHz, non HT20 6 to 54 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, 2412 MHz, HT20 M0 to M15 Mbps, (1-18GHz) Worst Case 20MHz BW




Peak Radiated Transmitter Spurs, 2437 MHz, HT20 M0 to M15 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, 2462 MHz, HT20 M0 to M15 Mbps, (1-18GHz) Worst Case 20MHz BW



Peak Radiated Transmitter Spurs, All modes, (18-26.5GHz) Worst Case



No emissions seen above 18GHz. The plot above is representative of all modes tested.

B.2 Receiver Spurious Emissions

RSS-Gen Receivers are required to comply with the limits of spurious emissions as set out in this section. Receiver emission measurements are to be performed as per the normative test method referenced in Section 3.

Radiated emissions which fall in the restricted bands, as defined in RSS-Gen section 8.10, must also comply with the radiated emission limits specified in RSS-Gen section 8.9.

For emissions at frequencies below 1 GHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. At frequencies above 1 GHz, measurements shall be performed using a linear average detector with a minimum resolution bandwidth of 1 MHz.

Ref. RSS-Gen section 8.9 & 8.10

ANSI C63.10: 2013 section 4.1.4.2.2, 4.1.4.2.3, 6.6.4 & 11.12.2

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span:	1GHz – 18 GHz
Reference Level:	80 dBuV
Attenuation:	10 dB
Sweep Time:	Coupled
Resolution Bandwidth:	1MHz
Video Bandwidth:	3MHz for Peak, 1 kHz for average
Detector:	Peak

Radiated emission measurements shall be performed with the receiver antenna connected to the receiver antenna terminals.

Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)

Save plot: 1) Average Plot (Vertical and Horizontal), Limit= 54dBuV/m @3m
2) Peak Plot (Vertical and Horizontal), Limit= 74dBuV/m @3m

This report represents the worst case data for all supported operating modes and antennas. There are no measurable emissions above 18 GHz.

System Number	Description	Samples	System under test	Support equipment
2	EUT	S03	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S04	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	

See Appendix C for list of test equipment

B.2.A Receiver Radiated Spurious Emissions (Average Measurements)

B.2.A.1 Radiated Receiver Spurs, All rates, All Mode, Average (1-18GHz) Horizontal & Vertical




B.2.P.2 Radiated Receiver Spurs, All rates, All Mode, Average (18-26.5GHz) Horizontal & Vertical




B.2.P Receiver Radiated Spurious Emissions (Peak Measurements)

B.2.P.1 Radiated Receiver Spurs, All rates, All Mode, Peak (1-18GHz) Horizontal & Vertical



B.2.P.2 Radiated Receiver Spurs, All rates, All Mode, Peak (18-26.5GHz) Horizontal & Vertical





B.3 Radiated Emissions 30MHz to 1GHz

15.205 / 15.209 / RSS-Gen / LP0002:3.10.1(5)/2.8 Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)) and RSS-Gen section 8.9.

Ref. ANSI C63.10: 2013 section 6.5

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span:	30MHz – 1GHz
Reference Level:	80 dBuV
Attenuation:	10 dB
Sweep Time:	Coupled
Resolution Bandwidth:	100kHz
Video Bandwidth:	300kHz
Detector:	Peak for Pre-scan, Quasi-Peak

Compliance shall be determined using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

Terminate the access Point RF ports with 50 ohm loads.

Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)

This report represents the worst case data for all supported operating modes and antennas.


System Number	Description	Samples	System under test	Support equipment
2	EUT	S03	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S04	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing: 01-Jun-16 to 26-Jun-16
Test Result : PASS	

See Appendix C for list of test equipment



Test Results



Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
903.813	9.34	2.5	22.55	34.39	Quasi Max	V	183	210	46	-11.61	Pass
34.556	12.48	0.45	17.9	30.82	Quasi Max	V	103	114	40	-9.18	Pass
46.975	13.4	0.52	9.24	23.17	Quasi Max	V	123	266	40	-16.83	Pass
1000	16.48	2.63	23.4	42.51	Quasi Max	V	118	55	54	-11.49	Pass
625	14.71	2.06	19.5	36.27	Quasi Max	V	104	62	46	-9.73	Pass
184.766	8.66	1.12	11.2	20.98	Quasi Max	V	198	72	43.5	-22.52	Pass
113.056	7.25	0.87	13.09	21.21	Quasi Max	V	157	329	43.5	-22.29	Pass

B.4 AC Conducted Emissions

FCC 15.207 (a) & RSS-Gen 8.8 / LP0002:2.3 Except when the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply, either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table in these sections. The more stringent limit applies at the frequency range boundaries.

Measurement Procedure
Accordance with ANSI C63.10:2013 section 6.2

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span:	150 KHz – 30 MHz
Attenuation:	10 dB
Sweep Time:	Coupled
Resolution Bandwidth:	9 KHz
Video Bandwidth:	30 KHz
Detector:	Quasi-Peak / Average

System Number	Description	Samples	System under test	Support equipment
2	EUT	S03	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Support	S04	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Tested By : Jose Aguirre	Date of testing:
Test Result : not tested	


The Radio is power over Ethernet (POE) only .

Test Setup Photo for Conducted Measurements




This is a dual band 2.4GHz / 5GHz device. All ports in this test set up photo are connected as all testing is automated. Section 2.6 of this test report given an overview of the different Tx antenna combinations used by this device.

Test Setup for Radiated Measurements



Title: Radiated Emissions Configuration Photograph



Title: Radiated Emissions Configuration Photograph

Test Setup for AC Conducted Emissions

Not tested, the Radio is power over Ethernet (POE) only .

Appendix C: List of Test Equipment Used to perform the test

Equip No	Model Manufacturer	Description	Last Cal	Next Cal	Tet Item
CIS051796	TTA1800-30-HG Miteq	SMA 18 GHz Pre-Amplifier	29-Sep-15	29-Sep-16	B.1, B.2
CIS035285	3117 ETS-Lindgren	Double Ridged Waveguide Horn Antenna	30-Sep-15	30-Sep-16	B.1, B.2
CIS008447	NSA 10m Chamber Cisco	NSA 10m Chamber	14-Oct-15	14-Oct-16	B.3
CIS045096	TH0118 Cisco	Mast Mount Preamplifier Array, 1-18GHz	4-Nov-15	4-Nov-16	B.1, B.2
CIS030652	JB1 Sunol Sciences	Combination Antenna, 30MHz-2GHz	4-Dec-15	4-Dec-16	B.3
CIS041929	iBTHP-5-DB9 Newport	5 inch Temp/RH/Press Sensor w/20ft cable	22-Dec-15	22-Dec-16	B.1, B.2, B.3
CIS043124	Above 1GHz Site Cal Cisco	Above 1GHz Cisp Site Verification	14-Jan-16	14-Jan-17	B.1, B.2
CIS047300	N9038A Agilent Technologies	MXE EMI Receiver 20Hz to 26.5 Ghz	28-Jan-16	28-Jan-17	B.1, B.2, B.3
CIS051642	Sucoflex 106PA Huber+Suhner	RF N Type Cable 8.5m	11-Feb-16	11-Feb-17	B.1, B.2, B.3
CIS030559	UFB311A-1-0950-504504 Micro-Coax	RF Coaxial Cable, to 18GHz, 95 in	15-Feb-16	15-Feb-17	B.1, B.2, B.3
CIS020975	UFB311A-0-1344-520520 Micro-Coax	RF Coaxial Cable, to 18GHz, 134.4 in	17-Feb-16	17-Feb-17	B.1, B.2, B.3
CIS051708	UFB293C-2-0840-300504 Micro-Coax	RF Coaxial SMA-N Type Cable	28-Jun-16	28-Jun-17	B.1, B.2, B.3
CIS044940	ESU40 Rohde & Schwarz	EMI Test Receiver, 20Hz-40GHz	2-Nov-15	2-Nov-16	B.1, B.2
CIS034075	RSG 2000 Schaffner	Reference Spectrum Generator, 1-18GHz	Cal Not Required	Cal Not Required	B.1, B.2
CIS041979	1840 Cisco	18-40GHz EMI Test Head/ Verification Fixture	13-Jul-15	13-Jul-16	B.1, B.2
CIS044940	ESU40 Rohde & Schwarz	EMI Test Receiver, 20Hz-40GHz	2-Nov-15	2-Nov-16	B.1, B.2,
CIS030652	JB1 Sunol Sciences	Combination Antenna, 30MHz-2GHz	4-Dec-15	4-Dec-16	B.3
CIS003003	83731B HP	Synthesized Signal Generator	29-Jan-16	29-Jan-17	B.1, B.2
CIS037236	50CB-015 JFW	GPIB Control Box			B.1, B.2

Test Equipment used for AC Mains Conducted Emissions					
Equip No	Model Manufacturer	Description	Last Cal	Next Cal	Test Item
					B.4

Test Equipment used for RF Conducted Tests					
Equip No	Model Manufacturer	Description	Last Cal	Next Cal	Test Item
CIS054666	RA08-S1S1-18 MegaPhase	SMA 18" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054667	RA08-S1S1-18 MegaPhase	SMA 18" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054668	RA08-S1S1-18 MegaPhase	SMA 18" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054669	RA08-S1S1-18 MegaPhase	SMA 18" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054686	NI PXI-2796 National Instruments	Plug-in switch module	6-Oct-15	6-Oct-16	A1 thru A7
CIS055166	RFLT4WDC40GK RF Lambda	4 Way Power Divider 40GHz	23-Nov-15	23-Nov-16	A1 thru A7
CIS054662	SF18-S1S1-36 MegaPhase	SMA 36" cable	24-Sep-15	24-Sep-16	A1 thru A7
CIS054656	BRC50705-02 Micro-Tronics	Band Reject Filter	24-Sep-15	24-Sep-16	A1 thru A7
CIS054655	BRC50704-02 Micro-Tronics	Notch Filter, SB:5.470-5.725GHz, to 12GHz	24-Sep-15	24-Sep-16	A1 thru A7
CIS054654	BRC50703-02 Micro-Tronics	Notch Filter, SB:5.150-5.350GHz, to 11GHz	24-Sep-15	24-Sep-16	A1 thru A7
CIS054653	BRM50702-02 Micro-Tronics	Notch Filter, SB:2.400-2.500GHz, to 18GHz	24-Sep-15	24-Sep-16	A1 thru A7
CIS054678	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054677	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054676	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054675	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054674	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054673	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054672	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054671	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054670	RA08-S1S1-12 MegaPhase	SMA 12" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054664	GC12-8181-16 MegaPhase	SMA 16" Cable	25-Sep-15	25-Sep-16	A1 thru A7
CIS054663	F120-S1S1-48 MegaPhase	SMA 48" Cable	25-Sep-15	25-Sep-16	A1 thru A7

CIS054686	NI PXI-2796 National Instruments	Plug-in switch module	6-Oct-15	6-Oct-16	A1 thru A7
CIS042005	BWS30W2+ Mini-Circuits	SMA 30dB Attenuator	16-Oct-15	16-Oct-16	A1 thru A7
CIS041995	BW-S6W2 Mini-Circuits	6dB Attenuator	16-Oct-15	16-Oct-16	A1 thru A7
CIS054695	D3C2060 Ditom	Circulator	20-Oct-15	20-Oct-16	A1 thru A7
CIS055146	RA08-S1S1-12 Megaphase	12" SMA Cable	17-Nov-15	17-Nov-16	A1 thru A7
CIS050721	N9030A Keysight	PXA Signal Analyzer	30-Mar-16	30-Mar-17	A1 thru A7
CIS054303	N5182B Keysight	MXG X-Series RF Vector Signal Generator	6-Apr-16	6-Apr-17	A1 thru A7
CIS055358	ZFSC-2-10G Mini-Circuits	Splitter	11-Apr-16	11-Apr-17	A1 thru A7
CIS055099	SMART2200RM2U Tripp-Lite	Power Supply	Cal Not Required		A1 thru A7
CIS055094	PXI-1042 National Instruments	Chassis	Cal Not Required		A1 thru A7

Appendix E: Abbreviation Key and Definitions

The following table defines abbreviations used within this test report.

Abbreviation	Description	Abbreviation	Description
EMC	Electro Magnetic Compatibility	°F	Degrees Fahrenheit
EMI	Electro Magnetic Interference	°C	Degrees Celsius
EUT	Equipment Under Test	Temp	Temperature
ITE	Information Technology Equipment	S/N	Serial Number
TAP	Test Assessment Schedule	Qty	Quantity
ESD	Electro Static Discharge	emf	Electromotive force
EFT	Electric Fast Transient	RMS	Root mean square
EDCS	Engineering Document Control System	Qp	Quasi Peak
Config	Configuration	Av	Average
CIS#	Cisco Number (unique identification number for Cisco test equipment)	Pk	Peak
Cal	Calibration	kHz	Kilohertz (1×10^3)
EN	European Norm	MHz	MegaHertz (1×10^6)
IEC	International Electro technical Commission	GHz	Gigahertz (1×10^9)
CISPR	International Special Committee on Radio Interference	H	Horizontal
CDN	Coupling/Decoupling Network	V	Vertical
LISN	Line Impedance Stabilization Network	dB	decibel
PE	Protective Earth	V	Volt
GND	Ground	kV	Kilovolt (1×10^3)
L1	Line 1	μ V	Microvolt (1×10^{-6})
L2	Line2	A	Amp
L3	Line 3	μ A	Micro Amp (1×10^{-6})
DC	Direct Current	mS	Milli Second (1×10^{-3})
RAW	Uncorrected measurement value, as indicated by the measuring device	μ S	Micro Second (1×10^{-6})
RF	Radio Frequency	μ S	Micro Second (1×10^{-6})
SLCE	Signal Line Conducted Emissions	m	Meter
Meas dist	Measurement distance	Spec dist	Specification distance
N/A or NA	Not Applicable	SL	Signal Line (or Telecom Line)
P	Power Line	L	Live Line
N	Neutral Line	R	Return
S	Supply	AC	Alternating Current

End