Label design:

.i|i.i|i.

Designed by Cisco (思科研发/Conçu par Cisco)





Apparatet må tilkopies jordet stikkontakt. Apparaten skall anslutas till jordat uttag. Latre on litrettävä suojakoskertimilla varustettuun nistorasiaan. Apparatets stikkonon Laite on littettava suojakoskettimilia varustettuun pistorasiaan. Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord.

Warning: Shock hazard - Do not open
AVIS: Risque de choc electrique - Ne pas ouvrir
警告: 电击危险-不要打开
This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference & (2) this device must accept any interference received, including interference that may cause undesired operation.

PID/VID: CS-ROOM-70-S

Made in Czech Fabriqué en La République tchèque

CMIIT ID: 123456789 CNC ID: X-12345 CAN ICES-3 (A)/NMB-3(A)



Label material:

UL standard: UL #: Manufacturer: Type: UL969 MH16584 Worldmark 339TXV-J1

<u>Label location:</u>

The rating label is placed on the system behind left cover, seen from front. The cover is held in place by magnets.

