



Dosimetric Assessment Test Report

for the

Cisco Systems

**Tested and Evaluated In Accordance With
FCC OET 65 Supplement C: 01-01**

Prepared for

Cisco Systems
170 West Tasman Drive
San Jose, CA 95134

Engineering Statement: The measurements shown in this report were made in accordance with the procedures specified in Supplement C to OET Bulletin 65 of the Federal Communications Commission (FCC) Guidelines [FCC 2001] and Industry Canada RSS-102 for uncontrolled exposure. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment evaluated is capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1999.



SAR Evaluation Certificate of Compliance

FCC ID: LDK7900001
APPLICANT: Cisco Systems

Applicant Name and Address: **Cisco Systems**
170 West Tasman Drive
San Jose, CA 95134

Test Location: MET Laboratories, Inc.
4855 Patrick Henry Dr. Bldg #6
Santa Clara, CA 95054
USA

EUT:	CP-7921G 802.11abg Phone					
Date of Receipt:	September 22, 2006					
Device Category:	FCC 15.407 and 15.247					
RF exposure environment:	Uncontrolled Exposure/General Population					
RF exposure category:	Portable					
Power supply:	3.7V 1400mAh Std Battery 3.7V 1840mAh Ext Battery					
Antenna:	Internal					
Production/prototype:	Prototype					
Modulation:	DTS					
Duty Cycle:	100%					
TX Range:	2400- 2483.5MHz 802.11 b	2400- 2483.5MHz 802.11 g	5150- 5250MHz 802.11 a	5250- 5350MHz 802.11 a	5470- 5725MHz 802.11 a	5725- 5825MHz 802.11 a
Maximum Peak RF Power Output	19.2dBm	22.6 dBm	15.0dBm	15.0dBm	14.8dBm	22.2dBm

Shawn McMillen
Senior Engineer





INTRODUCTION	4
SAR DEFINITION	4
DESCRIPTION OF DEVICE UNDER TEST (EUT)	5
SAR MEASUREMENT SYSTEM.....	6
MEASUREMENT SUMMARY	7
FLOW CHART OF THE RECOMMENDED PRACTICES AND PROCEDURES	14
DATA EVALUATION PROCEDURES	18
SYSTEM PERFORMANCE CHECK.....	20
SIMULATED EQUIVALENT TISSUES	21
SAR SAFETY LIMITS	22
ROBOT SYSTEM SPECIFICATIONS	23
1.1. Specifications.....	23
1.2. Data Acquisition Electronic (DAE) System:	23
1.3. Phantom(s):	23
SAR Measurement System	24
1.4. RX90BL Robot	24
1.5. Robot Controller	24
1.6. Light Beam Switch	24
1.7. Data Acquisition Electronics	24
1.8. Electro-Optical Converter (EOC).....	25
1.9. Measurement Server	25
1.10. Dosimetric Probe	25
1.11. SAM Phantom.....	25
1.12. Planar Phantom	25
1.13. Validation Planar Phantom	25
1.14. Device Holder	26
1.15. System Validation Kits	26
TEST EQUIPMENT LIST.....	27
MEASUREMENT UNCERTANTIES.....	28
REFERENCES	30
EUT PHOTOS	31
TEST SET-UP.....	37
APPENDIX A - SAR MEASUREMENT DATA.....	43
APPENDIX B - SYSTEM PERFORMANCE CHECK	44
APPENDIX C – PROBE CALIBRATION CERTIFICATE	45
APPENDIX D – DIPOLE CALIBRATION CERTIFICATE	46
APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS	47
APPENDIX F – PHANTOM CERTIFICATE OF CONFORMITY	48



INTRODUCTION

This measurement report demonstrates that the Cisco Systems CP-7921G 802.11abg Phone FCC ID: LDK7900001 described within this report complies with the Specific Absorption Rate (SAR) RF exposure requirements specified in ANSI/IEEE Std. C95.1-1999 and FCC 47 CFR §2.1093 for the Uncontrolled Exposure/General population environment. The test procedures described in FCC OET Bulletin 65, Supplement C, Edition 01-01 and IEEE Std. 1528 - 2003 were employed.

A description of the device under test, device operating configuration and test conditions, measurement and site description, methodology and procedures used in the evaluation, equipment used, detailed summary of the test results and the various provisions of the rules are included in this dosimetric assessment test report.

SAR DEFINITION

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1.1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1.1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \sigma E^2 / \rho$$

where:

- σ - conductivity of the tissue - simulant material (S/m)
- ρ - mass density of the tissue - simulant material (kg/m³)
- E - Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.




DESCRIPTION OF DEVICE UNDER TEST (EUT)

Applicant:	Cisco Systems		
Description of Test Item:	CP-7921G 802.11abg Phone		
Supply Voltage:	3.7V 1400mAh Std Battery 3.7V 1840mAh Ext Battery		
Antenna Type(s) Tested:	Internal		
Accessories:	Item	Part Number	Model Number
	Belt Clip	74-4879-01	CP-Holster-7921G
	Leather Carry Case	74-3861-01	CP-Case-7921G
	Shoulder Holster	74-4878-01	CP-Shoulder-7921G
	Locking Cable	74-4880-01	CP-Lock-7921G
Modes of Operation:	DSSS and OFDM		
Duty Cycle Tested:	100%		
Maximum SAR Measured:	2400-2483.5MHz b mode	0.207mW/g Head	0.102mW/g Body
	2400-2483.5MHz g mode	0.228mW/g Head	0.107mW/g Body
	5150-5250MHz a mode	0.510mW/g Head	0.372mW/g Body
	5470-5725MHz a mode	0.426mW/g Head	0.381mW/g Body
	5250-5350MHz a mode	0.491mW/g Head	0.492mW/g Body
	5725-5825MHz a mode	0.472mW/g Head	0.356mW/g Body
Application Type:	Certification		
Exposure Category:	Uncontrolled Exposure/General Population		
FCC and IC Rule Part(s):	FCC 47 CFR §2.1093, Part 15.407 and 15.247		
Standards:	IEEE Std. 1528-2003, FCC OET Bulletin 65, Supplement C, Edition 01-01		



SAR MEASUREMENT SYSTEM

MET Laboratories, Inc SAR measurement facility utilizes the DASY4 Professional Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland for performing SAR compliance tests. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). The Cell controller system contain the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit.



Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



MEASUREMENT SUMMARY

HEAD SAR MEASUREMENT RESULTS (2450MHz) Band									
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	EUT Test Position	Measured SAR 1g (W/kg)
2437.0	Mid	DSSS	1 Mbps	19.2	19.1	Standard	Right Head	Touch	0.165
2437.0	Mid	DSSS	1 Mbps	19.2	19.1	Standard	Right Head	Tilt	0.154
2437.0	Mid	OFDM	6 Mbps	22.6	22.6	Standard	Right Head	Touch	0.171
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Standard	Right Head	Tilt	0.171
2437.0	Mid	OFDM	6 Mbps	22.6	22.6	Extended	Right Head	Touch	0.172
2437.0	Mid	DSSS	1 Mbps	19.2	19.1	Standard	Left Head	Touch	0.197
2437.0	Mid	DSSS	1 Mbps	19.2	19.1	Standard	Left Head	Tilt	0.207
2437.0	Mid	OFDM	6 Mbps	22.6	22.6	Standard	Left Head	Touch	0.207
2437.0	Mid	OFDM	6 Mbps	22.6	22.6	Standard	Left Head	Tilt	0.232
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Extended	Left Head	Tilt	0.228
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population									
Measured Mixture Type		2450 MHz Head			Date Tested		Sept 27, 2006		
Dielectric Constant ϵ_r		IEEE Target		Measured		Duty Cycle		100%	
		39.2		38.8		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)		IEEE Target		Measured		Fluid Temperature (C)		21.7	
		1.80		1.83		Fluid Depth		$\geq 15\text{cm}$	



BODY SAR MEASUREMENT RESULTS (2450MHz) Band										
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	Accessory	Position	Measured SAR 1g (W/kg)
2437.0	Mid	DSSS	1 Mbps	19.2	19.2	Standard	Planar	Plastic Holster	Body	0.102
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Standard	Planar	Plastic Holster	Body	0.107
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Extended	Planar	Plastic Holster	Body	0.104
2437.0	Mid	DSSS	1 Mbps	19.2	19.0	Standard	Planar	Leather Holster	Body	0.071
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Standard	Planar	Leather Holster	Body	0.0737
2437.0	Mid	OFDM	6 Mbps	22.6	22.5	Extended	Planar	Leather Holster	Body	0.0717
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population										
Measured Mixture Type			2450 MHz Body				Date Tested		Sept 27, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured		Duty Cycle		100%	
			52.7		54.1		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured		Fluid Temperature (C)		21.7	
			1.95		2.04		Fluid Depth		≥ 15 cm	



HEAD SAR MEASUREMENT RESULTS (5150-5250MHz) Band									
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	EUT Test Position	Measured SAR 1g (W/kg)
5200.0	Mid	OFDM	6 Mbps	15.0	14.9	Standard	Right Head	Touch	0.510
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Right Head	Tilt	0.372
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Left Head	Touch	0.379
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Left Head	Tilt	0.442
5200.0	Mid	OFDM	6 Mbps	15.0	14.8	Extended	Right Head	Touch	0.437
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population									
Measured Mixture Type			5200 MHz Head			Date Tested		Sept 21, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured	Duty Cycle		100%	
			36.0		37.2	Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured	Fluid Temperature (C)		21.7	
			4.66		4.50	Fluid Depth		$\geq 15\text{cm}$	

HEAD SAR MEASUREMENT RESULTS (5250-5350MHz) Band									
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	EUT Test Position	Measured SAR 1g (W/kg)
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Right Head	Touch	0.426
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Right Head	Tilt	0.368
5300.0	Mid	OFDM	6 Mbps	15.0	14.9	Standard	Left Head	Touch	0.391
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Left Head	Tilt	0.378
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Extended	Right Head	Touch	0.422
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population									
Measured Mixture Type			5300 MHz Head			Date Tested		Sept 21, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured	Duty Cycle		100%	
			35.8		37.1	Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured	Fluid Temperature (C)		21.7	
			4.76		4.62	Fluid Depth		$\geq 15\text{cm}$	



HEAD SAR MEASUREMENT RESULTS (5470-5725MHz) Band									
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	EUT Test Position	Measured SAR 1g (W/kg)
5600.0	Mid	OFDM	6 Mbps	14.8	14.8	Standard	Right Head	Touch	0.491
5600.0	Mid	OFDM	6 Mbps	14.8	14.8	Standard	Right Head	Tilt	0.473
5600.0	Mid	OFDM	6 Mbps	14.8	14.7	Standard	Left Head	Touch	0.445
5600.0	Mid	OFDM	6 Mbps	14.8	14.8	Standard	Left Head	Tilt	0.465
5600.0	Mid	OFDM	6 Mbps	14.8	14.7	Extended	Right Head	Touch	0.486
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population									
Measured Mixture Type		5600 MHz Head				Date Tested		Sept 21, 2006	
Dielectric Constant ϵ_r		IEEE Target		Measured		Duty Cycle		100%	
		35.5		37.2		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)		IEEE Target		Measured		Fluid Temperature (C)		21.7	
		5.06		5.04		Fluid Depth		$\geq 15\text{cm}$	

HEAD SAR MEASUREMENT RESULTS (5725-5825MHz) Band									
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	EUT Test Position	Measured SAR 1g (W/kg)
5765.0	Mid	OFDM	6 Mbps	22.2	22.1	Standard	Right Head	Touch	0.472
5765.0	Mid	OFDM	6 Mbps	22.2	22.2	Standard	Right Head	Tilt	0.354
5765.0	Mid	OFDM	6 Mbps	22.2	22.2	Standard	Left Head	Touch	0.362
5765.0	Mid	OFDM	6 Mbps	22.2	22.1	Standard	Left Head	Tilt	0.385
5765.0	Mid	OFDM	6 Mbps	22.2	22.2	Extended	Right Head	Touch	0.468
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population									
Measured Mixture Type		5800 MHz Head				Date Tested		Sept 21, 2006	
Dielectric Constant ϵ_r		IEEE Target		Measured		Duty Cycle		100%	
		35.3		37.0		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)		IEEE Target		Measured		Fluid Temperature (C)		21.7	
		5.27		5.15		Fluid Depth		$\geq 15\text{cm}$	



BODY SAR MEASUREMENT RESULTS (5150-5250MHz) Band										
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	Accessory	Position	Measured SAR 1g (W/kg)
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Planar	Plastic Holster	Body	0.372
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Planar	Leather Holster	Body	0.218
5200.0	Mid	OFDM	6 Mbps	15.0	15.0	Extended	Planar	Plastic Holster	Body	0.365
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population										
Measured Mixture Type			5200 MHz Body				Date Tested		Sept 22, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured		Duty Cycle		100%	
			49.0		49.5		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured		Fluid Temperature (C)		21.7	
			5.30		5.40		Fluid Depth		$\geq 15\text{cm}$	

BODY SAR MEASUREMENT RESULTS (5350-5350MHz) Band										
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	Accessory	Position	Measured SAR 1g (W/kg)
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Planar	Plastic Holster	Body	0.381
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Standard	Planar	Leather Holster	Body	0.202
5300.0	Mid	OFDM	6 Mbps	15.0	15.0	Extended	Planar	Plastic Holster	Body	0.350
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population										
Measured Mixture Type			5300 MHz Body				Date Tested		Sept 22, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured		Duty Cycle		100%	
			48.8		49.2		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured		Fluid Temperature (C)		21.7	
			5.41		5.58		Fluid Depth		$\geq 15\text{cm}$	



BODY SAR MEASUREMENT RESULTS (5470-5725MHz) Band										
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	Accessory	Position	Measured SAR 1g (W/kg)
5600.0	Mid	OFDM	6 Mbps	14.8	14.8	Standard	Planar	Plastic Holster	Body	0.492
5600.0	Mid	OFDM	6 Mbps	14.8	14.7	Standard	Planar	Leather Holster	Body	0.258
5600.0	Mid	OFDM	6 Mbps	14.8	14.7	Extended	Planar	Plastic Holster	Body	0.472
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population										
Measured Mixture Type			5600 MHz Body				Date Tested		Sept 22, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured		Duty Cycle		100%	
			48.4		48.4		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured		Fluid Temperature (C)		21.7	
			5.76		5.94		Fluid Depth		$\geq 15\text{cm}$	

BODY SAR MEASUREMENT RESULTS (5725-5825MHz) Band										
Freq (MHz)	Chan	Test Mode	Data Rate	Cond. Pwr. Before (dBm)	Cond. Pwr. After (dBm)	Battery Type	Phantom Section	Accessory	Position	Measured SAR 1g (W/kg)
5765.0	Mid	OFDM	6 Mbps	22.2	22.1	Standard	Planar	Plastic Holster	Body	0.356
5765.0	Mid	OFDM	6 Mbps	22.2	22.1	Standard	Planar	Leather Holster	Body	0.234
5765.0	Mid	OFDM	6 Mbps	22.2	22.2	Extended	Planar	Plastic Holster	Body	0.344
ANSI/IEEE C95.1 1992 – SAFETY LIMIT BODY: 1.6 W/kg (averaged over 1 gram) Spatial Peak – Uncontrolled Exposure/General Population										
Measured Mixture Type			5800 MHz Body				Date Tested		Sept 22, 2006	
Dielectric Constant ϵ_r			IEEE Target		Measured		Duty Cycle		100%	
			48.2		48.0		Ambient Temperature (C)		22.6	
Conductivity σ (mho/m)			IEEE Target		Measured		Fluid Temperature (C)		21.7	
			6.00		6.18		Fluid Depth		$\geq 15\text{cm}$	




DETAILS OF SAR EVALUATION

The Cisco Systems CP-7921G 802.11abg Phone was determined to be compliant for localized Specific Absorption Rate based on the test provisions and conditions described below.

1. The EUT was tested for both head and body SAR. For the head SAR both touch and tilt positions were measured on the left and right side of the SAM phantom. The position which produced the highest SAR was re-measured with the extended battery. For the body worn position the EUT was placed into the two different holsters supplied with the EUT and was placed at a separation distance of 0.0cm from the phantom surface.
2. The EUT was placed into a test mode using Cisco's protocol software.
3. The SAR evaluations were performed with a fully charged battery.
4. The EUT's RF power was measured before and after each SAR test using an Anritsu Power Meter.
5. The dielectric parameters of the simulated body fluid were measured prior to the evaluation using an 85070D Dielectric Probe Kit and an 8722D Network Analyzer.
6. The fluid and air temperature was measured prior to and after each SAR evaluation to ensure the temperature remained within ± 2 deg C of the temperature of the fluid when the dielectric properties were measured.
7. During the SAR evaluations if a distribution produced several hotspots over the course of the area scan, each hotspot was evaluated separately.

FLOW CHART OF THE RECOMMENDED PRACTICES AND PROCEDURES



EAR Reference Point

Figure 12.1 shows the front, back and side views of the SAM Twin Phantom. The point M is the reference point for the center of the mouth, LE is the left ear reference point (ERP), and RE is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 12.2. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting. Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning.



Figure 12.1
Front, back and side view of SAM Twin Phantom




Figure 12.2
Side view of ERPs

HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the test device reference point located along the vertical centerline on the front of the device aligned to the ear reference point (See Fig. 12.3). The test device reference point was then located at the same level as the center of the ear reference point. The test device was positioned so that the vertical centerline was bisecting the front surface of the handset at its top and bottom edges, positioning the ear reference point on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 12.3
Handset Vertical Center & Horizontal Line Reference Points




POSITIONING FOR CHEEK/TOUCH

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom, such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.
2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 12.5)



Front, Side and Top View of Cheek/Touch Position



Side view with relevant markings

POSITIONING FOR EAR/15 DEGREE TILT

With the test device aligned in the Cheek/Touch Position:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head.



Front, Side and Top View of Ear/15 Tilt Position



EVALUATION PROCEDURES

The evaluation was performed in the applicable area of the phantom depending on the type of device being tested.

- (i) For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
- (ii) For body-worn and face-held devices a planar phantom was used.

The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 10mm x 10mm.

An area scan was determined as follows:

Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.

A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

A 1g and 10g spatial peak SAR was determined as follows:

For frequencies $\leq 4.5\text{GHz}$ a 32mm x 32mm x 34mm (7x7x7 data points) zoom scan was assessed at the position where the greatest V/m was detected. For frequencies $\geq 4.5\text{GHz}$ a 28mm x 28mm x 24mm (7x7x9 data points) zoom scan was assessed at the position where the greatest V/m was detected. The data at the surface was extrapolated since the distance from the probes sensors to the surface is 3.9cm. A least squares fourth-order polynomial was used to generate points between the probe detector and the inner surface of the phantom.

Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).

Z-Scan was determined as follows:

The Z-scan measures points along a vertical straight line. The line runs along a line normal to the inner surface of the phantom surface.



DATA EVALUATION PROCEDURES

The DASY4 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe Parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion Factor	$ConvF_i$
	- Dipole Compression Point	dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC - transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With V_i = Compensated signal of channel i (i = x, y, z)
 U_i = Input signal of channel i (i = x, y, z)
 cf = Crest factor of exciting field (DASY parameter)
 dcp_i = Diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E - fieldprobes : } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H - fieldprobes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = Compensated signal of channel i (i = x, y, z)
 $Norm_i$ = Sensor sensitivity of channel i (i = x, y, z)
 $\mu V/(V/m)^2$ for E-field probes
 $ConvF$ = Sensitivity enhancement in solution
 a_{ij} = Sensor sensitivity factors for H-field probes
 f = Carrier frequency (GHz)
 E_i = Electric field strength of channel i in V/m
 H_i = Magnetic field strength of channel i in A/m



The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = Equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m



Test Date	Fluid Type (MHz)	SAR 1g (W/kg)		Permittivity Constant ϵ_r		Conductivity σ (mho/m)		Ambient Temp. (C)	Fluid Temp. (C)	Fluid Depth (cm)
		Calibrated Target	Measured	IEEE Target	Measured	IEEE Target	Measured			
09/21/06	5200 Head	89.2±5%	85.6	36.0 ±5%	37.2	4.66±10%	4.50	22.0	21.6	≥15
09/21/06	5500 Head	83.6±5%	81.2	35.6 ±5%	37.2	4.96±10%	4.95	22.0	21.6	≥15
09/21/06	5800 Head	82.0±5%	79.6	35.3 ±5%	37.0	5.27±10%	5.15	22.0	21.6	≥15
09/22/06	5200 Body	68.0±5%	68.4	49.0 ±5%	48.6	5.30±10%	5.33	22.0	21.6	≥15
09/22/06	5500 Body	67.2±5%	68.8	48.6 ±5%	47.5	6.00±10%	6.18	22.0	21.6	≥15
09/22/06	5800 Body	64.8±5%	65.2	48.6 ±5%	47.5	6.00±10%	6.18	22.0	21.6	≥15
09/27/06	2450 Head	58.4±5%	57.6	39.2 ±5%	40.6	1.80±10%	1.88	22.6	21.7	>15



SIMULATED EQUIVALENT TISSUES

Simulated Tissue Mixture (Proprietary)	
Ingredient	5-6GHz Head and Body
Water	60-78%
Salt	0.4-3.0%
Emulsifiers	0.5-15.0
Mineral Oil	11.0-36.0

Simulated Tissue Mixture		
Ingredient	2450MHz Head	2450MHz Body
Water	46.7%	73.3%
DGMBE	53.3%	26.7%



SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

Notes:

1. Uncontrolled exposure environments are locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled exposure environments are locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.



ROBOT SYSTEM SPECIFICATIONS

1.1. SPECIFICATIONS

Positioner:

Robot:	Staubli Unimation Corp. Robot Model: RX90
Repeatability:	0.02 mm
No. of axis:	6

1.2. DATA ACQUISITION ELECTRONIC (DAE) SYSTEM:

Cell Controller

Processor:	Compaq Evo
	Clock Speed: 2.4 GHz
	Operating System: Windows XP Professional

Data Converter

Features:	Signal Amplifier, multiplexer, A/D converter, and control logic
Software:	DASY4 software
Connecting Lines:	Optical downlink for data and status info. Optical uplink for commands and clock

Dasy4 Measurement Server

Function:	Real-time data evaluation for field measurements and surface detection
Hardware:	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections:	COM1, COM2, DAE, Robot, Ethernet, Service Interface

E-Field Probe

Model:	ET3DV6
Serial No.:	1793
Construction:	Triangular core fiber optic detection system
Frequency:	10 MHz to 6 GHz
Linearity:	± 0.2 dB (30 MHz to 3 GHz)

EX-Probe

Model:	EX3DV3
Serial No.	3511
Construction:	Triangular core
Frequency:	10 MHz to > 6 GHz
Linearity:	± 0.2 dB (30 MHz to 3 GHz)
Tip diameter:	2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Note:	Only probe which enables compliance testing for frequencies up to 6GHz with precision of better 30%.


1.3. PHANTOM(S):

Validation & Evaluation Phantom

Type:	SAM V4.0C
Shell Material:	Fiberglass
Thickness:	2.0 ± 0.1 mm
Volume:	Approx. 20 liters



SAR Measurement System



Measurement System Diagram

1.4. RX90BL ROBOT

The Stäubli RX90BL Robot is a standard high precision 6-axis robot with an arm extension for accommodating the data acquisition electronics (DAE).

1.5. ROBOT CONTROLLER

The CS7MB Robot Controller system drives the robot motors. The system consists of a power supply, robot controller, and remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.

1.6. LIGHT BEAM SWITCH

The Light Beam Switch (Probe alignment tool) allows automatic "tooling" of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured as well as the probe length and the horizontal probe offset. The software then corrects all movements, so that the robot coordinates are valid for the probe tip. The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



1.7. DATA ACQUISITION ELECTRONICS

The Data Acquisition Electronics consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain switching multiplexer, a fast 16-bit A/D converter and a command decoder and control logic unit. Some of the tasks the DAE performs are signal amplification, signal multiplexing, A/D conversion, and offset measurements. The DAE also contains the mechanical probe-mounting device, which contains two different sensor systems for frontal and sideways probe contacts used for probe collision detection and mechanical surface detection for controlling the distance between the probe and the inner surface of the phantom shell. Transmission from the DAE to the measurement server, via the EOC, is through an optical downlink for data and status information as well as an optical uplink for commands and the clock.





1.8. ELECTO-OPTICAL CONVERTER (EOC)

The Electro-Optical Converter performs the conversion between the optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC connects to, and transfers data to, the DASY4 measurement server. The EOC also contains the fiber optical surface detection system for controlling the distance between the probe and the inner surface of the phantom shell.



1.9. MEASUREMENT SERVER

The Measurement Server performs time critical tasks such as signal filtering, all real-time data evaluation for field measurements and surface detection, controls robot movements, and handles safety operation. The PC-operating system cannot interfere with these time critical processes. A watchdog supervises all connections, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements.



1.10. DOSIMETRIC PROBE

Dosimetric Probe is a symmetrical design with triangular core that incorporates three 3 mm long dipoles arranged so that the overall response is close to isotropic. The probe sensors are covered by an outer protective shell, which is resistant to organic solvents i.e. glycol. The probe is equipped with an optical multi-fiber line, ending at the front of the probe tip, for optical surface detection. This line connects to the EOC box on the robot arm and provides automatic detection of the phantom surface. The optical surface detection works in transparent liquids and on diffuse reflecting surfaces with a repeatability of better than ± 0.1 mm.



1.11. SAM PHANTOM

The SAM (Specific Anthropomorphic Mannequin) twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm) integrated into a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left hand, right hand phone usage as well as body mounted usage at the flat phantom region. The flat section is also used for system validation and the length and width of the flat section are at least $0.75 \lambda_0$ and $0.6 \lambda_0$ respectively at frequencies of 824 MHz and above (λ_0 = wavelength in air).

Reference markings on the phantom top allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. white cover is provided to cover the phantom during off-periods preventing water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible. The phantom is filled with a tissue simulating liquid to a depth of at least 15 cm at each ear reference point. The bottom plate of the wooden table contains three pair of bolts for locking the device holder.



A

1.12. PLANAR PHANTOM

The planar phantom is constructed of Plexiglas material with a 2.0 mm shell thickness for face-held and body-worn SAR evaluations of handheld radio transceivers. The planar phantom is mounted on the wooden table of the DASY4 system.



1.13. VALIDATION PLANAR PHANTOM

The validation planar phantom is constructed of Plexiglas material with a 6.0 mm shell thickness for system validations at 450MHz and below. The validation planar phantom is mounted on the wooden table of the DASY4 system.





1.14. DEVICE HOLDER

The device holder is designed to cope with the different measurement positions in the three sections of the SAM phantom given in the standard. It has two scales, one for device rotation (with respect to the body axis) and one for device inclination (with respect to the line between the ear openings). The rotation center for both scales is the ear opening, thus the device needs no repositioning when changing the angles. The plane between the ear openings and the mouth tip has a rotation angle of 65° .

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



The dielectric properties of the liquid conform to all the tabulated values [2-5]. Liquids are prepared according to Annex A and dielectric properties are measured according to Annex B.

1.15. SYSTEM VALIDATION KITS

Power Capability: $> 100 \text{ W}$ ($f < 1\text{GHz}$); $> 40 \text{ W}$ ($f > 1\text{GHz}$)

Construction: Symmetrical dipole with $1/4$ balun Enables measurement of feed point impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

Frequency: 300, 450, 835, 1900, 2450 MHz, 5-6GHz

Return loss: $>20 \text{ dB}$ at specified validation position

Dimensions:

300 MHz Dipole:	Length: 396mm; Overall Height:430 mm; Diameter: 6 mm
450 MHz Dipole:	Length: 270 mm; Overall Height: 347 mm; Diameter: 6 mm
835 MHz Dipole:	Length: 161 mm; Overall Height: 270 mm; Diameter: 3.6 mm
1900 MHz Dipole:	Length: 68 mm; Overall Height: 219 mm; Diameter: 3.6 mm
2450 MHz Dipole:	Length: 51.5 mm; Overall Height: 300 mm; Diameter: 3.6 mm
5-6GHz Dipole:	Length: 26.0 mm; Overall Height: 170 mm; Diameter: 3.6 mm





TEST EQUIPMENT LIST

Test Equipment	Serial Number	Calibration Date
DASY4 System Robot ETVDV6 EX3DV3 DAE3 300MHz Dipole 450MHz Dipole 835MHz Dipole 1900MHz Dipole 2450MHz Dipole 5-6GHz Dipole SAM Phantom V4.0C EUT Planar Phantom Validation Phantom	FO3/SX19A1/A/01 1793 3511 584 003 004 493 001 002 001 N/A N/A N/A	N/A Sept 2005 Jan 2006 Sept 2005 Dec 2005 Dec 2005 Sept 2005 Feb 2006 Feb 2006 Aug 2006 N/A N/A N/A
85070D Dielectric Probe Kt	N/A	N/A
83650B Signal Generator	3844A00910	June 2006
HP E4418B Power Meter	GB40205140	June 2006
HP 8482A Power Sensor	2607A11286	June 2006
HP 8722D Vector Network Analyzer	3S36140188	March 2006
Anritsu Power Meter ML2488A	6K00001832	June 2006
Anritsu Power Sensor	030864	Jan 2006
Mini-Circuits Power Amplifier	D111903#8	N/A



MEASUREMENT UNCERTAINTIES

UNCERTAINTY ASSESSMENT 300MHz-3GHz

Error Description	Tol. ±%	Prob. Dist.	Div.	c_i 1g	c_i 10g	Std Unc ±% (1g)	Std Unc ±% (10g)	v_i or v_{eff}
Measurement System								
Probe calibration	4.8	N	1	1	1	4.8	4.8	∞
Axial isotropy of the probe	4.7	R	√3	0.7	0.7	1.9	1.9	∞
Spherical isotropy of the probe	9.6	R	√3	0.7	0.7	3.9	3.9	∞
Boundary effects	1.0	R	√3	1	1	4.8	4.8	∞
Probe linearity	4.7	R	√3	1	1	2.7	2.7	∞
Detection limit	1.0	R	√3	1	1	0.6	0.6	∞
Readout electronics	1.0	N	1	1	1	1.0	1.0	∞
Response time	0.8	R	√3	1	1	0.5	0.5	∞
Integration time	2.6	R	√3	1	1	0.8	0.8	∞
RF ambient conditions	3.0	R	√3	1	1	0.43	0.43	∞
Mech. constraints of robot	0.4	R	√3	1	1	0.2	0.2	∞
Probe positioning	2.9	R	√3	1	1	1.7	1.7	∞
Extrapolation & integration	1.0	R	√3	1	1	2.3	2.3	∞
Test Sample Related								
Device positioning	2.9	N	1	1	1	2.23	2.23	145
Device holder uncertainty	3.6	N	1	1	1	5.0	5.0	5
Power drift	5.0	R	√3			2.9	2.9	∞
Phantom and Setup								
Phantom uncertainty	4.0	R	√3	1	1	2.3	2.3	∞
Liquid conductivity (target)	5.0	R	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (measured)	2.5	N	1	0.64	0.43	1.6	1.1	∞
Liquid permittivity (target)	5.0	R	√3	0.6	0.5	1.7	1.4	∞
Liquid permittivity (measured)	2.5	N	1	0.6	0.5	1.5	1.2	∞
Combined Standard Uncertainty (k=1)		RSS				10.3	10.0	
Expanded Uncertainty (k=2) 95% Confidence Level						20.6	20.1	

Table: Worst-case uncertainty for DASY4 assessed according to IEEE P1528.

The budget is valid for the frequency range 300MHz to 3GHz and represents a worst-case analysis.



UNCERTAINTY ASSESSMENT 3-6GHz

Error Description	Tol. ±%	Prob. Dist.	Div.	c_i 1g	c_i 10g	Std Unc ±% (1g)	Std Unc ±% (10g)	v_i or v_{eff}
Measurement System								
Probe calibration	4.8	N	1	1	1	8.3	8.3	∞
Axial isotropy of the probe	4.7	R	√3	0.7	0.7	1.9	1.9	∞
Spherical isotropy of the probe	9.6	R	√3	0.7	0.7	3.9	3.9	∞
Boundary effects	1.0	R	√3	1	1	0.6	0.6	∞
Probe linearity	4.7	R	√3	1	1	2.7	2.7	∞
Detection limit	1.0	R	√3	1	1	0.6	0.6	∞
Readout electronics	1.0	N	1	1	1	1.0	1.0	∞
Response time	0.8	R	√3	1	1	0.5	0.5	∞
Integration time	2.6	R	√3	1	1	1.5	1.5	∞
RF ambient conditions	3.0	R	√3	1	1	1.7	1.7	∞
Mech. constraints of robot	0.4	R	√3	1	1	0.2	0.2	∞
Probe positioning	2.9	R	√3	1	1	1.7	1.7	∞
Extrapolation & integration	1.0	R	√3	1	1	0.6	0.6	∞
Test Sample Related								
Device positioning	2.9	N	1	1	1	2.9	2.9	145
Device holder uncertainty	3.6	N	1	1	1	3.6	3.6	5
Power drift	5.0	R	√3			2.9	2.9	∞
Phantom and Setup								
Phantom uncertainty	4.0	R	√3	1	1	2.3	2.3	∞
Liquid conductivity (target)	5.0	R	√3	0.64	0.43	1.8	1.2	∞
Liquid conductivity (measured)	2.5	N	1	0.64	0.43	1.6	1.1	∞
Liquid permittivity (target)	5.0	R	√3	0.6	0.5	1.7	1.4	∞
Liquid permittivity (measured)	2.5	N	1	0.6	0.5	1.5	1.2	∞
Combined Standard Uncertainty (k=1)		RSS				12.3	12.1	
Expanded Uncertainty (k=2)						24.6	24.2	
95% Confidence Level								

Table: Worst-case uncertainty for DASY4 assessed according to IEEE P1528.

The budget is valid for the frequency range 3-6GHz and represents a worst-case analysis.

REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Aug. 1992.
- [3] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [5] IEEE Standards Coordinating Committee 34, IEEE 1528 (August 2003), Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb.1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz , IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz , IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric Evaluation Of Mobile Communications Equipment With Known Precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz - 300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgen ssische Technische Hoschschule Z rich, Dosimetric Evaluation of the Cellular Phone.
- [20] Federal Communications Commission, Radiofrequency radiation exposure evaluation: portable devices, Rule Part 47 CFR 2.1093: 1999.
- [21] Health Canada, Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz , Safety Code 6.
- [22] Industry Canada, Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields, Radio Standards Specification RSS-102 Issue 1 (Provisional): September 1999.



EUT PHOTOS



Front of EUT



Back of EUT



EUT Label



ETU in Leather Holster



Side View of Leather Holster with belt clip



Standard and extended batteries inside View



Standard and extended batteries outside View



Leather strap and belt clip



Leather Strap and Belt Clip Body Side Position



Leather Strap and Belt Clip side view



Plastic Holster Front and Rear View



EUT Mounted in Plastic Holster


TEST SET-UP



Right Hand Touch Position




Right Hand Tilt Position



Left Hand Touch Position



Left Hand Tilt Position



Body Worn Position with Leather Holster



Body Worn Position with Plastic Holster



APPENDIX A - SAR MEASUREMENT DATA



APPENDIX B - SYSTEM PERFORMANCE CHECK



APPENDIX C – PROBE CALIBRATION CERTIFICATE



APPENDIX D – DIPOLE CALIBRATION CERTIFICATE



APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS



APPENDIX F – PHANTOM CERTIFICATE OF CONFORMITY