

	5	4	3		2			
				REV	REVISION DESCRIPTION	ECO	APPRO MECH	
				01 P4 BUILD 02 ART WORK			SG	S N S N
					CODE ADDED, SPACE ADDED F E SPACE REMOVED.NOTES UPD	OR CLEI ATED		SN
	CLASS I LASER							
D C	OLOR CISCO SAFETY YELLOW							
B—		VENDOR ID						
		PLACEHOLDER						
	VCCI-B							
			CM-I					
		Y						
-	4							
		ELICTROSTATIC SUMMITVE DEVI						
	FCC CLASS B—/	NOTES: (L	JNLESS OTHERWISE SPECIF	FIED)				
	SYMBOL AND LAI	DEL FOR	IS A COMPUTER GENERATED DE IN THE MASTER DATABA) DOCUMENT. AL ASE ONLY.	L CHANGES MUST			ŀ
	ELECTROSTATIC SE		CISCO SANS REGULAR, 4	PT & 6 PT.				
BA	CKGROUND COLOR CISCO SAFETY	YELLOW 3. LABEL Should	STOCK, ADHESIVE & PRIM D BE -40°CTO +85°C.	NTING TEMPERAT	TURE RANGE			
		4. SHALL	MEET ADHESIVE REQUIREN	MENT AS PER DO	DCUEMNT NO.95-6085-XX	< .		
			: And graphics - Logo Bla Round - ral 9002 & cisc					
		6. MATERI	IAL: .002 PRESSURE SENS NENT ACRYLIC ADHESIVE.	SITIVE WHITE F	POLYESTER WITH			
		(FLEXC Adhesi	CON CLASSICS PLUS 13092 IVE: ACRYLIC BASE PERMA	2 .OOI MATTE F Anent pressure	POLYESTER OR CISCO AF E SENSITIVE, OR CISCO	PPROVED EQUIVALE		
			IVE COVERED WITH PROTEC S TO BE SUPPLIED IN DIE					
		AND TA	AGGED WITH CISCO PART N IFICATION PER CISCO SPE	NUMBER, REVISI	ION, AND VENDOR			
			MUST BE PROCURED FROM BEAR THE AGREED UPON I			/ENDOR AND		
			ITEM NO. QTY F	PART NUMBER	DESCRIPTION			
				ED THIS DRAWING CONTAINS THE PROPRIETARY PROPER THIS DRAWING IS CONFIL CONTENTS MAY NOT BE D				
			ANGLES: ±-°	APPROVAL DES SHANKAR G	DATE			
		MATERIA	L: THIRD ANGLE PROJECTIC	ENG [—]	ATW ATW	VK COMPLIANC AGORA-FA	Ŀ,	
					SIZE DWG NO.			R E V
		FINISH:				6 - 20522 - 0		03

	3		2	SCALE 3/2	DO NOT SCA	LE DRAWING	CAD TYP	OF I e: proe	
					56-205			rev 03	
		RIKANTH N	08/07/13		AGO	RA-FA			
	ANGLES: \pm -°	APPROVAL iankar g	DATE 08/07/13 -			MPLIANC	E,		~ \
	TOLERANCES: . XX± . XXX±-	RAWING IS CONFIDENT ITS MAY NOT BE DISCLO WRITTEN CONSENT OF O	IAL AND ITS DSED WITHOUT CISCO SYSTEMS.			ISCO			А
	DIMENSIONS ADE IN INCUES. THE PE	RAWING CONTAINS INFO	OF CISCO SYSTEMS.						
	PROCURED FROM A UL AGREED UPON IDENTI			CERTIFIED	VENDOR	AND			
) WIT Ation	H CISCO PART NUMBER PER CISCO SPECIFIC	, REVISION Ation 95-0	N, AND VE)669-XX	INDOR					
		SHEET FORM		TO BAGGE	D				
CLASS ACRY	ICS PLUS I3092 .001 LIC BASE PERMANENT ED WITH PROTECTIVE	MATTE POL Pressure s	LYESTER C Sensitive	DR CISCO	APPROVE			Γ.	
	PRESSURE SENSITIVE LIC ADHESIVE. LAMIN				R				
	ICS - LOGO BLACK AS Al 9002 & CISCO SAF								В
F ADH	ESIVE REQUIREMENT A	s per doci	JEMNT NO.	95-6085-	ΧΧ.				
CK, A -40°(DHESIVE & PRINTING CTO +85°C.	ТЕМРЕКАТИЯ	re range						
CO SA	NS REGULAR, 4 PT &	6 PT.							
	UTER GENERATED DOCU MASTER DATABASE ON		CHANGES	MUST					
ss ot	HERWISE SPECIFIED)								
									С

D