

## Appendix B. Maximum Permissible Exposure

## 1. Maximum Permissible Exposure

### 1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Average RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

### 1.3. Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For 5GHz (Band1 + Band4) UNII Band:

Antenna Type : PIFA Antenna

Conducted Power for IEEE 802.11a: 21.22dBm

Distance (m)	Directional Gain (dBi)	Antenna Gain (numeric)	Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
			(dBm)	(mW)			
0.2	6.90	4.8981	21.2228	132.5190	0.129199	1	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{i=1}^{N_{ANT}} \left\{ \sum_{j=1}^{N_{ELEM}} G_{i,j} \right\}^2}{N_{ANT}} \right]$

For 5GHz (Band2+Band3) UNII Band:

Antenna Type : PIFA Antenna

Conducted Power for IEEE 802.11n HT 40: 21.45dBm

Distance (m)	Directional Gain (dBi)	Antenna Gain (numeric)	Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
			(dBm)	(mW)			
0.2	6.90	4.8981	21.4523	139.7118	0.136211	1	Complies

Note:  $DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{i=1}^{N_{ANT}} \left\{ \sum_{j=1}^{N_{ELEM}} G_{i,j} \right\}^2}{N_{ANT}} \right]$

For 2.4GHz Band:

Antenna Type : PIFA Antenna

Conducted Power for IEEE 802.11g: 20.67 dBm

Distance (m)	Directional Gain (dBi)	Antenna Gain (numeric)	Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
			(dBm)	(mW)			
0.2	5.98	3.9631	20.6684	116.6389	0.092008	1	Complies

#### CONCLUSION:

Both of the WLAN 2.4GHz Band and WLAN 5GHz Band can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is  $0.092008 / 1 + 0.136211 / 1 = 0.228219$ , which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.