

5 FCC §15.247(i), §1.1310, §2.1091 – Maximum Permissible Exposure (MPE)

5.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,j}} \leq 1$$

5.2 RF Exposure Evaluation Result

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	6	3.98	1	1.26	30	0.0004	1
WIFI 2.4GHz XOR	2412-2462	12	15.85	20.5	112.20	30	0.16	1
WIFI 5GHz XOR	5150-5850	12.02	15.92	22.5	177.83	30	0.25	1
WIFI 5GHz Regular	5150-5850	12.02	15.92	21.5	141.25	30	0.20	1
WIFI 5GHz Regular 8TX	5150-5850	13.78	23.88	25.5	354.81	30	0.75	1
WIFI 2.4GHz AUX	2412-2462	6	3.98	20	100.00	30	0.04	1
WIFI 5GHz AUX	5150-5850	6	3.98	20	100.00	30	0.04	1

Transmit simultaneously:

Worst case is Mode 6:

$$0.0004/1+0.75/1+0.04/1 = 0.7904 < 1$$

Result: The EUT meets exemption requirement- RF exposure evaluation greater than **30cm** distance.