

Model Number: CP-9971 series

Engineering Analysis per

FCC 2.1093

Industry Canada RSS-102

Australian ARPANSA Requirements

New Zealand Regulations

For

CP-9971-C-K9, CP-9971-CL-K9, CP-9971-W-K9 & CP-9971-WL-K9
Wireless IP Phone with Bluetooth ver 2.1

Prepared By: Phillip Carranco
Cisco Systems Inc
170 West Tasman
San Jose, CA 95134
USA

Model Number: CP-9971 series

08/05/2009

1.0: Attestation Statement of Compliance

The Cisco Systems Inc CP-9971 Series Wireless IP Phone with Bluetooth Ver 2.1 has been evaluated for Maximum Permissible Exposure in compliance with 47 Code of Federal Regulations 2.1093. The evaluation was in accordance with methodology as referenced in FCC Bulletin OET 65C (rev 01-01)

This report serves as the technical analysis of Cisco of the radios in the CP-9971 series. The technical information referenced for this study was derived from the FCC / Canada test report on the product.

For purposes of this study, the evaluation was only done with the worse case antennae for each programmable power level.

The limits used for this evaluation are in line with the recommendations of the World Health Organizations (WHO) International Committee on Non Ionizing Radiation Protection (ICNIRP) as well as the American National Standards Institute (ANSI) C95.1.

This analysis also complies with the requirements stated in Industry Canada RSS-102 as well as the applicable Australian and New Zealand regulations.

Phillip Carranco
Compliance Engineer
Cisco Systems Inc
170 W Tasman Dr
San Jose, CA 93727
Phone: 408.525.2635
Email: pcarranc@cisco.com

Model Number: CP-9971 series

2.0 EUT Description.

This is a Cisco Wireless IP Phone with Bluetooth Ver. 2.1 contains both an 802.11b/g radio, an 802.11a radio and an 802.15 Bluetooth Ver. 2.1 Radio.

3.0 Methodology

All calculations were made in accordance with ANSI C95.1, and FCC OET 65C.

4.0 Technical Requirements

4.1 Single Band Operation – Limits

As referenced by OET 65C / RSS-102

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (M Hz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²) (m)	Averaging Time E ² , H ² or S inutes)
0. 3-1.34	614	1.63	(100)*	30
1. 34-30	824/f	2.19/f	(180/f ²)* 30	
30-300	27.5	0.073	0.2	30
3 00-1500	--	--	f/1500	30
1 500-100,000	--	--	1.0	30

f = frequency in MHz *Plane-wave equivalent power density

NOTE 1: See Section 1 for discussion of exposure categories.

NOTE 2: The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirements for mobile and portable transmitters.

Model Number: CP-9971 series

Excerpt from Australian Radiation Protection Standard

**REFERENCE LEVELS FOR TIME AVERAGED EXPOSURE TO
RMS ELECTRIC AND MAGNETIC FIELDS (UNPERTURBED
FIELDS)**

Exposure category	Frequency range	E-field strength (V/m rms)	H-field strength (A/m rms)	Equivalent plane wave power flux density S_{eq} (W/m²)
Occupational	100 kHz – 1 MHz	614	$1.63 / f$	—
	1 MHz – 10 MHz	$614 / f$	$1.63 / f$	$1000 / f^2$ (see note 5)
	10 MHz – 400 MHz	61.4	0.163	10 (see note 5)
	400 MHz – 2 GHz	$3.07 \times f_{0.5}$	$0.00814 \times f_{0.5}$	$f / 40$
	2 GHz – 300 GHz	137	0.364	50
General public	100 kHz – 150 kHz	86.8	4.86	—
	150 kHz – 1 MHz	86.8	$0.729 / f$	—
	1 MHz – 10 MHz	$86.8 / f_{0.5}$	$0.729 / f$	—
	10 MHz – 400 MHz	27.4	0.0729	2 (see note 6)
	400 MHz – 2 GHz	$1.37 \times f_{0.5}$	$0.00364 \times f_{0.5}$	$f / 200$
	2 GHz – 300 GHz	61.4	0.163	10

5.0 Calculations

Given

$$E = \sqrt{(30 \cdot P \cdot G) / d}$$

Where E = field strength in Volts per meter

P = Power in Watts

G = Antenna Gain in dBi

D = distance in cm

Changing units of power to mW and meters to cm

Model Number: CP-9971 series

$P = \text{mW} = P (\text{W}) / 1000$ and

$d(\text{cm}) = 100 * d(\text{m})$

Yields

$$E = 100 * \sqrt{(30 * (P / 1000 * G) / d)}$$

$$E = 17.32 \sqrt{(P * G) / d}$$

Using the logarithmic formula for power and gain

$$P(\text{mW}) = 10^{((P + G) / 20) / d}$$

$$G (\text{numeric}) = 10^{(G (\text{dBi}) / 10)}$$

6.0 Results

Table 2

Frequency	TX Power	Antenna Gain	Distance	mW/cm²	Limit
2437 MHz	16.24 dBm	0.44 dBi	20cm	0.009	1 mW/cm ²
2402 MHz	2.87 dBm	0.44 dBi	20cm	0.000	1mW/m ²
5785 MHz	17.78 dBm	3.01 dBi	20cm	0.024	1mW/m ²