



ETS Dr.GenZ Taiwan PS Co., LTD

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory



A2LA Cert.No.: 2300.01

FCC

TEST - REPORT

FCC RULES PART 15 / SUBPART C § 15.249

FCC ID : LE2CCD-325LWS

Test report no.:

W6M20501-5672-P-15

TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.2.1	<i>Location</i>	3
1.2.2	<i>Details of accreditation status</i>	3
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS	4
1.5	GENERAL INFORMATION OF TEST ITEM	4
1.6	TEST STANDARDS	5
2	TECHNICAL TEST.....	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT.....	6
2.3	TEST EQUIPMENT LIST	7
3	TEST RESULTS (ENCLOSURE).....	11
3.1	PEAK OUTPUT POWER (TRANSMITTER)	12
3.2	EQUIVALENT ISOTROPIC RADIATED POWER	13
3.2.1	<i>Transmitter</i>	13
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	13
3.4	OUT OF BAND RADIATED EMISSIONS	13
3.6	RADIATED EMISSION ON THE BANDEDGE	17
3.7	POWER LINE CONDUCTED EMISSION	18
APPENDIX.....	19	
APPENDIX A.....	20	
APPENDIX B.....	21	
APPENDIX C	22	
APPENDIX D.....	23	

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Tester:

14.03.2005

Orville Chang



Date

ETS-Lab.

Name

Signature

Technical responsibility for area of testing:

14.03.2005

Steven Chuang



Date

ETS

Name

Signature



Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS DR. GENZ TAIWAN PS CO., LTD.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

1.3 Details of approval holder

Name:	JSW PACIFIC CORPORATION
Street:	3F-3, No. 700, Chung-Zheng Rd.
Town:	Chung Ho City, Taipei Hsien
Country:	TAIWAN, R.O.C.
Telephone:	+886-2-8227-8582
Fax:	+886-2-8227-8583

Contact	Mr. Lin Psai Chen
Telephone:	+886-2-8227-8582 Ext 128

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

1.4 Application details

Date of receipt of application: 26.01.2005

Date of receipt of test item: 18.02.2005

Date of test: 21.02.2005 to 04.03.2005

1.5 General information of Test item

Type of test item : Wireless Camera

Model Number : CCD-325LWS

Serial number : without

Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz

Operation Frequency : 2412, 2432, 2452, and 2472

Frequency 1 (ch 1) : 2.412 GHz

Frequency 2 (ch 3) : 2452 GHz

Frequency 3 (ch 4) : 2.472 GHz

Number of Channels : 4

Operation modes : Simplex

Modulation Type : F8F

Antenna transmitter : integral antenna

Power supply : 120 VAC (AC/DC Adapter)



Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

Manufacturer:
(if applicable)

Name : -/-
Street : -/-
Town : -/-
Country : -/-

Additional information : --

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART C § 15.249

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature : 23 °C

Relative humidity content : 20 ... 75 %

Air pressure : 86 ... 103 kPa

Details of power supply : 120 VAC (AC/DC Adapter)

Extreme conditions parameters : Not required

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	08.11.2005
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY				
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO LINE V-NETWORK	ESH3-Z5	840731/011	R&S	08.11.2006
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	03.11.2006
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	10.11.2006
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S	
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS- MESSWANDLER -ZANGE	04.11.2006
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P- U	MAA0305-009	GIANT FORCE	10.05.2005
ETSTW-CE 010	Comb Generator-conducted			ETS	
ETSTW-CE 011	Power Line Conducted Emission Only			ETS	
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	31.10.2005
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	CHAFFNER	03.11.2006
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	CHAFFNER	03.11.2006
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	CHAFFNER	03.11.2006
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	03.11.2005
ETSTW-RE 001	2MHz SWEEP FUNCTION GENERATOR	EGC-3230	02050018	Escort	
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	03.11.2005
ETSTW-RE 003	EMI TEST RECEIVER	ESI	831438/001	R&S	16.11.2005
ETSTW-RE 004	EMI TEST RECEIVER	ESI	831459/012	R&S	09.11.2005
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	01.11.2005
ETSTW-RE 006	HF-EICHELITUNG RF STEP ATTENUATOR	DPSP	848220/003	R&S	
ETSTW-RE 007	HF-EICHELITUNG RF STEP ATTENUATOR	DPSP	844581/024	R&S	
ETSTW-RE 008	Controller	HD100	C0100-L/047/ 6670703/L	Heinrich Deisel	
ETSTW-RE 009	Controller	HD100	100/341	Heinrich Deisel	
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH	
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0036	397	K&L	
ETSTW-RE 014	DUAL TRACKING WITH 5V FIXED	GPC-3030D		GW	
ETSTW-RE 015	ANTENNA	HK116	841489/003	R&S	
ETSTW-RE 016	ANTENNA	HL223	848953/006	R&S	
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	
ETSTW-RE 018	ANTENNA	AT 4560	27212	AR	07.11.2006

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

ETSTW-RE 019	ANTENNA , HORN	22240-25	121074	FM	
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	10.11.2005
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Agilent	01.11.2005
ETSTW-RE 023	Shielded room	SR 1		Frankonia	
ETSTW-RE 024	Anechoic Chamber	CHC 1		Frankonia	
ETSTW-RE 025	Anechoic Chamber	CHC 2		Frankonia	
ETSTW-RE 026	Open Area Test Site	10m		ETS	
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	29.06.2006
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	14.06.2006
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	16.06.2006
ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	04.05.2006
ETSTW-RE 031	Comb Generator-radiated			ETS	
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	17.11.2005
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14508	LeCory	
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	17.11.2005
ETSTW-RE 035	1.5GHz Active Voltage Probe	HFP1500	2332	LeCory	
ETSTW-RE 036	100MHz High Voltage Diff Probe	ADP305	3305	LeCory	
ETSTW-RE 037	Log-Periodic DipoleArray Antenna	3148	00034546	EMCO	17.11.2006
ETSTW-RE 038	Log-Periodic DipoleArray Antenna	3148	00034547	EMCO	17.11.2006
ETSTW-RE 039	Biconical Antenna	3110B	41760	EMCO	17.11.2006
ETSTW-RE 040	Biconical Antenna	3110B	41761	EMCO	17.11.2006
ETSTW-RE 041	Anechoic Chamber	CHC 3		Frankonia	
ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	17.11.2005
ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	01.11.2005
ETSTW-EMS 002	Frequency Converter	YF-6020	0308014		
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	01.11.2005
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	01.11.2005
ETSTW-EMS 005	Attenuator (50Ω)	VERI50	051	EMC-PARTNER	30.08.2006
ETSTW-EMS 006	Attenuator (1 KO)	VERI1K	019	EMC-PARTNER	20.10.2006
ETSTW-EMS 007	20GO Divider	ESD-VERI-V	021	EMC-PARTNER	16.03.2006
ETSTW-RS 001	14" COLOR VIDEO MONITOR	TP-1480HR	P009799	TOPICA	
ETSTW-RS 002	14" COLOR VIDEO MONITOR	TP-1480HR	P009814	TOPICA	
ETSTW-RS 003	AMPLIFIER RESEARCH	30S1G3	306933	AR	
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	18.11.2005
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	GW	03.09.2005
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	15.11.2005

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

ETSTW-RS 007	AUDIO ANALYZER	UPA3	843458/029	R&S	15.11.2005
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA Testsystems GmbH	
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	
	Parts of Anite SAT (6)E Platform Protocol Test System				
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	07.14.06
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	07.14.06
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052852	Agilent	07.17.06
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052984	Agilent	07.16.06
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	07.14.06
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	07.16.06
ETSTW-GSM 09	Controler PC	Dell GX 270	700F61J	Dell	
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	07.06
ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		Rohde & Schwarz	11.05

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table). The UUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

Peak readings were taken in three (3) orthogonal planes and the highest readings.

Measurements were made by ETS Dr. Genz Taiwan PS Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: 930600.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANTENNA & GROUND:

This unit uses integral antenna. (see photo).

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

3 Test results (enclosure)

TEST CASE	Required	Test passed	Test failed
Peak Output Power 15.249 (b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating 15.249 (e)	☒	☒	☐
Spurious Emissions conducted – Transmitter operating 15.249 (e)	☐	☐	☐
Out of Band Spurious Emission, Bandedge-Transmitter operating	☒	☒	☐
Power Line Conducted Emission 15.207	☒	☒	☐

The follows is intended to leave blank.

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

3.1 Peak Output Power (transmitter)

FCC Rule: 15.249 (b)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test conditions Channel 1		Transmitter field strength of fundamental	Transmitter field strength of harmonics
		[dB μ V/m]	
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120V$	81.64	--
Measurement uncertainty		< 3 dB	

Test conditions Channel 3		Transmitter field strength of fundamental	Transmitter field strength of harmonics
		[dB μ V/m]	
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120V$	82.63	--
Measurement uncertainty		< 3 dB	

Test conditions Channel 4		Transmitter field strength of fundamental	Transmitter field strength of harmonics
		[dB μ V/m]	
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120V$	84.37	--
Measurement uncertainty		< 3 dB	

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 017, ETSTW-RE 024

Remarks: The diagrams for the field strength measurements are included in appendix.

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

3.2 Equivalent isotropic radiated power

Because using an permanent antenna there are no deviations from the radiated test results according 3.1.

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules §15.249, subpart C, This unit uses permanent antenna. There is no provision for an external antenna (see photo).

3.3 RF Exposure Compliance Requirements

Not applicable for this Wireless Camera for the low power level.

3.4 Out of Band Radiated Emissions

FCC Rule: 15.49 (d)(e), 15.35(b)

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

For frequency above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

Limits:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.5
Above 960	500	54.0

For frequencies above 1 GHz (Peak measurements).

Limit + 20 dB

$$54.0 \text{ dB}\mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB}\mu\text{V/m}$$

Or

Must be antenuatted at least 50dB below the level of fundament

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 015 , ETSTW-RE 016 ,
ETSTW-RE 017 , ETSTW-RE 024

Remark: see attached diagram

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

3.5 Spurious emission (tx)

Spurious emission was measured with modulation (declared by manufacturer).

Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

For frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

SAMPLE CALCULATION OF LIMIT. ALL results will be updated by an automatic measuring system in accordance with point 2.3.

The peak and average spurious emission plots was measured with the average limits.
The critical peak value listed in the table agree with the above calculated limits.

Summary table with radiated data of the test plots

Freq.	Used Ch.	Frequency Marker [MHz]	Polarization	corrections dB	Corrected Reading [dBuV/m]	Compliance Limit [dBuV/m]	Detector	BW [MHz]	Margin
1	1	194.5491369	H		36,75	43.5	P	0.1	6,75
1	1	194.5491369	V		37,77	43.5	P	0.1	5,73
2	1	990.3818132	H		35,16	54	P	0.1	18,84
2	1	990.3818132	V		36,29	54	P	0.1	17,71
4	1	4817.635271	H		58,46	74	P	1	15,54
4	1	4817.635271	H		51,24	54	AV	1	2,76
4	1	4817.635271	V		53,78	54	P	1	0,22
4	1	7238.476954	H		55,93	74	P	1	18,07
4	1	7238.476954	H		49,33	54	AV	1	4,67
4	1	7238.476954	V		55,36	74	P	1	18,64
4	1	7238.476954	V		48,56	54	AV	1	5,44
5	1	11992.30598	H		51,77	54	P	1	2,23
5	1	11992.30598	V		51,06	54	P	1	2,94
6	1	12060.12024	H		48,32	54	P	1	5,68
6	1	12060.12024	V		49,11	54	P	1	4,89
7	1	24354.06481	H		49,03	54	P	1	4,97
7	1	24354.06481	V		49,37	54	P	1	4,63
1	2	173.426854	H		38,31	43.5	P	0.1	5,19
1	2	173.426854	V		37,94	43.5	P	0.1	5,56
2	2	985.571043	H		35,18	54	P	0.1	18,82
2	2	985.571043	V		36,68	54	P	0.1	17,32
3	2	3718.16287	H		44,06	54	P	1	9,94

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

3	2	3718.16287	V		43,24	54	P	1	10,76
4	2	4857.715431	H		48,98	54	P	1	5,02
4	2	4857.715431	V		49,97	54	P	1	4,03
4	2	7302.605210	H		61,25	74	P	1	12,75
4	2	7302.605210	H		53,89	54	AV	1	0,11
4	2	7302.605210	V		60,53	74	P	1	13,47
4	2	7302.605210	V		52,56	54	AV	1	1,44
5	2	11992.01384	H		52,05	54	P	1	1,95
5	2	11992.01384	V		51,30	54	P	1	2,70
6	2	12156.31263	H		49,56	54	P	1	4,44
6	2	12156.31263	V		50,74	54	P	1	3,26
7	2	25751.34281	H		48,23	54	P	1	5,77
7	2	25751.34281	V		49,79	54	P	1	4,21
1	4	194.8901322	H		37,78	43.5	P	0.1	5,72
1	4	194.8901322	V		37,52	43.5	P	0.1	5,98
2	4	998.3971347	H		35,73	54	P	0.1	18,27
2	4	998.3971347	V		35,12	54	P	0.1	18,88
3	4	3272.64819	H		43,76	54	P	1	10,24
3	4	3272.64819	V		42,14	54	P	1	11,86
4	4	4945.891784	V		50,74	54	P	1	3,26
4	4	4945.891784	H		54,28	74	P	1	19,72
4	4	4945.891784	H		47,92	54	AV	1	6,08
4	4	7422.845691	V		58,83	74	P	1	15,17
4	4	7422.845691	V		50,94	54	AV	1	3,06
4	4	7422.845691	H		60,01	74	P	1	13,99
4	4	7422.845691	H		52,32	54	AV	1	1,68
5	4	11391.3468	H		51,70	74	P	1	22,30
5	4	11391.3468	V		50,14	74	P	1	23,86
6	4	17760.3015	H		50,08	74	P	1	23,92
6	4	17760.3015	V		50,41	74	P	1	23,59
7	4	24933.2946	V		50,42	74	P	2	23,58
7	4	24933.2946	H		48,21	74	P	1	25,79



Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

Freq. – Frequency Range:

1:	30	-	200 MHz
2:	200	-	1000 MHz
3:	1	-	4 GHz
4:	4	-	8 GHz
5:	8	-	12 GHz
6:	12	-	17 GHz
7:	17	-	26.5 GHz

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 015, ETSTW-RE 016,
ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

3.6 Radiated Emission on the bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band and hey at least 50 dB below the carrier level at band edge (2400,0 and 2483,5 MHz). It meets the requirement of section 15.249(d).

Test conditions Tnom = 23°C, Vnom = 120V Frequency [MHz]	Transmitter field strength of Radiated Emission (Peak Detector) [dBμV/m]	Transmitter field strength of Radiated Emission (Average Detector)
2400	55,67	45,04
2483,5	57,85	46,72

Limit:

Frequency Range (MHz)	Limit (dBμV/m)	
	Peak	Average
902 – 928	74	54
2400 – 2483,5		
5725 – 5875		
24000 - 24250		

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20501-5672-P-15

FCC ID: LE2CCD-325LWS

3.7 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Limits:

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test is not required the sample is battery used.

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagrams

Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

Appendix

- A Fundamental Field Strength
- B Spurious Emissions radiated – Transmitter operating
- C Power Line Conducted Emission
- D Pictures



Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS


Appendix A

Fundamental Field Strength

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.409GHz, Emax: 76.11dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.412GHz, Emax: 81.64dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.432GHz, Emax: 76.53dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.432GHz, Emax: 82.63dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.472GHz, Emax: 77.29dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.472GHz, Emax: 84.37dBµV/m, RBW: 1MHz



Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS


Appendix B

Spurious Emissions radiated – Transmitter operating

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 194.549MHz, Emax: 37.77dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 199.319MHz, Emax: 37.62dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 990.381MHz, Emax: 36.29dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 971.142MHz, Emax: 35.97dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.407GHz, Emax: 76.92dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.407GHz, Emax: 81.78dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.238GHz, Emax: 55.42dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.818GHz, Emax: 58.46dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.735GHz, Emax: 51.65dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.992GHz, Emax: 51.77dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.796GHz, Emax: 50.55dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.808GHz, Emax: 50.29dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.354GHz, Emax: 49.37dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 1
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 23.996GHz, Emax: 49.23dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.934MHz, Emax: 37.94dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 173.427MHz, Emax: 38.31dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 985.571MHz, Emax: 36.68dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 985.571MHz, Emax: 35.50dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.431GHz, Emax: 77.94dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.431GHz, Emax: 75.50dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.303GHz, Emax: 60.53dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.303GHz, Emax: 61.25dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 10.325GHz, Emax: 51.81dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.992GHz, Emax: 52.05dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.687GHz, Emax: 50.42dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.820GHz, Emax: 50.45dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.751GHz, Emax: 49.79dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 2
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.296GHz, Emax: 49.43dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 181.263MHz, Emax: 38.55dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 194.890MHz, Emax: 37.78dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 902.204MHz, Emax: 35.38dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.
Freq: 998.397MHz, Emax: 35.73dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.467GHz, Emax: 75.53dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.467GHz, Emax: 75.59dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.415GHz, Emax: 59.10dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.423GHz, Emax: 60.01dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.575GHz, Emax: 51.53dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.391GHz, Emax: 51.70dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.760GHz, Emax: 50.41dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 50.37dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.933GHz, Emax: 50.42dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

EUT: Wireless Camera
MODEL NO.: CCD-325LWS CH 4
Approval Holder: JSW PACIFIC CORPORATION
Test Site / Operator: ETS / Orville Chang
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (ac / dc Adaptor)
Test Specification: according to §15.249, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.507GHz, Emax: 49.06dBμV/m, RBW: 1MHz





Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS


Appendix C

Power Line Conducted Emission

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: Wireless Camera
Manufacturer: JSW PACIFIC CORPORATION.
Operating Condition: Unom: 120 VAC (ac/dc adaptor) , Tnom: 23°C
Test Site: ETS
Operator: Catey
Test Specification: V-network: ESH3-Z5 N
Comment: model: CCD-325LWS mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: Wireless Camera
Manufacturer: JSW PACIFIC CORPORATION.
Operating Condition: Unom: 120 VAC (ac/dc adaptor) , Tnom: 23°C
Test Site: ETS
Operator: Catey
Test Specification: V-network: ESH3-Z5 L1
Comment: model: CCD-325LWS mode: active





Registration number: W6M20501-5672-P-15
FCC ID: LE2CCD-325LWS

Appendix D

Pictures