




	Date(s) of Evaluation October 06-07, 2010	Test Report Serial No. 100410LEA-T1055-S90U	Test Report Revision No. Rev. 1.0 (Initial Release)	
	Test Report Issue Date October 28, 2010	Description of Test(s) Specific Absorption Rate	RF Exposure Category Occupational (Controlled)	

## DECLARATION OF COMPLIANCE - SAR RF EXPOSURE EVALUATION (FCC/IC)

<b>Test Lab Information</b>	<b>Name</b> CELLTECH LABS INC.				
	<b>Address</b> 21-364 Lougheed Road, Kelowna, B.C. V1X 7R8 Canada				
<b>Applicant Information</b>	<b>Name</b> UNICATION CO., LTD.				
	<b>Address</b> 5F, No. 6, Wu-Kung 5 Road, Hsinchuang City, Taipei, Taiwan R.O.C				
<b>Standard(s) Applied</b>	<b>FCC</b> 47 CFR §2.1093	<b>IC</b> Health Canada Safety Code 6			
<b>Procedure(s) Applied</b>	<b>FCC</b> OET Bulletin 65, Supplement C	<b>FCC</b> KDB 447498 D01v04			
	<b>IC</b> RSS-102 Issue 4	<b>IEEE</b> 1528-2003	<b>IEC</b> 62209-1:2005		
<b>Device Classification(s)</b>	<b>FCC</b> Licensed Non-Broadcast Transmitter Held to Face (TNF) - FCC Part 90				
	<b>IC</b> Land Mobile Radio Transmitter/Receiver (27.41-960 MHz) - RSS-119 Issue 10				
<b>Device Identifier(s)</b>	<b>FCC ID:</b> LEA-U3-UHF-MID	<b>IC</b> 3819A-U3UHF MID			
<b>Device Model(s)</b>	U3UHF MID	<b>Test Sample Serial No.</b> BUGBCAT2226 (Identical Prototype)			
<b>Hardware / Firmware Revision No.s</b>	<b>Hardware</b> 1500-01300-01 Rev. 13	<b>Firmware</b> DSP 1.05D, Application 1.11			
<b>Date of Sample Receipt</b>	October 04, 2010				
<b>Date of Evaluations</b>	October 06-07, 2010				
<b>Device Description</b>	Portable UHF Push-To-Talk (PTT) Radio Transceiver				
<b>Device Mode(s) of Operation</b>	Analog FM	P25 Digital FM	2-Slot TDMA w/ Digital FM		
	Class 2 Bluetooth - Max. Output Power < 5 mW - Closest Distance to UHF Antenna = 34 mm				
<b>Co-located Transmitter (Simultaneous Transmission)</b>	Bluetooth Antenna to Front Keypad = 10.8 mm		Bluetooth Antenna to Rear Battery = 22.2 mm		
<b>UHF Transmit Frequency Range(s)</b>	<b>FCC</b> 406.1 - 470.0 MHz				
	<b>IC</b> 406.1 - 430.0 MHz / 450.0 - 470.0 MHz				
<b>Manufacturer's Rated Output Power</b>	4 Watts (Conducted)				
<b>Manufacturer's Tolerance Spec.</b>	+ 0.8 Watts (Conducted)				
<b>RF Output Power Level(s) Tested</b>	36.2 dBm	4.2 Watts	406.1 MHz	Average Conducted	
	36.0 dBm	4.0 Watts	422.0 MHz	Average Conducted	
	36.0 dBm	4.0 Watts	438.0 MHz	Average Conducted	
	36.0 dBm	4.0 Watts	454.0 MHz	Average Conducted	
	36.2 dBm	4.2 Watts	470.0 MHz	Average Conducted	
<b>Antenna Type(s) Tested</b>	Dual-Band Whip	403 - 470 MHz	Length = 151 mm	P/N: 7100-02011	
<b>Battery Type(s) Tested</b>	Lithium-Ion	7.2 V	2400 mAh	P/N: 6653-00002-01	
<b>Body-worn Accessories Tested</b>	U3 Belt-Clip Assembly (contains metal)			P/N: 2160-01003	
<b>Audio Accessories Tested</b>	U3 Basic Remote Speaker-Microphone			P/N: 7106-00009-02	
	U3 Receive Only Earpiece (for Speaker-Microphone)			P/N: P0880516	
<b>Max. SAR Level(s) Evaluated</b>	Face-held	2.85 W/kg	1g	50% PTT duty cycle	Occupational / Controlled Exp.
	Body-worn	4.52 W/kg	1g	50% PTT duty cycle	Occupational / Controlled Exp.
<b>FCC/IC Spatial Peak SAR Limit</b>	Head/Body	8.0 W/kg	1g	50% PTT duty cycle	Occupational / Controlled Exp.
Celltech Labs Inc. declares under its sole responsibility that this wireless portable device has demonstrated compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada Safety Code 6 for the Occupational / Controlled Exposure environment. The device was tested in accordance with the measurement procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01), Industry Canada RSS-102 Issue 4, IEEE Standard 1528-2003 and IEC International Standard 62209-1:2005. All measurements were performed in accordance with the SAR system manufacturer recommendations.					
I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.					
This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc.					
The results and statements contained in this report pertain only to the device(s) evaluated.					
<b>Test Report Approved By</b>			<b>Sean Johnston</b>	<b>Lab Manager</b>	<b>Celltech Labs Inc.</b>


<b>Applicant:</b> Unication Co., Ltd.	<b>FCC ID:</b> LEA-U3-UHF-MID	<b>IC:</b> 3819A-U3UHF MID	
<b>DUT Type:</b> Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b> U3UHF MID	<b>406.1 - 470 MHz</b>	
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.	
			Page 1 of 52



<b>TABLE OF CONTENTS</b>	
1.0 INTRODUCTION	4
2.0 SAR MEASUREMENT SYSTEM	4
3.0 RF CONDUCTED OUTPUT POWER MEASUREMENTS	4
4.0 FCC POWER THRESHOLDS FOR PTT DEVICES ( $f < 0.5$ GHz)	5
5.0 SAR PROBE CALIBRATION & MEASUREMENT FREQUENCIES	5
6.0 NO. OF TEST CHANNELS ( $N_c$ )	5
7.0 MANUFACTURER'S DISCLOSED ACCESSORY LISTING	6
8.0 SAR MEASUREMENT SUMMARY	7
9.0 SAR SCALING (MANUFACTURER TOLERANCE)	8
10.0 SIMULTANEOUS TRANSMISSION ASSESSMENT	8
11.0 FLUID DIELECTRIC PARAMETERS	9
12.0 DETAILS OF SAR EVALUATION	10
13.0 EVALUATION PROCEDURES	10
14.0 SYSTEM PERFORMANCE CHECK	11
15.0 SIMULATED EQUIVALENT TISSUES	12
16.0 SAR LIMITS	12
17.0 ROBOT SYSTEM SPECIFICATIONS	13
18.0 PROBE SPECIFICATION (ET3DV6)	14
19.0 SIDE PLANAR PHANTOM	14
20.0 BARSKI PLANAR PHANTOM	14
21.0 DEVICE HOLDER	14
22.0 TEST EQUIPMENT LIST	15
23.0 MEASUREMENT UNCERTAINTIES	16
24.0 REFERENCES	17
APPENDIX A - SAR MEASUREMENT DATA	18
APPENDIX B - SYSTEM PERFORMANCE CHECK	32
APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS	35
APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS	38
APPENDIX E - DIPOLE CALIBRATION	50
APPENDIX F - PROBE CALIBRATION	51
APPENDIX G - BARSKI PHANTOM CERTIFICATE OF CONFORMITY	52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

REVISION HISTORY			
REVISION NO.	DESCRIPTION	IMPLEMENTED BY	RELEASE DATE
1.0	Initial Release	Jon Hughes	October 28, 2010

TEST REPORT SIGN-OFF			
DEVICE TESTED BY	REPORT PREPARED BY	QA REVIEW BY	REPORT APPROVED BY
Scott Kulifaj	Scott Kulifaj	Jon Hughes	Sean Johnston

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 3 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## 1.0 INTRODUCTION


This measurement report demonstrates that the Unication Co., Ltd. Model: U3UHF MID Portable UHF PTT Radio Transceiver complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]) and Health Canada's Safety Code 6 (see reference [2]) for the Occupational / Controlled Exposure environment. The measurement procedures described in FCC OET Bulletin 65, Supplement C 01-01 (see reference [3]), IC RSS-102 Issue 4 (see reference [4]), IEEE Standard 1528-2003 (see reference [5]) and IEC Standard 62209-1:2005 (see reference [6]) were employed. A description of the device, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used and the various provisions of the rules are included within this test report.



## 2.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for head and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses a controller with a built in VME-bus computer.

## 3.0 RF CONDUCTED OUTPUT POWER MEASUREMENTS

MEASURED RF CONDUCTED OUTPUT POWER LEVELS					
Test Freq. (MHz)	Band	Mode	dBm	Watts	Method
406.1	FCC/IC UHF	CW	36.2	4.2	Average Conducted
422.0	FCC/IC UHF	CW	36.0	4.0	Average Conducted
438.0	FCC UHF	CW	36.0	4.0	Average Conducted
454.0	FCC/IC UHF	CW	36.0	4.0	Average Conducted
470.0	FCC/IC UHF	CW	36.2	4.2	Average Conducted
<b>Notes</b>					
1. The test channels were selected in accordance with the procedures specified in FCC KDB 447498 Section 6) c) (see reference [7]).					
2. The RF conducted output power levels of the DUT were measured by Celltech prior to the SAR evaluations using a Gigatronics 8652A Universal Power Meter at the external antenna connector of the radio in accordance with FCC 47 CFR §2.1046 (see reference [13]) and IC RSS-Gen (see reference [14]).					

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 4 of 52

	Date(s) of Evaluation October 06-07, 2010	Test Report Serial No. 100410LEA-T1055-S90U	Test Report Revision No. Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	Test Report Issue Date October 28, 2010	Description of Test(s) Specific Absorption Rate	RF Exposure Category Occupational (Controlled)	

#### 4.0 FCC POWER THRESHOLDS FOR PTT DEVICES ( $f \leq 0.5$ GHz)

FCC SAR Evaluation Power Thresholds for PTT Devices, $f \leq 0.5$ GHz*			Manufacturer's Rated RF Output Power	
Exposure Conditions	P mW (General Population)	P mW (Occupational)	100% PTT Duty Cycle	50% PTT Duty Cycle
Held to face, $d \geq 2.5$ cm	250	<b>1250</b>	5 Watts	<b>2.5 Watts</b>
Body-worn, $d \geq 1.5$ cm	200	1000		
<b>Body-worn, <math>d \geq 1.0</math> cm</b>	150	<b>750</b>	5 Watts	<b>2.5 Watts</b>
1. The time-averaged output power, corresponding to the required PTT duty factor, is compared with these thresholds. 2. The closest distance between the user and the device or its antenna is used to determine the power thresholds. * Per FCC KDB 447498 D01v04 Section 5)b)i) (see reference [7]).			1. The conducted output power level of the DUT exceeds the FCC power threshold and therefore SAR evaluation is required.	

#### 5.0 SAR PROBE CALIBRATION & MEASUREMENT FREQUENCIES

The following procedures are recommended for measurements at 150 MHz - 3 GHz to minimize probe calibration and tissue dielectric parameter discrepancies. In general, SAR measurements below 300 MHz should be within  $\pm 50$  MHz of the probe calibration frequency. At 300 MHz to 3 GHz, measurements should be within  $\pm 100$  MHz of the probe calibration frequency. Measurements exceeding 50% of these intervals,  $+25$  MHz  $< 300$  MHz and  $\pm 50$  MHz  $\geq 300$  MHz, require additional steps (per FCC KDB 450824 D01 v01r01, SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz - 3 GHz - see reference [9]).


Probe Calibration Freq.	Device Measurement Freq.	Frequency Interval	$\pm 50$ MHz $\geq 300$ MHz
<b>450 MHz</b>	406.1 MHz	43.9 MHz	< 50 MHz
	422.0 MHz	28 MHz	< 50 MHz
	438.0 MHz	12 MHz	< 50 MHz
	454.0 MHz	4 MHz	< 50 MHz
	470.0 MHz	20 MHz	< 50 MHz



Note: The probe calibration and measurement frequency interval is < 50 MHz; therefore additional steps were not required.

#### 6.0 NO. OF TEST CHANNELS ( $N_c$ )

Antenna Part No.	Antenna Freq. Range	Test Freq. Range	Band(s)	$N_c$	Test Frequencies (MHz)
7100-02011	403 - 470 MHz	406.1 - 470.0 MHz	FCC/IC	5	406.1, 422.0, 438.0, 454.0, 470.0 MHz

Note: The number of test channels per antenna frequency range was calculated in accordance with the procedures specified in FCC KDB 447498 Section 6) c) (see reference [7]).

Applicant:	Unication Co., Ltd.	FCC ID:	LEA-U3-UHF-MID	IC:	3819A-U3UHF MID	
DUT Type:	Portable UHF PTT Radio Transceiver	Device Model(s):	U3UHF MID		406.1 - 470 MHz	
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 5 of 52


	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## 7.0 MANUFACTURER'S DISCLOSED ACCESSORY LISTING

Part No.	Description	Accessory Type
7100-02011	Dual band monopole antenna - UHF 2 dBi (403-470 MHz) - GPS 2.5 dBi	Antenna
6653-00002-01	7.2 V, 2400 mAh Lithium-Ion battery	Battery
2160-01003	U3 Belt-Clip Assembly (contains metal)	Body-worn
7106-00009-02	U3 Basic Remote Speaker-Microphone	Audio
P0880516	U3 Receive Only Earpiece (for Spkr-Mic)	

Note(s):

1. Manufacturer's disclosed accessory listing information was provided by Unication Co., Ltd.

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 6 of 52

## 8.0 SAR MEASUREMENT SUMMARY

SAR EVALUATION RESULTS (UHF Band)														
Test Config.	Test Date	Test Freq.	Band	Battery Type	Body-worn Accessory	Audio Accessory	Device Distance to Planar Phantom (cm)		Cond. Power Before Test Watts	Measured SAR 1g (W/kg)		SAR Drift dB	Scaled SAR with droop 1g (W/kg)	
		MHz					DUT	ANT		PTT Duty Cycle			PTT Duty Cycle	
										100%	50%		100%	50%
<b>FACE</b>	Oct 7	406.1	FCC/IC	Li-ion	n/a	n/a	2.5	4.5	4.2	5.12	2.56	-0.463	5.70	2.85
	Oct 7	422.0	FCC/IC				2.5	4.5	4.0	3.30	1.65	-0.347	3.57	1.79
	Oct 7	438.0	FCC				2.5	4.5	4.0	2.41	1.21	-0.256	2.56	1.28
	Oct 7	454.0	FCC/IC				2.5	4.5	4.0	2.22	1.11	-0.225	2.34	1.17
	Oct 7	470.0	FCC/IC				2.5	4.5	4.2	2.59	1.30	-0.635	3.00	1.50
<b>BODY</b>	Oct 6	406.1	FCC/IC	Li-ion	Belt-Clip	Speaker-Microphone with Earpiece	1.3	2.0	4.2	8.61	4.31	-0.207	9.03	4.52
	Oct 6	422.0	FCC/IC				1.3	2.0	4.0	6.09	3.05	-0.097	6.23	3.12
	Oct 6	438.0	FCC				1.3	2.0	4.0	5.54	2.77	-0.526	6.25	3.13
	Oct 6	454.0	FCC/IC				1.3	2.0	4.0	4.61	2.31	-0.336	4.98	2.49
	Oct 6	470.0	FCC/IC				1.3	2.0	4.2	4.62	2.31	-0.495	5.18	2.59

SAR LIMIT(S)				HEAD / BODY		SPATIAL PEAK		RF EXPOSURE CATEGORY			
FCC 47 CFR 2.1093		Health Canada Safety Code 6		8.0 W/kg		averaged over 1 gram		Occupational / Controlled			

- Notes**
- Battery Type(s) Evaluated = Lithium-Ion 7.2V 2400mAh Battery Pack (P/N: 6653-00002-01)
  - Device Test Mode = CW (Unmodulated Continuous Wave)
  - Phantom Type = Plexiglas Side Planar

Test Date	Fluid Type	Ambient Temp.	Fluid Temp.	Fluid Depth	Atmospheric Pressure	Relative Humidity	ρ (Kg/m <sup>3</sup> )
Oct 6	450 Body	24.4°C	23.0 °C	≥ 15 cm	101.1 kPa	35%	1000
Oct 7	450 Head	22.4°C	23.0 °C	≥ 15 cm	101.1 kPa	35%	1000



## 9.0 SAR SCALING (MANUFACTURER TOLERANCE)

<b>SAR LEVELS SCALED TO MANUF. MAX. UPPER TOLERANCE SPEC.</b>					
Test Config.	Test Freq. (MHz)	Meas. Cond. Pwr. (Watts)	SAR Level 1g (W/kg)	Scaling to 4.8 Watts*	Scaled SAR 1g (W/kg)
Face-held	406.1	4.2	<b>2.85</b>	<b>+ 0.580 dB</b>	<b>3.26</b>
	422.0	4.0	1.79	+0.792 dB	2.15
	438.0	4.0	1.28	+0.792 dB	1.54
	454.0	4.0	1.17	+0.792 dB	1.40
	470.0	4.2	1.50	+ 0.580 dB	1.71
Body-worn	406.1	4.2	<b>4.52</b>	<b>+0.580 dB</b>	<b>5.17</b>
	422.0	4.0	3.12	+0.792 dB	3.74
	438.0	4.0	3.13	+0.792 dB	3.76
	454.0	4.0	2.49	+0.792 dB	2.99
	470.0	4.2	2.59	+ 0.580 dB	2.96

Notes:

- \* Manufacturer's rated power & maximum upper tolerance specification is 4 W +0.8 W.
- The SAR levels reported are based on 50% PTT duty factor including SAR droop.
  - The scaled SAR levels are below the FCC/IC Occupational SAR Limit of 8.0 W/kg.

## 10.0 SIMULTANEOUS TRANSMISSION ASSESSMENT

Co-transmitting Antennas: External UHF and Internal Bluetooth  
 Max. Rated Output Power: < 5 mW (Bluetooth)  
 Antenna-to-Antenna Distance: 34 mm  
 Antenna-to-User Distance: < 5 cm

### Summary

- The closest antenna-to-antenna separation distance is < 5 cm (FCC KDB 447498 D01v04 Section 3)b)ii)(1)(a)).
- Assessment of the DUT for simultaneous transmission was evaluated under the provision of FCC KDB 447498 D01v04 Section 4) d) (see reference [5]) whereby the applicable criteria of FCC KDB 648474 D01v01r05 Section 4, Footnote 12 (see reference [8]) was applied as shown below.

MAX. SAR LEVEL (UHF ANTENNA)		CO-TX SAR LEVEL (BLUETOOTH)	SUM OF 1-g SAR (UHF + BLUETOOTH)	SAR LIMIT (Controlled Exposure)
Body	4.52 W/kg (1g)	0 <sup>1</sup>	4.52 W/kg (1g)	8.0 W/kg (1g)
<b>Note(s)</b>				
1. When stand-alone 1-g SAR is not required for a transmitter or antenna; for example, when the antenna is between 2.5 and 5.0 cm from other antennas, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements (FCC KDB 648474 D01v01r05 Section 4., Footnote 12).				
2. Stand-alone SAR evaluation was not required for the unlicensed Bluetooth transmitter based on the output power is < 12 mW P <sub>Ref</sub> (FCC KDB 648474 D01v01r05, Section 3.).				
3. The UHF SAR level reported in the above table is based on a 50% PTT duty factor including SAR droop.				





## 11.0 FLUID DIELECTRIC PARAMETERS

FLUID DIELECTRIC PARAMETERS						
Date: 10/06/2010		Frequency: 450 MHz			Tissue: Body	
Freq	Test_e	Test_s	450MHz Target	450MHz Target	Deviation Permittivity	Deviation Conductivity
0.4	58.56	0.93	56.7	0.94	3.28%	-1.06%
0.4061*	58.6	0.94	56.7	0.94	3.35%	0.00%
0.41	58.19	0.92	56.7	0.94	2.63%	-2.13%
0.42	58.45	0.95	56.7	0.94	3.09%	1.06%
0.422*	58.5	0.94	56.7	0.94	3.17%	0.00%
0.43	58.29	0.96	56.7	0.94	2.80%	2.13%
0.438*	58.2	0.95	56.7	0.94	2.65%	1.06%
0.44	58.22	0.95	56.7	0.94	2.68%	1.06%
0.45	58.56	0.96	56.7	0.94	3.28%	2.13%
0.454*	58.1	0.96	56.7	0.94	2.47%	2.13%
0.46	58.05	0.96	56.7	0.94	2.38%	2.13%
0.47	57.91	0.98	56.7	0.94	2.13%	4.26%
0.48	57.88	0.99	56.7	0.94	2.08%	5.32%

FLUID DIELECTRIC PARAMETERS						
Date: 10/07/2010		Frequency: 450 MHz			Tissue: Head	
Freq	Test_e	Test_s	450MHz Target	450MHz Target	Deviation Permittivity	Deviation Conductivity
0.4	45.62	0.87	43.5	0.87	4.87%	0.00%
0.4061*	45.4	0.87	43.5	0.87	4.37%	0.00%
0.41	45.07	0.87	43.5	0.87	3.61%	0.00%
0.42	45.07	0.87	43.5	0.87	3.61%	0.00%
0.422*	45.4	0.87	43.5	0.87	4.37%	0.00%
0.43	43.95	0.87	43.5	0.87	1.03%	0.00%
0.438*	44	0.88	43.5	0.87	1.15%	1.15%
0.44	43.94	0.88	43.5	0.87	1.01%	1.15%
0.45	44	0.9	43.5	0.87	1.15%	3.45%
0.454*	43.8	0.9	43.5	0.87	0.69%	3.45%
0.46	43.77	0.91	43.5	0.87	0.62%	4.60%
0.47	43.12	0.91	43.5	0.87	-0.87%	4.60%
0.48	43.52	0.91	43.5	0.87	0.05%	4.60%

\*Note: Interpolated Values using DASY4 Software


	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	



## 12.0 DETAILS OF SAR EVALUATION

- The face-held SAR evaluations were performed with the front keypad side of the radio placed parallel to the outer surface of the planar phantom. A 2.5 cm spacing was maintained between the front side of the DUT and the outer surface of the planar phantom.
- The body-worn SAR evaluations were performed with the belt-clip accessory attached to the DUT and touching the outer surface of the planar phantom with the DUT battery parallel to the planar phantom. The SAR evaluations were performed with the supplied speaker-microphone audio accessory connected to the audio connector of the DUT. The supplied earpiece audio accessory was connected to the supplied speaker-microphone for the duration of the tests.
- The area scan evaluation was performed with a fully charged battery. After the area scan was completed the radio was cooled down and the battery was replaced with a fully charged battery prior to the zoom scan evaluation.
- The SAR drift of the DUT during the SAR evaluations was measured by the DASY4 system.
- A SAR-versus-Time power droop evaluation was performed in the test configuration that reported the maximum scaled SAR level (body-worn). See Appendix A (SAR Test Plots) for SAR-versus-Time power droop evaluation plot.
- The fluid temperature was measured prior to and after the SAR evaluations. The fluid temperature remained within +/-2°C for the duration of the SAR evaluations.
- The dielectric parameters of the simulated tissue mixtures were measured prior to the SAR evaluations using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).
- The DUT was tested at the maximum conducted output power level preset by the manufacturer in unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle) with the transmit key constantly depressed. For a push-to-talk device the 50% duty cycle compensation reported assumes a transmit/receive cycle of equal time base.
- The SAR evaluations were performed within 24 hours of the system performance check.
- FCC PTT SAR test reduction considerations (KDB 447498 D01v04, Section 6 - see reference [7]) were not applied to the SAR evaluation of this device.

## 13.0 EVALUATION PROCEDURES

- The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
  - For body-worn and face-held devices a planar phantom was used.
- The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.  
An area scan was determined as follows:
- Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.  
A 1g and 10g spatial peak SAR was determined as follows:
- Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix F). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
- A zoom scan volume of 32 mm x 32 mm x 30 mm (5 x 5 x 7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7 x 7 x 7) to ensure complete capture of the peak spatial-average SAR.

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 10 of 52


	Date(s) of Evaluation October 06-07, 2010	Test Report Serial No. 100410LEA-T1055-S90U	Test Report Revision No. Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	Test Report Issue Date October 28, 2010	Description of Test(s) Specific Absorption Rate	RF Exposure Category Occupational (Controlled)	


## 14.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluations a daily system check was performed with a planar phantom and 450 MHz SPEAG dipole (see Appendix B for system performance check test plots) in accordance with the procedures described in IEEE Standard 1528-2003 (see reference [5]) and IEC Standard 62209-1:2005 (see reference [6]). The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C for measured fluid dielectric parameters). A forward power of 398 mW was applied to the dipole and the system was verified to a tolerance of  $\pm 10\%$  from the system manufacturer's dipole calibration target SAR value (see Appendix E for system manufacturer's dipole calibration procedures). The SAR evaluations were performed within 24 hours of the system performance check.

### SYSTEM PERFORMANCE CHECK EVALUATION


Test Date	Equiv. Tissue Freq. (MHz)	SAR 1g (W/kg)			Dielectric Constant $\epsilon_r$			Conductivity $\sigma$ (mho/m)			$\rho$ (Kg/m <sup>3</sup> )	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
		SPEAG Target	Meas.	Dev.	SPEAG Target	Meas.	Dev.	SPEAG Target	Meas.	Dev.						
Oct 6	Body 450	1.78 $\pm 10\%$	1.91	+7.3%	56.7 $\pm 5\%$	58.6	+3.4%	0.94 $\pm 5\%$	0.96	+2.1%	1000	24.3	22.9	$\geq 15$	35	101.1
Notes	1.	The target SAR values are the measured values from the dipole calibration performed by SPEAG (see Appendix E).														
	2.	The target dielectric parameters are the nominal values from the dipole calibration performed by SPEAG (see Appendix E).														
	3.	The fluid temperature was measured prior to and after the SAR evaluations. The fluid temperature remained within $\pm 2^\circ\text{C}$ for the duration of the SAR evaluations.														
	4.	The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using a Dielectric Probe Kit and a Network Analyzer (see Appendix C).														







**System Performance Check Measurement Setup (IEEE Standard 1528-2003)**

**SPEAG 450 MHz Validation Dipole Setup**

Applicant:	Unication Co., Ltd.	FCC ID:	LEA-U3-UHF-MID	IC:	3819A-U3UHF MID	 Unication
DUT Type:	Portable UHF PTT Radio Transceiver	Device Model(s):	U3UHF MID	406.1 - 470 MHz		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.			Page 11 of 52	

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


## 15.0 SIMULATED EQUIVALENT TISSUES



The simulated equivalent tissue recipes in the table below are derived from the SAR system manufacturer's suggested recipes in the DASY4 manual (see references [10] and [11]) in accordance with the procedures and requirements specified in IEEE Standard 1528-2003 (see reference [5]) and IEC Standard 62209-1:2005 (see reference [6]). The ingredient percentage may have been adjusted minimally in order to achieve the appropriate target dielectric parameters within the specified tolerance.

SIMULATED TISSUE MIXTURES		
INGREDIENT	450 MHz HEAD	450 MHz BODY
Water	38.56 %	52.00 %
Sugar	56.32 %	45.65 %
Salt	3.95 %	1.75 %
HEC	0.98 %	0.50 %
Bactericide	0.19 %	0.10 %

## 16.0 SAR LIMITS


SAR RF EXPOSURE LIMITS			
FCC 47 CFR 2.1093	Health Canada Safety Code 6	(General Population / Uncontrolled Exposure)	(Occupational / Controlled Exposure)
Spatial Average (averaged over the whole body)		0.08 W/kg	0.4 W/kg
Spatial Peak (averaged over any 1 g of tissue)		1.6 W/kg	<b>8.0 W/kg</b>
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)		4.0 W/kg	20.0 W/kg
The Spatial Average value of the SAR averaged over the whole body.			
The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.			
Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.			
Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.			



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 12 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## 17.0 ROBOT SYSTEM SPECIFICATIONS

<u>Specifications</u>	
<b>Positioner</b>	Stäubli Unimation Corp. Robot Model: RX60L
<b>Repeatability</b>	0.02 mm
<b>No. of axis</b>	6
<u>Data Acquisition Electronic (DAE) System</u>	
<u>Cell Controller</u>	
<b>Processor</b>	AMD Athlon XP 2400+
<b>Clock Speed</b>	2.0 GHz
<b>Operating System</b>	Windows XP Professional
<u>Data Converter</u>	
<b>Features</b>	Signal Amplifier, multiplexer, A/D converter, and control logic
<b>Software</b>	Measurement Software: DASY4, V4.7 Build 44
	Postprocessing Software: SEMCAD, V1.8 Build 171
<b>Connecting Lines</b>	Optical downlink for data and status info., Optical uplink for commands and clock
<u>DASY4 Measurement Server</u>	
<b>Function</b>	Real-time data evaluation for field measurements and surface detection
<b>Hardware</b>	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
<b>Connections</b>	COM1, COM2, DAE, Robot, Ethernet, Service Interface
<u>E-Field Probe</u>	
<b>Model</b>	ET3DV6
<b>Serial No.</b>	1590
<b>Construction</b>	Triangular core fiber optic detection system
<b>Frequency</b>	10 MHz to 6 GHz
<b>Linearity</b>	±0.2 dB (30 MHz to 3 GHz)
<u>Evaluation Phantom</u>	
<b>Type</b>	Side Planar Phantom
<b>Shell Material</b>	Plexiglas
<b>Bottom Thickness</b>	2.0 mm ± 0.1 mm
<b>Inner Dimensions</b>	72.6 cm (L) x 20.3 cm (W) x 20.3 cm (H)
<u>Validation Phantom</u>	
<b>Type</b>	Barski Planar Phantom
<b>Shell Material</b>	Fiberglass
<b>Thickness</b>	2.0 ±0.1 mm
<b>Volume</b>	Approx. 70 liters

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 13 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## 18.0 PROBE SPECIFICATION (ET3DV6)

**Construction:** Symmetrical design with triangular core;  
 Built-in shielding against static charges  
 PEEK enclosure material (resistant to organic solvents, glycol)  
**Calibration:** In air from 10 MHz to 2.5 GHz  
 In head simulating tissue at frequencies of 900 MHz  
 and 1.8 GHz (accuracy  $\pm 8\%$ )  
**Frequency:** 10 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)  
**Directivity:**  $\pm 0.2$  dB in head tissue (rotation around probe axis)  
 $\pm 0.4$  dB in head tissue (rotation normal to probe axis)  
**Dynamic Range:** 5  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB  
**Surface Detect:**  $\pm 0.2$  mm repeatability in air and clear liquids over diffuse reflecting surfaces  
**Dimensions:** Overall length: 330 mm; Tip length: 16 mm;  
 Body diameter: 12 mm; Tip diameter: 6.8 mm  
 Distance from probe tip to dipole centers: 2.7 mm  
**Application:** General dosimetry up to 3 GHz; Compliance tests of mobile phone



## 19.0 SIDE PLANAR PHANTOM

The side planar phantom is constructed of Plexiglas material with a 2.0 mm shell thickness for face-held and body-worn SAR evaluations of portable radio transceivers. The side planar phantom is mounted on the side of the DASY4 compact system table.




## 20.0 BARSKI PLANAR PHANTOM


The Barski Planar Phantom is a fiberglass shell phantom with a 2.0 mm (+/-0.2mm) thick device measurement area at the center of the phantom for SAR evaluations of devices with a larger surface area than the planar section of the SAM phantom. The planar phantom is integrated in a wooden table. The planar phantom is used for DUT SAR evaluations and system performance check evaluations. See Appendix G for dimensions and specifications of the Barski Planar Phantom.





## 21.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.




<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 14 of 52





	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## 22.0 TEST EQUIPMENT LIST

TEST EQUIPMENT		ASSET NO.	SERIAL NO.	DATE CALIBRATED	CALIBRATION INTERVAL
USED	DESCRIPTION				
x	Schmid & Partner DASY4 System	-	-	-	-
x	-DASY4 Measurement Server	00158	1078	CNR	CNR
x	-Robot	00046	599396-01	CNR	CNR
x	-DAE4	00019	353	27Apr10	Annual
x	-ET3DV6 E-Field Probe	00017	1590	15Jul10	Annual
x	-SPEAG D450V3 Validation Dipole	00217	1068	18Jan10	Biennial
x	Side Planar Phantom	00156	161	CNR	CNR
x	Barski Planar Phantom	00155	03-01	CNR	CNR
x	HP 85070C Dielectric Probe Kit	00033	none	CNR	CNR
x	Gigatronics 8652A Power Meter	00007	1835272	04May10	Biennial
x	Gigatronics 80701A Power Sensor	00014	1833699	04May10	Biennial
x	HP 8753ET Network Analyzer	00134	US39170292	04May10	Biennial
x	Rohde & Schwarz SMR20 Signal Generator	00006	100104	CNR	CNR
x	Amplifier Research 5S1G4 Power Amplifier	00106	26235	CNR	CNR
Abbr.	CNR = Calibration Not Required				

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 15 of 52




	Date(s) of Evaluation October 06-07, 2010	Test Report Serial No. 100410LEA-T1055-S90U	Test Report Revision No. Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	Test Report Issue Date October 28, 2010	Description of Test(s) Specific Absorption Rate	RF Exposure Category Occupational (Controlled)	



## 23.0 MEASUREMENT UNCERTAINTIES

UNCERTAINTY BUDGET FOR DEVICE EVALUATION									
Uncertainty Component	IEEE 1528 Section	Uncertainty Value $\pm\%$	Probability Distribution	Divisor	ci 1g	ci 10g	Uncertainty Value $\pm\%$ (1g)	Uncertainty Value $\pm\%$ (10g)	$V_i$ or $V_{eff}$
<b>Measurement System</b>									
Probe Calibration (450 MHz)	E.2.1	6.65	Normal	1	1	1	6.65	6.65	$\infty$
Axial Isotropy	E.2.2	4.7	Rectangular	1.732050808	0.7	0.7	1.9	1.9	$\infty$
Hemispherical Isotropy	E.2.2	9.6	Rectangular	1.732050808	0.7	0.7	3.9	3.9	$\infty$
Boundary Effect	E.2.3	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
Linearity	E.2.4	4.7	Rectangular	1.732050808	1	1	2.7	2.7	$\infty$
System Detection Limits	E.2.5	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
Readout Electronics	E.2.6	0.3	Normal	1	1	1	0.3	0.3	$\infty$
Response Time	E.2.7	0.8	Rectangular	1.732050808	1	1	0.5	0.5	$\infty$
Integration Time	E.2.8	2.6	Rectangular	1.732050808	1	1	1.5	1.5	$\infty$
RF Ambient Conditions	E.6.1	3	Rectangular	1.732050808	1	1	1.7	1.7	$\infty$
Probe Positioner Mechanical Tolerance	E.6.2	0.4	Rectangular	1.732050808	1	1	0.2	0.2	$\infty$
Probe Positioning wrt Phantom Shell	E.6.3	2.9	Rectangular	1.732050808	1	1	1.7	1.7	$\infty$
Extrapolation, interpolation & integration algorithms for max. SAR evaluation	E.5	1	Rectangular	1.732050808	1	1	0.6	0.6	$\infty$
<b>Test Sample Related</b>									
Test Sample Positioning	E.4.2	2.9	Normal	1	1	1	2.9	2.9	12
Device Holder Uncertainty	E.4.1	3.6	Normal	1	1	1	3.6	3.6	8
SAR Drift Measurement	6.6.2	5	Rectangular	1.732050808	1	1	2.9	2.9	$\infty$
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty	E.3.1	4	Rectangular	1.732050808	1	1	2.3	2.3	$\infty$
Liquid Conductivity (target)	E.3.2	5	Rectangular	1.732050808	0.64	0.43	1.8	1.2	$\infty$
Liquid Conductivity (measured)	E.3.3	4.6	Normal	1	0.64	0.43	2.9	2.0	$\infty$
Liquid Permittivity (target)	E.3.2	5	Rectangular	1.732050808	0.6	0.49	1.7	1.4	$\infty$
Liquid Permittivity (measured)	E.3.3	4.37	Normal	1	0.6	0.49	2.6	2.1	$\infty$
<b>Combined Standard Uncertainty</b>			<b>RSS</b>				<b>11.69</b>	<b>11.26</b>	
<b>Expanded Uncertainty (95% Confidence Interval)</b>			<b>k=2</b>				<b>23.38</b>	<b>22.52</b>	

**Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003**


This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 16 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


## 24.0 REFERENCES



- [1] Federal Communications Commission - "Radiofrequency radiation exposure evaluation: portable devices"; Rule Part 47 CFR §2.1093.
- [2] Health Canada - "Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz", Safety Code 6: 1999.
- [3] Federal Communications Commission - "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [4] Industry Canada - "Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)", Radio Standards Specification RSS-102 Issue 4: March 2010.
- [5] IEEE Standard 1528-2003 - "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": December 2003.
- [6] IEC International Standard 62209-1:2005 - "Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures."
- [7] Federal Communications Commission, Office of Engineering and Technology - "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies"; KDB 447498 D01 v04: November 2009.
- [8] Federal Communications Commission, Office of Engineering and Technology - "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas"; KDB 648474 D01v01r05: September 2008.
- [9] Federal Communications Commission, Office of Engineering and Technology - "Application Note: SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz - 3 GHz"; KDB 450824 D01 v01r01: January 2007.
- [10] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 16 Application Note, Head Tissue Recipe: Sept. 2005.
- [11] Schmid & Partner Engineering AG - DASY4 Manual V4.6, Chapter 17 Application Note, Body Tissue Recipe: Sept. 2005.
- [12] ISO/IEC 17025 - "General requirements for the competence of testing and calibration laboratories (ISO/IEC 17025:2005)."
- [13] Federal Communications Commission - "Measurements Required: RF Power Output"; Rule Part 47 CFR §2.1046.
- [14] Industry Canada - "General Requirements and Information for the Certification of Radiocommunication Equipment", Radio Standards Specification RSS-Gen Issue 2: June 2007.

<b>Applicant:</b>	<b>Unication Co., Ltd.</b>	<b>FCC ID:</b>	<b>LEA-U3-UHF-MID</b>	<b>IC:</b>	<b>3819A-U3UHF MID</b>	 Unication
<b>DUT Type:</b>	<b>Portable UHF PTT Radio Transceiver</b>	<b>Device Model(s):</b>	<b>U3UHF MID</b>	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 17 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX A - SAR MEASUREMENT DATA**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 18 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/07/2010

## Face-held SAR - 406.1 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**

Ambient Temp: 22.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 406.1 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 406.1 \text{ MHz}$ ;  $\sigma = 0.87 \text{ mho/m}$ ;  $\epsilon_r = 45.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 5.15 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 81.9 V/m; Power Drift = -0.463 dB

Peak SAR (extrapolated) = 6.96 W/kg


**SAR(1 g) = 5.12 mW/g; SAR(10 g) = 3.85 mW/g**



Maximum value of SAR (measured) = 5.34 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 19 of 52

## Z-Axis Scan



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/07/2010

## Face-held SAR - 422.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**

Ambient Temp: 22.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 422 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 422 \text{ MHz}$ ;  $\sigma = 0.87 \text{ mho/m}$ ;  $\epsilon_r = 45.4$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 3.33 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 65.3 V/m; Power Drift = -0.347 dB



Peak SAR (extrapolated) = 4.42 W/kg

**SAR(1 g) = 3.3 mW/g; SAR(10 g) = 2.5 mW/g**

Maximum value of SAR (measured) = 3.43 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 21 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/07/2010

## Face-held SAR - 438.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**

Ambient Temp: 22.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 438 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 438 \text{ MHz}$ ;  $\sigma = 0.879 \text{ mho/m}$ ;  $\epsilon_r = 44$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.33 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 55.0 V/m; Power Drift = -0.256 dB

Peak SAR (extrapolated) = 3.24 W/kg



**SAR(1 g) 2.41 mW/g; SAR(10 g) = 1.82 mW/g**

Maximum value of SAR (measured) = 2.52 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 22 of 52



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/07/2010

## Face-held SAR - 454.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**

Ambient Temp: 22.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 454 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used (interpolated):  $f = 454 \text{ MHz}$ ;  $\sigma = 0.901 \text{ mho/m}$ ;  $\epsilon_r = 43.8$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.00 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 51.9 V/m; Power Drift = -0.225 dB



Peak SAR (extrapolated) = 3.00 W/kg

**SAR(1 g) 2.22 mW/g; SAR(10 g) = 1.69 mW/g**

Maximum value of SAR (measured) = 2.33 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 23 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/07/2010

## Face-held SAR - 470.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**

Ambient Temp: 22.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 470 MHz; Duty Cycle: 1:1

Medium: HSL450 Medium parameters used:  $f = 470 \text{ MHz}$ ;  $\sigma = 0.91 \text{ mho/m}$ ;  $\epsilon_r = 43.1$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.25, 7.25, 7.25); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Face-held SAR - 2.5 cm Spacing from Front of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.22 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 57.6 V/m; Power Drift = -0.635 dB



Peak SAR (extrapolated) = 3.52 W/kg

**SAR(1 g) 2.59 mW/g; SAR(10 g) = 1.97 mW/g**

Maximum value of SAR (measured) = 2.71 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 24 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

## Body-worn SAR - 406.1 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**  
**Body-worn Accessory: Belt-Clip (P/N: 2160-01003)**  
**Audio Accessory: Speaker-Microphone (P/N: 7106-00009-02) with Earpiece (P/N: 7106-00010)**

Ambient Temp: 24.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 406.1 MHz; Duty Cycle: 1:1

Medium: MSL450 Medium parameters used (interpolated):  $f = 406.1 \text{ MHz}$ ;  $\sigma = 0.94 \text{ mho/m}$ ;  $\epsilon_r = 58.6$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 1.3 cm Belt-Clip Spacing from Back of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 8.87 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 74.8 V/m; Power Drift = -0.207 dB

Peak SAR (extrapolated) = 12.8 W/kg


**SAR(1 g) = 8.61 mW/g; SAR(10 g) = 6.06 mW/g**



Maximum value of SAR (measured) = 9.08 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 25 of 52

**Z-Axis Scan**



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

## Body-worn SAR - 422.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**  
**Body-worn Accessory: Belt-Clip (P/N: 2160-01003)**  
**Audio Accessory: Speaker-Microphone (P/N: 7106-00009-02) with Earpiece (P/N: 7106-00010)**

Ambient Temp: 24.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 422 MHz; Duty Cycle: 1:1

Medium: MSL450 Medium parameters used (interpolated):  $f = 422 \text{ MHz}$ ;  $\sigma = 0.936 \text{ mho/m}$ ;  $\epsilon_r = 58.5$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 1.3 cm Belt-Clip Spacing from Back of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 7.04 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 62.4 V/m; Power Drift = -0.097 dB



Peak SAR (extrapolated) = 8.99 W/kg

**SAR(1 g) = 6.09 mW/g; SAR(10 g) = 4.31 mW/g**

Maximum value of SAR (measured) = 6.39 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 27 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

## Body-worn SAR - 438.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**  
**Body-worn Accessory: Belt-Clip (P/N: 2160-01003)**  
**Audio Accessory: Speaker-Microphone (P/N: 7106-00009-02) with Earpiece (P/N: 7106-00010)**

Ambient Temp: 24.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 438 MHz; Duty Cycle: 1:1

Medium: MSL450 Medium parameters used (interpolated):  $f = 438 \text{ MHz}$ ;  $\sigma = 0.95 \text{ mho/m}$ ;  $\epsilon_r = 58.2$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 1.3 cm Belt-Clip Spacing from Back of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 5.23 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 76.0 V/m; Power Drift = -0.526 dB



Peak SAR (extrapolated) = 8.37 W/kg

**SAR(1 g) = 5.54 mW/g; SAR(10 g) = 3.86 mW/g**

Maximum value of SAR (measured) = 5.83 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 28 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

### Body-worn SAR - 454.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**  
**Body-worn Accessory: Belt-Clip (P/N: 2160-01003)**  
**Audio Accessory: Speaker-Microphone (P/N: 7106-00009-02) with Earpiece (P/N: 7106-00010)**

Ambient Temp: 24.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 454 MHz; Duty Cycle: 1:1

Medium: MSL450 Medium parameters used (interpolated):  $f = 454 \text{ MHz}$ ;  $\sigma = 0.957 \text{ mho/m}$ ;  $\epsilon_r = 58.1$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 1.3 cm Belt-Clip Spacing from Back of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 4.46 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 70.8 V/m; Power Drift = -0.336 dB

Peak SAR (extrapolated) = 7.07 W/kg



**SAR(1 g) = 4.61 mW/g; SAR(10 g) = 3.18 mW/g**

Maximum value of SAR (measured) = 4.77 mW/g



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 29 of 52



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

## Body-worn SAR - 470.0 MHz

**DUT: Unication U3UHF MID; Type: Portable UHF PTT Radio Transceiver; Serial: BUGBCAT2226**  
**Body-worn Accessory: Belt-Clip (P/N: 2160-01003)**  
**Audio Accessory: Speaker-Microphone (P/N: 7106-00009-02) with Earpiece (P/N: 7106-00010)**

Ambient Temp: 24.4°C; Fluid Temp: 23.0°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 470 MHz; Duty Cycle: 1:1

Medium: MSL450 Medium parameters used:  $f = 470 \text{ MHz}$ ;  $\sigma = 0.98 \text{ mho/m}$ ;  $\epsilon_r = 57.9$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Side Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### Body-worn SAR - 1.3 cm Belt-Clip Spacing from Back of DUT to Side Planar Phantom

**Area Scan (8x21x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 5.17 mW/g


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=7.5\text{mm}$ ,  $dy=7.5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 67.6 V/m; Power Drift = -0.495 dB

Peak SAR (extrapolated) = 6.99 W/kg

**SAR(1 g) 4.62 mW/g; SAR(10 g) = 3.22 mW/g**


Maximum value of SAR (measured) = 4.87 mW/g





<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 30 of 52

## SAR-versus-Time Droop Evaluation


Body-worn Configuration  
 Test Freq: 470.0 MHz





Start SAR: 5.655 mW/g  
 SAR after 500s: 5.311 mW/g (-0.273 dB)  
 SAR after 340s: 5.401 mW/g (-0.200 dB)

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX B - SYSTEM PERFORMANCE CHECK**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 32 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

Date Tested: 10/06/2010

## System Performance Check - 450 MHz Dipole - Body

**DUT: Dipole 450 MHz; Type: D450V3; Serial: 1068; Calibrated: 18/01/2010**

Ambient Temp: 24.3°C; Fluid Temp: 22.9°C; Barometric Pressure: 101.1 kPa; Humidity: 35%

Communication System: CW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: 450 MSL Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 58.6$ ;  $\rho = 1000 \text{ kg/m}^3$

- Probe: ET3DV6 - SN1590; ConvF(7.73, 7.73, 7.73); Calibrated: 15/07/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 27/04/2010
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

### System Performance Check - 450 MHz Dipole

**Head/d=15mm, Pin = 398mW**

**Area Scan (6x11x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.97 mW/g


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 45.1 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 3.06 W/kg


**SAR(1 g) = 1.91 mW/g; SAR(10 g) = 1.27 mW/g**



Maximum value of SAR (measured) = 2.03 mW/g




<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 33 of 52



### Z-Axis Scan



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 35 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


### 450 MHz Body



\*\*\*\*\*

Celltech Labs Inc.  
Test Result for UIM Dielectric Parameter  
06/Oct/2010  
Frequency (GHz)  
FCC\_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon  
FCC\_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma  
FCC\_eB FCC Limits for Body Epsilon  
FCC\_sB FCC Limits for Body Sigma  
Test\_e Epsilon of UIM  
Test\_s Sigma of UIM

\*\*\*\*\*

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.3500	57.70	0.93	59.51	0.89
0.3600	57.60	0.93	58.67	0.89
0.3700	57.50	0.93	58.90	0.90
0.3800	57.40	0.93	58.98	0.92
0.3900	57.30	0.93	59.08	0.93
0.4000	57.20	0.93	58.56	0.93
0.4100	57.10	0.93	58.19	0.92
0.4200	57.00	0.94	58.45	0.95
0.4300	56.90	0.94	58.29	0.96
0.4400	56.80	0.94	58.22	0.95
0.4500	56.70	0.94	58.56	0.96
0.4600	56.66	0.94	58.05	0.96
0.4700	56.62	0.94	57.91	0.98
0.4800	56.58	0.94	57.88	0.99
0.4900	56.54	0.94	57.27	1.00
0.5000	56.51	0.94	57.31	1.02
0.5100	56.47	0.94	57.69	1.01
0.5200	56.43	0.95	56.92	1.03
0.5300	56.39	0.95	57.15	1.03
0.5400	56.35	0.95	57.38	1.05
0.5500	56.31	0.95	57.22	1.05

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 36 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


### 450 MHz Head

\*\*\*\*\*



Celltech Labs Inc.  
Test Result for UIM Dielectric Parameter  
07/Oct/2010  
Frequency (GHz)  
FCC\_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon  
FCC\_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma  
Test\_e Epsilon of UIM  
Test\_s Sigma of UIM

\*\*\*\*\*


Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.3500	44.70	0.87	46.25	0.82
0.3600	44.58	0.87	46.18	0.83
0.3700	44.46	0.87	46.07	0.84
0.3800	44.34	0.87	46.18	0.86
0.3900	44.22	0.87	45.22	0.85
0.4000	44.10	0.87	45.62	0.87
0.4100	43.98	0.87	45.07	0.87
0.4200	43.86	0.87	45.07	0.87
0.4300	43.74	0.87	43.95	0.87
0.4400	43.62	0.87	43.94	0.88
0.4500	43.50	0.87	44.00	0.90
0.4600	43.45	0.87	43.77	0.91
0.4700	43.40	0.87	43.12	0.91
0.4800	43.34	0.87	43.52	0.91
0.4900	43.29	0.87	43.09	0.93
0.5000	43.24	0.87	42.91	0.93
0.5100	43.19	0.87	42.97	0.95
0.5200	43.14	0.88	42.41	0.96
0.5300	43.08	0.88	42.12	0.95
0.5400	43.03	0.88	42.68	0.97
0.5500	42.98	0.88	42.33	0.99



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 37 of 52



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX D - SAR TEST SETUP & DUT PHOTOGRAPHS**



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 38 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


**FACE-HELD SAR TEST SETUP PHOTOGRAPHS**




Face-held Configuration - DUT with 2.5 cm spacing from front keypad side of radio to planar phantom

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**FACE-HELD SAR TEST SETUP PHOTOGRAPHS**



**DUT with Detachable Whip Antenna P/N: 7100-02011**



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 40 of 52




**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**




**Body-worn Configuration - DUT with Belt-Clip Accessory & Speaker-Microphone with Earpiece Audio Accessory**

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**





**DUT with Detachable Whip Antenna P/N: 7100-02011 - Battery Parallel to Planar Phantom**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 42 of 52





	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**DUT PHOTOGRAPHS**



**Left Side of DUT with Belt-Clip accessory**




**Right Side of DUT with Belt-Clip accessory**





**Bottom end of DUT with Belt-Clip accessory**



**Top end of DUT with Belt-Clip accessory**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 44 of 52



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	


**DUT PHOTOGRAPHS**





**Belt-Clip Thickness Measurement**




**Side view of DUT with Belt-Clip Accessory & Detachable Whip Antenna**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 45 of 52



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**DUT PHOTOGRAPHS**




<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 46 of 52





	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

## DUT PHOTOGRAPHS



<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 47 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	



**DUT PHOTOGRAPHS**



**Front of DUT with Speaker-Microphone (P/N: 7106-00009-02) and Earpiece (P/N: 7106-00010) audio accessories**




**Back of DUT with Speaker-Microphone (P/N: 7106-00009-02) and Earpiece (P/N: 7106-00010) audio accessories**



	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**DUT PHOTOGRAPHS**




**U3 Basic Remote Speaker-Microphone Audio Accessory (P/N: 7106-00009-02)**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 49 of 52

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX E - DIPOLE CALIBRATION**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 50 of 52



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No.: **D450V3-1068 Jan10**

## CALIBRATION CERTIFICATE

Object **D450V3 - SN: 1068**

Calibration procedure(s) **QA CAL-15.v5  
Calibration Procedure for dipole validation kits below 800 MHz**

Calibration date: **January 18, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41495277	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41498087	1-Apr-09 (No. 217-01030)	Apr-10
Reference 3 dB Attenuator	SN: S5054 (3c)	31-Mar-09 (No. 217-01026)	Mar-10
Reference 20 dB Attenuator	SN: S5086 (20b)	31-Mar-09 (No. 217-01028)	Mar-10
Type-N mismatch combination	SN: 5047.2 / 06327	31-Mar-09 (No. 217-01029)	Mar-10
Reference Probe ET3DV6 (LF)	SN: 1507	03-Jul-09 (No. ET3-1507_Jul09)	Jul-10
DAE4	SN: 654	04-May-09 (No. DAE4-654_May09)	May-10
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	04-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-09)	In house check: Oct-10

Calibrated by: **Jeton Kastrati**      Function: **Laboratory Technician**      Signature: *i.v. [Signature]*

Approved by: **Katja Pokovic**      Technical Manager      *[Signature]*

Issued: January 20, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.





Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### Glossary:

TSL	tissue simulating liquid
ConF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

### Additional Documentation:

- DASY4 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

<b>DASY Version</b>	DASY5	V5.2
<b>Extrapolation</b>	Advanced Extrapolation	
<b>Phantom</b>	ELI4 Flat Phantom	Shell thickness: $2 \pm 0.2$ mm
<b>Distance Dipole Center - TSL</b>	15 mm	with Spacer
<b>Area Scan Resolution</b>	dx, dy = 15 mm	
<b>Zoom Scan Resolution</b>	dx, dy, dz = 5 mm	
<b>Frequency</b>	450 MHz $\pm$ 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
<b>Nominal Head TSL parameters</b>	22.0 °C	43.5	0.87 mho/m
<b>Measured Head TSL parameters</b>	(22.0 $\pm$ 0.2) °C	44.2 $\pm$ 6 %	0.86 mho/m $\pm$ 6 %
<b>Head TSL temperature during test</b>	(22.0 $\pm$ 0.2) °C	----	----

## SAR result with Head TSL

<b>SAR averaged over 1 cm<sup>3</sup> (1 g) of Head TSL</b>	condition	
SAR measured	398 mW input power	1.87 mW / g
SAR normalized	normalized to 1W	4.70 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>4.76 mW / g <math>\pm</math> 18.1 % (k=2)</b>

<b>SAR averaged over 10 cm<sup>3</sup> (10 g) of Head TSL</b>	condition	
SAR measured	398 mW input power	1.25 mW / g
SAR normalized	normalized to 1W	3.14 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	<b>3.17 mW / g <math>\pm</math> 17.6 % (k=2)</b>

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	56.7	0.94 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.1 ± 6 %	0.90 mho/m ± 6 %
Body TSL temperature during test	(22.0 ± 0.2) °C	----	----

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	condition	
SAR measured	398 mW input power	1.78 mW / g
SAR normalized	normalized to 1W	4.47 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>4.58 mW / g ± 18.1 % (k=2)</b>

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	398 mW input power	1.19 mW / g
SAR normalized	normalized to 1W	2.99 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	<b>3.06 mW / g ± 17.6 % (k=2)</b>

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	57.5 $\Omega$ - 5.9 j $\Omega$
Return Loss	- 21.0 dB

### Antenna Parameters with Body TSL

Impedance, transformed to feed point	54.8 $\Omega$ - 9.3 j $\Omega$
Return Loss	- 20.0 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.350 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	July 16, 2009

# DASY5 Validation Report for Head TSL

Date/Time: 1/18/2010 10:59:37 AM

**DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN:1068**

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450

Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.86$  mho/m;  $\epsilon_r = 44.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ET3DV6 - SN1507 (LF); ConvF(6.66, 6.66, 6.66); Calibrated: 7/3/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 5/4/2009
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Head/d=15mm, Pin=398mW/Area Scan (41x111x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.99 mW/g


**Head/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 50.2 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 2.78 W/kg

**SAR(1 g) = 1.87 mW/g; SAR(10 g) = 1.25 mW/g**

Maximum value of SAR (measured) = 2 mW/g



0 dB = 2mW/g

# Impedance Measurement Plot for Head TSL

18 Jan 2010 10:25:40

CH1 S11 1 U FS

1: 57.502  $\Omega$  -5.9180  $\Omega$  59.763 pF


450.000 000 MHz

\*  
Del

Cor

Avg  
16

↑



CH2 S11 LOG

5 dB/REF -20 dB


1: -21.035 dB

450.000 000 MHz

Cor

Avg  
16

↑



START 250.000 000 MHz

STOP 650.000 000 MHz

# DASY5 Validation Report for Body TSL

Date/Time: 1/18/2010 1:24:11 PM

**DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN:1068**

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium: MSL450

Medium parameters used:  $f = 450 \text{ MHz}$ ;  $\sigma = 0.9 \text{ mho/m}$ ;  $\epsilon_r = 54.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ET3DV6 - SN1507 (LF); ConvF(7.11, 7.11, 7.11); Calibrated: 7/3/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 5/4/2009
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- Measurement SW: DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Body/d=15mm, Pin=398mW/Area Scan (61x201x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 1.9 mW/g


**Body/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 47.4 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 2.71 W/kg

**SAR(1 g) = 1.78 mW/g; SAR(10 g) = 1.19 mW/g**

Maximum value of SAR (measured) = 1.9 mW/g



0 dB = 1.9mW/g



# Impedance Measurement Plot for Body TSL


18 Jan 2010 12:18:41

CH1 S11 1 U FS

1: 54.824  $\Omega$  -9.3047  $\Omega$  38.011 pF

450.000 000 MHz

\*  
Del  
Cor



Avg  
16


↑

CH2 S11 L06 5 dB/REF -20 dB 1:-20.034 dB 450.000 000 MHz

Cor



Avg  
16

↑




START 250.000 000 MHz

STOP 650.000 000 MHz

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX F - PROBE CALIBRATION**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 51 of 52



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech**

Certificate No: **ET3-1590\_Jul10**

## CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1590**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-12.v6, QA CAL-23.v3 and QA CAL-25.v2  
Calibration procedure for dosimetric E-field probes**

Calibration date: **July 15, 2010**



This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	30-Dec-09 (No. ES3-3013_Dec09)	Dec-10
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-09)	In house check: Oct10

Calibrated by	Name <b>Jeton Kastrati</b>	Function <b>Laboratory Technician</b>	Signature 
Approved by:	Name <b>Katja Pokovic</b>	Technical Manager	

Issued: July 15, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization $\varphi$	$\varphi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

**Methods Applied and Interpretation of Parameters:**

- **NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below *ConvF*).
- **NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- **DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- **A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- **ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- **Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- **Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe ET3DV6

## SN:1590

Manufactured:	March 19, 2001
Last calibrated:	July 16, 2009
Recalibrated:	July 15, 2010

Calibrated for DASYS/EASY Systems

(Note: non-compatible with DASYS2 system!)

## DASY/EASY - Parameters of Probe: ET3DV6 SN:1590

### Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup>	1.86	2.06	1.77	$\pm 10.1\%$
DCP (mV) <sup>B</sup>	91.4	92.4	83.5	

### Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc <sup>E</sup> (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	300.0	$\pm 1.5\%$
			Y	0.00	0.00	1.00	300.0	
			Z	0.00	0.00	1.00	300.0	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6)

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying recatangular distribution and is expressed for the square of the field value.

## DASY/EASY - Parameters of Probe: ET3DV6 SN:1590

### Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	43.5 ± 5%	0.87 ± 5%	7.25	7.25	7.25	0.20	2.19 ± 13.3%
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.27	6.27	6.27	0.32	2.49 ± 11.0%
900	± 50 / ± 100	41.5 ± 5%	0.97 ± 5%	6.12	6.12	6.12	0.27	2.86 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

## DASY/EASY - Parameters of Probe: ET3DV6 SN:1590

### Calibration Parameter Determined in Body Tissue Simulating Media


f [MHz]	Validity [MHz] <sup>c</sup>	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	56.7 ± 5%	0.94 ± 5%	7.73	7.73	7.73	0.13	2.06 ± 13.3%
835	± 50 / ± 100	55.2 ± 5%	0.97 ± 5%	6.33	6.33	6.33	0.22	3.60 ± 11.0%
900	± 50 / ± 100	55.0 ± 5%	1.05 ± 5%	6.15	6.15	6.15	0.28	2.94 ± 11.0%

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.





### Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

### Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$ )





Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

### Conversion Factor Assessment



### Deviation from Isotropy in HSL



Error ( $\phi$ ,  $\theta$ ), f = 900 MHz




Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)

## Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	enabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	6.8 mm
Probe Tip to Sensor X Calibration Point	2.7 mm
Probe Tip to Sensor Y Calibration Point	2.7 mm
Probe Tip to Sensor Z Calibration Point	2.7 mm
Recommended Measurement Distance from Surface	4 mm

	<u>Date(s) of Evaluation</u> October 06-07, 2010	<u>Test Report Serial No.</u> 100410LEA-T1055-S90U	<u>Test Report Revision No.</u> Rev. 1.0 (Initial Release)	 Test Lab Certificate No. 2470.01
	<u>Test Report Issue Date</u> October 28, 2010	<u>Description of Test(s)</u> Specific Absorption Rate	<u>RF Exposure Category</u> Occupational (Controlled)	

**APPENDIX G - BARSKI PHANTOM CERTIFICATE OF CONFORMITY**

<b>Applicant:</b>	Unication Co., Ltd.	<b>FCC ID:</b>	LEA-U3-UHF-MID	<b>IC:</b>	3819A-U3UHF MID	 Unication
<b>DUT Type:</b>	Portable UHF PTT Radio Transceiver	<b>Device Model(s):</b>	U3UHF MID	<b>406.1 - 470 MHz</b>		
2010 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 52 of 52

2378 Westlake Road  
Kelowna, B.C. Canada  
V1Z-2V2



Ph. # 250-769-6848  
Fax # 250-769-6334  
E-mail: [barskiind@shaw.ca](mailto:barskiind@shaw.ca)  
Web: [www.bcfiberglass.com](http://www.bcfiberglass.com)

## FIBERGLASS FABRICATORS

### Certificate of Conformity

Item : Flat Planar Phantom Unit # 03-01  
Date: June 16, 2003  
Manufacturer: Barski Industries (1985 Ltd)

Test	Requirement	Details
Shape	Compliance to geometry according to drawing	Supplied CAD drawing
Material Thickness	Compliant with the requirements	2mm +/- 0.2mm in measurement area
Material Parameters	Dielectric parameters for required frequencies Based on Dow Chemical technical data	100 MHz-5 GHz Relative permittivity < 5 Loss Tangent < 0.05

#### Conformity

Based on the above information, we certify this product to be compliant to the requirements specified.

Signature: \_\_\_\_\_

A handwritten signature in black ink, appearing to read 'Daniel Chailier', is written over a horizontal line.

Daniel Chailier





**Fiberglass Planar Phantom - Top View**



**Fiberglass Planar Phantom - Front View**




**Fiberglass Planar Phantom - Back View**



**Fiberglass Planar Phantom - Bottom View**

## Dimensions of Fiberglass Planar Phantom

(Manufactured by Barski Industries Ltd. - Unit# 03-01)



**Note: Measurements that aren't repeated for the opposite sides are the same as the side measured.  
This drawing is not to scale.**