



849 NW STATE ROAD 45
 NEWBERRY, FL 32669 USA
 PH: 888.472.2424 OR 352.472.5500
 FAX: 352.472.2030
 EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

**FCC PART 90
 AND IC RSS-119, RSS-GEN
 TEST REPORT**

APPLICANT	UNIFICATION CO., LTD.
	5F, NO.6, WU-KUNG 5 RD. HSINCHUANG CITY, TAIPEI TAIWAN
FCC ID	LEA-U3-UHF-MID
IC CERTIFICATION	3819A-U3UHF MID
MODEL NUMBER	U3UHF MID
PRODUCT DESCRIPTION	UHF PTT HANDHELD TRANSCEIVER WITH GPS AND BLUETOOTH
DATE SAMPLE RECEIVED	10/4/2010
DATE TESTED	10/26/2010
TESTED BY	Nam Nguyen
APPROVED BY	Mario de Aranzeta
TIMCO REPORT NO.	2352AT10_TestReport_Rev.doc
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
 WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



TABLE OF CONTENTS

GENERAL REMARKS3

GENERAL INFORMATION4

TEST PROCEDURES5

RF POWER OUTPUT6

MODULATION CHARACTERISTICS7

AUDIO FREQUENCY RESPONSE8

AUDIO INPUT VERSUS MODULATION10

OCCUPIED BANDWIDTH11

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)28

FIELD STRENGTH OF SPURIOUS EMISSIONS31

RADIATION INTERFERENCE – CO LOCATION34

RECEIVER RADIATED SPURIOUS EMISSIONS35

FREQUENCY STABILITY37

TRANSIENT FREQUENCY BEHAVIOR38

EQUIPMENT LIST42

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: November 5th, 2010

Applicant: UNICATION CO., LTD.
FCC ID: LEA-U3-UHF-MID
IC CERT #: 3819A-U3UHF MID
Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

GENERAL INFORMATION
DUT Specification

DUT Description	UHF PTT HANDHELD TRANSCEIVER WITH GPS AND BLUETOOTH
FCC ID	LEA-U3-UHF-MID
IC Certification	3819A-U3UHF MID
Model Number	U3UHF MID
Serial Number	N/A
Operating Frequency	406 MHz to 470 MHz
Test Frequencies	(406.125, 436.625, and 469.125) MHz
No. of Channels	16
Type of Emission	Analog: 11K0F3E, 16K0F3E, 5K41F2E, 8K87F2E, 7K60FXE, 7K60FXD, 7K60FXW, 8K17F1E, 8K17F1D Digital: See report
DUT Power Source	<input type="checkbox"/> 110–120Vac/50– 60Hz <input type="checkbox"/> DC Power 12V <input checked="" type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable
Test Conditions	The temperature was 26°C with a relative humidity of 50%.
Modification to the DUT	None
Test Exercise	The DUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-C:2004, FCC CFR 47 Part 90, IC RSS-119, RSS-GEN
Test Facility	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA.

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

TEST PROCEDURES

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-C:2004 using a 50uH LISN. Both lines were observed with the DUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI/TIA 603-C:2004 using an Agilent spectrum receiver with pre-selector. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a micro volt at the output of the antenna.

Applicant: UNICATION CO., LTD.
FCC ID: LEA-U3-UHF-MID
IC CERT #: 3819A-U3UHF MID
Report: Z:\U\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


RF POWER OUTPUT

Rule Part No.: FCC Part 2.1046(a), IC RSS-119 4.1 and 5.4, RSS-GEN 4.8

Test Requirements:

Method of Measurement: RF power is measured by connecting a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage, and the transmitter properly adjusted the RF output measures:

Test Setup Diagram:



Test Data:

OUTPUT POWER: HIGH – 4.0 Watts
 LOW – 1.0 Watts

Part 2.1033 (C)(8) DC Input into the final amplifier (analog mode)

FOR LOW POWER SETTING INPUT POWER: $(7.4V)(0.63A) = 4.7$ Watts
 FOR HIGH POWER SETTING INPUT POWER: $(7.4V)(1.4A) = 10.4$ Watts

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

MODULATION CHARACTERISTICS

Part 2.1033(c)

Part 2.1033(c) (4) Type of Emission: 11K0F3E, 16K0F3E

FCC Part 90.209, IC RSS-119 5.5

FCC Part 90.207

Type of Emission: 11K0F3E

$$B_n = 2M + 2DK$$

$$M = 3000$$

$$D = 2500$$

$$K=1$$

$$B_n = 2(3000)+2(2500) = 11.0k$$

Type of Emission: 16K0F3E

$$B_n = 2M + 2DK$$

$$M = 3000$$

$$D = 5000$$

$$K=1$$

$$B_n = 2(3000)+2(5000) = 16.0k$$

See operational description for detailed information on the other modulation types which are summarized below:

Digital Voice over Analog (DVOA)

5K41F2E

8K87F2E

Uni2TDMA (Digital Voice and Data messaging).

7K60FXE 7K60FXD 7K60FXW

P25 phase 1 (digital modulation)

8K17F1E

8K17F1D

Applicant: UNICATION CO., LTD.
FCC ID: LEA-U3-UHF-MID
IC CERT #: 3819A-U3UHF MID
Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

AUDIO FREQUENCY RESPONSE

Rule Part No.: FCC Part 2.1047(a)(b), IC RSS-119 5.2


Test Requirements:

Method of Measurement:


The audio frequency response was measured in accordance with ANSI/TIA 603-C:2004. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 – 5000Hz shall be submitted. The audio frequency response curve is shown below.

AUDIO FREQUENCY RESPONSE PLOT

12.5 kHz:



25 kHz:




Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

AUDIO LOW PASS FILTER

VOICE MODULATED COMMUNICATION EQUIPMENT

Part 2.1047(a) Voice modulated communication equipment: For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all the circuitry installed between the modulation limiter and the modulated stage shall be submitted.

AUDIO LOW PASS FILTER



Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

AUDIO INPUT VERSUS MODULATION

Rule Part No.: FCC Part 2.1047(b) & 90, IC RSS-119 5.2


Test Requirements:

Method of Measurement: **Modulation cannot exceed 100%**, The audio input level needed for a particular percentage of modulation was measured in accordance with ANSI/TIA 603-C:2004. The audio input curves versus modulation are shown below. Curves are provided for audio input frequencies of 300, 1000, and 2500 Hz.


Test data:

Modulation Limiting Plot

12.5 kHz:



25.0 kHz:



Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

OCCUPIED BANDWIDTH

FCC Part 2.1049(c), RSS-GEN 4.6 EMISSION BANDWIDTH

FCC Part 90.210(b) RSS-119 4.2 Emission Mask B - 25kHz Channel Spacing

For transmitters that are equipped with an audio low pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB.
- (2) On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least $43 + 10\log(P)$ dB.

Part 90.210(c) Emission Mask C - 25 kHz Channel Spacing Not Equipped with a Low Pass Filter

For transmitters that are not equipped with an audio low pass filter pursuant to S90.211 (b), the power of any emission must be attenuated below the un-modulated carrier output power as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5 kHz but not more than 10 kHz: At least $83 \log(f_d/5)$ dB;
- (2) ON any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but not more than 250% of the authorized bandwidth: At least $29 \log(f_d/11)$ dB or 50 dB, whichever is the lesser attenuation;
- (3) On any frequency removed from the center of the authorized bandwidth by more than 250% of the authorized bandwidth: At least $43+10 \log(P_0)$ dB.

Part 90.210(d) Emission Mask D - 12.5 kHz channel BW equipment.

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10\log(P)$ dB or 70 dB, whichever is the lesser attenuation.


Applicant: UNICATION CO., LTD.
FCC ID: LEA-U3-UHF-MID
IC CERT #: 3819A-U3UHF MID
Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

OCCUPIED BANDWIDTH MEASUREMENT

Test procedure: ANSI/TIA-603-C:2004 para 2.2.11.

Test Setup Diagram:

OCCUPIED BANDWIDTH MEASUREMENT



Test Data: See the plots below


12.5 kHz

Analog CTCSS (Tone = 250.3Hz)

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Analog - CTCSS)

FCC 90.210 Mask D




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog CDCSS (Code = 532)

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Analog - CDCSS)

FCC 90.210 Mask D




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog MDC 1200

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Analog - MDC 1200)

FCC 90.210 Mask D




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog None

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Analog - None)

FCC 90.210 Mask D



Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


12.5kHz - DIGITAL

Digital DVOA

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Digital - DVOA)

FCC 90.210 Mask D




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Digital TDMA Voice

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Digital - TDMA Voice)

FCC 90.210 Mask D




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Digital ARDS Voice

NOTES:

UNICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Digital - ARDS Voice)

FCC 90.210 Mask D




Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Digital P25 Voice

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 12.5 kHz (Digital - P25 Voice)

FCC 90.210 Mask D



Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


25.0kHz

Analog CTCSS (Tone =250.3 Hz)

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Analog - CTCSS)

FCC 90.210 Mask B




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog CDCSS (Code = 532)

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Analog - CDCSS)

FCC 90.210 Mask B




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog MDC 1200

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Analog - MDC 1200)

FCC 90.210 Mask B




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Analog None

NOTES:

UNICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Analog - None)

FCC 90.210 Mask B



Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


25.0kHz – DIGITAL

Digital DVOA

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Digital - DVOA)

FCC 90.210 Mask B




Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Digital TDMA Voice

NOTES:

UNICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Digital - TDMA Voice)

FCC 90.210 Mask B




Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Digital ARDS Voice

NOTES:

UNIFICATION CO., LTD. - FCC ID: LEA-U3-UHF-MID
 OCCUPIED BANDWIDTH PLOT - 25.0 kHz (Digital - ARDS Voice)

FCC 90.210 Mask B



Applicant: UNIFICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNIFICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)

Rule Part No.: FCC Part 2.1051(a), RSS-GEN 7.1.4

Requirements: 25 kHz Channel Spacing = 49dBc (for 4 Watts)

Method of Measurement: The carrier was modulated 100% using a 2500 Hz tone. The spectrum was scanned from 0.4 to at least the 10th harmonic of the fundamental. The measurements were made in accordance with standard ANSI/TIA 603-C:2004.

FCC Limit for:
 25kHz Channel Spacing = 49
 12.5kHz Spacing = 56

Test Data:

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
406.13	812.25	90.9		406.13	812.25	98.3
	1218.38	90.8			1218.38	89.4
	1624.50	95.2			1624.50	89.7
	2030.63	98.6			2030.63	92.2
	2436.75	NF			2436.75	NF
	2842.88	NF			2842.88	NF
	3249.00	NF			3249.00	NF
	3655.13	NF			3655.13	NF
	4061.25	NF			4061.25	NF

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
436.63	873.25	97.1		436.63	873.25	97.7
	1309.88	92.1			1309.88	88.8
	1746.50	94.4			1746.50	89.7
	2183.13	97.5			2183.13	91.9
	2619.75	NF			2619.75	NF
	3056.38	NF			3056.38	NF
	3493.00	NF			3493.00	NF
	3929.63	NF			3929.63	NF
	4366.25	NF			4366.25	NF


Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

TEST DATA CONTD.

TF HIGH POWER	EF	dB below carrier		TF LOW POWER	EF	dB below carrier
469.13	938.25	98.6		469.13	938.25	98.4
	1407.38	90.1			1407.38	88.9
	1876.50	93.8			1876.50	88
	2345.63	89.9			2345.63	91.7
	2814.75	99.3			2814.75	NF
	3283.88	NF			3283.88	NF
	3753.00	NF			3753.00	NF
	4222.13	NF			4222.13	NF
	4691.25	NF			4691.25	NF

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\U\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

Method of Measuring Conducted Spurious Emissions



METHOD OF MEASUREMENT: The procedure used was ANSI/TIA 603-C:2004. The measurements were made at TIMCO ENGINEERING INC. 849 N.W. State Road 45, Newberry, Florida 32669.

Applicant: UNICATION CO., LTD.
FCC ID: LEA-U3-UHF-MID
IC CERT #: 3819A-U3UHF MID
Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


FIELD STRENGTH OF SPURIOUS EMISSIONS

Rule Parts. No.: FCC Part 2.1053, RSS-GEN 4.9

Requirements: The FCC limits for radiated emissions are the same as previously stated for the conducted emissions.

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-C:2004 using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:



Test Data:

High Power

TF	EF	Ant Polarity	dB below carrier
406.13	812.25	V	81.49
	1218.38	V	94.43
	1624.50	V	90.91
	2030.63	V	94.55
	2436.75	V	93.97
	2842.88	V	96.13
	3249.00	H/V	*
	3655.13	H/V	*
	4061.25	H/V	*

Low Power

TF	EF	Ant Polarity	dB below carrier
406.13	812.25	V	76.59
	1218.38	V	88.43
	1624.50	V	85.01
	2030.63	V	88.05
	2436.75	H	89.47
	2842.88	H/V	*
	3249.00	H/V	*
	3655.13	H/V	*
	4061.25	H/V	*

High Power

TF	EF	Ant Polarity	dB below carrier
436.63	873.25	V	77.81
	1309.88	V	91.28
	1746.50	V	86.87
	2183.13	V	91.13
	2619.75	V	91.07
	3056.38	H/V	*
	3493.00	H/V	*
	3929.63	H/V	*
	4366.25	H/V	*

Low Power

TF	EF	Ant Polarity	dB below carrier
436.63	873.25	V	69.91
	1309.88	V	85.38
	1746.50	V	81.37
	2183.13	V	83.63
	2619.75	V	85.07
	3056.38	H/V	*
	3493.00	H/V	*
	3929.63	H/V	*
	4366.25	H/V	*

* Noise floor

TEST DATA CONTD.

High Power

TF	EF	Ant Polarity	dB below carrier
469.13	938.25	V	68.63
	1407.38	V	92.61
	1876.50	V	88.35
	2345.63	H	91.67
	2814.75	V	95.59
	3283.88	H/V	*
	3753.00	H/V	*
	4222.13	H/V	*
	4691.25	H/V	*

Low Power

TF	EF	Ant Polarity	dB below carrier
469.13	938.25	V	62.73
	1407.38	H	87.94
	1876.50	V	83.76
	2345.63	V	88.26
	2814.75	V	89.86
	3283.88	H/V	*
	3753.00	H/V	*
	4222.13	H/V	*
	4691.25	H/V	*

* Noise floor

RADIATION INTERFERENCE – CO LOCATION

Rules Part No.: 15.247, 15.209, RSS-210

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) μ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) μ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB μ V/m @ 30 meters
30 – 88	40.0 dB μ V/m @ 3 meters
80 – 216	43.5 dB μ V/m @ 3 meters
216 – 960	46.0 dB μ V/m @ 3 meters
Above 960	54.0 dB μ V/m @ 3 meters
Part 15.247	
Fundamental 902 – 928 MHz	127.37 dB μ V/m @ 3 meters
Fundamental 2.4 – 2.4835 MHz	127.37 dB μ V/m @ 3 meters
Harmonics	54.0 dB μ V/m @ 3 meters

Any emissions that fall in the restricted bands (15.205) must be less than or equal to 54 dB μ V/m. Spurious emissions not in a restricted band must be 20 dBc. Harmonics were checked through the 10th harmonic.

Test Data: The U3 is in TX mode for both UHF and Bluetooth.
 All values are peak unless noted.
 Items mark with an * designate a frequency in a restricted band.

The only emissions found were as previously submitted either under 15.247/ RSS-210 or in this report under Part 90/RSS-119 field strength of spurious emissions. No intermodulation products noted.

RECEIVER RADIATED SPURIOUS EMISSIONS

Receiver data as shown below is not part of the FCC certification process. Per FCC Rules Part 15.101(b), the receiver is subject to verification.

The data shown below is part of the IC Certification process only.

Rule Parts. No.: RSS-GEN 4.10, 6

Requirements:

Frequency MHz	Limits
30 – 88	40.0 dBμV/m measured @ 3 meters
88 – 216	43.5 dBμV/m measured @ 3 meters
216 – 960	46.0 dBμV/m measured @ 3 meters
Above 960	54.0 dBμV/m measured @ 3 meters

TEST DATA:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBuV/m	Margin dB
406.1	67.40	5.4	H	0.56	5.51	11.47	28.53
406.1	95.60	13.7	V	0.64	11.50	25.84	17.66
406.1	139.80	8.7	V	0.69	16.05	25.44	18.06
406.1	141.50	11.1	V	0.69	16.37	28.16	15.34
406.1	336.00	4.6	V	1.14	14.56	20.30	25.70
406.1	454.40	5.2	H	1.25	16.86	23.31	22.69
406.1	667.20	4.4	H	1.67	20.59	26.66	19.34
406.1	779.20	5.1	V	1.86	20.80	27.76	18.24
436.0	58.60	7.0	H	0.53	8.32	15.85	24.15
436.0	61.80	7.3	H	0.54	6.98	14.82	25.18
436.0	95.60	13.5	V	0.64	11.50	25.64	17.86
436.0	159.20	4.6	V	0.74	17.05	22.39	21.11
436.0	228.80	5.9	V	0.96	11.20	18.06	27.94
436.0	663.20	14.1	H	1.66	20.43	36.19	9.81
470.0	95.50	13.7	V	0.64	11.50	25.84	17.66
470.0	157.70	6.2	V	0.73	17.14	24.07	19.43

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

RX TEST DATA CONTD.

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dBμV	Ant. Polarity	Coax Loss dB	Correction Factor dB/m	Field Strength dBμV/m	Margin dB
470.0	199.70	6.7	H	0.90	16.72	24.32	19.18
470.0	231.20	10.7	V	0.96	11.28	22.94	23.06
470.0	483.20	16.4	H	1.28	17.64	35.32	10.68

The values listed represent noise floor values.
No significant emissions found.

FREQUENCY STABILITY

Rule Parts. No.: FCC Part 2.1055, Part 90.213, RSS-119 5.3, RSS-GEN 7.2.4

Requirements: Temperature range requirements: -30 to +50° C.
Voltage Variation +, -15%
±1.5 PPM

Method of Measurements: ANSI/TIA 603-C:2004

Test Data:

Assigned Frequency (Ref. Frequency) (MHz)		436.625070
Temperature (°C)	Frequency (MHz)	Frequency Stability (PPM)
-30	436.625132	0.14
-20	436.625154	0.19
-10	436.625147	0.17
0	436.625087	0.03
+10	436.625168	0.22
+20	436.625209	0.31
+30	436.625186	0.26
+40	436.625161	0.20
+50	436.625158	0.19

Assigned Frequency (Ref. Frequency) (MHz)		
% Battery (%)	Frequency (MHz)	Frequency Stability (PPM)
-15%	436.625072	0.0
	436.625070	0.0
+15%	436.625146	0.17

TRANSIENT FREQUENCY BEHAVIOR

FCC Part 2.1055(a)(1)

FCC Part 90.214, IC RSS-119 5.8

REQUIREMENTS: Transmitters designed to operate in the 150-174 MHz and 421-512 MHz frequency bands must maintain transient frequencies within the maximum transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time Intervals	Maximum frequency difference	All Equipment	
		150-174 MHz	421-512 MHz

Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels

t ₁ ⁴	±25.0 kHz	5.0 ms	10.0 ms
t ₂	±12.5 kHz	20.0 ms	25.0 ms
t ₃ ⁴	±25.0 kHz	5.0 ms	10.0 ms



Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels

t ₁ ⁴	±12.5 kHz	5.0 ms	10.0 ms
t ₂	±6.25 kHz	20.0 ms	25.0 ms
t ₃ ⁴	±12.5 kHz	5.0 ms	10.0 ms

Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels



t ₁ ⁴	±6.25 kHz	5.0 ms	10.0 ms
t ₂	±3.125 kHz	20.0 ms	25.0 ms
t ₃ ⁴	±6.25 kHz	5.0 ms	10.0 ms

12.5 kHz



Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc


25.0 kHz



Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc

TEST PROCEDURE: ANSI/TIA 603-C:2004 PARA 2.2.19

1. Using the variable attenuator the transmitter level was set to 40 dB below the test receivers maximum input level, then the transmitter was turned off.
2. With the transmitter off the signal generator was set 20dB below the level of the transmitter in the above step, this level will be maintained with the signal generator through-out the test.
3. Reduce the attenuation between the transmitter and the RF detector by 30 dB. With the levels set as above the transient frequency behavior was observed & recorded.



EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 3/10/10	3/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 3/23/09	3/23/11
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 6/10/09	6/10/11
Frequency Counter	HP	5385A	3242A07460	CAL 5/26/09	5/26/11
Hygro-Thermometer	Extech	445703	0602	CAL 1/30/09	1/30/11
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/26/09	5/26/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/18/09	5/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12

Applicant: UNICATION CO., LTD.
 FCC ID: LEA-U3-UHF-MID
 IC CERT #: 3819A-U3UHF MID
 Report: Z:\UNICATION TWN\2352AT10\2352AT10_TestReport_Rev.doc