

# VARIANT FCC TEST REPORT (PART 24)



Applicant:	Continental Automotive Systems, Inc.
Address:	21440 W Lake Cook Rd., Deer Park, IL 60010, USA

Manufacturer or Supplier:	Continental Automotive Systems, Inc.
Address:	21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Product:	FE3NA0031
Brand Name:	Continental
Model Name:	FE3NA0031
FCC ID:	LHJ-FE3NA0031
Date of tests:	Jun. 19, 2023 ~ Jun. 28, 2023

The tests have been carried out according to the requirements of the following standard:

- FCC PART 24, Subpart E**
 **FCC PART 2**  
 **ANSI/TIA/EIA-603-D**
 **ANSI/TIA/EIA-603-E**
 **ANSI C63.26-2015**

**CONCLUSION:** The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jun. 28, 2023	Date: Jun. 28, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>3</b>
<b>1 SUMMARY OF TEST RESULTS .....</b>	<b>4</b>
1.1 MEASUREMENT UNCERTAINTY .....	5
1.2 TEST SITE AND INSTRUMENTS .....	6
<b>2 GENERAL INFORMATION .....</b>	<b>7</b>
2.1 GENERAL DESCRIPTION OF EUT .....	7
2.2 CONFIGURATION OF SYSTEM UNDER TEST .....	9
2.3 DESCRIPTION OF SUPPORT UNITS .....	10
2.4 TEST ITEM AND TEST CONFIGURATION.....	10
2.5 EUT OPERATING CONDITIONS .....	12
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
<b>3 TEST TYPES AND RESULTS .....</b>	<b>13</b>
3.1 OUTPUT POWER MEASUREMENT .....	13
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....	13
3.1.2 TEST PROCEDURES.....	13
3.1.3 TEST SETUP .....	14
3.1.4 TEST RESULTS.....	14
3.2 RADIATED EMISSION MEASUREMENT .....	22
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	22
3.2.2 TEST PROCEDURES.....	22
3.2.3 DEVIATION FROM TEST STANDARD.....	22
3.2.4 TEST SETUP .....	23
3.2.5 TEST RESULTS.....	25
<b>4 INFORMATION ON THE TESTING LABORATORIES .....</b>	<b>29</b>
<b>5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>30</b>



Test Report No.: W7L-230619W001RF02

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-211220W001RF02	Original release	Jan. 17, 2022
W7L-230619W001RF02	Based on the original product changing the hardware version and software version, The new Sample only verify RSE worst case and conducted power, So this report only replaces conducted Power and the low frequency data and the high frequency data (WCDMA Band2 CH9538) of RSE.	Jun. 28, 2023



# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
§2.1046	Conducted Output Power	Compliance
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance
§2.1055 §24.235	Frequency Stability	See Note
§2.1049	Occupied Bandwidth	See Note
§24.232(d)	Peak to average ratio	See Note
§24.238(a)(b)	Band Edge Measurements	See Note
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	See Note
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance

**NOTE:** Please refer to the original report W7L-211220W001RF02, FCC ID: LHJ-FE3NA0031.

## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



## 1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.13,23	May.12,24
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,22	Sep.02,23
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,23	Feb. 17,24
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,23	Feb. 17,24
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.04, 22	Sep.03, 23
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,23	Feb. 13,24
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,23	May. 05,24
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.11,23	May.10,24
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,23	Feb.16,24
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	May. 18,23	May. 17,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,23	May. 05,24
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,23	Feb. 13,24
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,23	Feb. 13,24
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,23	May. 05,24
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,23	Feb. 13,24
Base station R&S CMW500	Rohde&Schwa rz	CMW500	153085	May.11,23	May.10,24
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 12,22	Aug. 11,23

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
  3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	FE3NA0031	
<b>BRAND NAME</b>	Continental	
<b>MODEL NAME</b>	FE3NA0031	
<b>NOMINAL VOLTAGE</b>	EUT 4.0V	
<b>MODULATION TYPE</b>	<b>GSM/GPRS: GMSK</b> <b>EDGE: 8PSK</b> <b>WCDMA: QPSK</b> <b>LTE Band 2: QPSK, 16QAM</b>	
<b>FREQUENCY RANGE</b>	<b>GSM/GPRS, EDGE</b>	1850.2MHz ~ 1909.8MHz
	<b>WCDMA</b>	1852.4MHz ~ 1907.6MHz
	<b>LTE Band 2 Channel Bandwidth: 1.4MHz</b>	1850.7MHz ~ 1909.3MHz
	<b>LTE Band 2 Channel Bandwidth: 3MHz</b>	1851.5MHz ~ 1908.5MHz
	<b>LTE Band 2 Channel Bandwidth: 5MHz</b>	1852.5MHz ~ 1907.5MHz
	<b>LTE Band 2 Channel Bandwidth: 10MHz</b>	1855.0MHz ~ 1905.0MHz
	<b>LTE Band 2 Channel Bandwidth: 15MHz</b>	1857.5MHz ~ 1902.5MHz
	<b>LTE Band 2 Channel Bandwidth: 20MHz</b>	1860.0MHz ~ 1900.0MHz
	<b>MAX. EIRP POWER</b>	<b>GSM/GPRS</b>
<b>EDGE</b>		459.2mW
<b>WCDMA</b>		316.96mW
<b>LTE Band 2 Channel Bandwidth: 1.4MHz</b>		261.82mW
<b>LTE Band 2 Channel Bandwidth: 3MHz</b>		263.63mW
<b>LTE Band 2 Channel Bandwidth: 5MHz</b>		261.82mW
<b>LTE Band 2 Channel Bandwidth: 10MHz</b>		262.42mW
<b>LTE Band 2 Channel Bandwidth: 15MHz</b>		262.42mW



	<b>LTE Band 2 Channel Bandwidth: 20MHz</b>	264.24mW
<b>EMISSION DESIGNATOR</b>	<b>GSM/GPRS</b>	242KGXW
	<b>EDGE</b>	244KG7W
	<b>WCDMA</b>	4M17F9W
	<b>LTE Band 2 Channel Bandwidth: 1.4MHz</b>	QPSK: 1M09G7D
		16QAM: 1M09W7D
	<b>LTE Band 2 Channel Bandwidth: 3MHz</b>	QPSK: 2M70G7D
		16QAM: 2M69W7D
	<b>LTE Band 2 Channel Bandwidth: 5MHz</b>	QPSK: 4M50G7D
		16QAM: 4M50W7D
	<b>LTE Band 2 Channel Bandwidth: 10MHz</b>	QPSK: 8M98G7D
16QAM: 8M99W7D		
<b>LTE Band 2 Channel Bandwidth: 15MHz</b>	QPSK: 13M5G7D	
	16QAM: 13M5W7D	
<b>LTE Band 2 Channel Bandwidth: 20MHz</b>	QPSK: 18M0G7D	
	16QAM: 18M0W7D	
<b>ANTENNA TYPE</b>	Dipole Antenna with 1.52dBi gain for GSM1900 Dipole Antenna with 1.52dBi gain for WCDMA II/LTE B2	
<b>HW VERSION</b>	P2	
<b>SW VERSION</b>	MODEMSA415M_01.16.34	
<b>I/O PORTS</b>	Refer to user's manual	
<b>CABLE SUPPLIED</b>	N/A	
<b>EXTREME TEMPERATURE</b>	-30-75 °C	
<b>EXTREME VOLTAGE</b>	EUT 3.8V - EUT 4.2V	

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
<b>GSM/GPRS/EDGE</b>	1TX/1RX
<b>WCDMA</b>	1TX/1RX
<b>LTE</b>	1TX/1RX


- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.





## 2.2 CONFIGURATION OF SYSTEM UNDER TEST

### FOR RADIATION EMISSION TEST





### 2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	Kikusui/JP	PMX18-5A	0000001	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m

### 2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + DC Source with GSM or WCDMA or LTE link

#### GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM, EDGE



**BUREAU  
VERITAS**

**Test Report No.: W7L-230619W001RF02**

**WCDMA**

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

**LTE BAND 2 MODE**

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	1 RB / 0 RB Offset



**BUREAU  
VERITAS**

Test Report No.: W7L-230619W001RF02

**TEST CONDITION:**

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	EUT 4.0V	Jace Hu
RADIATED EMISSION	23deg. C, 70%RH	EUT 4.0V	Jace Hu

## 2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

## 2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 24**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**ANSI/TIA/EIA-603-D**

**ANSI/TIA/EIA-603-E**

**ANSI C63.26-2015**

**NOTE:** All test items have been performed and recorded as per the above standards.

## 3 TEST TYPES AND RESULTS

### 3.1 OUTPUT POWER MEASUREMENT

#### 3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

#### 3.1.2 TEST PROCEDURES

##### **EIRP MEASUREMENT:**

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as  $P_{\text{Meas}}$ , typically dBW or dBm);

$P_{\text{Meas}}$  = measured transmitter output power or PSD, in dBm or dBW;

$G_{\text{T}}$  = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

$L_{\text{C}}$  = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

##### **CONDUCTED POWER MEASUREMENT:**


The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



### 3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



### 3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency	1850.2	1880	1909.8
GPRS (GMSK, 1Tx-slot)	29.11	<b>29.13</b>	29.04
GPRS (GMSK, 2Tx-slot)	27.34	27.39	27.38
GPRS (GMSK, 3Tx-slot)	25.58	25.54	25.44
GPRS (GMSK, 4Tx-slot)	24.40	24.34	24.29
EDGE (8PSK, 1Tx-slot)	25.06	25.06	25.10
EDGE (8PSK, 2Tx-slot)	23.69	23.64	23.41
EDGE (8PSK, 3Tx-slot)	22.67	22.48	22.37
EDGE (8PSK, 4Tx-slot)	21.46	21.53	21.32

Band	WCDMA II		
Channel	9262	9400	9538
Frequency	1852.4	1880	1907.6
RMC 12.2K	23.43	<b>23.49</b>	23.47
HSDPA Subtest-1	22.38	22.39	22.43
HSDPA Subtest-2	22.40	22.48	22.48
HSDPA Subtest-3	22.14	22.16	22.20
HSDPA Subtest-4	22.08	22.14	22.26
DC-HSDPA Subtest-1	22.43	22.39	22.51
DC-HSDPA Subtest-2	22.30	22.38	22.40
DC-HSDPA Subtest-3	22.05	22.08	22.17
DC-HSDPA Subtest-4	22.14	22.13	22.11
HSUPA Subtest-1	22.29	22.39	22.38
HSUPA Subtest-2	20.47	20.39	20.49
HSUPA Subtest-3	21.25	21.30	21.36
HSUPA Subtest-4	20.46	20.42	20.44
HSUPA Subtest-5	22.24	22.27	22.32



**LTE BAND 2**

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz
2/ 1.4	QPSK	1	0	22.55	22.60	22.64
		1	2	22.58	22.52	22.66
		1	5	22.59	22.61	22.65
		3	0	22.16	22.14	22.27
		3	1	22.26	22.23	22.22
		3	3	22.27	22.25	22.36
	16QAM	6	0	21.82	21.79	21.80
		1	0	21.87	21.87	21.94
		1	2	21.92	21.86	21.99
		1	5	21.88	21.83	21.95
		3	0	21.28	21.28	21.37
		3	1	21.34	21.38	21.44
		3	3	21.36	21.42	21.48
		6	0	20.73	20.74	20.81

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz
2/ 3	QPSK	1	0	22.54	22.59	22.67
		1	7	22.59	22.50	22.66
		1	14	22.56	22.60	22.69
		8	0	21.68	21.67	21.74
		8	3	21.69	21.74	21.75
		8	7	21.78	21.78	21.91
		15	0	21.77	21.83	21.77
	16QAM	1	0	21.85	21.89	21.97
		1	7	21.86	21.92	21.96
		1	14	21.91	21.83	21.94
		8	0	20.64	20.67	20.74
		8	3	20.76	20.77	20.83
		8	7	20.73	20.82	20.87
		15	0	20.73	20.69	20.81



Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz
2/5	QPSK	1	0	22.54	22.65	22.63
		1	12	22.54	22.53	22.66
		1	24	22.55	22.61	22.65
		12	0	21.65	21.67	21.77
		12	6	21.69	21.73	21.74
		12	13	21.74	21.82	21.90
		25	0	21.79	21.80	21.74
	16QAM	1	0	21.84	21.93	21.97
		1	12	21.89	21.89	21.97
		1	24	21.91	21.83	21.95
		12	0	20.64	20.69	20.77
		12	6	20.79	20.73	20.87
		12	13	20.78	20.80	20.84
		25	0	20.73	20.68	20.84

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz
2/10	QPSK	1	0	22.59	22.63	22.61
		1	24	22.57	22.55	22.62
		1	49	22.59	22.67	22.66
		25	0	21.66	21.67	21.78
		25	12	21.76	21.73	21.75
		25	25	21.74	21.76	21.90
		50	0	21.82	21.81	21.79
	16QAM	1	0	21.89	21.93	21.93
		1	24	21.90	21.89	21.99
		1	49	21.87	21.89	21.93
		25	0	20.70	20.65	20.81
		25	12	20.74	20.75	20.84
		25	25	20.77	20.81	20.87
		50	0	20.78	20.71	20.78





Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz
2/ 15	QPSK	1	0	22.52	22.63	22.64
		1	37	22.59	22.50	22.67
		1	74	22.53	22.64	22.65
		36	0	21.69	21.66	21.77
		36	19	21.75	21.68	21.75
		36	39	21.76	21.75	21.90
		75	0	21.82	21.83	21.74
	16QAM	1	0	21.85	21.86	21.93
		1	37	21.91	21.88	21.99
		1	74	21.91	21.84	21.91
		36	0	20.66	20.65	20.80
		36	19	20.80	20.71	20.88
		36	39	20.72	20.83	20.84
		75	0	20.77	20.68	20.85

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz
2/ 20	QPSK	1	0	22.60	22.67	22.69
		1	50	22.61	22.58	22.68
		1	99	22.61	22.68	<b>22.70</b>
		50	0	21.72	21.72	21.79
		50	25	21.77	21.75	21.80
		50	50	21.82	21.83	21.92
		100	0	21.83	21.85	21.82
	16QAM	1	0	21.92	21.94	21.99
		1	50	21.94	21.94	22.01
		1	99	21.93	21.91	21.96
		50	0	20.72	20.73	20.82
		50	25	20.82	20.79	20.89
		50	50	20.80	20.87	20.89
		100	0	20.79	20.76	20.86



**EIRP POWER (dBm)**

**GSM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	29.11	1.52	30.63	1156.11	2
661	1880.0	29.13	1.52	30.65	1161.45	2
810	1909.8	29.04	1.52	30.56	1137.63	2

**EDGE**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	25.06	1.52	26.58	454.99	2
661	1880.0	25.06	1.52	26.58	454.99	2
810	1909.8	25.1	1.52	26.62	459.2	2

**WCDMA**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9662	1852.4	23.43	1.52	24.95	312.61	2
9800	1880	23.49	1.52	25.01	316.96	2
9938	1907.6	23.47	1.52	24.99	315.5	2



**LTE BAND 2**

**CHANNEL BANDWIDTH: 1.4MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.59	1.52	24.11	257.63	2
18900	1880.0	22.61	1.52	24.13	258.82	2
19193	1908.3	22.66	1.52	24.18	261.82	2

**CHANNEL BANDWIDTH: 1.4MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	21.92	1.52	23.44	220.8	2
18900	1880.0	21.87	1.52	23.39	218.27	2
19193	1908.3	21.99	1.52	23.51	224.39	2

**CHANNEL BANDWIDTH: 3MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22.59	1.52	24.11	257.63	2
18900	1880.0	22.6	1.52	24.12	258.23	2
19185	1908.5	22.69	1.52	24.21	263.63	2

**CHANNEL BANDWIDTH: 3MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	21.91	1.52	23.43	220.29	2
18900	1880.0	21.92	1.52	23.44	220.8	2
19185	1908.5	21.97	1.52	23.49	223.36	2



**CHANNEL BANDWIDTH: 5MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.55	1.52	24.07	255.27	2
18900	1880.0	22.65	1.52	24.17	261.22	2
19175	1907.5	22.66	1.52	24.18	261.82	2

**CHANNEL BANDWIDTH: 5MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	21.91	1.52	23.43	220.29	2
18900	1880.0	21.93	1.52	23.45	221.31	2
19175	1907.5	21.97	1.52	23.49	223.36	2

**CHANNEL BANDWIDTH: 10MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	22.59	1.52	24.11	257.63	2
18900	1880.0	22.67	1.52	24.19	262.42	2
19150	1905.0	22.66	1.52	24.18	261.82	2

**CHANNEL BANDWIDTH: 10MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T</sub> -L <sub>C</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	21.9	1.52	23.42	219.79	2
18900	1880.0	21.93	1.52	23.45	221.31	2
19150	1905.0	21.99	1.52	23.51	224.39	2



**CHANNEL BANDWIDTH: 15MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.59	1.52	24.11	257.63	2
18900	1880.0	22.64	1.52	24.16	260.62	2
19125	1902.5	22.67	1.52	24.19	262.42	2

**CHANNEL BANDWIDTH: 15MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	21.91	1.52	23.43	220.29	2
18900	1880.0	21.88	1.52	23.4	218.78	2
19125	1902.5	21.99	1.52	23.51	224.39	2

**CHANNEL BANDWIDTH: 20MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.61	1.52	24.13	258.82	2
18900	1880	22.68	1.52	24.2	263.03	2
19100	1900	22.7	1.52	24.22	264.24	2

**CHANNEL BANDWIDTH: 20MHz 16QAM**

Channel	Frequency (MHz)	Conducted Power (dBm)	G <sub>T-LC</sub> (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	21.94	1.52	23.46	221.82	2
18900	1880	21.94	1.52	23.46	221.82	2
19100	1900	22.01	1.52	23.53	225.42	2



## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

### 3.2.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.4 TEST SETUP


#### < Frequency Range below 30MHz >



#### < Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).





**3.2.5 TEST RESULTS**

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**BELOW 1GHz WORST-CASE DATA**


**30 MHz – 1GHz data:**

**WCDMA Band II**

**CHANNEL BANDWIDTH: 9262 ~ 9538**

<b>MODE</b>	TX channel 9538	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH	<b>INPUT POWER</b>	EUT 4.0V
<b>TESTED BY</b>	Jace Hu		
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	57.160	-68.89	-50.63	-13.00	-55.89	-18.26	Peak	Horizontal
2	154.160	-62.87	-45.12	-13.00	-49.87	-17.75	Peak	Horizontal
3	235.640	-61.11	-47.94	-13.00	-48.11	-13.17	Peak	Horizontal
4 PP	303.540	-54.73	-42.35	-13.00	-41.73	-12.38	Peak	Horizontal
5	445.160	-66.33	-57.11	-13.00	-53.33	-9.22	Peak	Horizontal
6	590.660	-62.24	-57.80	-13.00	-49.24	-4.44	Peak	Horizontal






**BUREAU  
VERITAS**

Test Report No.: W7L-230619W001RF02

<b>MODE</b>	TX channel 9538	<b>FREQUENCY RANGE</b>	Below 1000MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH	<b>INPUT POWER</b>	EUT 4.0V
<b>TESTED BY</b>	Jace Hu		
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	40.670	-69.01	-44.09	-13.00	-56.01	-24.92	Peak	Vertical
2	97.900	-65.15	-56.81	-13.00	-52.15	-8.34	Peak	Vertical
3	211.390	-72.48	-55.46	-13.00	-59.48	-17.02	Peak	Vertical
4 PP	314.210	-60.80	-50.24	-13.00	-47.80	-10.56	Peak	Vertical
5	447.100	-62.75	-54.18	-13.00	-49.75	-8.57	Peak	Vertical
6	528.580	-68.17	-60.65	-13.00	-55.17	-7.52	Peak	Vertical





BUREAU  
VERITAS

Test Report No.: W7L-230619W001RF02

### ABOVE 1GHz


**Note:** For higher frequency, the emission is too low to be detected.

### WCDMA Band II

### CH 9538

MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3815.200	-50.89	-59.02	-13.00	-37.89	8.13	Peak	Horizontal
2	5722.800	-51.14	-62.04	-13.00	-38.14	10.90	Peak	Horizontal






**BUREAU  
VERITAS**

Test Report No.: W7L-230619W001RF02

<b>MODE</b>	TX channel 9538	<b>FREQUENCY RANGE</b>	Above 1000MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH	<b>INPUT POWER</b>	EUT 4.0V
<b>TESTED BY</b>	Jace Hu		
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3815.200	-49.77	-57.55	-13.00	-36.77	7.78	Peak	Vertical
2	5722.800	-50.48	-61.84	-13.00	-37.48	11.36	Peak	Vertical





Test Report No.: W7L-230619W001RF02

## 4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Shenzhen EMC/RF Lab:**

Tel: +86-755-88696566

Fax: +86-755-88696577

**Email:** [customerservice.sw@bureauveritas.com](mailto:customerservice.sw@bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



Test Report No.: W7L-230619W001RF02

## 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---