## Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: LHJ-FE3RW0051

Items to be covered by Single modular transmitters.	Answer from applicant
The modular transmitter must have its own RF shielding.	The radio portion of this module is shielded.
2. The modular transmitter must have buffered modulation/data inputs (if such input are provided) to ensure that the module will comply with Part 15 requirement under conditions of excessive data rates or over-modulation.	
3. The modular transmitter must have its own power supply regulation.	The module has its own power supply regulation.
4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(b)(c). The antenna must either be permanently attached of employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable).	r connector and spurious
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	The required rule has been fulfilled.
6. The modular transmitter must be equipped with either a permanently affixed laber or must be capable of electronically displaying its FCC identification number is accordance with 15.212 (a)(1)(vi)(A) / (B).	
7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strengt level and timing requirements. Compliance with these requirements must be assured.	fulfilled and all the instructions for maintaining compliance have been clearly stated in the User Manual.

8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 1.1310, 2.1091, 2.1093, and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance. Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.

The required rule has been fulfilled and all the instructions for maintaining compliance have been clearly stated in the User Manual.

If you should have any question(s) regarding this declaration, please don't hesitate to contact us. Thank you!

James Zhang

Continental Automotive Systems, Inc.

Tel: 8478622435

Fax: 847-8628016

E-mail: jianming01.zhang@continental-corporation.com