



731 Enterprise Drive
Lexington, KY 40510

Telephone: 859-226-1000
Facsimile: 859-226-1040
www.intertek-etlsemko.com

TEST REPORT

Report Number: 100512934LEX-001
Project Number: G100512934

Report Issue Date: 10/22/2011

Model Number: GNOV1B
FCCID: LHJGNOV1B
ICID: 2807E-GNOV1B
FCC Standards: FCC Part 22 Subpart H
FCC Part 24 Subpart E

Industry Canada Standards: RSS-132 Issue 2
RSS-133 Issue 5

Tested by:
Intertek Testing Services NA, Inc.
731 Enterprise Drive
Lexington, KY 40510

Client:
Continental Automotive Systems
21440 West Lake Cook Road
Deer Park, IL 60010

Report prepared by

Jason Centers, Senior Project Engineer

Report reviewed by

Yuriy Litvinov, EMC Business Manager



This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TABLE OF CONTENTS

1 Introduction and Conclusion..... 3

2 Test Summary 3

3 Description of Equipment Under Test 4

4 Conducted Output Power..... 7

5 Occupied Bandwidth 10

6 Conducted Spurious Emissions at Antenna Terminals..... 13

7 Radiated Output Power 35

8 Radiated Spurious Emissions (Transmitter)..... 36

9 Frequency Stability..... 42

10 Measurement Uncertainty..... 47

11 Revision History 48

1 Introduction and Conclusion

The tests indicated in section 2 were performed on the product constructed as described in section 3. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test method, a list of the actual test equipment used, documentation photos, results and raw data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested complied with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

The INTERTEK-Lexington is located at 731 Enterprise Drive, Lexington Kentucky, 40510. The radiated emission test site is a 10-meter semi-anechoic chamber. The chamber meets the characteristics of CISPR 16-1 and ANSI C63.4. For measurements, a remotely controlled flush-mount metal-top turntable is used to rotate the EUT a full 360 degrees. A remote controlled non-conductive antenna mast is used to scan the antenna height from one to four meters. The test site is listed with the FCC under registration number 485103.

2 Test Summary

Page	Test full name	FCC Reference	Industry Canada	Result
7	Conducted Output Power	§2.1046 §24.232(d)	RSS-132 (4.4), RSS-133 (4.1), RSS-133 (6.4)	Pass
10	Occupied Bandwidth	§2.1049, §22.917(b)(d), and §24.238(a)	RSS-GEN (4.6.1), RSS-133 (2.3)	Pass
13	Conducted Spurious Emissions	§2.1049, §2.1051, §22.917(a)(b), and § 24.238(a)(b)	RSS-132 (4.5), RSS-133 (6.5.1)	Pass
35	Radiated Output Power	§ 22.913(a) and § 24.232(c)	RSS-132 (4.4), RSS-133 (6.4)	Pass
35	Radiated Spurious Emissions (Transmitter)	§2.1053, §22.917(a)(b), and §24.238(a)(b)	RSS-132 (4.5), RSS-133 (6.5)	Pass
42	Frequency Stability	§2.1055, §22.355, and §24.235	RSS-132 (4.3), RSS-133 (6.3)	Pass
45	Radiated Spurious Emissions (Receiver)	---	RSS-132 (4.6), RSS-133 (6.6), RSS-GEN (4.10)	Pass

3 Description of Equipment Under Test

Equipment Under Test	
Manufacturer	Continental Automotive Systems
Model Number	GNOV1B
Serial Number	NE00009D (IMEI: 352865030020796)
FCC Identifier	LHJGNOV1B
IC Identifier	2807E-GNOV1B
Receive Date	9/22/2011
Test Start Date	9/23/2011
Test End Date	10/22/2011
Device Received Condition	Good
Test Sample Type	Production
Frequency Band	824MHz - 849MHz (GSM 850 Band) 1850MHz - 1910MHz (GSM 1900 Band)
Modulation Type	GSM (GMSK), GPRS (GMSK), EDGE (8-PSK)
Transmission Control	Base Station Simulator
Maximum Output Power (Conducted)	32.9 dBm (GSM 850 - GMSK) 30.0 dBm (GSM 1900 - GMSK) 27.8 dBm (GSM 850 - 8-PSK) 26.3dBm (GSM 1900 - 8-PSK)
Test Channels	128, 190, & 251 (GSM 850 Band) 512, 661, & 810 (GSM 1900 Band)
Antenna Type	Internal
Operating Voltage	14VDC Nominal
Power Supply	Powered by automotive battery

Description of Equipment Under Test


The GNOV1B is a GSM/GPRS/EDGE module.

Operating modes of the EUT:


No.	Descriptions of EUT Exercising
1	Transmitting a GSM signal
2	Receive / idle mode

3.1 System setup including cable interconnection details, support equipment and simplified block diagram

3.2 EUT Block Diagram:



Block Diagram for Radiated Tests



Block Diagram for Conducted Tests at the Antenna Port

3.3 Cables:

Cables					
Description	Length	Shielding	Ferrites	Connection	
				From	To
Power Cable	3 ft	No	No	AC/DC Power Supply	DC Input
Serial Cable	3 ft	No	No	Serial Port	Laptop

3.4 Support Equipment:

No support equipment was necessary for the evaluation.

4 Conducted Output Power

4.1 Test Limits

§ 2.1046

For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in §2.1033(c)(8).

§ 24.232 (d)

Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.2 Test Procedure

The transmitter output was connected to a calibrated coaxial cable, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The EUT was placed into a call and the burst average power was measured with the base station in dBm. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. Tests were performed at three frequencies (low, middle, and high channels) and on the highest power levels, which can be setup on the transmitters.

The peak-to-average ratio (PAR) was measured using a spectrum analyzer with a RBW wider than the EBW of the measured signal. The delta between the peak and average trace was recorded.

4.3 Test Equipment Used:


Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Base Station Simulator	2522	Rohde & Schwarz	CMU200	9/30/2011	9/30/2012
Spectrum Analyzer	2522	Rohde & Schwarz	FSP7	9/23/2011	9/23/2012
RF Combiner	E18106	Weinschel Engineering	1506A	TOU	TOU
Directional Coupler	08736	Narda	4226-20	TOU	TOU

4.4 Results:

Conducted Output Power at Nominal Temperature


Band	Channel	Frequency (MHz)	GSM (dBm)	GPRS - 1 Tx Slot (dBm)	GPRS - 2 Tx Slots (dBm)	EDGE - 1 Tx Slot (dBm)	EDGE - 2 Tx Slots (dBm)
GSM 850	128	824.2	32.9	32.9	32.9	27.60	27.4
	190	836.6	32.8	32.8	32.8	27.60	27.4
	251	848.8	32.8	32.8	32.8	27.80	27.6
GSM 1900	512	1850.2	30	30	30	26.30	26
	661	1880	29.9	29.9	29.9	26.20	26
	810	1909.8	29.8	29.8	29.8	26.20	26

Peak-to-Average Ratio – GPRS Mode



Date: 29.SEP.2011 15:08:04

Peak-to-Average Ratio – EDGE Mode



Date: 29.SEP.2011 15:05:16

5 Occupied Bandwidth

5.1 Test Limits

§2.1049:

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.


5.2 Test Procedure

The EUT was connected to a spectrum analyzer using a calibrated coaxial cable and power divider. The EUT was placed into a call using base station simulator. The base station simulator was set to force the EUT to its maximum power setting. The occupied bandwidth function of the analyzer was used to automatically generate the occupied bandwidth plots below.


5.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	9/23/2011	9/23/2012
Base Station Simulator	2522	Rohde & Schwarz	CMU200	9/30/2011	9/30/2012
RF Combiner	E18106	Weinschel Engineering	1506A	TOU	TOU

5.4 Results:




Date: 29.SEP.2011 14:03:29




Date: 29.SEP.2011 14:09:06

GSM 850Band, Mid Channel – EDGE



Date: 29.SEP.2011 14:05:43

GSM 1900 Band, Mid Channel – EDGE



Date: 29.SEP.2011 14:07:31

6 Conducted Spurious Emissions at Antenna Terminals

6.1 Test Limits

§ 2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

- (h) Transmitters employing digital modulation techniques—when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at the discretion of the user.

§ 2.1051

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

§ 22.917

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

§ 24.238

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The base station simulator was set to force the EUT to its maximum power setting. The resolution bandwidth of the spectrum analyzer was set at 100kHz or 1MHz depending on the transmit band. Sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.


6.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	9/23/2011	9/23/2012
EMC Analyzer	2142	HP	E7405	9/23/2011	9/23/2012
Base Station Simulator	2522	Rohde & Schwarz	CMU200	9/30/2011	9/30/2012
RF Combiner	E18106	Weinschel Engineering	1506A	TOU	TOU

6.4 Results:


The following plots show that all spurious emissions are attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. Plots for emissions within 1MHz of the band edge as well as for emission outside of this range are shown.

GPRS – GSM 850 Low Channel




No Peak Found

Agilent 05:27:51 Sep 30, 2011 R T




No Peak Found

GPRS – GSM 850 Mid Channel




No Peak Found

Agilent 05:29:08 Sep 30, 2011 R T




GPRS – GSM 850 High Channel




No Peak Found

Agilent 05:32:26 Sep 30, 2011 R T




GPRS – GSM 1900 Low Channel

Agilent 08:09:14 Oct 22, 2011 R T



Start 30 MHz Res BW 1 MHz VBW 3 MHz Sweep 7.785 ms (401 pts) Stop 3 GHz



No Peak Found
Agilent 05:22:19 Sep 30, 2011 R T





Start 3 GHz Res BW 1 MHz VBW 3 MHz Sweep 170 ms (4001 pts) Stop 20 GHz

No Peak Found


GPRS – GSM 1900 Mid Channel



GPRS – GSM 1900 High Channel




EDGE – GSM 850 Low Channel




No Peak Found

Agilent 05:35:22 Sep 30, 2011 R T




EDGE – GSM 850 Mid Channel




No Peak Found

Agilent 05:37:32 Sep 30, 2011 R T




EDGE – GSM 850 High Channel




File already exists

Agilent 05:54:39 Sep 30, 2011 R T




EDGE – GSM 1900 Low Channel

Agilent 07:31:13 Oct 22, 2011 R T



Start 30 MHz Res BW 1 MHz VBW 3 MHz Sweep 7.785 ms (401 pts) Stop 3 GHz



No Peak Found
Agilent 05:57:17 Sep 30, 2011 R T





Start 3 GHz Res BW 1 MHz VBW 3 MHz Sweep 170 ms (4001 pts) Stop 20 GHz

No Peak Found

EDGE – GSM 1900 Mid Channel




EDGE – GSM 1900 High Channel




Emissions within 4MHz of the block edge:

GSM 850 Band – Low Channel - GPRS




Date: 29.SEP.2011 15:22:47

GSM 850 Band – High Channel - GPRS




Date: 29.SEP.2011 15:24:02

GSM 1900 Band – Low Channel - GPRS




Date: 29.SEP.2011 15:14:46

GSM 1900 Band – High Channel – GPRS




Date: 29.SEP.2011 15:17:19

GSM 850 Band – Low Channel - EDGE




Date: 29.SEP.2011 15:27:27

GSM 850 Band – High Channel - EDGE




Date: 29.SEP.2011 15:26:24

GSM 1900 Band – Low Channel - EDGE




Date: 29.SEP.2011 15:19:58

GSM 1900 Band – High Channel – EDGE




Date: 29.SEP.2011 15:18:33

Emissions within 1MHz of the band edge:




Date: 22.OCT.2011 09:08:48




Date: 22.OCT.2011 09:11:14

GSM 1900 Band - Low Band Edge - GPRS




Date: 22.OCT.2011 09:31:47

GSM 1900 Band - High Band Edge - GPRS




Date: 22.OCT.2011 09:28:32

GSM 850 Band - Low Band Edge - EDGE




Date: 22.OCT.2011 09:18:48

GSM 850 Band - High Band Edge - EDGE




Date: 22.OCT.2011 09:16:35

GSM 1900 Band - Low Band Edge - EDGE



Date: 22.OCT.2011 09:21:42

GSM 1900 Band - High Band Edge - EDGE



Date: 22.OCT.2011 09:24:34

7 Radiated Output Power

7.1 Test Limits

§ 22.913

(a) (2) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

§ 24.232

(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

7.2 Test Procedure

The radiated output power was determined by adding the peak antenna gain to the measured conducted output power to determine the peak radiated power.

$$ERP = ConductedOutputPower(dBm) + AntennaGain(dBi) - 2.15$$

$$EIRP = ConductedOutputPower(dBm) + AntennaGain(dBi)$$

7.3 Results:

The GNOV1B meets the radiated power requirements of FCC §22.913 and §24.232.

Band	Channel	Frequency (MHz)	Conducted Power (dBm)	Peak Antenna Gain (dBi)	EIRP (dBm)	ERP(dBm)
GSM 850 (GPRS)	128	824.2	32.90	-1.11	-	29.64
	190	836.6	32.80	-0.75	-	29.90
	251	848.8	32.80	-0.32	-	30.33
GSM 1900 (GPRS)	512	1850.2	30.00	1.66	31.66	-
	661	1880	29.90	1.09	30.99	-
	810	1909.8	29.80	0.16	29.96	-
GSM 850 (EDGE)	128	824.2	27.60	-1.11	-	24.34
	190	836.6	27.60	-0.75	-	24.70
	251	848.8	27.80	-0.32	-	25.33
GSM 1900 (EDGE)	512	1850.2	26.30	1.66	27.96	-
	661	1880	26.20	1.09	27.29	-
	810	1909.8	26.20	0.16	26.36	-

8 Radiated Spurious Emissions (Transmitter)

8.1 Test Limits

§ 2.1053

- (a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of §2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

§ 22.917

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

§ 24.238

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

8.2 Test Procedure

The EUT was placed on a non-conductive turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. The EUT was forced to transmit at its maximum output power setting. During the tests, the antenna height and EUT azimuth were varied in order to identify the maximum level of emissions from the EUT.

The frequency range up to tenth harmonic was investigated in order to identify the spurious emission. Once the spurious emissions were identified, the power of the emission was determined using the substitution method described in TIA-603-C. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and at the spurious emissions frequency.

8.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	10887490.26	Rohde & Schwarz	ESI26	6/29/2011	6/29/2012
Preamplifier	987410	Miteq	AFS44-00102000-30-10P-44	2/4/2011	2/4/2012
Preamplifier	SF456200904	Mini-Circuits	ZX60-3018G-S+	2/4/2011	2/4/2012
Biconnilog Antenna	00051864	ETS	3142C	12/20/2010	12/20/2011
Horn Antenna	6556	ETS	3115	8/24/2011	8/24/2012
Horn Antenna	1096	Antenna Research	DRG-118/A	7/20/2011	7/20/2012
System Controller	121701-1	Sunol Sciences	SC99V	Time of Use	Time of Use
High Pass Filter	3986-01 DC0408	Microwave Circuits, Inc.	H3G020G2	Time of Use	Time of Use
Base Station Simulator	2522	Rohde & Schwarz	CMU200	9/30/2011	9/30/2012
Sweep Generator	3844A01327	Agilent	83620B	9/23/2011	9/30/2012

8.4 Results:

All radiated spurious emissions were attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB which is equivalent to -13dBm.

Worst Case Spurious Measurements – GSM 850 Band – GPRS Mode

Radiated Spurious Emissions Measurement								
Test Engineer: J. Centers Test Date: 9/27/2011 Temp. / Humidity / Pressure: 23.7C/48%/985.4 mbar Bandwidth Settings: RBW = VBW = 1MHz Notes: Spurious emissions not reported here were below the measurement noise floor.								
Band/Channel	Spurious Frequency (MHz)	Polarity	A Device Reading (dBm)	B Signal Generator Level (dBm)	C Cable Loss (dB)	D Tx Antenna Gain (dBd)	E Limit (dBm)	F Radiated Spurious Emission Level (dBm)
GSM 850 Band; GPRS Mode; Low Channel (128)	1648.4	H	-78.27	-42.18	3.26	6.70	-13	-38.74
	1648.4	V	-73.73	-38.66	3.26	6.70	-13	-35.22
	2472.6	H	-80.36	-40.4	4.17	7.16	-13	-37.41
	2472.6	V	-78.08	-36.17	4.17	7.16	-13	-33.18
	3296.8	H	-69.4	-65.69	4.58	7.14	-13	-63.13
	3296.8	V	-66.29	-59.99	4.58	7.14	-13	-57.43
	4121	H	-65.5	-58.97	5.33	8.15	-13	-56.15
	4121	V	-65.88	-58.41	5.33	8.15	-13	-55.59
	4945.2	H	-66.49	-58.39	5.82	8.80	-13	-55.41
	4945.2	V	-68.23	-60.67	5.82	8.80	-13	-57.69
	5769.4	H	-68.76	-57.46	6.75	9.27	-13	-54.94
	5769.4	V	-67.81	-57.91	6.75	9.27	-13	-55.39
	6593.6	H	-71.97	-55.41	7.45	9.96	-13	-52.90
	6593.6	V	-68.96	-52.52	7.45	9.96	-13	-50.01
7417.8	H	-71.45	-51.27	7.78	8.72	-13	-50.33	
7417.8	V	-69.54	-48.84	7.78	8.72	-13	-47.90	
8242	H	-71.51	-48.26	8.23	9.16	-13	-47.33	
8242	V	-70.31	-50.31	8.23	9.16	-13	-49.38	
GSM 850 Band; GPRS Mode; Mid Channel (190)	1673.2	H	-79.05	-42.59	3.30	6.70	-13	-39.19
	1673.2	V	-76.48	-40.31	3.30	6.70	-13	-36.91
	2509.8	H	-77.63	-37.1	3.97	7.43	-13	-33.64
	2509.8	V	-77.51	-34.86	3.97	7.43	-13	-31.40
	3346.4	H	-63.4	-60	4.63	7.19	-13	-57.45
	3346.4	V	-63.89	-59.58	4.63	7.19	-13	-57.03
	4183	H	-65.36	-59.37	5.19	8.15	-13	-56.41
	4183	V	-64.95	-59.33	5.19	8.15	-13	-56.37
	5019.6	H	-65.36	-56.65	6.19	8.87	-13	-53.97
	5019.6	V	-65.37	-57.49	6.19	8.87	-13	-54.81
	5856.2	H	-66.15	-54.25	7.28	9.57	-13	-51.96
	5856.2	V	-66.4	-54.37	7.28	9.57	-13	-52.08
	6692.8	H	-68.37	-51.43	7.47	9.81	-13	-49.09
	6692.8	V	-67.43	-50.78	7.47	9.81	-13	-48.44
7529.4	H	-70.32	-47.98	8.31	9.02	-13	-47.27	
7529.4	V	-69.85	-50.07	8.31	9.02	-13	-49.36	
8366	H	-71.2	-48.15	8.56	9.22	-13	-47.49	
8366	V	-71.86	-47.92	8.56	9.22	-13	-47.26	
GSM 850 Band; GPRS Mode; High Channel (251)	1697.6	H	-77.39	-40.6	3.18	6.70	-13	-37.08
	1697.6	V	-75.58	-38.5	3.18	6.70	-13	-34.98
	2546.4	H	-77.39	-35.91	4.09	7.43	-13	-32.57
	2546.4	V	-76.18	-32.59	4.09	7.43	-13	-29.25
	3395.2	H	-64.64	-59.94	4.84	7.19	-13	-57.60
	3395.2	V	-64.62	-58.11	4.84	7.19	-13	-55.77
	4244	H	-65.53	-59.2	5.00	8.37	-13	-55.83
	4244	V	-65.69	-59.7	5.00	8.37	-13	-56.33
	5092.8	H	-65.11	-55.6	6.25	8.87	-13	-52.98
	5092.8	V	-65.92	-57.06	6.25	8.87	-13	-54.44
	5941.6	H	-66.57	-52.78	7.03	9.53	-13	-50.28
	5941.6	V	-67.37	-54.81	7.03	9.53	-13	-52.31
	6790.4	H	-67.93	-51.26	7.71	9.55	-13	-49.42
	6790.4	V	-68.34	-51.27	7.71	9.55	-13	-49.43
7639.2	H	-69.64	-48.32	7.87	9.20	-13	-46.99	
7639.2	V	-70.09	-50.05	7.87	9.20	-13	-48.72	
8488	H	-71.05	-46.1	8.57	9.13	-13	-45.55	
8488	V	-71.02	-46.4	8.57	9.13	-13	-45.85	

F=B-C+D

Worst Case Spurious Measurements – GSM 1900 Band – GPRS Mode

Radiated Spurious Emissions Measurement								
Test Engineer: J. Centers Test Date: 9/27/2011 Temp. / Humidity / Pressure: 23.7C/48%/985.4 mbar Bandwidth Settings: RBW = VBW = 1MHz Notes: Spurious emissions not reported here were below the measurement noise floor.								
Band/Channel	Spurious Frequency (MHz)	Polarity	A Device Reading (dBm)	B Signal Generator Level (dBm)	C Cable Loss (dB)	D Tx Antenna Gain (dBd)	E Limit (dBm)	F Radiated Spurious Emission Level (dBm)
GSM 1900 Band; GPRS Mode; Low Channel (512)	3700.4	H	-63.39	-56.58	4.85	7.07	-13	-54.36
	3700.4	V	-64.59	-57.61	4.85	7.07	-13	-55.39
	5550.6	H	-65.81	-53.51	6.91	8.48	-13	-51.94
	5550.6	V	-65.01	-53.5	6.91	8.48	-13	-51.93
	7400.8	H	-69.85	-50.32	7.75	8.72	-13	-49.35
	7400.8	V	-69.83	-53.16	7.75	8.72	-13	-52.19
	9251	H	-68.73	-44.85	9.21	9.41	-13	-44.66
	9251	V	-67.39	-45.85	9.21	9.41	-13	-45.66
	11101.2	H	-73.73	-43.87	10.47	10.70	-13	-43.64
11101.2	V	-68.08	-39.97	10.47	10.70	-13	-39.74	
GSM 1900 Band; GPRS Mode; Mid Channel (661)	3760	H	-64.14	-56.9	5.20	7.07	-13	-55.03
	3760	V	-64.22	-57.32	5.20	7.07	-13	-55.45
	5640	H	-65.16	-53.29	7.09	8.84	-13	-51.54
	5640	V	-63.21	-52.13	7.09	8.84	-13	-50.38
	7520	H	-69.67	-50.07	8.01	9.02	-13	-49.06
	7520	V	-71.66	-53.56	8.01	9.02	-13	-52.55
	9400	H	-67.84	-42.62	9.15	9.52	-13	-42.25
	9400	V	-65.43	-43.1	9.15	9.52	-13	-42.73
	11280	H	-71.95	-42.11	10.16	10.65	-13	-41.63
11280	V	-70.7	-43.04	10.16	10.65	-13	-42.56	
GSM 1900 Band; GPRS Mode; High Channel (810)	3819.6	H	-65.9	-58.38	5.00	6.73	-13	-56.65
	3819.6	V	-64.12	-58.1	5.00	6.73	-13	-56.37
	5729.4	H	-63.16	-49.73	7.06	9.27	-13	-47.52
	5729.4	V	-62.44	-50.87	7.06	9.27	-13	-48.66
	7639.2	H	-70.87	-49.06	7.87	9.20	-13	-47.73
	7639.2	V	-69.47	-50.57	7.87	9.20	-13	-49.24
	9549	H	-66.95	-41.3	8.41	9.77	-13	-39.94
	9549	V	-65.46	-42.67	8.41	9.77	-13	-41.31
	11458.8	H	-71.87	-43.41	9.51	10.54	-13	-42.38
11458.8	V	-66.16	-40.26	9.51	10.54	-13	-39.23	
								F=B-C+D

Worst Case Spurious Measurements – GSM 850 Band – EDGE Mode

Radiated Spurious Emissions Measurement								
Test Engineer: J. Centers Test Date: 9/27/2011 Temp. / Humidity / Pressure: 23.7C/48%/985.4 mbar Bandwidth Settings: RBW = VBW = 1MHz Notes: Spurious emissions not reported here were below the measurement noise floor.								
Band/Channel	Spurious Frequency (MHz)	Polarity	A Device Reading (dBm)	B Signal Generator Level (dBm)	C Cable Loss (dB)	D Tx Antenna Gain (dBd)	E Limit (dBm)	F Radiated Spurious Emission Level (dBm)
GSM 850 Band; EDGE Mode; Low Channel (128)	1648.4	H	-78.89	-42.8	3.26	6.70	-13	-39.36
	1648.4	V	-75.4	-40.33	3.26	6.70	-13	-36.89
	2472.6	H	-78.46	-38.5	4.17	7.16	-13	-35.51
	2472.6	V	-78.95	-37.04	4.17	7.16	-13	-34.05
	3296.8	H	-64.53	-60.82	4.58	7.14	-13	-58.26
	3296.8	V	64.61	70.91	4.58	7.14	-13	73.47
	4121	H	-66.5	-59.97	5.33	8.15	-13	-57.15
	4121	V	64.87	72.34	5.33	8.15	-13	75.16
	4945.2	H	-65.39	-57.29	5.82	8.80	-13	-54.31
4945.2	V	-65.31	-57.75	5.82	8.80	-13	-54.77	
GSM 850 Band; EDGE Mode; Mid Channel (190)	1673.2	H	-80.79	-44.33	3.30	6.70	-13	-40.93
	1673.2	V	-77.2	-41.03	3.30	6.70	-13	-37.63
	2509.8	H	-78.16	-37.63	3.97	7.43	-13	-34.17
	2509.8	V	-79.32	-36.67	3.97	7.43	-13	-33.21
	3346.4	H	-63.88	-60.48	4.63	7.19	-13	-57.93
	3346.4	V	-63.49	-59.18	4.63	7.19	-13	-56.63
	4183	H	-64.99	-59	5.19	8.15	-13	-56.04
	4183	V	-64.58	-58.96	5.19	8.15	-13	-56.00
	5019.6	H	-64.97	-56.26	6.19	8.87	-13	-53.58
5019.6	V	-65.76	-57.88	6.19	8.87	-13	-55.20	
GSM 850 Band; EDGE Mode; High Channel (251)	1697.6	H	-80.37	-43.58	3.18	6.70	-13	-40.06
	1697.6	V	-77	-39.92	3.18	6.70	-13	-36.40
	2546.4	H	-79.23	-37.75	4.09	7.43	-13	-34.41
	2546.4	V	-77.65	-34.06	4.09	7.43	-13	-30.72
	3395.2	H	-64.61	-59.91	4.84	7.19	-13	-57.57
	3395.2	V	-63.66	-57.15	4.84	7.19	-13	-54.81
	4244	H	-64.22	-57.89	5.00	8.37	-13	-54.52
	4244	V	-65.49	-59.5	5.00	8.37	-13	-56.13
	5092.8	H	-66.04	-56.53	6.25	8.87	-13	-53.91
5092.8	V	-66.26	-57.4	6.25	8.87	-13	-54.78	
								F=B-C+D

Worst Case Spurious Measurements – GSM 1900 Band – EDGE Mode

Radiated Spurious Emissions Measurement

Test Engineer: J. Centers
 Test Date: 9/30/2011
 Temp. / Humidity / Pressure: 24.3C/38.4%/978.6 mbar
 Bandwidth Settings: RBW = VBW = 1MHz

Notes: Spurious emissions not reported here were below the measurement noise floor.

			A	B	C	D	E	F
Band/Channel	Spurious Frequency (MHz)	Polarity	Device Reading (dBm)	Signal Generator Level (dBm)	Cable Loss (dB)	Tx Antenna Gain (dBd)	Limit (dBm)	Radiated Spurious Emission Level (dBm)
GSM 1900 Band; EDGE Mode; Low Channel (512)	3700.4	H	-63.78	-56.97	4.85	7.07	-13	-54.75
	3700.4	V	-64.19	-57.21	4.85	7.07	-13	-54.99
	5550.6	H	-66.8	-54.5	6.91	8.48	-13	-52.93
	5550.6	V	-63.47	-51.96	6.91	8.48	-13	-50.39
GSM 1900 Band; EDGE Mode; Mid Channel (661)	3760	H	-65.16	-57.92	5.20	7.07	-13	-56.05
	3760	V	-65.38	-58.48	5.20	7.07	-13	-56.61
	5640	H	-64.11	-52.24	7.09	8.84	-13	-50.49
	5640	V	-68.11	-57.03	7.09	8.84	-13	-55.28
GSM 1900 Band; EDGE Mode; High Channel (810)	3819.6	H	-66.05	-58.53	5.00	6.73	-13	-56.80
	3819.6	V	-66.51	-60.49	5.00	6.73	-13	-58.76
	5729.4	H	-62.98	-49.55	7.06	9.27	-13	-47.34
	5729.4	V	-67.48	-55.91	7.06	9.27	-13	-53.70

F=B-C+D

9 Frequency Stability

9.1 Test Limits

§ 2.1055, §22.355, §24.235

The frequency stability of the transmitter was required to maintain a ± 2.5 ppm tolerance.

9.2 Test Procedure

The equipment under test was connected to an external DC power supply and the RF output was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for that purpose. After the temperature stabilized for approximately 30 minutes, the frequency error was read from the base station simulator. At 20C the input voltage was varied from 85% to 115% and the frequency stability vs input voltage was recorded.

9.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Base Station Simulator	2522	Rohde & Schwarz	CMU200	9/30/2011	9/30/2012
Environmental Chamber	29410	Thermotron	SE-1000-5-5	4/6/2011	4/6/2012
Multimeter	1705	Fluke	87	3/9/2011	3/9/2012

9.4 Results:

The tables below show the frequency stability data for both Cell and PCS Bands. In both cases the test sample met the ± 2.5 ppm limit.

Frequency Stability for GSM 850 Band – GPRS Mode

Operating Frequency: 836,520,000 Hz

Channel: 190

Reference Voltage: 14 VDC

Deviation Limit: 2.5 ppm

Notes: Frequency Stability in GSM 850 Band, GPRS Mode

Voltage (%)	Voltage (VDC)	Temp (°C)	Frequency Error (Hz)	Deviation (%)	Deviation (ppm)
100%	14	-30	41	0.0000049	0.0490
100%	14	-20	42	0.0000050	0.0502
100%	14	-10	44	0.0000053	0.0526
100%	14	0	49	0.0000059	0.0586
100%	14	10	38	0.0000045	0.0454
100%	14	20	33	0.0000039	0.0394
100%	14	30	39	0.0000047	0.0466
100%	14	40	30	0.0000036	0.0359
100%	14	50	34	0.0000041	0.0406
115%	16.1	20	32	0.0000038	0.0383
End Point	9	20	38	0.0000045	0.0454

Frequency Stability for GSM 1900 Band – GPRS Mode

Operating Frequency: 1,880,000,000 Hz

Channel: 661

Reference Voltage: 14 VDC

Deviation Limit: 2.5 ppm

Notes: Frequency Stability in GSM 1900 Band, GPRS Mode

Voltage (%)	Voltage (VDC)	Temp (°C)	Frequency Error (Hz)	Deviation (%)	Deviation (ppm)
100%	14	-30	68	0.0000036	0.0362
100%	14	-20	61	0.0000032	0.0324
100%	14	-10	57	0.0000030	0.0303
100%	14	0	39	0.0000021	0.0207
100%	14	10	63	0.0000034	0.0335
100%	14	20	66	0.0000035	0.0351
100%	14	30	68	0.0000036	0.0362
100%	14	40	68	0.0000036	0.0362
100%	14	50	71	0.0000038	0.0378
115%	16.1	20	64	0.0000034	0.0340
End Point	9	20	68	0.0000036	0.0362

Frequency Stability for GSM 850 Band – EDGE Mode

Operating Frequency: 836,520,000 Hz
Channel: 190
Reference Voltage: 14 VDC
Deviation Limit: 2.5 ppm

Notes: Frequency Stability in GSM 850 Band, EDGE Mode

Voltage (%)	Voltage (VDC)	Temp (°C)	Frequency Error (Hz)	Deviation (%)	Deviation (ppm)
100%	14	-30	37	0.0000044	0.0442
100%	14	-20	43	0.0000051	0.0514
100%	14	-10	52	0.0000062	0.0622
100%	14	0	31	0.0000037	0.0371
100%	14	10	36	0.0000043	0.0430
100%	14	20	25	0.0000030	0.0299
100%	14	30	22	0.0000026	0.0263
100%	14	40	31	0.0000037	0.0371
100%	14	50	28	0.0000033	0.0335
115%	16.1	20	27	0.0000032	0.0323
End Point	9	20	26	0.0000031	0.0311

Frequency Stability for GSM 1900 Band – EDGE Mode

Operating Frequency: 1,880,000,000 Hz
Channel: 661
Reference Voltage: 14 VDC
Deviation Limit: 2.5 ppm

Notes: Frequency Stability in GSM 1900 Band, EDGE Mode

Voltage (%)	Voltage (VDC)	Temp (°C)	Frequency Error (Hz)	Deviation (%)	Deviation (ppm)
100%	14	-30	79	0.0000042	0.0420
100%	14	-20	43	0.0000023	0.0229
100%	14	-10	54	0.0000029	0.0287
100%	14	0	38	0.0000020	0.0202
100%	14	10	63	0.0000034	0.0335
100%	14	20	59	0.0000031	0.0314
100%	14	30	52	0.0000028	0.0277
100%	14	40	61	0.0000032	0.0324
100%	14	50	57	0.0000030	0.0303
115%	16.1	20	54	0.0000029	0.0287
End Point	9	20	56	0.0000030	0.0298

10 Radiated Spurious Emissions (Receiver)

10.1 Test Limits

§ 15.109: Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of emission (MHz)	Field strength (microvolts/meter)	Field strength (dBuV/m)
30–88	100	40
88–216	150	43.5
216–960	200	46
Above 960	500	54

These limits are identical to those in RSS-GEN

10.2 Test Procedure

ANSI C63.4: 2009

10.3 Example of Field Strength Calculation Method:

The measured field strength was calculated by summing the readings taken from the spectrum analyzer with the appropriate correction factors associated with the antenna losses and cable losses. The calculation formula and sample calculations are listed below:

Formula:

$$FS = RA + AF + CF$$

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude in dB μ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB (Including preamplifier and filter attenuation)

Example Calculation:

$$RA = 19.48 \text{ dB}\mu\text{V}$$

$$AF = 18.52 \text{ dB}$$

$$CF = 0.78 \text{ dB}$$

$$FS = 19.48 + 18.52 + 0.78 = 38.78 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(38.78 \text{ dB}\mu\text{V/m})/20] = 86.89 \mu\text{V/m}$$

10.4 Test Equipment Used:


Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	10887490.26	Rohde & Schwarz	ESI26	6/29/2011	6/29/2012
Preamplifier	SF456200904	Mini-Circuits	ZX60-3018G-S+	2/4/2011	2/4/2012
Biconnilog Antenna	00051864	ETS	3142C	12/20/2010	12/20/2011
Horn Antenna	1096	Antenna Research	DRG118A	7/20/2011	7/20/2012
Horn Antenna	6556	ETS	3115	8/24/2011	8/24/2012
System Controller	121701-1	Sunol Sciences	SC99V	Time of Use	Time of Use

10.5 Results:

All spurious emissions with the test sample in receive mode were below the limits specified in Part 15.109 for a class B digital device and RSS-GEN Section 6.1.

Radiated Emissions										
Test Engineer: J. Centers		Start Date: 9/30/2011		End Date: 9/30/2011						
Temperature: 25.2		Humidity: 27.60%		Pressure: 985.4 mbar						
Specification: FCC Part 15			Test Limit: Class B							
Notes: Rx Mode										
A	B	C	D	E	F	G	H	I	J	K
Frequency	Polarity (H/V)	Raw Reading (dBuV)	Cab. (dB)	Ant. (dB)	Corr. Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	RBW / Detector	Test Distance	Results
42.799 MHz	V	7.3	0.85	11.38	19.53	40	-20.47	120kHz/QP	3m	Compliant
50.036 MHz	V	13.73	0.94	9.39	24.06	40	-15.94	120kHz/QP	3m	Compliant
60.912 MHz	V	3.19	1.06	7.33	11.57	40	-28.43	120kHz/QP	3m	Compliant
70.662 MHz	V	18.21	1.15	6.5	25.86	40	-14.14	120kHz/QP	3m	Compliant
71.833 MHz	V	17.7	1.16	6.58	25.44	40	-14.56	120kHz/QP	3m	Compliant
78.794 MHz	V	12.06	1.23	7.84	21.13	40	-18.87	120kHz/QP	3m	Compliant
Calculations:				F = C + D + E			H = F - G			

Peak Scan (Receive Mode)



11 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements.

The measurement uncertainty figures were calculated and correspond to a coverage factor of $k = 2$, providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Measurement uncertainty Table

Parameter	Uncertainty	Notes
Radiated emissions, 30 to 1000 MHz	+3.9dB	
Radiated emissions, 1 to 18 GHz	+4.2dB	
Radiated emissions, 18 to 40 GHz	+4.3dB	
Power Port Conducted emissions, 150kHz to 30 MHz	+2.8dB	

12 Revision History

Revision Level	Date	Report Number	Notes
0	10/22/2011	100512934LEX-001	Original Issue
1	11/1/2011	100512934LEX-001	Correction to Test Equipment List