

MPE Calculation

§ 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Part 1.1310 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

1.1 Test Procedure

An MPE evaluation was performed in order to show that the device was compliant with §2.1091. The maximum power density was calculated for each transmitter at a separation distance of 20cm.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{ConductedPower(dBm)/10}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$



1.2 Results:

The device contains a Cellular transmitter. The following calculations show that the total power density from each transmitter at 20cm is less than the limit for general population / un-controlled exposure. The device meets the RF exposure limit at a 20cm separation distance as required by part 2.1091 of the FCC rules with all modules transmitting simultaneously.

Burst Average Conducted Output Power of Cellular Module

Band	Channel	Frequency (MHz)	GSM	GPRS - 1 Tx Slot	GPRS - 2 Tx Slots	EDGE - 1 Tx Slot	EDGE - 2 Tx Slots
GSM 850	128	824.2	32.9	32.9	32.9	27.60	27.4
	190	836.6	32.8	32.8	32.8	27.60	27.4
	251	848.8	32.8	32.8	32.8	27.80	27.6
GSM 1900	512	1850.2	30	30	30	26.30	26
	661	1880	29.9	29.9	29.9	26.20	26
	810	1909.8	29.8	29.8	29.8	26.20	26

Time Average Conducted Output Power of Cellular Module (Duty Cycle (10*Log(Tx Slots/8) Included)

Band	Channel	Frequency (MHz)	GSM	GPRS - 1 Tx Slot	GPRS - 2 Tx Slots	EDGE - 1 Tx Slot	EDGE - 2 Tx Slots
GSM 850	128	824.2	23.87	23.87	26.88	18.57	21.38
	190	836.6	23.77	23.77	26.78	18.57	21.38
	251	848.8	23.77	23.77	26.78	18.77	21.58
GSM 1900	512	1850.2	20.97	20.97	23.98	17.27	19.98
	661	1880	20.87	20.87	23.88	17.17	19.98
	810	1909.8	20.77	20.77	23.78	17.17	19.98



Test Summary

GSM 850 Band Transmitter:

Frequency	848.8	MHz		
Limit	0.5659	mW/cm ²		
Distance	20	cm		
Conducted Power	26.78	dBm	476.43099	mW
TX Ant Gain	-0.32	dBi		
EIRP	26.46	dBm	442.58837	mW
ERP = EIRP - 2.15	24.31	dBm	269.77394	mW
Power Density	0.0299	mW/cm ² at 20cm		

GSM 1900 Band Transmitter:

Frequency	1850.2	MHz		
Limit	1.0000	mW/cm ²		
Distance	20	cm		
Conducted Power	23.98	dBm	250.03454	mW
TX Ant Gain	1.66	dBi		
EIRP	25.64	dBm	366.43757	mW
Power Density	0.0729	mW/cm ² at 20cm		