

Advanced  
Compliance Laboratory

6 Randolph Way  
Hillsborough, NJ 08844  
Tel: (908) 927 9288  
Fax: (908) 927 0728

## ELECTROMAGNETIC EMISSION COMPLIANCE REPORT of

RADIO CONTROL CAR TRANSMITTER

MODEL: 925

FCC ID: LIE925

*February 1, 2005*

This report concerns (check one): Original grant <input checked="" type="checkbox"/> Class II change <input type="checkbox"/> Equipment type: <u>Low Power Intentional Radiator</u>	
Deferred grant requested per 47 CF 0.457(d)(1)(ii)?      yes <input type="checkbox"/> no <input checked="" type="checkbox"/> If yes, defer until: _____ (date) Company agrees to notify the Commission by _____ (date) of the intended date of announcement of the product so that the grant can be issued on that date.	
Transition Rules Request per 15.37?      yes <input type="checkbox"/> no <input checked="" type="checkbox"/> If no, assumed Part 15, Subpart B for unintentional radiators - the new 47 CFR [10-1-90 Edition] provision.	
Report prepared for:	WELL-TECH TOYS CO., LTD.
Report prepared by:	Advanced Compliance Lab
Report number:	0048-050201-01



The test result in this report IS supported and covered by the NVLAP accreditation

## Table of Contents

<b>Report Cover Page .....</b>	<b>1</b>
<b>Table of Contents .....</b>	<b>2</b>
<b>Figures.....</b>	<b>3</b>
 <b>1. GENERAL INFORMATION .....</b>	 <b>4</b>
<b>1.1 Verification of Compliance .....</b>	<b>4</b>
<b>1.2 Equipment Modifications .....</b>	<b>5</b>
<b>1.3 Product Information .....</b>	<b>6</b>
<b>1.4 Test Methodology .....</b>	<b>6</b>
<b>1.5 Test Facility .....</b>	<b>6</b>
<b>1.6 Test Equipment .....</b>	<b>6</b>
<b>1.7 Statement of the Document Use .....</b>	<b>7</b>
 <b>2. PRODUCT LABELING.....</b>	 <b>8</b>
 <b>3. SYSTEM TEST CONFIGURATION .....</b>	 <b>9</b>
<b>3.1 Justification .....</b>	<b>9</b>
<b>3.2 Special Accessories.....</b>	<b>9</b>
<b>3.3 Configuration of Tested System .....</b>	<b>9</b>
 <b>4. SYSTEM SCHEMATICS .....</b>	 <b>12</b>
 <b>5. RADIATED EMISSION DATA.....</b>	 <b>13</b>
<b>5.1 Field Strength Calculation .....</b>	<b>13</b>
<b>5.2 Test Methods and Conditions .....</b>	<b>13</b>
<b>5.3 Test Data .....</b>	<b>13</b>
 <b>6. PHOTOS OF TESTED EUT .....</b>	 <b>15</b>

## Figures

<b>Figure 2.1 FCC ID Label.....</b>	<b>8</b>
<b>Figure 2.2 Location of Label on Back of the EUT .....</b>	<b>8</b>
<b>Figure 3.1 Radiated Test Setup, Position 1.....</b>	<b>10</b>
<b>Figure 3.2 Radiated Test Setup, Position 2.....</b>	<b>10</b>
<b>Figure 3.3 Radiated Test Setup, Position 3.....</b>	<b>11</b>
<b>Figure 4.1 EUT Schematics .....</b>	<b>12</b>
<b>Figure 6.1 Front View.....</b>	<b>16</b>
<b>Figure 6.2 Rear View .....</b>	<b>17</b>
<b>Figure 6.2 Inside View, Cover Opened .....</b>	<b>18</b>
<b>Figure 6.3 Component Side.....</b>	<b>19</b>
<b>Figure 6.4 Foil Side .....</b>	<b>20</b>

# 1. GENERAL INFORMATION

## 1.1 Verification of Compliance

EUT: RADIO CONTROL CAR TRANSMITTER

Model: 925

Applicant: WELL-TECH TOYS CO., LTD..  
RM 1004, CHINACHEM GOLDEN PLAZA  
77 MODY ROAD, TSIMSHATSUI EAST  
KOWLOON, HONGKONG

Test Type: FCC Part 15C CERTIFICATION

Result: PASS

Tested by: ADVANCED COMPLIANCE LABORATORY


Test Date: February 1, 2005

Report Number: 0048-050201-01

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty $u_c$	norm.	$\pm 2.36$	$\pm 2.99$	$\pm 1.83$



Wei Li  
Lab Manager  
Advanced Compliance Lab

Date: February 1, 2005

## **1.2 Equipment Modifications**

N/A

### 1.3 Product Information

#### System Configuration

ITEM	DESCRIPTION	FCC ID	CABLE
Product	RADIO CONTROL CAR TRANSMITTER 925 <sup>(1)</sup>	LIE925	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Clock/OSC Freq.	27.145 MHz		
Receiver	925 (RX)		

(1) EUT submitted for grant.

### 1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2001 at an antenna to EUT distance of 3 meters.

### 1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey. This site has been accepted by FCC to perform measurements under Part 15 or 18 in a letter dated May 19, 1997 (Refer to: 31040/PRV 1300F2). The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

### 1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Last Cal dd/mm/yy	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3448A00290	EMI Receiver	12/01/05	12/01/06
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	12/02/04	12/02/05
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	09/02/04	09/02/05
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	23/08/04	23/08/05
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	23/08/04	23/08/05
EMCO	6502	2665	10KHz-30MHz Active Loop Antenna	27/02/04	27/02/05
EMCO	3115	4945	Double Ridge Guide Horn Antenna	11/08/04	11/08/05

All Test Equipment Used are Calibrated Traceable to NIST Standards.

### **1.7 Statement for the Document Use**

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

## 2. PRODUCT LABELING

**FCC ID: LIE 925**

**This device complies with part 15 of the FCC Rules. Operating is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.**

**Figure 2.1 FCC ID Label**



**Figure 2.2 Location of the Label**



### **3. SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT with max length, 19in.

This manually operated transmitter will deactivate immediately after any control switch was released.

Testing was performed as EUT was operated at frequency channel 27.145MHz continuously.

#### **3.2 Special Accessories**

N/A

#### **3.3 Configuration of Tested System**

Figure 3.1 to Figure 3.3 illustrate this system, which is tested standing along.



**Figure 3.1 Radiated Test Setup, position 1**




**Figure 3.2 Radiated Test Setup, position 2**



**Figure 3.3 Radiated Test Setup, position 3**

## 4. SYSTEM SCHEMATICS



**Figure 4.1 System Schematics**

## 5. RADIATED EMISSION DATA

### 5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB $\mu$ V/m

RA: Amplitude of EMI Receiver before correction in dB $\mu$ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

### 5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 120KHz IF bandwidth / 120KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. Up to 10<sup>th</sup> harmonics were investigated.

### 5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel:



Typed/Printed Name: Edward Lee

Date: February 1, 2005

**Radiated Test Data (CH-27.145MHz)**

<b>Frequency (MHz)</b>	<b>Polarity [H, V] Position</b>	<b>Height (m)</b>	<b>Azimuth (Degree)</b>	<b>Peak(2) Reading (dBmV/m)</b>	<b>3m Limit(1) (dBmV/m)</b>	<b>Difference from limit (dB)</b>
27.14	X,H	2.0	190	68.1	80	-11.9
54.29	X,H	1.8	190	22.5	40	-17.5
81.44	X,H	1.2	190	23.8	40	-16.2
27.14	X,V	1.1	180	50.1	80	-29.9
54.29	X,V	1.1	180	24.1	40	-15.9
81.44	X,V	1.2	180	25.8	40	-14.2
27.14	Y,H	1.8	225	48.0	80	-32.0
54.29	Y,H	1.6	225	22.1	40	-17.9
27.14	Y,V	1.2	200	62.5	80	-17.5
54.29	Y,V	1.3	200	25.1	40	-14.9
27.14	Z,H	1.3	230	68.4	80	-11.6
54.29	Z,H	1.6	230	24.0	40	-16.0
27.19	Z,V	1.2	190	61.7	80	-18.3
54.29	Z,V	1.4	190	30.1	40	-9.9

(1) The limit for emissions within the 26.96-27.28MHz band is 10,000uV(80dB). Sec. 15.227.

The limit for other emissions is defined in Sec. 15.209.

(2) If each peak reading is less than the FCC average limit, it'll be not necessary to show the calculated average reading based on the pulse train characteristics.

## **6. PHOTOS OF TESTED EUT**

The following photos show the inside details of the EUT.




Front View







Rear View



Open View



Component Side



Foil Side