

### FCC Report (Bluetooth)

**Applicant:** Lionel L.L.C.

**Address of Applicant:** 6301 Performance Drive, Concord, North Carolina 28027, United States

**Manufacturer:** Shenzhen Jinmaihong Electronics Co., Ltd.

**Address of Manufacturer:** 38 Jianxin Road, Longgang Street, Longgang District, Shenzhen, China

**Equipment Under Test (EUT)**

Product Name: Lionel Bluetooth Radio Tower

Model No.: 1829000

Trade Mark: Lionel

**FCC ID:** LIV-BTSPKR1

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** April 02, 2018

**Date of Test:** April 03-10, 2018

**Date of report issued:** April 11, 2018

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



**Robinson Lo**

**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
00	April 11, 2018	Original

Prepared By:

*Bill. Yuan*

Date:

April 11, 2018

Project Engineer & Test Engineer

Check By:

*Andy. Wu*

Date:

April 11, 2018

Reviewer

## 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY .....</b>	<b>4</b>
<b>5 GENERAL INFORMATION .....</b>	<b>5</b>
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	7
5.3 TEST FACILITY.....	7
5.4 TEST LOCATION.....	7
5.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
5.6 DESCRIPTION OF SUPPORT UNITS .....	7
5.7 ADDITIONAL INSTRUCTIONS.....	8
<b>6 TEST INSTRUMENTS LIST .....</b>	<b>9</b>
<b>7 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>11</b>
7.1 ANTENNA REQUIREMENT .....	11
7.2 CONDUCTED EMISSIONS .....	12
7.3 CONDUCTED PEAK OUTPUT POWER.....	15
7.4 20DB EMISSION BANDWIDTH.....	18
7.5 CARRIER FREQUENCIES SEPARATION.....	21
7.6 HOPPING CHANNEL NUMBER .....	24
7.7 DWELL TIME.....	26
7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....	29
7.9 BAND EDGE.....	30
7.9.1 <i>Conducted Emission Method</i> .....	30
7.9.2 <i>Radiated Emission Method</i> .....	33
7.10 SPURIOUS EMISSION .....	35
7.10.1 <i>Conducted Emission Method</i> .....	35
7.10.2 <i>Radiated Emission Method</i> .....	37
<b>8 TEST SETUP PHOTO .....</b>	<b>45</b>
<b>9 EUT CONSTRUCTIONAL DETAILS.....</b>	<b>47</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

*Remark: Test according to ANSI C63.10:2013*

### Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

Product Name:	Lionel Bluetooth Radio Tower
Model No.:	1829000
Serial No.:	20180311
Test sample(s) ID:	GTS201804000033-1
Sample(s) Status	Engineer sample
Hardware:	BT_Radio Tower 1.2
Software:	BT V4.2
Bluetooth version:	V4.2
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, Pi/4 DQPSK
Antenna Type:	PCB antenna
Antenna gain:	2.0 dBi (Declared by Applicant)
Power supply:	DC/AC 7-18V

Note: Because of firmware limitation, this device only supports Bluetooth V4.2 GFSK modulation for BR mode and Pi/4 DQPSK modulation for EDR mode, without 8DPSK modulation & BLE mode.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

## 5.2 Test mode

Transmitting mode	keep the Bluetooth in continuously transmitting mode
-------------------	--

## 5.3 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>● <b>FCC —Registration No.: 381383</b> Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.</li> <li>● <b>Industry Canada (IC) —Registration No.: 9079A-2</b> The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.</li> </ul>
--

## 5.4 Test Location

All tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

## 5.5 Other Information Requested by the Customer

None.
-------

## 5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number
Instek	D.C. Power Supply	PS-3030	N/A

## 5.7 Additional Instructions

Power level setup in software			
Test Software Name	FCCAssist 1.5		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Apple	A1278
Mode	Channel	Frequency (MHz)	Soft Set
GFSK, Pi/4 DQPSK	CH1	2402	TX level : default
	CH40	2441	
	CH79	2480	

### Run Software

The screenshot shows the FCCAssist 1.5 software interface. The 'Parameter' section includes the following settings:

- MODE: TX
- Channel: 35
- Transmit Power: 7
- Packet type: 1-DH1
- Hopping: OFF
- Data Types: Pn9
- Serial Port: COM7

A 'Send configuration' button is visible. The log window displays the following messages:

```

2018-03-29_18:23:05
open COM7 succeed
2018-03-29_18:23:11
Channel: 35      Data Types: Pn9
Transmit Power : 7   Packet type: 1-DH1
Send configuration information successfully
    
```

The 'Description' section provides the following information:

- 1、 Channel: range 0-78, corresponding frequency 2.402GHz-2.480GHZ
- 2、 Transmit Power range 0-10, 0 is the minimum, maximum 10



## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
5	Loop Antenna (9kHz-30MHz)	ZHINAN	ZN30900A	GTS534	June 28 2017	June 27 2018
6	BiConiLog Antenna (30MHz-1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
7	Double -ridged waveguide horn (1GHz -18GHz)	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
8	Horn Antenna (18GHz -40GHz)	ETS-LINDGREN	3116C	GTS574	June 28 2017	June 27 2018
9	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
10	Coaxial Cable (9kHz-1GHz)	GTS	N/A	GTS213	June 28 2017	June 27 2018
11	Coaxial Cable (9kHz-1GHz)	GTS	N/A	GTS211	June 28 2017	June 27 2018
12	Coaxial cable (9kHz -26GHz)	GTS	N/A	GTS210	June 28 2017	June 27 2018
13	Coaxial Cable (9kHz -26GHz)	GTS	N/A	GTS212	June 28 2017	June 27 2018
14	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
15	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
16	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
17	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
18	Temporary antenna connector (9kHz -25GHz)	JUHUA	CRC9	N/A	N/A	N/A


Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	Coaxial Cable (9kHz-30MHz)	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<b>E.U.T Antenna:</b>	
<p><i>The antenna is PCB antenna, the best case gain of the antenna is 2.0dBi</i></p> 	

## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	<p>Remark  E.U.T: Equipment Under Test  LISN: Line Impedance Stabilization Network  Test table height=0.8m</p>														
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	TX mode														
Test voltage:	AC 120V,60Hz														
Test results:	Pass														


**Remark:**

1. During the test, pre-scan the GFSK, Pi/4 DQPSK modulation, and found the GFSK modulation which it is worse case.

**Measurement data:**

Test channel:	Middle
---------------	--------


Line:



Freq MHz	Reading level dBuV	lISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.157	51.02	0.40	0.08	51.50	65.60	-14.10	QP
0.157	46.02	0.40	0.08	46.50	55.60	-9.10	Average
0.233	44.50	0.40	0.11	45.01	62.35	-17.34	QP
0.233	40.46	0.40	0.11	40.97	52.35	-11.38	Average
0.317	41.80	0.39	0.10	42.29	59.80	-17.51	QP
0.317	37.75	0.39	0.10	38.24	49.80	-11.56	Average
0.402	40.43	0.35	0.11	40.89	57.81	-16.92	QP
0.402	35.17	0.35	0.11	35.63	47.81	-12.18	Average
0.686	35.85	0.26	0.13	36.24	56.00	-19.76	QP
0.686	31.39	0.26	0.13	31.78	46.00	-14.22	Average
0.909	34.23	0.22	0.14	34.59	56.00	-21.41	QP
0.909	28.74	0.22	0.14	29.10	46.00	-16.90	Average

Test channel:	Middle
---------------	--------

**Neutral:**




Freq MHz	Reading level dBUV	LISN/ISN factor dB	Cable loss dB	level dBUV	Limit level dBUV	Over limit dB	Remark
0.161	46.62	0.40	0.08	47.10	65.43	-18.33	QP
0.161	42.75	0.40	0.08	43.23	55.43	-12.20	Average
0.204	42.31	0.40	0.11	42.82	63.45	-20.63	QP
0.204	38.29	0.40	0.11	38.80	53.45	-14.65	Average
0.322	39.31	0.39	0.10	39.80	59.66	-19.86	QP
0.322	34.74	0.39	0.10	35.23	49.66	-14.43	Average
0.499	33.07	0.32	0.11	33.50	56.01	-22.51	QP
0.499	28.24	0.32	0.11	28.67	46.01	-17.34	Average
0.634	28.96	0.28	0.12	29.36	56.00	-26.64	QP
0.634	24.39	0.28	0.12	24.79	46.00	-21.21	Average
0.839	29.14	0.23	0.14	29.51	56.00	-26.49	QP
0.839	24.02	0.23	0.14	24.39	46.00	-21.61	Average

**Notes:**

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

### 7.3 Conducted Peak Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm(for GFSK),20.97dBm(for EDR)
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Measurement Data


Modulation mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	2.45	30.00	Pass
	Middle	2.43		
	Highest	2.42		
Pi/4 DQPSK	Lowest	2.07	20.97	Pass
	Middle	1.90		
	Highest	2.01		

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel




Modulation mode: Pi/4 DQPSK



Lowest channel




Middle channel



Highest channel

## 7.4 20dB Emission Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data


Modulation mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.845	Pass
	Middle	0.852	
	Highest	0.849	
Pi/4 DQPSK	Lowest	1.212	Pass
	Middle	1.215	
	Highest	1.215	

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode: Pi/4 DQPSK



Lowest channel




Middle channel



Highest channel

## 7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	GFSK: 0.025MHz or the 20dB bandwidth(whichever is greater) Pi/4 DQPSK: 0.025MHz or 2/3 of the 20dB bandwidth(whichever is greater)
Test setup:	 <p>The diagram shows a Spectrum Analyzer and an E.U.T. connected by a red cable. They are positioned on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data


Modulation mode	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK	Lowest	1005	852	Pass
	Middle	1005	852	Pass
	Highest	1005	852	Pass
Pi/4 DQPSK	Lowest	1005	810	Pass
	Middle	1005	810	Pass
	Highest	1005	810	Pass

Note: According to section 7.4


Modulation mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	852	852
Pi/4 DQPSK	1215	810

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Modulation mode: Pi/4 DQPSK



Lowest channel




Middle channel



Highest channel

## 7.6 Hopping Channel Number


Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data:


Modulation mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
Pi/4 DQPSK	79	15	Pass




Modulation mode: **GFSK**



Modulation mode: **Pi/4 DQPSK**



## 7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	130.14	400	Pass
2441MHz	DH3	266.40	400	Pass
2441MHz	DH5	310.19	400	Pass
2441MHz	2-DH1	133.86	400	Pass
2441MHz	2-DH3	264.80	400	Pass
2441MHz	2-DH5	311.15	400	Pass

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot =  $0.4067(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 130.14\text{ms}$

DH3 time slot =  $1.665(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 266.40\text{ms}$

DH5 time slot =  $2.908(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 310.19\text{ms}$


2-DH1 time slot =  $0.4183(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 133.86\text{ms}$

2-DH3 time slot =  $1.655(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 264.80\text{ms}$


2-DH5 time slot =  $2.917(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 311.15\text{ms}$

Test plot as follows:


Modulation mode:	GFSK	Test channel:	2441MHz
------------------	------	---------------	---------



DH1




DH3




DH5


Modulation mode:	Pi/4 DQPSK	Test channel:	2441MHz
------------------	------------	---------------	---------



2-DH1



2-DH3




2-DH5

## 7.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) requirement:
<p><i>Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</i></p> <p><i>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</i></p>	
EUT Pseudorandom Frequency Hopping Sequence	
<p><i>The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.</i></p> <ul style="list-style-type: none"> <li>• Number of shift register stages: 9</li> <li>• Length of pseudo-random sequence: <math>2^9 - 1 = 511</math> bits</li> <li>• Longest sequence of zeros: 8 (non-inverted signal)</li> </ul> <div data-bbox="244 1016 1297 1167" style="text-align: center;"> </div> <p style="text-align: center;"><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p><i>An example of Pseudorandom Frequency Hopping Sequence as follow:</i></p> <div data-bbox="244 1263 1240 1417" style="text-align: center;"> </div> <p><i>Each frequency used equally on the average by each transmitter.</i></p> <p><i>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</i></p>	

## 7.9 Band Edge


### 7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:

**GFSK Mode:**

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel




No-hopping mode




Hopping mode

**Pi/4 DQPSK Mode:**

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel



No-hopping mode



Hopping mode



## 7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

**Remark:**

1. During the test, pre-scan the GFSK, Pi/4 DQPSK modulation, and found the GFSK modulation which it is worse case.

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	42.38	27.59	5.38	30.18	45.17	74.00	-28.83	Horizontal
2400.00	59.09	27.58	5.39	30.18	61.88	74.00	-12.12	Horizontal
2390.00	42.88	27.59	5.38	30.18	45.67	74.00	-28.33	Vertical
2400.00	61.08	27.58	5.39	30.18	63.87	74.00	-10.13	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	33.04	27.59	5.38	30.18	35.83	54.00	-18.17	Horizontal
2400.00	44.25	27.58	5.39	30.18	47.04	54.00	-6.96	Horizontal
2390.00	32.95	27.59	5.38	30.18	35.74	54.00	-18.26	Vertical
2400.00	45.85	27.58	5.39	30.18	48.64	54.00	-5.36	Vertical

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.42	27.53	5.47	29.93	47.49	74.00	-26.51	Horizontal
2500.00	43.69	27.55	5.49	29.93	46.80	74.00	-27.20	Horizontal
2483.50	45.18	27.53	5.47	29.93	48.25	74.00	-25.75	Vertical
2500.00	44.64	27.55	5.49	29.93	47.75	74.00	-26.25	Vertical

**Average value:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.86	27.53	5.47	29.93	38.93	54.00	-15.07	Horizontal
2500.00	33.94	27.55	5.49	29.93	37.05	54.00	-16.95	Horizontal
2483.50	37.03	27.53	5.47	29.93	40.10	54.00	-13.90	Vertical
2500.00	33.82	27.55	5.49	29.93	36.93	54.00	-17.07	Vertical

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.10 Spurious Emission

### 7.10.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 Meas Guidance V04
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Measurement data:

#### Remark:


During the test, pre-scan the GFSK, Pi/4 DQPSK modulation, and found the GFSK modulation which it is worse case.

Test channel: Lowest channel




30MHz~25GHz

Test channel: Middle channel




30MHz~25GHz


Test channel: Highest channel



30MHz~25GHz

## 7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Test setup:	Below 30MHz				
					
Below 1GHz					

	 <p>Above 1GHz</p>
<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the</li> </ol>

	EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Measurement data:****9 kHz ~ 30 MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


*Remark:*

- 2. During the test, pre-scan the GFSK, Pi/4 DQPSK modulation, and found the GFSK modulation which it is worse case.*

■ Below 1GHz

Test channel:	Middle
---------------	--------

Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
42.154	41.81	12.22	0.69	35.79	18.93	40.00	-21.07	QP
48.502	37.60	12.29	0.76	36.11	14.54	40.00	-25.46	QP
54.643	37.18	11.82	0.81	36.25	13.56	40.00	-26.44	QP
97.798	35.35	11.93	1.17	36.70	11.75	43.50	-31.75	QP
191.745	42.63	9.99	1.80	37.29	17.13	43.50	-26.37	QP
287.990	37.95	13.27	2.31	37.41	16.12	46.00	-29.88	QP



Test channel:	Middle
---------------	--------

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
40.559	39.01	12.21	0.67	35.70	16.19	40.00	-23.81	QP
95.762	38.02	11.59	1.16	36.69	14.08	43.50	-29.42	QP
155.910	42.68	8.05	1.60	37.11	15.22	43.50	-28.28	QP
167.824	42.39	8.46	1.67	37.18	15.34	43.50	-28.16	QP
191.745	43.58	9.99	1.80	37.29	18.08	43.50	-25.42	QP
383.932	37.21	15.08	2.78	37.51	17.56	46.00	-28.44	QP

■ Above 1GHz

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	58.31	31.78	8.60	32.09	66.60	74.00	-7.40	Vertical
7206.00	40.94	36.15	11.65	32.00	56.74	74.00	-17.26	Vertical
9608.00	35.99	37.95	14.14	31.62	56.46	74.00	-17.54	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	57.48	31.78	8.60	32.09	65.77	74.00	-8.23	Horizontal
7206.00	40.61	36.15	11.65	32.00	56.41	74.00	-17.59	Horizontal
9608.00	36.98	37.95	14.14	31.62	57.45	74.00	-16.55	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	38.61	31.78	8.60	32.09	46.90	54.00	-7.10	Vertical
7206.00	23.66	36.15	11.65	32.00	39.46	54.00	-14.54	Vertical
9608.00	21.65	37.95	14.14	31.62	42.12	54.00	-11.88	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	38.20	31.78	8.60	32.09	46.49	54.00	-7.51	Horizontal
7206.00	24.67	36.15	11.65	32.00	40.47	54.00	-13.53	Horizontal
9608.00	21.16	37.95	14.14	31.62	41.63	54.00	-12.37	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

*Remark:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“\*”, means this data is the too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:	Middle
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	58.49	31.85	8.67	32.12	66.89	74.00	-7.11	Vertical
7323.00	41.05	36.37	11.72	31.89	57.25	74.00	-16.75	Vertical
9764.00	36.09	38.35	14.25	31.62	57.07	74.00	-16.93	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	57.69	31.85	8.67	32.12	66.09	74.00	-7.91	Horizontal
7323.00	40.74	36.37	11.72	31.89	56.94	74.00	-17.06	Horizontal
9764.00	37.10	38.35	14.25	31.62	58.08	74.00	-15.92	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	38.78	31.85	8.67	32.12	47.18	54.00	-6.82	Vertical
7323.00	23.77	36.37	11.72	31.89	39.97	54.00	-14.03	Vertical
9764.00	21.76	38.35	14.25	31.62	42.74	54.00	-11.26	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	38.40	31.85	8.67	32.12	46.80	54.00	-7.20	Horizontal
7323.00	24.80	36.37	11.72	31.89	41.00	54.00	-13.00	Horizontal
9764.00	21.28	38.35	14.25	31.62	42.26	54.00	-11.74	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	58.36	31.93	8.73	32.16	66.86	74.00	-7.14	Vertical
7440.00	40.97	36.59	11.79	31.78	57.57	74.00	-16.43	Vertical
9920.00	36.02	38.81	14.38	31.88	57.33	74.00	-16.67	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	57.54	31.93	8.73	32.16	66.04	74.00	-7.96	Horizontal
7440.00	40.64	36.59	11.79	31.78	57.24	74.00	-16.76	Horizontal
9920.00	37.01	38.81	14.38	31.88	58.32	74.00	-15.68	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	38.84	31.93	8.73	32.16	47.34	54.00	-6.66	Vertical
7440.00	23.81	36.59	11.79	31.78	40.41	54.00	-13.59	Vertical
9920.00	21.79	38.81	14.38	31.88	43.10	54.00	-10.90	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	38.47	31.93	8.73	32.16	46.97	54.00	-7.03	Horizontal
7440.00	24.85	36.59	11.79	31.78	41.45	54.00	-12.55	Horizontal
9920.00	21.32	38.81	14.38	31.88	42.63	54.00	-11.37	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

*Remark:*

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *“\*\*”, means this data is too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

## 8 Test Setup Photo



Radiated Emission





## Conducted Emission







## 9 EUT Constructional Details























-----End-----