

## Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Train Unit) for a RC Train.

The sample supplied operated on 10 channels, normally at 2420 - 2465MHz.  
The channels are shown in below table.

2420	2425	2429	2435	2440
2445	2450	2455	2460	2465

The EUT is powered by 6 x 1.5V C batteries. After switching on the EUT, the train will be moved forward or backward and turned left and right based on the switches pressed in the controller.

### Train with ultrasonic function

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Nominal rated field strength is 94.8dB $\mu$ V/m at 3m (Peak), 71.1dB $\mu$ V/m at 3m (Average)

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 74.1dB $\mu$ V/m at 3m in frequency 2.440GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

$$= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$$

$$= 3.0 * 5 / \text{sqrt} (2.483.5) \text{ mW}$$

$$= 9.52 \text{ mW}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(\text{FS} * \text{D}) ^2 * 1000 / 30]$$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum average field strength plus production tolerance  $\leq$  105dBuV/m @3m and antenna gain is  $\geq$  0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.