

Exhibit A Technical Report, Diagram

Applicant Name And Address

Their full name and mailing address is given below:

Name : LITE-ON AUTOMOTIVE CORPORATION

***Address : 37, CHUNG YANG ROAD, N.E.P.Z. KAOHSIUNG 811,
TAIWAN, R.O.C.***

Model No. : VS520

Brand Name : LITE-ON

Block Diagram

Exhibit C Measurement Report

FCC Part 15 Subpart B
EMI TEST REPORT
of

E.U.T. : VEHICLE SECURITY (RX)

FCC ID. : LJL990601R

MODEL : VS520

Receiving Frequency : 432.960 MHz

for

APPLICANT : LITE-ON AUTOMOTIVE CORPORATION
ADDRESS : 37, CHUNG YANG ROAD, N.E.P.Z.
 KAOHSIUNG 811, TAIWANA, R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN
NO. 8 LANE 29, WENMIMG ROAD,
LOSHAN TSUN, KWEISHAN HSIANG,
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026-32

Fax:(03)3280034

Report Number : ET88R-06-049-03

TEST REPORT NOTIFICATION

Applicant : LITE-ON AUTOMOTIVE CORPORATION
37, CHUNG YANG ROAD, N.E.P.Z. KAOHSIUNG 811,
TAIWANA, R.O.C.

Manufacturer : LITE-ON AUTOMOTIVE CORPORATION
37, CHUNG YANG ROAD, N.E.P.Z. KAOHSIUNG 811,
TAIWAN, R.O.C.

Description of EUT :

- a) Type of EUT : VEHICLE SECURITY (RX)
- b) Trade Name : LITE-ON
- c) Model No. : VS520
- d) FCC ID : LJL990601R
- e) Receiving Frequency : 432.960 MHz
- f) Power Supply : DC 12V Battery

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B (1996)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

- Note : 1. The results of the testing report relate only to the items tested.
2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Issued Date : JUL. 21, 1999

Test Engineer : Jeff Chuang
(Jeff Chuang)

Approve & Authorized Signer : Will Yauo
Will Yauo, Supervisor
EMI Test Site of ELECTRONICS
TESTING CENTER, TAIWAN

<i>Table of Contents</i>	<i>Page</i>
1. GENERAL INFORMATION.....	1
1.1 PRODUCT DESCRIPTION	1
1.2 CHARACTERISTICS OF DEVICE	1
1.3 TEST METHODOLOGY	1
1.4 TEST FACILITY.....	1
2. DEFINITION AND LIMITS	2
2.1 DEFINITION	2
2.2 LIMITATION	2
2.3 LABELING REQUIREMENT	3
2.4 USER INFORMATION	3
3. RADIATED EMISSION MEASUREMENT	4
3.1 APPLICABLE STANDARD	4
3.2 MEASUREMENT PROCEDURE	4
3.3 RADIATED EMISSION DATA	6
3.4 FIELD STRENGTH CALCULATION.....	8
3.5 RADIATED EMISSION MEASURING EQUIPMENT	8
3.6 RADIATED MEASUREMENT PHOTOS	9
4. CONDUCTED EMISSION MEASUREMENT.....	10
4.1 STANDARD APPLICABLE	10

1. GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : VEHICLE SECURITY (RX)
- b) Trade Name : LITE-ON
- c) Model No. : VS520
- d) FCC ID : LJL990601R
- e) Receiving Frequency : 432.960 MHz
- f) Power Supply : DC 12V Battery

1.2 Characteristics of Device

The EUT is the Receiver of the Vehicle Security.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in section 12.1 of ANSI C63.4(1992).

For detail procedures, please see each measuring item.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No.34, Lin 5, Ding Fu Tsun, Linkou Hsiang, Taipei Hsien, Taiwan, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Feb. 10 , 1997.

2. DEFINITION AND LIMITS

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

2.2 Limitation

(1) Conducted Emission Limits :

According to 15.107 , Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 450 kHz to 30 MHz shall not exceed 250 microvolts. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

Class B Line Conducted Emission Limits :

Frequency MHz	Emissions μV	Emissions dB μV
0.45 - 30.0	250	48.0

(2) Radiated Emission Limits :

According to 15.109 , Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Class B Radiated Emission Limits :

Frequency MHz	Distance Meters	Radiated dB $\mu V/m$	Radiated $\mu V/m$
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

2.3 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.4 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. RADIATED EMISSION MEASUREMENT

3.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with § 15.109(a).

3.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test. For super-regeneration receiver, there is tow mode of measurement, one is stand-by without a TX signal (CW), and the other is receiving a proper TX signal.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



3.3 Radiated Emission Data**A.**

Operation Mode : TX ON

Test Date : JUN. 21, 1999

Temperature : 23 °C

Humidity : 60 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
432.960	H	48.1	-5.5	42.6	46.0	-3.4	360	1.20
865.920	H	28.7	2.3	31.0	46.0	-15.0	235	1.20
1298.880	H	30.9	-8.4	22.5	54.0	-31.5	45	1.00
1731.840	H/V	---	-6.2	---	54.0	---	---	---
2164.800	H/V	---	-4.0	---	54.0	---	---	---
2597.760	H/V	---	-2.4	---	54.0	---	---	---
3030.720	H/V	---	-1.1	---	54.0	---	---	---
3463.680	H/V	---	-0.1	---	54.0	---	---	---
3896.640	H/V	---	1.6	---	54.0	---	---	---
4329.600	H/V	---	2.0	---	54.0	---	---	---

Remark “—” means that the emission level is too low to be measured.

B.

Operation Mode : TX OFF

Test Date : JUN. 21, 1999

Temperature : 23 °C

Humidity : 60 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
432.960	H	45.1	-5.5	39.6	46.0	-6.4	360	1.20
865.920	H	28.0	2.3	30.3	46.0	-15.7	235	1.20
1298.880	H	37.1	-8.4	28.7	54.0	-25.3	45	1.00
1731.840	H/V	---	-6.2	---	54.0	---	---	---
2164.800	H/V	---	-4.0	---	54.0	---	---	---
2597.760	H/V	---	-2.4	---	54.0	---	---	---
3030.720	H/V	---	-1.1	---	54.0	---	---	---
3463.680	H/V	---	-0.1	---	54.0	---	---	---
3896.640	H/V	---	1.6	---	54.0	---	---	---
4329.600	H/V	---	2.0	---	54.0	---	---	---

Remark “—” means that the emission level is too low to be measured.

3.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{CORR. FACTOR}$$

where CORR. FACTOR = Antenna FACTOR + Cable FACTOR

Assume a receiver reading of 22.5 dB μ V is obtained. The Antenna Factor of 14.5 and a Cable Factor of 1.5 is added . The total of field strength is 38.5 dB μ V/m.

$$\text{RESULT} = 22.5 + 14.5 + 1.5 = 38.5 \text{ dB } \mu \text{ V/m}$$

$$\begin{aligned} \text{Level in } \mu \text{ V/m} &= \text{Common Antilogarithm}[(38.5 \text{ dB } \mu \text{ V/m})/20] \\ &= 84.14 \mu \text{ V/m} \end{aligned}$$

3.5 Radiated Emission Measuring Equipment

The following test equipment are used during the radiated test .

Equipment	Manufacturer	Model No.	Next Cal. Date
Spectrum Analyzer	Hewlett-Packard	8568B	12/02/1999
Pre-selector	Hewlett-Packard	85685A	12/07/1999
Quasi Peak Detector	Hewlett-Packard	85650A	12/02/1999
RF Test Receiver	Rohde & Schwarz	ESVS 30	01/10/2000
Log periodic Antenna	EMCO	3146	09/15/1999
Biconical Antenna	EMCO	3110	09/15/1999
Preamplifier	Hewlett-Packard	8447D	11/30/1999
Microwave EMI Test System	Hewlett-Packard	84158C	01/24/2000

4. CONDUCTED EMISSION MEASUREMENT

4.1 Standard Applicable

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to § 15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

Exhibit D Equipment ID. Label

- 1. A label of FCC ID. in the next page will be affixed to the back of the device.*