



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Transmitter Certification

of

FCC ID: LJPRH-31

Model: RH-31

Serial Number of Unit Tested: 001004/00/116804/7

to

Federal Communications Commission

Rule Part(s) 22E, 24H, Confidentiality

Date Of Report: August 15, 2003

On the Behalf of the Applicant:

Nokia Corporation

At the Request of:

P.O. K. Oksanen 08/04/2003

Nokia Corporation
Elektroniikkatie 10
Fin-90570
Oulu, Finland

Attention of:

Kare Oksanen, TCC Oulu
kare.oksanen@nokia.com
011 358 7180 08000; FAX: 011 358 7180 47222

Supervised By:

A handwritten signature in black ink, reading 'M. Flom P. Eng.' with a stylized flourish at the end.

Morton Flom, P. Eng.

The applicant has been cautioned as to the following:

15.21 Information to User.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

Rule	Description	Page
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	General Information	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	ERP Carrier Power (Radiated)	8
2.1049(c)(1), 22		
	Emission Masks (Occupied Bandwidth)	10
2.1051, 2.1049(c), 24, 24.238(b)		
	Transmitter Conducted Measurements	31
2.1053(a)	Field Strength of Spurious Radiation	61
2.1055(a)(1)	Frequency Stability (Temperature Variation)	65
2.1055(b)(1)	Frequency Stability (Voltage Variation)	68
2.202(g)	Necessary Bandwidth and Emission Bandwidth	69

Page Number 1 of 69.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) **Test Report**

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0380019

d) Client: Nokia Corporation
Elektroniikkatie 10
Fin-90570
Oulu, Finland

e) Identification: RH-31
FCC ID: LJPRH-31
Description: GSM850/1800/1900/FM Radio

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: August 15, 2003
EUT Received: August 04, 2003

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:

Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

Accessories Used During Testing:

Type	Model	Serial Number	Specimen
EUT	RH-31	001004/00/116804/7	S00824
Battery	BLD-3	N/A	S00826
Charger	ACP-12U	N/A	S01275
Charger	ACP-7U	N/A	S01248
Charger	ACP-8U	N/A	S01250
Desktop Stand	DCV-14	N/A	S00729
Music Stand	DT-1	N/A	
Stereo Headset	HDS-3	N/A	

Page Number 2 of 69.

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

22E, 24H, Confidentiality

Sub-Part 2.1033

(c)(1): Name and Address of Applicant:

Nokia Corporation
Elektroniikkatie 10
Fin-90570
Oulu, Finland

Manufacturer:

Nokia TMC., Ltd.
Yangduck-Dong 973-6
Hwe won-Ku, Masan, Korea

(c)(2): **FCC ID:** LJPRH-31

Model Number: RH-31

(c)(3): Instruction Manual(s):

Please See Attached Exhibits

(c)(4): **Type of Emission:** 300KGXW, 300KG7W

(c)(5): **FREQUENCY RANGE, MHz:** 824.2 to 848.8 GSM850
1850.2 to 1909.8 GSM1900

(c)(6): **Power Rating, Watts:** 1.288 ERP (850)
1.318 EIRP (1900)
____ Switchable x Variable ____ N/A

(c)(7): **Maximum Power Rating, Watts:** 2 GSM 850
1 GSM 1900

Page Number 3 of 69.

Subpart 2.1033 (continued)

(c)(8): Voltages & Currents in All Elements in Final RF Stage, Including Final Transistor or Solid State Device:

Collector Current, A	=	per manual
Collector Voltage, Vdc	=	per manual
Supply Voltage, Vdc	=	3.9

(c)(9): **Tune-Up Procedure:**

Please See Attached Exhibits

(c)(10): **Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please See Attached Exhibits

(c)(11): **Label Information:**

Please See Attached Exhibits

(c)(12): **Photographs:**

Please See Attached Exhibits

(c)(13): **Digital Modulation Description:**

☐ Attached Exhibits
☒ N/A

(c)(14): **Test and Measurement Data:**

Follows

Page Number

4 of 69.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.



**THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION**

ACCREDITED LABORATORY

A2LA has accredited

M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 - 1999 "General Requirements for the Competence of Testing and Calibration Laboratories" and any additional program requirements in the identified field of testing. Testing and calibration laboratories that comply with this International Standard also operate in accordance with ISO 9001 or ISO 9002.

Presented this 2nd day of March, 2001.



Pete Mlyns
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2002

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:1999

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85225
Morton Flom Phone: 480 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2002 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-2000; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1; CNS 13438
Harmonic Currents	EN 61000-3-2
Fluctuation and Flicker	EN 61000-3-3
RF Immunity	EN: 50082-1, 50082-2, 55024; AS/NZS 4251.1
Electrostatic Discharge (ESD)	EN 61000-4-2
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
Voltage Dips, Short Interruptions, and Line Voltage Variations	EN 61000-4-11
47 CFR (FCC)	Parts: 2, 18, 21, 22, 23, 24, 25, 26, 27, 74, 80, 87, 90, 95, 97, 101 (excluding SAR Testing)
Power Frequency Magnetic Field Immunity	EN 61000-4-8
Immunity to Conducted Disturbances	EN 61000-4-6

(A2LA Cert. No. 1008.01) 08/01/02

Page 1 of 1

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8373 • Phone: 301-644 3248 • Fax: 301-662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

Page Number

5 of 69.

Sub-part

2.1033(c)(14):**Test and Measurement Data**

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 – Domestic Public Fixed Radio Services
- ☒ 22 – Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 – International Fixed Public Radiocommunication services
- ☒ 24 – Personal Communications Services
- ☐ 74 Subpart H - Low Power Auxiliary Stations
- ☐ 80 – Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☐ 87 – Aviation Services
- ☐ 90 – Private Land Mobile Radio Services
- ☐ 94 – Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 – Fixed Microwave Services

General Information

1. Prior to testing, the deviation for audio modulation and each of the respective SAT + ST tones were set as close as possible to the required limit.
2. Except for audio modulation, which was applied externally, Wideband Data SAT, ST and all other tones and operational modes were provided by a test control unit incorporating appropriate software. Worst case repetition rate for Wideband Data was 10 kb/s.
3. Spurious radiation was measured at three (3) meters.
4. The two cellular frequency bands are available to the user automatically. Please refer to the manual contained in the documentation.
5. The normal modes of modulation are:
 - ☐ (a) GSM/GPRS 850
 - ☒ (b) EGPRS 850
 - ☐ (c) GSM/GPRS 1900
 - ☐ (d) EGPRS 1900

Standard Test Conditions
and
Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

Page Number 8 of 69.


Name of Test: ERP/EIRP Carrier Power (Radiated)

Specification: TIA/EIA 603A (Substitution Method)

Definition: The average radiated power of device is the equivalent power required, when delivered to a substitution antenna, to produce at a distant point the same average received power as produced by the licensed device.

Method Of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 4m and rotate turntable from 0° to 360°. Record the highest received signal in dB as E_T .

c) Replace the transmitter under test with a substitution antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power level using the same modulation as with the transmitter. Raise and lower the test antenna like in step b) and record the highest received signal in dB as E_S .

d) Calculate radiated power as following:

$$\text{Radiated power} = \text{Level} + E_T - E_S + \text{Gain}_{\text{Ant}}$$

E_T Signal level received from transmitter

E_S Signal level received from substitution antenna

Results Attached

Page Number

9 of 69.

Test Results For:

ERP/EIRP Carrier Power (Radiated)

Freq MHz	Level dBm	Antenna Gain dBi	$E_T - E_S$ dBm	P ol	Radiated P Out dbm	Radiated P Out Watts
GSM850/GPRS850						
824.2	30.8	-0.9dBd	97.5-98.0	V	29.4 ERP	0.871
836.4	31.1	-0.6dBd	97.0-97.7	V	29.8 ERP	0.955
848.8	31.3	-0.2dBd	97.0-97.0	V	31.1 ERP	1.288
EGPRS850						
824.2	24.4	-0.9dBd	93.2-95.2	V	21.5 ERP	0.141
836.4	24.7	-0.6dBd	94.2-94.0	V	24.3 ERP	0.269
848.8	24.8	-0.2dBd	94.0-93.8	V	24.8 ERP	0.302
GSM1900/GPRS1900						
1850.2	25.6	+0.2dBi	97.0-92.2	H	31.2 EIRP	1.318
1880.0	25.8	-0.5dBi	96.7-91.5	H	28.9 EIRP	0.776
1909.8	26.1	-0.8dBi	97.0-93.5	H	25.9 EIRP	0.389
EGPRS1900						
1850.2	20.7	+0.2dBi	93.7-90.2	H	25.8 EIRP	0.380
1880.0	20.7	-0.5dBi	94.3-89.5	H	24.4 EIRP	0.275
1909.8	20.4	-0.8dBi	94.8-91.3	H	20.7 EIRP	0.117

SAMPLE CALCULATION:

$$P_{\text{ANT OUT}} + \text{ANT GAIN} + E_T - E_S = P.O. \text{ RADIATED}$$

$$30.8 - 0.9 + 97.5 - 98.0 = 29.4 \text{ dbm ERP}$$

$$= 0.871 \text{ W ERP}$$

ANTENNAS: EMCO 3125-870 dipole s/n 1017 cal. May 02
 EMCO 3125-1880 dipole s/n 1010 cal. Oct 02

Page Number 10 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)

Specification: 47 CFR 2.1049(c)(1), 22


Test Equipment: As per previous page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ± 2.5 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. Measurement Results: Attached

Page Number 11 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380048: 2003-Aug-06 Wed 14:20:00
State: 1:Low Power



Power:
Modulation:


LOW
GSM/GPRS850
99% BANDWIDTH

Performed By:

David Lee

Page Number 12 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380049: 2003-Aug-06 Wed 14:21:00
State: 1:Low Power



Power:
Modulation:


LOW
EGPRS850
99% BANDWIDTH

Performed By:

David Lee

Page Number 13 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380018: 2003-Aug-05 Tue 11:27:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS850
99% BANDWIDTH

Performed By:

David Lee

Page Number 14 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380019: 2003-Aug-05 Tue 11:30:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS850
99% BANDWIDTH

Performed By:

David Lee

Page Number 15 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380020: 2003-Aug-05 Tue 11:32:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS850
A LOWER BAND EDGE

Performed By:

David Lee

Page Number 16 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380028: 2003-Aug-05 Tue 11:45:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS850
UPPER BAND EDGE

Performed By:

David Lee

Page Number 17 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380021: 2003-Aug-05 Tue 11:35:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS850
A1 UPPER BAND EDGE

Performed By:

David Lee

Page Number 18 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380022: 2003-Aug-05 Tue 11:36:00
State: 2:High Power



Power:
Modulation:

HIGH
GSM/GPRS850
B1 LOWER BAND EDGE


Performed By:

David Lee

Page Number

19 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380023: 2003-Aug-05 Tue 11:38:00
State: 2:High Power



Power:
Modulation:

HIGH
GSM/GPRS850
B1 UPPER BAND EDGE




Performed By:

David Lee

Page Number 20 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380024: 2003-Aug-05 Tue 11:40:00
State: 2:High Power



Power:
Modulation:

HIGH
GSM/GPRS850
A2 LOWER BAND EDGE


Performed By:

David Lee

Page Number

22 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380027: 2003-Aug-05 Tue 11:44:00
State: 2:High Power



Power:
Modulation:

HIGH
GSM/GPRS850
B2 LOWER BAND EDGE


Performed By:

David Lee

Page Number

23 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380030: 2003-Aug-05 Tue 11:48:00
State: 2:High Power



Power:
Modulation:

HIGH
EGPRS 850
A1 UPPER BAND EDGE




Performed By:

David Lee

Page Number

24 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380031: 2003-Aug-05 Tue 11:48:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS850
B1 LOWER BAND EDGE

Performed By:

David Lee

Page Number 25 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380032: 2003-Aug-05 Tue 11:49:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS850
B1 UPPER BAND EDGE

Performed By:

David Lee

Page Number 28 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380035: 2003-Aug-05 Tue 11:53:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS850
B2 LOWER BAND EDGE

Performed By:

David Lee

Page Number 29 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380029: 2003-Aug-05 Tue 11:47:00
State: 2:High Power



Power:
Modulation:

HIGH
EGPRS850
LOWER BAND EDGE


Performed By:

David Lee

Page Number

30 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380036: 2003-Aug-05 Tue 11:57:00
State: 2:High Power



Power:
Modulation:

HIGH
EGPRS850
UPPER BAND EDGE

Performed By:

David Lee

Page Number 31 of 69.

Name of Test: Transmitter Conducted Measurements

Specification: 47 CFR 2.1051: Unwanted (spurious) Emissions
2.1049(c), 24.238(b): Occupied Bandwidth
24: Emissions at Band Edges

Test Equipment: As per attached page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page with the Spectrum Analyzer connected.
2. The low and high channels for all RF powers within the designated frequency block(s) were measured.
3. Measurement Results: Attached




Performed By:

David Lee

Transmitter Spurious Emission

Test A. Occupied Bandwidth (In-Band Spurious)


Test B. Out-of-Band Spurious



Asset (as applicable)	Description	s/n
(1)	Audio Oscillator/Generator	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00012	HP 3312A	1432A11250
(2)	Coaxial Attenuator	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(3)	Filters; Notch, HP, LP, BP	
i00126	Eagle TNF-1	100-250
i00125	Eagle TNF-1	50-60
i00124	Eagle TNF-1	250-850
(4)	Spectrum Analyzer	
i00048	HP 8566B	2511A01467
i00029	HP 8563E	3213A00104

Page Number 33 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380221: 2003-Aug-04 Mon 15:53:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
LOWER BAND EDGE

Performed By:

David Lee

Page Number 34 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380232: 2003-Aug-04 Mon 16:08:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
UPPER BAND EDGE

Performed By:

David Lee

Page Number 35 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380236: 2003-Aug-04 Mon 16:14:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
LOWER BAND EDGE

Performed By:

David Lee

Page Number 36 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380247: 2003-Aug-04 Mon 16:23:00
State: 2:High Power



Power:
Modulation:

HIGH
EGPRS1900
UPPER BAND EDGE


Performed By:

David Lee

Page Number

37 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380044: 2003-Aug-06 Wed 14:11:00
State: 1:Low Power



Power:
Modulation:


LOW
GSM/GPRS1900
99% BANDWIDTH

Performed By:

David Lee

Page Number 38 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380045: 2003-Aug-06 Wed 14:12:00
State: 1:Low Power



Power:
Modulation:

LOW
EGPRS1900
99% BANDWIDTH


Performed By:

David Lee

Page Number

39 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380222: 2003-Aug-04 Mon 15:54:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
A UPPER BAND EDGE

Performed By:

David Lee

Page Number 40 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380223: 2003-Aug-04 Mon 15:55:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
D LOWER BAND EDGE

Performed By:

David Lee

Page Number 41 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380224: 2003-Aug-04 Mon 16:01:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
D UPPER BAND EDGE

Performed By:

David Lee

Page Number 42 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380225: 2003-Aug-04 Mon 16:02:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
B LOWER BAND EDGE

Performed By:

David Lee

Page Number 43 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380226: 2003-Aug-04 Mon 16:03:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
B UPPER BAND EDGE

Performed By:

David Lee

Page Number 44 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380227: 2003-Aug-04 Mon 16:04:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
E LOWER BAND EDGE

Performed By:

David Lee

Page Number 45 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380228: 2003-Aug-04 Mon 16:05:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
E UPPER BAND EDGE

Performed By:

David Lee

Page Number 46 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380229: 2003-Aug-04 Mon 16:06:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
F LOWER BAND EDGE

Performed By:

David Lee

Page Number 47 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380230: 2003-Aug-04 Mon 16:07:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
F UPPER BAND EDGE

Performed By:

David Lee

Page Number 48 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380231: 2003-Aug-04 Mon 16:08:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
C LOWER BAND EDGE

Performed By:

David Lee

Page Number 49 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380234: 2003-Aug-04 Mon 16:11:00
State: 2:High Power



Power:
Modulation:


HIGH
GSM/GPRS1900
99% BANDWIDTH

Performed By:

David Lee

Page Number 50 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380235: 2003-Aug-04 Mon 16:12:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
99% BANDWIDTH

Performed By:

David Lee

Page Number 51 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380237: 2003-Aug-04 Mon 16:14:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
A UPPER BAND EDGE

Performed By:

David Lee

Page Number 52 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380238: 2003-Aug-04 Mon 16:15:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
D LOWER BAND EDGE

Performed By:

David Lee

Page Number 53 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380239: 2003-Aug-04 Mon 16:16:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
D UPPER BAND EDGE

Performed By:

David Lee

Page Number 54 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380240: 2003-Aug-04 Mon 16:17:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
B LOWER BAND EDGE

Performed By:

David Lee

Page Number 55 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380241: 2003-Aug-04 Mon 16:17:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
B UPPER BAND EDGE

Performed By:

David Lee

Page Number 56 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380242: 2003-Aug-04 Mon 16:18:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
E LOWER BAND EDGE

Performed By:

David Lee

Page Number 58 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380244: 2003-Aug-04 Mon 16:20:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
F LOWER BAND EDGE

Performed By:

David Lee

Page Number 59 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380245: 2003-Aug-04 Mon 16:21:00
State: 2:High Power



Power:
Modulation:


HIGH
EGPRS1900
F UPPER BAND EDGE

Performed By:

David Lee

Page Number 60 of 69.

Name of Test: Emission Masks (Occupied Bandwidth)
g0380246: 2003-Aug-04 Mon 16:22:00
State: 2:High Power



Power:
Modulation:

HIGH
EGPRS1900
C LOWER BAND EDGE

Performed By:

David Lee

Page Number 61 of 69.

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)


Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917

Measurement Procedure

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.


1.2.12.2 Method of Measurement

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth ≥ 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to $\pm$ the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Page Number 63 of 69.

Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

$$\text{Radiated spurious emissions dB} = 10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I)}$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset (as applicable)	Description	s/n	Cycle	Last Cal
Per ANSI C63.4-1992/2000 Draft, 10.1.4				
Transducer				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-02
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-02
i00089	Apriel 2001 200MHz-1GHz	001500	12 mo.	Sep-02
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-02
Amplifier				
i00028	HP 8449A	2749A00121	12 mo.	Mar-03
Spectrum Analyzer				
i00029	HP 8563E	3213A00104	12 mo.	Jan-03
i00033	HP 85462A	3625A00357	12 mo.	Jan-03
i00048	HP 8566B	2511AD1467	6 mo.	Jul-03

Page Number 64 of 69.

Name of Test: Field Strength of Spurious Radiation

GSM850 g0380011: 2003-Aug-04 Mon 13:23:00

Frequency Tuned, MHz	Frequency Emission, MHz	ERP, dBm	ERP, dbc
836.400000	1672.751667	-28.6	-59.7
836.400000	2509.151667	-37.6	-68.7
836.400000	3345.551667	-56.1	-87.2
836.400000	4181.951667	-55	-86.1
836.400000	5018.351667	-55.2	-86.3
836.400000	5854.751667	-54.1	-85.2
836.400000	6691.151667	-52.1	-83.2
836.400000	7527.551667	-50.5	-81.4
836.400000	8363.951667	-49.2	-80.3

EGPRS850 g0380012: 2003-Aug-04 Mon 14:16:00

Frequency Tuned, MHz	Frequency Emission, MHz	ERP, dBm	ERP, dbc
836.400000	1672.816667	-30.9	-62
836.400000	2509.216667	-31.9	-63
836.400000	3345.616667	-28.7	-59.8
836.400000	4182.016667	-27.5	-58.6
836.400000	5018.416667	-27.1	-58.2
836.400000	5854.816667	-53.1	-84.2
836.400000	6691.216667	-52.4	-83.5
836.400000	7527.616667	-49	-80.1
836.400000	8364.016667	-48.9	-80

GSM1900 g0380010: 2003-Aug-04 Mon 12:41:00

Frequency Tuned, MHz	Frequency Emission, MHz	EIRP, dBm	EIRP, dbc
1880.000000	3760.003333	-41.8	-73
1880.000000	5640.003333	-51.6	-82.8
1880.000000	7519.735000	-39.9	-71.1
1880.000000	9400.003333	-46.6	-77.8
1880.000000	11280.003333	-44	-75.2
1880.000000	13160.003333	-43.2	-74.4
1880.000000	15040.003333	-41.2	-72.4

EGPRS1900 g0380041: 2003-Aug-04 Mon 14:24:00

Frequency Tuned, MHz	Frequency Emission, MHz	EIRP, dBm	EIRP, dbc
1880.000000	3760.001667	-48.3	-79.5
1880.000000	5640.001667	-51.6	-82.8
1880.000000	7520.001667	-47.2	-78.4
1880.000000	9400.001667	-45.5	-76.7
1880.000000	11280.001667	-44.3	-75.5
1880.000000	13160.001667	-42.7	-73.9
1880.000000	15040.001667	-39.4	-70.6
1880.000000	16920.001667	-39.6	-70.8

Page Number 65 of 69.

Name of Test: Frequency Stability (Temperature Variation)

Specification: 47 CFR 2.1055(a)(1)

Test Conditions: As Indicated


Test Equipment: As per previous page

Measurement Procedure

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. Measurement Results: Attached

Transmitter Test Set-Up

Test A. Operational Stability
 Test B. Carrier Frequency Stability
 Test C. Operational Performance Stability
 Test D. Humidity
 Test E. Vibration
 Test F. Environmental Temperature
 Test G. Frequency Stability: Temperature Variation
 Test H. Frequency Stability: Voltage Variation



Asset (as applicable)	Description	s/n
(1)	Temperature, Humidity, Vibration	
i00027	Tenney Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	Coaxial Attenuator	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	RF Power	
i00014	HP 435A Power Meter	1733A05839
i00039	HP 436A Power Meter	2709A26776
i00020	HP 8901A Power Mode	2105A01087
(4)	Frequency Counter	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

Page Number 67 of 69.

Name of Test: Frequency Stability (Temperature Variation)

GSM/GPRS/EGPRS CELLULAR BAND

°C	Change, Hz	Change, ppm
-30	17.2	0.0
-20	21.9	0.0
-10	11.3	0.0
0	9.6	0.0
10	19.9	0.0
20	20.2	0.0
30	21.6	0.0
40	12.0	0.0
50	18.5	0.0

GSM/GPRS/EGPRS PCS BAND

°C	Change, Hz	Change, ppm
-30	5.3	0.0
-20	10.0	0.0
-10	-5.9	0.0
0	16.0	0.0
10	2.6	0.0
20	-16.0	0.0
30	10.7	0.0
40	14.8	0.0
50	16.1	0.0

Page Number 68 of 69.

Name of Test: Frequency Stability (Voltage Variation)

Specification: 47 CFR 2.1055 (b)(1)

Test Equipment: As per previous page

Measurement Procedure

1. The EUT was placed in a temperature chamber at $25 \pm 5^\circ\text{C}$ and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

Results: Frequency Stability (Voltage Variation)

GSM/GPRS/EGPRS CELLULAR BAND

BATTERY END POINT (Voltage) = 3.35

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
100	3.9	836.4000202	20.2	0.0
B.E.P.	3.25	836.4000101	10.1	0.0

GSM/GPRS/EGPRS PCS BAND

BATTERY END POINT (Voltage) = 3.25

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
100	3.9	1879.9999840	-16.0	0.0
B.E.P.	3.25	1880.0000076	7.6	0.0

Limit: Must remain within authorized frequency block.



Performed By:

David Lee

Page Number 69 of 69.

Name of Test: Necessary Bandwidth and Emission Bandwidth

Specification: 47 CFR 2.202(g)

Modulation = 300KGXW

Necessary Bandwidth:

Necessary Bandwidth (B_N), kHz = 300
(measured at the 99.75% power bandwidth)

Modulation = 300KG7W

Necessary Bandwidth:

Necessary Bandwidth (B_N), kHz = 300
(measured at the 99.75% power bandwidth)



Performed By:

David Lee

END OF TEST REPORT

**Testimonial
and
Statement of Certification**

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:

A handwritten signature in black ink, appearing to read "M. Flom P. Eng.", with a horizontal line drawn underneath the signature.

Morton Flom, P. Eng.