

GSM1900 test report for RM-8

CONTENTS

1	LABORATORY INFORMATION	4
2	CUSTOMER INFORMATION	4
3	SUMMARY OF TEST RESULTS	5
4	EUT INFORMATION	6
4.1	EUT description	6
5	EUT TEST SETUPS	6
6	APPLICABLE STANDARDS	6
7	RADIATED RF OUTPUT POWER	7
7.1	Test setup	7
7.2	Test method	7
7.3	EUT operation modes	8
7.4	Limit	8
7.5	Results	8
8	99% OCCUPIED BANDWIDTH	10
8.1	Test setup	10
8.2	EUT operation mode	10
8.3	Results	10
8.4	Screen shot	11
8.5	EUT operation mode	11
8.6	Results	11
8.7	Screen shot	12
9	BANDEDGE COMPLIANCE	13
9.1	Test setup	13
9.2	EUT operation mode	13
9.3	Limit	13
9.4	Results	13
9.5	Screen shots	14
9.6	EUT operation mode	14
9.7	Limit	14
9.8	Results	15
9.9	Screen shots	15
10	SPURIOUS RADIATED EMISSION	16
10.1	Test setup	16
10.2	Test method	16
10.3	EUT operation mode	17
10.4	Limit	17
10.5	Results	17
10.6	EUT operation mode	18
10.7	Limit	18
10.8	Results	18
11	FREQUENCY STABILITY, TEMPERATURE VARIATION	19
11.1	Test setup	19
11.2	EUT operation mode	19
11.3	Limit	19
11.4	Test method	19
11.5	Results	20
12	FREQUENCY STABILITY, VOLTAGE VARIATION	21
12.1	Test setup	21
12.2	EUT operation mode	21
12.3	Limit	21
12.4	Test method	21
12.5	Results	21
13	TEST EQUIPMENT	22

13.1	Conducted measurements	22
13.2	Radiated measurements	22
14	TEST SETUP PHOTOGRAPHS.....	23

1 LABORATORY INFORMATION

Test laboratory:	TCC Tampere Sinitaival 5 FIN-33720 TAMPERE Tel. +358 7180 46800 Fax. +358 7180 46880
FCC registration number:	94436 (June 14, 2002)
IC file number:	IC 3608 (March 5, 2003)

2 CUSTOMER INFORMATION

Client:	Nokia Corporation Yrtyipellontie 6F Peltola III, F406.09 FIN-90230 OULU FINLAND Tel. +358503872478 Fax. +358718008000
Contact person:	Sonja Perälä
Receipt of EUT:	24.09.2004
Date of testing:	24.09 - 01.10.2004
Date of report:	25.10.2004

The tests listed in this report have been done to demonstrate compliance with the applicable requirements in FCC rules Part 24 and IC standard RSS-133.

Contents approved:


Asko Välimäki Quality Manager

3 SUMMARY OF TEST RESULTS

Section in CFR 47	Section in RSS-133		Result
§2.1046 (a)	6.2	Conducted RF output	-
§24.232 (b)	6.2	Radiated RF output	PASS
§2.1049 (h)	5.6	99% occupied bandwidth	PASS
§24.238 (a)	6.3	Bandedge compliance	PASS
§24.238 (a), §2.1051	6.3	Spurious emissions at antenna terminals	-
§24.238 (a), §2.1053	6.3	Radiated spurious emissions	PASS
§24.235, §2.1055 (a)(1)(b)	7	Frequency stability, temperature variation	PASS
§24.235, §2.1055 (d)(1)(2)	7	Frequency stability, voltage variation	PASS

PASS Pass
 FAIL Fail
 X Measured, but there is no applicable performance criteria
 - Not done

4 EUT INFORMATION

The EUT and accessories used in the tests are listed below. Later in this report only EUT numbers are used as reference.

	Device	Type	S/N	EUT number
EUT(s)	Nokia Phone	RM-8	004400481662896	40072
	Nokia Phone	RM-8	004400481662995	40070
	Nokia Phone	RM-8	004400351765340	40066
Accessories	Nokia Charger	ACP-12U	399791K216J3008 9257	40074
	Nokia Battery	BL-4C	-	40067
	Nokia Battery	B-4C	-	40068
	Nokia Data Cable	DKU-2	-	40075
	Dummy Battery	BTD-8	-	40073

Notes: -

4.1 EUT description

The EUT is a triple band (900/1800/1900, E-GPRS) phone, with FM radio.

The EUT was not modified during the tests.

5 EUT TEST SETUPS

For each test the EUT was exercised to find out the worst case of operation modes and device configuration.

The test setup photographs are in the document referenced in section 14.

6 APPLICABLE STANDARDS


The tests were performed in guidance of CFR 47 part 24, part 2, ANSI/TIA/EIA-603-A and RSS-133. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method" for each test case.

7 RADIATED RF OUTPUT POWER

EUT	40066		
Accessories	40067		
Temp, Humidity, Air Pressure	20.. 21 °C	48.. 52 RH%	990.. 991 mbar
Date of measurement	24, 28.9.2004		
FCC rule part	§24.232 (b)		
RSS-133 section	6.2		
Measured by	Jari Jantunen		
Result	PASS		

7.1 Test setup

The EUT was set on a non-conductive turn table in a semi anechoic chamber. In the corner of the chamber there was a communication antenna, which was connected to the BS simulator located outside the chamber. The radiated power from the EUT was measured with an antenna fixed to a antenna tower. The tower and turn table were remotely controlled to turn the EUT and change the antenna polarization. The measured signal was routed from the measuring antenna to the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



7.2 Test method

- The maximum power level was searched by moving the turn table and measuring antenna and manipulating the EUT. This level (P_{EUT}) was recorded.
- The EUT was replaced with a substituting antenna.
- The substituting antenna was fed with the power (P_{Subst_TX}) giving a convenient reading on the spectrum analyzer. That reading (P_{Subst_RX}) on spectrum analyzer was recorded.

7.3 EUT operation modes

Table 1 GMSK, 1 time slot transmission

EUT operation mode	TX on, 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	512, 661, 810
EUT TX power level	0 (+30dBm)

Table 2 8-PSK, 1 time slot transmission

EUT operation mode	TX on, 1 time slot transmission, 8PSK modulation
EUT channel	512, 661, 810
EUT TX power level	0 (+30dBm)

Table 3 GPRS, 2 time slot transmission

EUT operation mode	TX on, 2 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	512, 661, 810
EUT TX power level	0 (+30dBm)

7.4 Limit

EIRP [W]
≤ 2

7.5 Results

The formula below was used to calculate the EIRP of the EUT.

$$P_{EIRP[W]} = \frac{10^{(P_{Subst_TX}[dBm] + (P_{EUT}[dBm] - P_{Subst_RX}[dBm]) + G_{Substitute_antenna}[dBi] - L_{Cable}[dB]) / 10}}{1000}$$

where the variables are as follows:

P_{EUT} [dBm]	Measured power level (from step a in 7.2) from the EUT
P_{Subst_TX} [dBm]	Power (from step c in 7.2) fed to the substituting antenna
P_{Subst_RX} [dBm]	Power (from step c in 7.2) received with the spectrum analyzer
$G_{Substitute_antenna}$ [dBi]	Gain of the substitutive antenna over isotropic radiator
L_{Cable} [dB]	Loss of the cable between signal generator and the substituting antenna

Table 4 GMSK, 1 time slot transmission

EUT Channel	P _{EUT} [dBm]	P _{Subst TX} [dBm]	P _{Subst RX} [dBm]	Cable loss [dB]	Antenna gain [dBi]	EIRP [dBm]	EIRP [W]
512	-12.62	+10	-33.26	5.84	1.1	25.90	0.389045
661	-13.41	+10	-33.39	5.88	1.8	25.90	0.389045
810	-13.80	+10	-33.65	5.95	0.8	24.70	0.295121

Table 5 8-PSK, 1 time slot transmission

EUT Channel	P _{EUT} [dBm]	P _{Subst TX} [dBm]	P _{Subst RX} [dBm]	Cable loss [dB]	Antenna gain [dBi]	EIRP [dBm]	EIRP [W]
512	-15.83	+10	-33.26	5.84	1.1	22.69	0.185780
661	-16.72	+10	-33.39	5.88	1.8	22.59	0.181552
810	-17.26	+10	-33.65	5.95	0.8	21.24	0.133045

Table 6 GPRS, 2 time slot transmission


EUT Channel	P _{EUT} [dBm]	P _{Subst TX} [dBm]	P _{Subst RX} [dBm]	Cable loss [dB]	Antenna gain [dBi]	EIRP [dBm]	EIRP [W]
512	-16.01	+10	-33.26	5.84	1.1	22.51	0.178238
661	-15.74	+10	-33.39	5.88	1.8	23.57	0.227510
810	-16.39	+10	-33.65	5.95	0.8	22.11	0.162555

8 99% OCCUPIED BANDWIDTH

EUT	40070		
Accessories	40071		
Temp, Humidity, Air Pressure	20 °C	47RH%	992mbar
Date of measurement	28.9.2004		
FCC rule part	§2.1049 (h)		
RSS-133 section	5.6		
Measured by	Jari Jantunen		

8.1 Test setup

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



8.2 EUT operation mode


EUT operation mode	TX on, GMSK modulation, 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	661
EUT TX power level	0 (+30dBm)

8.3 Results

Table 7 The 99% occupied bandwidth was measured using the in-built function of the spectrum analyzer.

EUT Channel	99% occupied bandwidth [kHz]
661	243.5897

8.4 Screen shot



Date: 28.SEP.2004 13:29:54

Picture 1 99% occupied bandwidth, channel 661

8.5 EUT operation mode


EUT operation mode	TX on, 8-PSK modulation, 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	661
EUT TX power level	0 (+30dBm)

8.6 Results

Table 8 The 99% occupied bandwidth was measured using the in-built function of the spectrum analyzer.

EUT Channel	99% occupied bandwidth [kHz]
661	235.5769

8.7 Screen shot



Date: 28.SEP.2004 13:40:16


Picture 2 99% occupied bandwidth, channel 661

9 BANDEDGE COMPLIANCE

EUT	40066
Accessories	40068
Temp, Humidity, Air Pressure	21°C 50RH% 992mbar
Date of measurement	28.9.2004
FCC rule part	§24.238 (a)
RSS-133 section	6.3
Measured by	Jan-Erik Lilja
Result	PASS

9.1 Test setup

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



9.2 EUT operation mode

EUT operation mode	TX on, GMSK modulation, 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	See section 9.4
EUT TX power level	0 (+30dBm)

9.3 Limit


Frequency [MHz]	Level [dBm]
<1850 or 1910<	-13

9.4 Results


The line in the screen shots is the -13dBm limit line. The results were corrected with measurement path loss set as "offset" in the spectrum analyzer.

EUT Channel	Level [dBm]
512	-24.26
810	-24.86

9.5 Screen shots



Picture 3 Lower bandedge, channel 512



Picture 4 Upper bandedge, channel 801

9.6 EUT operation mode

EUT operation mode	TX on, 8-PSK modulation, 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	See section 9.8
EUT TX power level	0 (+30dBm)

9.7 Limit


Frequency [MHz]	Level [dBm]
<1850 or 1910<	-13

9.8 Results


The line in the screen shots is the -13dBm limit line. The results were corrected with measurement path loss set as "offset" in the spectrum analyzer.

EUT Channel	Level [dBm]
512	-29.21
810	-35.63

9.9 Screen shots



Picture 5 Lower bandedge, channel 512




Picture 6 Upper bandedge, channel 810

10 SPURIOUS RADIATED EMISSION

EUT	40072		
Accessories	40067		
Temp, Humidity, Air Pressure	21 °C	50RH%	992mbar
Date of measurement	28.9.2004		
FCC rule part	§24.238 (a), §2.1053		
RSS-133 section	6.3		
Measured by	Jan-Erik Lilja		
Result	PASS		

10.1 Test setup

A set of LP/HP/BS filters was used to prevent overloading the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where the measurement devices were controlled by a computer.



10.2 Test method

- The emissions were searched and maximized by moving the turn table and measuring antenna and manipulating the EUT.
- All suspicious frequencies with emission levels were recorded.
- The EUT was replaced with a substituting antenna.
- For each frequency recorded, the substituting antenna was fed with the power (from signal generator) giving the same reading as in (b). These power levels were reported.

10.3 EUT operation mode

EUT operation mode	TX on, GMSK modulation 1 time slot transmission, PRBS 2E9-1 audio modulation
EUT channel	661
EUT TX power level	0 (+30dBm)

10.4 Limit

Frequency [MHz]	Level [dBm]
30 – 19100	-13

10.5 Results

The formula below was used to calculate the EIRP of the spurious emissions. If there were no emissions closer than 20dB below the limit line, then the emission levels were measured at the transmitter's harmonics.

$$P_{\text{Emission[dBm]}} = P_{\text{SubstTX[dBm]}} - L_{\text{Cable[dB]}} + G_{\text{Antenna[dBi]}}$$

where the variables are as follows:

$P_{\text{Measured [dBm]}}$	Measured emission level (from step b in 10.2)
$P_{\text{Subst_TX [dBm]}}$	Signal generator power (from step d in 10.2) fed to the substituting antenna
$L_{\text{Cable [dB]}}$	Loss of the cable between antenna and signal generator (from step d in 10.2)
$G_{\text{Antenna [dBi]}}$	Gain of the substitutive antenna over isotropic radiator

Table 9 Emission levels, channel 661

Frequency [MHz]	P_{Measured} [dBm]	$P_{\text{Subst_TX}} - L_{\text{Cable}} + G_{\text{Antenna}}$ [dB]	P_{Emission} [dBm]
3760.023046	-43.0	9.4	-33.60
4260.525050	-47.8	7.8	-40.00
9399.801603	-41.7	18.7	-23.00
11280.061122	-51.4	19.6	-31.80
11760.023046	-55.1	21.7	-33.40

10.6 EUT operation mode

EUT operation mode	TX on, 8PSK modulation, 1 time slot transmission
EUT channel	661
EUT TX power level	0 (+30dBm)

10.7 Limit

Frequency [MHz]	Level [dBm]
30 – 19100	-13

10.8 Results

The formula below was used to calculate the EIRP of the spurious emissions. If there were no emissions closer than 20dB below the limit line, then the emission levels were measured at the transmitter's harmonics.

$$P_{\text{Emission[dBm]}} = P_{\text{SubstTX[dBm]}} - L_{\text{Cable[dB]}} + G_{\text{Antenna[dBi]}}$$

where the variables are as follows:

$P_{\text{Measured [dBm]}}$	Measured emission level (from step b in 10.2)
$P_{\text{Subst_TX [dBm]}}$	Signal generator power (from step d in 10.2) fed to the substituting antenna
$L_{\text{Cable [dB]}}$	Loss of the cable between antenna and signal generator (from step d in 10.2)
$G_{\text{Antenna [dBi]}}$	Gain of the substitutive antenna over isotropic radiator

Table 10 Emission levels, channel 661


Frequency [MHz]	P_{Measured} [dBm]	$P_{\text{Subst TX}} - L_{\text{Cable}} + G_{\text{Antenna}}$ [dB]	P_{Emission} [dBm]
3760.023046	-49.6	9.4	-40.20

11 FREQUENCY STABILITY, TEMPERATURE VARIATION

EUT	40070
Accessories	40073
Temp, Humidity, Air Pressure	21 °C 48-50RH% 1007-1020mbar
Date of measurement	29-30.9.2004
FCC rule part	§24.235, §2.1055 (a)(1)(b)
RSS-133 section	7
Measured by	Jan-Erik Lilja
Result	PASS

11.1 Test setup

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



11.2 EUT operation mode

EUT operation mode	TX on, 1 time slot transmission, PRBS 2E9-1 modulation
EUT channel	661
EUT TX power level	0 (+30dBm)

11.3 Limit

Frequency deviation [ppm]
± 2.5

11.4 Test method

- The climate chamber temperature was set to the minimum value and the temperature was allowed to stabilize.
- The EUT was placed in the chamber
- The EUT was set in idle mode for 45 minutes.
- The EUT was set to transmit.
- The transmit frequency error was measured immediately

f) The steps c - e were repeated for each temperature

11.5 Results

Table 11 Frequency deviation, temperature variation


Temperature [°C]	Deviation [Hz]	Deviation [ppm]
-30	-36	0.001844
-20	-24	0.001856
-10	-24	0.001856
0	-33	0.001847
10	-28	0.001852
20	-30	0.001850
30	-22	0.001858
40	-32	0.001848
50	-33	0.001847

12 FREQUENCY STABILITY, VOLTAGE VARIATION

EUT	40070
Accessories	40073
Temp, Humidity, Air Pressure	21°C 50RH% 992mbar
Date of measurement	28.9.2004
FCC rule part	§24.235, §2.1055 (d)(1)(2)
RSS-133 section	7
Measured by	Jari Jantunen
Result	PASS

12.1 Test setup

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



12.2 EUT operation mode

EUT operation mode	TX on, 1 time slot transmission, PRBS 2E9-1 modulation
EUT channel	661
EUT TX power level	0 (+30dBm)

12.3 Limit

Frequency deviation [ppm]
± 2.5

12.4 Test method

The EUT battery was replaced with an adjustable power supply. The frequency stability was measured at nominal voltage and at the battery cut-off point.

12.5 Results

Table 12 Frequency deviation, voltage variation

Level	Voltage [V]	Deviation [Hz]	Deviation [ppm]
Nominal	3.7	-30	0.001868
Battery cut-off point	3.2	-12	0.001850

13 TEST EQUIPMENT

Each test equipment is calibrated once a year.

13.1 Conducted measurements

Equipment	Manufacturer	Model
EMI receiver	Rohde & Schwarz	ESI 40
Radio communication tester	Rohde & Schwarz	CMU-200
Attenuator 10 dB	Huber+Suhner AG	6251.17.A
Step attenuator 110dB	Hewlett-Packard	8496A
Power splitter	Hewlett-Packard	11667A
High pass filter	Trilithic	WHK2010-10SS
Low pass filter	Trilithic	WLK1750-10SS
Tunable notch filter	Wainwright	WRCD1850/1910-0.2/40
Temperature chamber	Vötsch	VT4002
DC power supply	HP	6632A
Multimeter	Fluke	87

13.2 Radiated measurements

Equipment	Manufacturer	Model
3m semi-anechoic chamber	TDK	
EMI receiver	Rohde & Schwarz	ESI 40
Preamplifier	MITEQ	AMF-5D-020180-26-10P
Preamplifier	MITEQ	AMF-4D-10M-3G-25-20P
Dipole antenna	EMCO	3125-870
Dipole antenna	EMCO	3125-1880
Biconilog antenna	Rohde & Schwarz	HL562
Double ridged waveguide antenna	EMCO	3115
Double ridged waveguide antenna	EMCO	3115
Horn antenna	EMCO	3116
Reference dipole set	Schwarzbeck	UHAP/VHAP
Radio communication tester	Rohde & Schwarz	CMU-200
Signal generator	Hewlett-Packard	83640L
Step attenuator 110dB	Hewlett-Packard	8496A
Power splitter	Hewlett-Packard	11667A
High pass filter	Trilithic	WHK2010-10SS
Low pass filter	Trilithic	WLK1750-10SS
Tunable notch filter	Wainwright	WRCD1850/1910-0.2/40
Turntable controller	Deisel	HD-100
Turntable	Deisel	DS412
Antenna mast controller	EMCO	2090
Antenna mast	EMCO	2075
Temperature chamber	Vötsch	VT4002
DC power supply	Hewlett-Packard	6632A
Multimeter	Fluke	87

14 TEST SETUP PHOTOGRAPHS

See "RM-8_test_setup_photographs.doc".