

| | | | | | | | | | | | |
|--|-------------------|-----------------|--------------------------------------|-----------------------|--|--|-----------------------|------------------|---------------------|---------------------|--|
| Alvarion Ltd | | | | | | | | | | | |
| FCC ID: LKT-BMAX-BA4M-B25 | | | | | | | | | | | |
| Part 27 BRS/EBS | | | | | | Calculate mW/cm2 here. Enter frequency in MHz: | | | | | |
| 2.5 GHz Base Station | | | | | | | | | | | |
| RF Hazard Distance Calculation | | | | | | Calculation of Limits from 1.1310 Table 1 | | | | | |
| mW/cm2 from Table1: | 1.00 | | | | | F(MHz) | Actual F, MHz | | Controlled | Uncontrolled | |
| | | | | | | 0.3-3 | 0.5 | | Ave 6 min | Ave 30 min | |
| Max RF Power, P, dBm | TX Antenna G, dBi | MPE distance cm | S, mW/cm@ at 20 cm | Comment | | 3.0 - 30.0 30.0-300 | 5 55 | | 100.0 1.0 | 100.0 0.2 | |
| 38.3 | 18.00 | 184.2 | 84.86 | Manual states 2m sep. | | 300-1500 1500-100000 | 902 5555 | | 3.0 5.0 | 0.60 1.0 | |
| | | | | | | Enter P(mW) | Equivalent dB | Enter dBm | Equivalent Watts | | |
| Basis of Calculations: | | | | | | 895.4 | 29.52 | 29.52 | 895.4 | | |
| E^2/3770 = S, mW/cm2 | | | | | | | | | | | |
| E, V/m = (Pwatts*Ggain*30)^.5/d, meters | | | | | | | | | | | |
| d = ((Pwatts*G*30)/3770*S))^0.5 | | | Pwatts*Ggain = 10^(PdBm-30+GdBi)/10) | | | | | | | | |
| S@20cm = 20 log (MPE dist/20cm) | | | | | | | | | | | |
| NOTE: For mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |