

Alvarion Ltd									
FCC ID: LKT-BMAX-OR-25									
Part 25 Terrestrial Part 27 BRS/EBS					Calculate mW/cm2 here. Enter frequency in MHz:				
2.4836/2.5 GHz Base Station									
RF Hazard Distance Calculation: Worst Case					Calculation of Limits from 1.1310 Table 1				
							Controlled	Uncontrolled	
mW/cm2 from Table1:							Ave 6 min	Ave 30 min	
		1.00			F(MHz)	Actual F, MHz	Occ, mW/c2	Gen, mW/cm2	
					0.3-3	0.5	100.0	100.0	
Max RF Power	TX Antenna	MPE distance	S, mW/cm@	Comment	3.0 - 30.0	5	180.0	36.0	
P, dBm	G, dBi	cm	at 20 cm		30.0-300	55	1.0	0.2	
					300-1500	902	3.0	0.60	
38.3	18.00	184.2	84.86	Manual states 2m sep.	1500-100000	5555	5.0	1.0	
					Enter P(mW)	Equivalent dBm	Enter dBm	Equivalent Watts	
Basis of Calculations:					895.4	29.52	29.52	895.4	
E^2/3770 = S, mW/cm2									
E, V/m = (Pwatts*Ggain*30)^.5/d, meters									
d = ((Pwatts*G*30)/3770*S)^0.5									
S@20cm = 20 log (MPE dist/20cm)									
Pwatts*Ggain = 10^(PdBm-30+GdBi)/10									
NOTE: For mobile or fixed location transmitters, minimum separation distance is for FCC compliance is 20 cm, even if calculations indicate MPE distance is less									