

Alvarion Ltd										
FCC ID: LKT-EXTR-CPE-58										
5.8 GHz DTS										
RF Hazard Distance Calculation										
mW/cm ² from Table1:	1.00									
Max RF Power P, dBm	TX Antenna G, dBi	MPE distance cm	S, mW/cm@ at 20 cm	Comment		F(MHz)	Actual F, MHz	Controlled Ave 6 min	Uncontrolled Ave 30 min	
29.2	17.00	57.3	8.22	max P2P eirp	3.0 - 30.0 30.0-300 300-1500	0.5 55 902	100.0 1.0 3.0	180.0 0.2 5.0	100.0 0.60 1.0	
					Enter P(mW)	Equivalent dBm	Enter dBm	Equivalent Watts		
Basis of Calculations:					895.4	29.52	29.52	895.4		
E^2/3770 = S, mW/cm ²										
E, V/m = (Pwatts*Ggain*30)^0.5/d, meters										
d = ((Pwatts*G*30)/3770*S))^0.5				Pwatts*Ggain = 10^(PdBm-30+GdBi)/10						
S@20cm = 20 log (MPE dist/20cm)										
NOTE: For mobile or fixed location transmitters, minimum separation distance is for FCC compliance is 20 cm, even if calculations indicate MPE distance is less										