## Indoor Antennas OMNI-6

## **OMNI-6, Indoor Omni-directional Antenna**

The OMNI-6, 6 dBi, omnidirectional antenna can be used with the <u>BreezeNET PRO.11 D Model Bridges</u> and <u>DS.11 Outdoor Bridges</u> for long range indoor applications.

The OMNI-6 antenna attaches to the female connector on the PRO.11 D Model Bridges and the DS.11 Outdoor Bridges and provides 360 degree horizontal/20 degree vertical transmission. Click <a href="https://example.com/here">here</a> to view BreezeNET PRO.11 Range Table. Click here to view the BreezeNET DS.11 Range Table.



SPECIFICATIONS	
Antenna:	
Antenna Gain*	6 dBi
Kit Gain!	5 dBi
Frequency Range	2.4 – 2.5 GHz
Impedance	50 Ohms
Dispersion	360° horizontal/20° vertical
Polarization	Vertical
VSWR	1.5:1 Max
Dimensions	10.5" x 0.75"; 38 x 18mm tubular
Operating temperature range	-86° to 158° F; -30° to 70° C
Weight	4 oz; 100 g
Mounting	Wall, standard
Cable:	
Туре	RG-58
Impedance	50 Ohms
Attenuation	0.2 dB (ft.);
Length	4'
Connector	N type

<sup>\*</sup> Antenna gain is the gain of the antenna without the cable.

! Kit gain is the actual gain of the antenna kit as it is shipped from BreezeCOM.

## Back to Antennas & Accessories

|| <u>Home || About BreezeCOM || Products || Applications || News and Events || Ordering and Tracking || Technical Support || Partners || Site Map || Contact Us ||</u>

©Copyrighted BreezeCOM® All Rights Reserved