

LLB09001

February 6, 2009

RF Exposure calculations

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65.

(1) Categorical Exclusion from RF exposure Evaluation: According to FCC regulations, RF exposure evaluation is Categorical Excluded if transmitter's operation frequency is less than 1.5 Ghz and ERP is less than 1.5 watt.

(2) Absolute Maximum specifications of LLB09001 transmitter

- Operational frequency band 450 MHz to 470 MHz.
- The LLB09001 transmitter is measured for Max RF Power = 0.25 W.
- Absolute Maximum transmission time (duration) for any Hexagram transmitters does not exceed 100 mS (0.10second).
- Transmission period – Absolute maximum is 4 transmissions per hour.
- All Hexagram Transmitters utilize FSK modulation.

(3) Average RF Power Calculation:

FCC regulations on permissible RF exposure are not based on peak envelope power (PEP), but on average power ( $P_{ave}$ ) over a 30-minute time period for uncontrolled environments. As mentioned in (2), during any 30 minute Hexagram MTU can transmit only two times. Duration = 0.10 second. With maximum RF radiation equal to 0.25 W, the Average RF Power over 30 minutes is:  $P_{ave}$  (worst case) at 30 minute =  $250mW \times 2 \times [0.10sec / ((30 \times 60)sec)] = 250 \times 2 \times 0.000055 = 0.0275mW$

(4) Maximum Radiated Power Density prediction (S): To predict power density (S) at distance  $R=20$  cm from transmitter with  $P_{ave} = 0.00007W$ , next formula is used:  $S = P_{ave} / (4 \times (PI) \times R^2)$  For the worst of the worst worst-case prediction of power density at or near a transmitter surface let's use:  $S = P_{ave} / ((PI) \times R^2) = 0.0275mW / (4 \times 3.14 \times 20cm \times 20cm) = 21.8uW/cm^2$ . This is the worst case of the near field power density of LLB09001 transmitter.

(5) Maximum Permissible Exposure (MPE) from LLB09001: AS FCC require, the maximum permissible exposure for general public in "uncontrolled situation" at 20 cm is:  $MPE = 460MHz / 1500 = 0.307 mW/cm^2$ . By comparing results in (4) and (5),  $S=21.8 uW/cm^2 < MPE=0.307 mW/cm^2$ . We see that LLB09001 fully complies with RF safety at a distance of 20 cm.

Mark Wilbur  
Aclara RF Systems  
Formally Hexagram  
216-896-8600