

ACLARA RF SYSTEMS
Formally HEXAGRAM, Inc.
30400 Solon Road .
Solon, OH 44139
440-528-7200

Thursday , August, 2010

LLB10000

RF Exposure calculations

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65.

(1) Categorical Exclusion from RF exposure Evaluation: According to FCC regulations, RF exposure evaluation is Categorical Exclusion if transmitter's operation frequency is less than 1.5 GHz and ERP is less than 1.5 watt.

(2) Absolute Maximum specifications of LLB10000 transmitter

- Operational frequency band 450 MHz to 470 MHz
- The LLB10000 transmitter is measured for Max RF Power = .05W

Absolute Maximum transmission time (duration) for any Hexagram transmitters does not exceed 313 mS (0.313second).

- Transmission period – Absolute maximum is 4 transmissions per hour.
- All Hexagram Transmitters utilize FSK modulation.

(3) Average RF Power Calculation:

FCC regulations on permissible RF exposure are not based on peak envelope power (PEP), but on average power (P_{ave}) over a 30-minute time period for uncontrolled environments. As mentioned in (2), during any 30 minute Hexagram MTU can transmit only two times. Duration = 0.313 second. With maximum RF radiation equal to .05 W, the Average RF Power over 30 minutes is: P_{ave} (worst case) at 30 minute = $.05W * 2 * [0.313sec / ((30*60) sec)] = .05 * 2 * .313 / 1800 = 0.000055 = 0.017mW$

(4) Maximum Radiated Power Density prediction (S): To predict power density (S) at distance $R=20$ cm from transmitter with $P_{ave} = 0.017mW$, next formula is used:

$$S = P_{ave} / (4 * (\pi) * R^2)$$

For the worst of the worst worst-case prediction of power density at or near a transmitter surface let's use: $S = P_{ave} / (\pi * R^2) = 0.017mW / (4 * 3.14 * 20cm * 20cm) = 1.35uW/cm^2$. This is the worst case of the near field power density of LLB10000 transmitter.

(5) Maximum Permissible Exposure (MPE) from LLB10000: AS FCC requires, the maximum permissible exposure for general public in “uncontrolled situation” at 20 cm is:

$$\text{MPE} = 460\text{MHz}/1500 = 0.307 \text{ mW/cm}^2.$$

By comparing results in (4) and (5),

$$S=1.35 \text{ uW/cm}^2 \ll \text{MPE}=0.307 \text{ mW/cm}^2.$$

We see that LLB10000 fully complies with RF safety at a distance of 20 cm.

Sincerely,
Siva Jambulingam
Principal Engineer
RF and Microwave Systems
440-528-7200
sjambulingam@aclara.com