





# Test Report - FCC Part 1.1310/ MPE Simultaneous Transmission Applicant: Aclara Technologies LLC

		OFRIE
Signature:	Unes D. Egg	Sr. EMC Engineer EMC-003838-NE
_		OINEE
Name & Title:	Tim Royer, EMC Engineer	
-	,	-
Date of Signature	11/6/2024	
_		-
	VHI CI	
Signature:	AMO DO	
_		
Name & Title:	Kristoffer Costa, EMC Techn	ician
_		-
Date of Signature	11/6/2024	
-		_

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



# Table of Contents

1.	APPLICANT INFORMATION	3
2.	LOCATION OF TESTING	3
	2.1 Test Laboratory	3
	TEST SAMPLE(S) (EUT/DUT)	
	3.1 Description of the EUT	
4.	TEST METHODS & APPLICABLE REGULATORY LIMITS	
	4.1 Test methods/Standards/Guidance:  4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)	6
	4.2 EQUATIONS	
5.	RF EXPOSURE RESULTS	8
6.	HISTORY OF TEST REPORT CHANGES	9



## 1. Applicant Information

Applicant: Aclara Technologies LLC Address: 77 Westport Plaza Drive

Suite 500

St. Louis, Missouri, 63146, United States

### 2. Location of Testing

### 2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86<sup>th</sup> Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780 FCC Designation # US1070 FCC site registration is under A2LA certificate # 0955.01 ISED Canada test site registration # 2056A EU Notified Body # 1177 For all designations see A2LA scope # 0955.01

## 3. Test Sample(s) (EUT/DUT)

The test sample was received: 5/21/2024

Dates of Testing: 5/23/2024 - 5/29/2024



### 3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

### 400MHz data

Identification						
FCC ID:	LLB2022002					
Brief Description	Ultrasonic Gas Meter					
Model(s) #	3511-066-LCW					
Firmware version	N/A					
Software version	N/A					
Serial Number	N/A					

Technical Characteristics					
Frequency Range	450 MHz- 470 MHz				
RF O/P Power (Max.)	1W				
Modulation	FM				
Bandwidth & Emission Class	F1D				
Number of Channels	N/A				
Duty Cycle	50%				
Antenna Connector	N/A				
Voltage Rating (AC or Batt.)	3.4 VDC				

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	n/a	n/a	0 dBi

Note: Information such as antenna gain, firmware/software numbers are provided by the manufacturer and cannot be validated by the test lab.



### 2GHz data

Identification					
FCC ID:	LLB2022002				
Brief Description	Ultrasonic Gas Meter				
Model(s) #	3511-066-LCW				
Firmware version	N/A				
Software version	N/A				
Serial Number	N/A				

Technical Characteristics						
Frequency Range	2400 MHz- 2483.5 MHz					
RF O/P Power (Max.)	1W					
Modulation	FM					
Bandwidth & Emission Class	F1D					
Number of Channels	N/A					
Duty Cycle	50%					
Antenna Connector	N/A					
Voltage Rating (AC or Batt.)	3.4 VDC					

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	n/a	n/a	0 dBi

Note: Information such as antenna gain, firmware/software numbers are provided by the manufacturer and cannot be validated by the test lab.



# 4. Test methods & Applicable Regulatory Limits

### 4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

#### 4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging Time (minutes)							
A Limits for Occupational/Controlled Exposure											
0.3-3.0	614	1.63	*(100)	≤6							
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6							
30-300	61.4	0.163	1.0	<6							
300-1,500			f/300	<6							
1,500-100,000			5	<6							
	B Limits for Gene	ral Population/Unco	ntrolled Exposure								
0.3-1.34	614	1.63	*(100)	<30							
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30							
30-300	27.5	0.073	0.2	<30							
300-1,500			f/1500	<30							
1,500-100,000			1.0	<30							



### 4.2 Equations

### **POWER DENSITY**

$$E(V/m) = SQRT (30 * P * G) / d$$

 $Pd(W/m^2) = E^2 / 377$ 

 $S = EIRP / (4 * Pi * D^2v)$ 

Where.

 $S = Power density, in mW/cm^2$ 

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of  $\underline{\text{mW/cm}^2}$  to units of  $\underline{\text{W/m}^2}$  by multiplying by 10.

### DISTANCE

$$D = SQRT (EIRP / (4 * Pi * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

 $S = Power density in mW/cm^2$ 

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

Source-based time-average EIRP = ( DC / 100 ) \* EIRP

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW



# 5. RF Exposure Results

### 400MHz data

### MPF

Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
450-470 MHz	20	35.50	5.00	100%	3.5481	0.706 mW/cm2	0.3 mW/cm2	1.5 mW/cm2	30.68

RESULT: Pass at DISTANCE 30.68 cm

### 2G data

MPE									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
2400-2483.5 MHz	30.68	7.43	1.50	100%	0.0055	0.001 mW/cm2	1 mW/cm2	5 mW/cm2	30.68

RESULT: Pass at DISTANCE 20 cm

Per KDB 447498 D01 General RF Exposure Guidance v06 Sec 7.2.

Equation: (TX1 MPE/MPE Limit 1 + TX2MPE/MPE Limit 2)

Frequency	Power Density at separation distance	Limit	MPE Ratio	Limit
400MHz	0.706 mW/cm2	0.3 mW/cm2	1	<b>~1</b>
2GHz	0.001 mW/cm2	1 mW/cm2		<u>≤</u>



# 6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_13810-24_FCC 1.1310/ MPE_Simultaneous Transmission_	1	Initial release	11/6/2024
	2	Updated page 8	11/15/2024

# **END OF TEST REPORT**