

Test Report

Customer:

Life Fitness

9525 BRYN MAWR AVENUE
ROSEMONT, IL 60018
USA

Tel.: +1 847 288 3657

RF test report

170825-AU01+W02



Industry Industrie
Canada Canada

Life Fitness

NFC Card Reader Module

Life Fitness NFC Card Reader



The test result refers exclusively to the tested model.
This test report may not be copied or published in a part without the written authorization of the accreditation agency and/or EMV **TESTHAUS** GmbH



EMV **TESTHAUS** GmbH

Gustav-Hertz-Straße 35
94315 Straubing
Tel.: +49 9421 56868-0
Fax: +49 9421 56868-100
Email: info@emv-testhaus.com

Accreditation:



FCC facility registration number: 221458
Test Firm Type "2.948 listed": Valid until 2017-07-12
Test Firm Type "accredited": Valid until 2019-05-06
MRA US-EU, FCC designation number: DE0010
BnetzA-CAB-02/21-02/04 Valid until 2018-11-27

Industry Canada test site numbers with registration expiry date:
3472A-1, expiring 2018-11-09
3472A-2, expiring 2018-11-12

Test Laboratory:

EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

The technical accuracy is guaranteed through the quality management of the
EMV **TESTHAUS** GmbH



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 2 of 37

Table of contents

1	Test regulations	5
2	Summary of test results	6
3	Equipment under Test (EUT)	7
4	AC power line conducted emissions	10
5	Radiated emission measurement (<1 GHz)	14
6	Radiated emission measurement (>1 GHz)	25
7	Carrier frequency stability	26
8	Bandwidths	30
9	Equipment calibration status	35
10	Measurement uncertainty	36
11	Revision History	37



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 3 of 37

List of pictures

Picture 1: Outline of conducted emission test setup	11
Picture 2: Graphic - Conducted emission on mains, phase 1 (without termination).....	12
Picture 3: Graphic - Conducted emission on mains, neutral (without termination).....	13
Picture 4: Test setup for radiated emission measurement (< 30 MHz).....	17
Picture 5: Test setup for radiated emission measurement (< 1 GHz).....	17
Picture 6: Radiated emission 9 kHz – 30 MHz @ 3m distance	19
Picture 7: Radiated emission 30 MHz - 1000MHz @ 3m distance	21
Picture 8: Spectrum mask for 13.56 MHz @ 3m distance.....	23
Picture 9: Test setup for carrier frequency stability measurement.....	27
Picture 10: Occupied bandwidth (99 %).....	32
Picture 11: -20 dB emission bandwidth.....	33

List of tables

Table 1: Equipment calibration status.....	35
Table 2: Measurement uncertainty	36



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 4 of 37

1 Test regulations

47 CFR Part 2: 10-2017	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)
47 CFR Part 15: 03-2017	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)
ANSI C63.10:2013-06	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
FCC KDB 174176 D01 June 3, 2015	AC power-line conducted emissions Frequently Asked Questions
ICES-003 Issue 6, January 2016	Spectrum Management and Telecommunications Interference-Causing Equipment Standard Information Technology Equipment (ITE) – Limits and methods of measurement
RSS-Gen Issue 4, November 2014	Spectrum Management and Telecommunications Radio Standards Specification General Requirements and Information for the Certification of Radiocommunication Equipment
RSS-210 Issue 9, August 2016	Spectrum Management and Telecommunications Radio Standards Specification Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 5 of 37

2 Summary of test results

Standard	Test result
47 CFR Part 15, sections 15.207 and 15.225	Passed
RSS-210 Issue 9 Section 4.3 and Annex B6 (with appropriate references to RSS-Gen Issue 4)	Passed

Straubing, November 16, 2017



Andreas Menacher
Test engineer
EMV **TESTHAUS** GmbH



Christian Kiermeier
Head of EMC department
EMV **TESTHAUS** GmbH



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

3 Equipment under Test (EUT)

Product type: NFC Card Reader Module
Model Name: Life Fitness NFC Card Reader
Applicant: Life Fitness
Manufacturer: Life Fitness
Serial number: ---
FCC ID: LM6-LFNFCCR1
IC certification number: 23315-LFNFCCR1
Application frequency band: 13.110 to 14.010 MHz
Frequency range: 13.560 MHz
Operating frequency: 13.560 MHz
Number of RF-channels: 1
Modulation: ASK
Antenna connector: permanent temporary none
Antenna types: PCB antenna
 detachable not detachable
Maximum antenna gain: N/A
Maximum conducted power: N/A
Power supply: nominal: 5.0 VDC ± 5 %
Temperature range: 0°C to +60°C



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 7 of 37

3.1 Photo documentation

For external photos of the EUT see annex B, for internal ones see annex C.
For photos taken during testing and including EUT-positions see annex A.

3.2 Short description of the EUT

EUT is a Transmitter working on 13.56 MHz.

3.3 Operation mode

During the pre-tests it was observed that the continuous Transmission mode is the respective worst- case. Therefore this mode was selected for final testing.

The EUT was tested in 3 orthogonal positions. This is documented in annex A.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 8 of 37

3.4 Configuration

The following peripheral devices and interface cables were connected during the tests:

Device	Model:	Serial or inventory no.
Transmitter	Life Fitness NFC Card Reader	1007521-0011_AA
DC supply	HCPS-JUMPER	1201-0013
DC supply	Statron 3231.1	E00528

3.5 Used cables

Count	Description (type / lengths / remarks)	Serial no.
2	Power Supply Cable (1,5 m/unshielded)	---



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 9 of 37

4 AC power line conducted emissions

according to 47 CFR Part 15, section 15.207, and
RSS-210, section 3.1 with RSS-Gen, section 8.8

4.1 Test location

Description	Manufacturer	Inventory No.
Shielded room	Siemens - Matsushita	E00107

4.2 Test instruments

	Description	Manufacturer	Inventory No.
<input checked="" type="checkbox"/>	ESCS 30	Rohde & Schwarz	E00003
<input type="checkbox"/>	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/>	ESCI	Rohde & Schwarz	E00001
<input type="checkbox"/>	ESH3-Z2	Rohde & Schwarz	E00028
<input checked="" type="checkbox"/>	ESH2-Z5	Rohde & Schwarz	E00004
<input type="checkbox"/>	ESH2-Z5	Rohde & Schwarz	E00005
<input checked="" type="checkbox"/>	Cable set shielded room	Huber + Suhner	E00424
<input checked="" type="checkbox"/>	Programmable AC Source Model 61602	Chroma	E00057

4.3 Limits

Frequency [MHz]	Quasi-peak [dB μ V]	Average [dB μ V]
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5 – 30	60	50



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02


Page 10 of 37

4.4 Test procedure

1. The tests of conducted emission were carried out in a shielded room using a line impedance stabilization network (LISN) 50 μ H/50 Ohms and an EMI test receiver.
2. The EMI test receiver was connected to the LISN and set to a measurement bandwidth of 9 kHz in the frequency range from 0.15 MHz to 30 MHz.
3. The EUT was placed on a wooden table and connected to the LISN.
4. To accelerate the measurement the detector of the EMI test receiver was set to peak and the whole frequency range from 0.15 MHz to 30 MHz was scanned.
5. After that all peaks values with less margin than 10 dB to quasi-peak limit or exceeding the limit were marked and re-measured with quasi-peak detector.
6. If after that all values are under the average limit no addition measurement is necessary. In case there are still values between quasi-peak and average limit then these values were re-measured with average detector.
7. These measurements were done on all power lines.

According to ANSI C63.10, section 6.2.2 testing of intentional radiators with detachable antennas shall be done with a dummy load otherwise the tests should be done with connected antenna and if adjustable fully extended.

4.5 Test setup




Picture 1: Outline of conducted emission test setup

Comments: All peripheral devices were additionally decoupled by means of a line stabilization network.

4.6 Test results

Temperature:	22°C	Humidity:	41%
Tested by:	Andreas Menacher	Test date:	2017-11-15



REGULATIONS:
47 CFR Part 15.207
PEAK / CISPR / AV

TEST EQUIPMENT:
R&S ESCS30 (E00003)
R&S ESH 2-Z5 (E00004)

ORDER NO.:
170825-AU01+W02

EUT:
Life Fitness
Transmitter
Life Fitness NFC Card Reader
10075 21-0011_AA

OPERATION MODE:
See clause 7.2

Mains 120 VAC 60Hz
Phase L1

TEST FACILITY:
EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing

DATE / TIME:
2017-11-16 14:45:42

TEST ENGINEER:
Andreas Menacher

170825-AU01+W02_CEM_L1_FOC
handelsübliches Netzteil E10

Picture 2: Graphic - Conducted emission on mains, phase 1 (without termination)




EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 12 of 37

Interference Voltage Test



REGULATIONS:
47 CFR Part 15.207
PEAK / CISPR / AV

TEST EQUIPMENT:
R&S ESCS30 (E00003)
R&S ESH 2-Z5 (E00004)

ORDER NO.:
170825-AU01+W02

EUT:
Life Fitness
Transmitter
Life Fitness NFC Card Reader
10075 21-0011_AA

OPERATION MODE:
See clause 7.2

Mains 120 VAC 60Hz
Neutral N

TEST FACILITY:
EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing

DATE / TIME:
2017-11-16 14:45:42

TEST ENGINEER:
Andreas Menacher

170825-AU01+W02_CEM_N_FCC
handelsübliches Netzteil E10

Picture 3: Graphic - Conducted emission on mains, neutral (without termination)



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 13 of 37

5 Radiated emission measurement (<1 GHz)

according to 47 CFR Part 15, section 15.205(a), 15.209(a), 15.225(a) to (e), and

RSS-210, section 4.3 and Annex B6 with RSS-Gen, sections 8.10 and 8.9

5.1 Test Location

Emission < 30 MHz

- Scan with PK / AV detector in 3 m CDC.
- Final CISPR measurement with QP detector in 3 m OATS

Emission > 30 MHz

- Scan with QP detector in 3 m SAC.
- Final CISPR measurement with QP detector in 3 m SAC

5.2 Test instruments

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Compact Diagnostic Chamber (CDC)	VK041.0174	Albatross Projects	E00026
<input checked="" type="checkbox"/> Semi Anechoic Chamber (SAC)	---	Albatross Projects	E00716
<input checked="" type="checkbox"/> Open area test site	---	EMV TESTHAUS GmbH	E00354
<input checked="" type="checkbox"/> EMI test receiver (CDC / OATS)	ESCI 3	Rohde & Schwarz	E00001
<input checked="" type="checkbox"/> EMI test receiver (SAC)	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> TRILOG broadband antenna (CDC)	VULB 9160	Schwarzbeck	E00011
<input type="checkbox"/> TRILOG broadband antenna (OATS)	VULB 9163	Schwarzbeck	E00013
<input checked="" type="checkbox"/> TRILOG broadband antenna (SAC)	VULB 9162	Schwarzbeck	E00643
<input checked="" type="checkbox"/> Loop Antenna	HFH2-Z2	Rohde & Schwarz	E00060
<input type="checkbox"/> Switch box	COSB 4-1-26	Conformitas	W00091
<input type="checkbox"/> Preamplifier	AMF-5D-00501800	Parzich	W00089
<input type="checkbox"/> Measurement software	E10 v1.4.12	EMV TESTHAUS GmbH	E00443
<input checked="" type="checkbox"/> Measurement software	EMC 32	Rohde & Schwarz	---
<input checked="" type="checkbox"/> Cable set SAC 3 m	---	Huber + Suhner	E00434 E00755 E00320



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 14 of 37

5.3 Limits

The field strength of any emissions appearing outside of the 13.110 to 14.010 MHz band including spurious emissions falling into restricted bands as specified in 15.205(a) shall not exceed the general radiated emission limits as specified in 15.209.

Frequency [MHz]	Field strength Fs [$\mu\text{V/m}$]	Field strength [dB $\mu\text{V/m}$]	Measurement distance d [m]
0.009 – 0.490	266.6 – 4.9	48.5 – 13.8	300
0.490 – 1.705	48.98 – 14.08	33.8 – 22.97	30
1.705 – 30.0	30	29.54	30
30 – 88	100	40	3
88 – 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

As noted in 15.205(d)(7) devices according to 15.225 are exempt from complying with restricted band requirements for the 13.36 to 13.41 MHz band. Instead they have to comply with the limits as specified in 15.225 (a) to (d):

Frequency [MHz]	Field strength Fs [$\mu\text{V/m}$]	Field strength [dB $\mu\text{V/m}$]	Measurement distance d [m]
13.553 - 13.567	15,848	84	30
13.410 - 13.553	334	50.47	30
13.567 - 13.710	334	50.47	30
13.110 - 13.410	106	40.51	30
13.710 - 14.010	106	40.51	30
f < 13.110	according to limits in §15.209		
f > 14.010			



5.4 Test procedure

1. EUT was configured according to ANSI C63.10. It was placed on the top of the turntable 0.8 meter above ground. The receiving antenna was placed 3 meters from the turntable. The test setup was placed inside a compact diagnostic chamber.
2. EUT and all peripherals were powered on.
3. The broadband antenna was set to vertical polarization.
4. The EMI receiver performed a scan from 30 MHz to 1000 MHz with peak detector peak and measurement bandwidth set to 120 kHz.
5. The turn table was rotated to 6 different positions ($360^\circ / 6$) and the antenna polarization was changed to horizontal.
6. Test procedure at step 4 and 5 was repeated.
7. The test setup was then placed in an OATS at 3 m distance and all peak values over or with less margin to the limit than 6dB were marked and re-measured with a quasi-peak detector.
8. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
9. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization. The highest value was recorded.
10. For emissions below 30 MHz measurements were done using a loop antenna. Prescan was performed with peak detector and final measurements with quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 k Hz where average detector applies. Antenna height was not changed during this test. Appropriate CISPR bandwidths of 200 Hz for frequencies up to 150 kHz and 9 or 10 kHz for frequencies above were used.




EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader


170825-AU01+W02

Page 16 of 37

5.5 Test setup



Picture 4: Test setup for radiated emission measurement (< 30 MHz)



Picture 5: Test setup for radiated emission measurement (< 1 GHz)

5.6 Test deviation

There is no deviation from the standards referred to.

5.7 Test results

Temperature:	20°C	Humidity:	41%
Tested by:	Andreas Menacher	Test date:	2017-11-02

Radiated Emission Measurement 9 kHz - 30 MHz

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 "Extrapolation from the measurement of a single point":

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}, \text{ or}$$

$$f_{\text{MHz}} = 47.77 / d_{\text{near field}}$$

The frequency f_{MHz} at which the near field distance is equal to the limit and/or test distance is important for selection of the right formula for determining the recalculation factor:

$$f_{\text{MHz}}(300 \text{ m}) \approx 0.159 \text{ MHz}$$

$$f_{\text{MHz}}(30 \text{ m}) \approx 1.592 \text{ MHz}$$

$$f_{\text{MHz}}(3 \text{ m}) \approx 15.923 \text{ MHz}$$

For $9 \text{ kHz} \leq f \leq 159 \text{ kHz}$ and $490 \text{ kHz} < f \leq 1.592 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{limit}} / d_{\text{measure}})$$

For $159 \text{ kHz} < f \leq 490 \text{ kHz}$ and $1.592 \text{ MHz} < f \leq 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

For $f > 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -20 \log(d_{\text{limit}} / d_{\text{measure}})$$

The limits in the graphics and value lists are derived from the general radiated emission limits as specified in 15.209 using the recalculation factor as described above.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany


Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 18 of 37

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
9 kHz – 90 kHz	80 Hz	200 Hz	PK	AV	1 ms	1 s	off
90 kHz – 110 kHz	80 Hz	200 Hz	PK	QPK	1 ms	1 s	off
110 kHz – 150 kHz	80 Hz	200 Hz	PK	AV	1 ms	1 s	off
150 kHz – 490 kHz	4 kHz	9 kHz	PK	AV	1 ms	1 s	off
490 kHz – 30 MHz	4 kHz	9 kHz	PK	QPK	1 ms	1 s	off

The following picture shows the worst-case-emissions for the spurious emissions at EUT-position 3, antenna in line.



Picture 6: Radiated emission 9 kHz – 30 MHz @ 3m distance

Frequency [MHz]	Measured value [dBµV/m]	Detector	Recalculation factor [dB]	Field strength [dBµV/m]	Limit [dBµV/m]	Margin	Result
0.045	69.20	AV	-80.00	-10.80	34.54	45.34	Pass
0.045	69.77	PK	-80.00	-10.23	54.54	64.77	Pass
0.521	45.74	QPK	-40.00	5.74	33.27	27.53	Pass
2.760	42.33	QPK	-35.22	7.11	29.54	22.43	Pass
13.560	58.70	QPK	-21.39	37.31	84.00	46.69	Carrier
13.560	67.53	PK	-21.39	46.13	---	---	Carrier

Note: Emissions at 0.45 MHz are spurious emissions and not unwanted emissions caused by transmission or modulation.

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 "Extrapolation from the measurement of a single point":

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}$$

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$


f_{MHz} [MHz]	d_{near field} [m]	d_{measure} [m]	d_{limit} [m]	Recalculation factor [dB]
0.045	3.523	3.0	300.0	-80.00
0.521	3.523	3.0	30.0	-40.00
2.760	3.523	3.0	30.0	-35.22
13.56	3.523	3.0	30.0	-21.39



Radiated Emission Measurement 30 MHz - 1000 MHz

Frequency range	Polarisation	Step size	IF Bandwidth	Detector		Measurement Time		Pre-amplifier
				Prescan	Final scan	Prescan	Final scan	
30 MHz – 1 GHz	H / V	60 kHz	120 kHz	PK	QPK	1 ms	1 s	20 dB

The following pictures show the worst-case-emissions at EUT-position 3.



- Preview Result 1V-QPK
- Preview Result 1H-QPK
- 47 CFR §15.109 Radiated emission 3m Class B QP
- * Final_Result QPK

Picture 7: Radiated emission 30 MHz - 1000MHz @ 3m distance

Spectrum Mask

Test procedure

The EUT was placed in a fully anechoic chamber and the testing was performed in accordance with ANSI C63.10 and 47 CFR Part 15, section 15.225 (a) to (d). The measurement distance was 3 m. To find the closest margin of the spectrum to the limit mask adapted to the test distance the EUT was rotated by 360 degrees with detector of the test receiver set to peak. The loop antenna placed in a fixed height of 1 meter was rotated by 360 degrees to get the maximum of emission. In case of exceeding the limits the detector is switched to quasi peak for final testing in position of maximum emission.

Test result

Temperature:	20°C	Humidity:	41%
Tested by:	Andreas Menacher	Test date:	2017-11-02

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 "Extrapolation from the measurement of a single point":

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}, \text{ or}$$

$$f_{\text{MHz}} = 47.77 / d_{\text{near field}}$$

The frequency f_{MHz} at which the near field distance is equal to the limit and/or test distance is important for selection of the right formula for determining the recalculation factor:

$$f_{\text{MHz}}(300 \text{ m}) \approx 0.159 \text{ MHz}$$

$$f_{\text{MHz}}(30 \text{ m}) \approx 1.592 \text{ MHz}$$

$$f_{\text{MHz}}(3 \text{ m}) \approx 15.923 \text{ MHz}$$

For $9 \text{ kHz} \leq f \leq 159 \text{ kHz}$ and $490 \text{ kHz} < f \leq 1.592 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{limit}} / d_{\text{measure}})$$

For $159 \text{ kHz} < f \leq 490 \text{ kHz}$ and $1.592 \text{ MHz} < f \leq 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

For $f > 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -20 \log(d_{\text{limit}} / d_{\text{measure}})$$

The limits in the graphics and value lists are derived from the general radiated emission limits as specified in 15.209 using the recalculation factor as described above.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany


Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 22 of 37

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
490 kHz – 30 MHz	4 kHz	9 kHz	PK	QPK	1 ms	1 s	off

The following picture shows the worst-case-emissions for spectrum mask at EUT-position 3, antenna in line.



Picture 8: Spectrum mask for 13.56 MHz @ 3m distance

Frequency [MHz]	Measured value [dBµV/m]	Detector	Recalculation factor [dB]	Field strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result
13.560	67.77	PK	-21.40	38.78	84.00	16.23	Pass



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

Life Fitness
 NFC Card Reader Module
 Life Fitness NFC Card Reader

170825-AU01+W02

Page 23 of 37

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 “Extrapolation from the measurement of a single point”:

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}$$

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

f_{MHz} [MHz]	$d_{\text{near field}}$ [m]	d_{measure} [m]	d_{limit} [m]	Recalculation factor [dB]
13.560	3.523	3.000	30.000	-21.40



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

Life Fitness
 NFC Card Reader Module
 Life Fitness NFC Card Reader

170825-AU01+W02

Page 24 of 37

6 Radiated emission measurement (>1 GHz)

according to 47 CFR Part 15, section 15.209(a),
RSS-210, section 4.3 with RSS-Gen, section 8.9

Remark:

This measurement needs not to be applied because

- the intentional radiator operates below 10 GHz and tenth harmonic of the highest fundamental frequency is lower than 1 GHz (see 47 CFR Part 15, section 15.33(a)(1), and RSS-Gen, section 6.13), and
- the digital part of the device does not generate or use internal frequencies higher than 108 MHz (see 47 CFR Part 15 section 15.33(b)(1), and RSS-Gen, section 2.3.3 with ICES-003, section 6.2).



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 25 of 37

7 Carrier frequency stability

according to CFR 47 Part 15, section 15.225(e), and
RSS-210, Annex B6 with RSS-Gen, section 6.11

7.1 Test Location

	Description	Manufacturer	Inventory No.
<input type="checkbox"/>	Climatic chamber VC 4100	Vötsch Industrietechnik	C00014
<input checked="" type="checkbox"/>	Climatic chamber VC ³ 4034	Vötsch Industrietechnik	C00015

7.2 Test instruments

	Description	Manufacturer	Inventory No.
<input type="checkbox"/>	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/>	ESCI 3	Rohde & Schwarz	E00552
<input checked="" type="checkbox"/>	RF-R 400-1	Langer EMV-Technik	E00270

7.3 Limits

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ (100 ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

For battery operated equipment, the equipment tests shall be performed using a new battery. Alternatively, an external supply voltage can be used and set at the battery nominal voltage, and again at the battery operating end point voltage which must be specified by the equipment manufacturer.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader


170825-AU01+W02

Page 26 of 37

7.4 Test procedure

1. If possible EUT is operating providing an unmodulated carrier. The peak detector of the spectrum analyzer is selected and resolution as well as video bandwidth are set to values appropriate to the shape of the spectrum of the EUT. The frequency counter mode of the spectrum analyzer is used to maximize the accuracy of the measured frequency tolerance.
If an unmodulated carrier is not available a significant and stable point on the spectrum is selected and the span is reduced to a value that delivers an accuracy which shall be better than 1% of the maximum frequency tolerance allowed for the carrier signal. This method may be performed as long as the margin to the frequency tolerance allowed is larger than the uncertainty of the measured frequency tolerance.
2. The carrier frequency is measured depending on the variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment an external supply voltage can be used and set at the battery nominal voltage, and again at the battery operating end point voltage which must be specified by the equipment manufacturer. Alternatively, tests shall be performed using a new battery.
3. The carrier frequency is measured over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage.

7.5 Test setup



Picture 9: Test setup for carrier frequency stability measurement


7.6 Test deviation

There is no deviation from the standards referred to.

7.7 Test results

Temperature:	20°C	Humidity:	41%
Tested by:	Andreas Menacher	Test date:	2017-11-02

Carrier frequency stability vs. temperature



Supply voltage:	5V	Frequency under nominal conditions:	13.560067 MHz		
Temperature (°C)	Frequency (MHz)	Frequency Tolerance (Hz)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
±0	13.560120	53	+100.0	-100.0	96.1
+10	13.560105	38	+100.0	-100.0	97.2
+20	13.560067	0	+100.0	-100.0	100.0
+30	13.560045	-22	+100.0	-100.0	98.4
+40	13.560015	-52	+100.0	-100.0	96.2
+50	13.559987	-80	+100.0	-100.0	94.1
+60	13.559986	-81	+100.0	-100.0	94.0




EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

Life Fitness
 NFC Card Reader Module
 Life Fitness NFC Card Reader

170825-AU01+W02

Page 28 of 37

Carrier frequency stability vs. supply voltage



Temperature:	+20 °C	Battery End Point:	Not applicable			
Frequency under nominal conditions:	13.560067 MHz					
Supply Voltage (V)	Frequency (MHz)	Frequency Tolerance (Hz)	Frequency Tolerance (ppm)	Upper Limit (ppm)	Lower Limit (ppm)	Margin (ppm)
5.25	13.560008	-59	-4.4	+100.0	-100.0	95.6
5.00	13.560067	0	0.0	+100.0	-100.0	100.0
4.75	13.560023	-44	-3.2	+100.0	-100.0	96.8



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

Life Fitness
 NFC Card Reader Module
 Life Fitness NFC Card Reader

170825-AU01+W02

Page 29 of 37

8 Bandwidths

according to CFR 47 Part 2, section 2.202(a), and RSS-Gen, section 6.6

8.1 Test Location

See clause 5.1 on page 14.

8.2 Test instruments

See clause 0 on page 14.

8.3 Limits

The bandwidths are recorded only. There are no limits specified in CFR 47 Part 15, section 15.225, and RSS-210, Annex B6

8.4 Test setup

See clause 5.5 on page 17.

8.5 Test deviation

There is no deviation from the standards referred to.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 30 of 37

8.6 Test results

Temperature:	20°C	Humidity:	41%
Tested by:	Andreas Menacher	Test date:	2017-11-15

Occupied bandwidth (99 %)

Test procedure

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual.

The trace data points are recovered and directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth. For this purpose the appropriate measurement function of the spectrum analyzer is used.




EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 31 of 37



Picture 10: Occupied bandwidth (99 %)

Measured occupied bandwidth (99 %): 45,5 kHz



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

Life Fitness
 NFC Card Reader Module
 Life Fitness NFC Card Reader


170825-AU01+W02

Page 32 of 37

-20 dB emission bandwidth

Test procedure

Where indicated, the -20 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 20 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.



Picture 11: -20 dB emission bandwidth

Measured -20 dB emission bandwidth: 10,30 kHz



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

f_{assigned} (MHz)	Index	$f_{-20\text{dB}}$ (MHz)	Δf_T (kHz)	Δf_U (kHz)	$f_{-20\text{dB}(T, U)}$ (MHz)	Limit (MHz)	Margin (kHz)	Result
13.560000	low	13,555000	0.081	0.059	13.554860	13.110000	444.860	Passed
	high	13,565300	0.053	0.000	13.565353	14.010000	444.647	Passed
	Bandwidth	10.300 kHz			10.493 kHz			

- with:
- $f_{-20\text{dB}(\text{low})}$ = lower frequency in MHz where emission is at least 20 dB below the carrier
 - $f_{-20\text{dB}(\text{high})}$ = upper frequency in MHz where emission is at least 30 dB below the carrier
 - f_{assigned} = assigned frequency in kHz
 - $\Delta f_{T(\text{low})}$ = maximum absolute value of negative frequency offset to frequency at nominal conditions caused by temperature variation in kHz
 - $\Delta f_{U(\text{low})}$ = maximum absolute value of negative frequency offset to frequency at nominal conditions caused by voltage variation in kHz
 - $\Delta f_{T(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by temperature variation in kHz
 - $\Delta f_{U(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by voltage variation in kHz
 - $\Delta f_{\text{volt}(\text{high})}$ = maximum absolute value of positive frequency offset to frequency at nominal conditions caused by voltage variation in kHz
 - $f_{-20\text{dB}(T, U)}$ = frequency in MHz where emission is at least 20 dB below the carrier, including offset caused by variations of temperature and supply voltage as recorded in clause 7.7

Measured -20 dB emission bandwidth:

At nominal conditions: 10.300 kHz

Including variations in temperature and supply voltage: 10.493 kHz



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 34 of 37

9 Equipment calibration status

Description	Modell number	Serial number	Inventory number(s)	Last calibration	Next calibration
Test receiver	ESCI 3	100013	E00001	2016-02	2018-02
Test receiver	ESCI 3	100328	E00552	2016-09	2018-09
Test receiver	ESCS 30	825442/0002	E00003	2016-04	2018-04
Test receiver	ESW 44	101538	E00895	2016-12	2018-12
LISN	ESH2-Z5	893406/009	E00005	2016-02	2018-02
Loop antenna	HFH2-Z2	871398/0050	E00060	2016-09	2018-09
Broadband antenna	VULB 9162	9160-3050	E00011	2015-11	2017-11
Magnetic field probe	RF-R 400-1	02-2030	E00270	N/A (see note 1)	
Shielded room	P92007	B83117C1109T211	E00107	N/A	
Compact diagnostic chamber (CDC)	VK041.0174	D62128-A502-A69-2-0006	E00026	N/A	
Climatic chamber 340 I	VC ³ 4034	58566123250010	C00015	2016-10	2018-10
Cable set shielded room	Cable no. 30	---	E00424	2016-07	2018-07
Cable set CDC	Cables no. 37 and 38	---	E00459 E00460	2017-05	2019-05

Table 1: Equipment calibration status

Note 1: Used for relative measurements only (see test instruments for “Carrier frequency stability”, clause 7.2)

Note 2: Expiration date of test firm accreditation for OATS and SAC:
FCC test firm type “accredited”: 2019-05



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 35 of 37

10 Measurement uncertainty

Description	Max. deviation	k=
Conducted emission AMN (9kHz to 30 MHz)	± 3.8 dB	2
Radiated emission open field (3 m) (30 MHz to 300 MHz) (300MHz to 1 GHz)	± 5.4 dB ± 5.9 dB	2
Radiated emission absorber chamber (> 1000 MHz)	± 4.5 dB	2

Table 2: Measurement uncertainty

The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k. For a confidence level of 95 % the coverage factor k is 2.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 36 of 37

11 Revision History

Date	Description	Person	Revision
2017-11-23	First edition	Ch. Kiermeier	0



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

Life Fitness
NFC Card Reader Module
Life Fitness NFC Card Reader

170825-AU01+W02

Page 37 of 37