



ATEC01

Maximum Permissible Exposure

FCC, Part 15 §1.1310

Industry Canada RSS-Gen §5.6

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4πd²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use highest gain antennas for the client EUT. Where the antenna gain exceeds 6dBi the transmitter power is reduced where necessary to meet the EIRP requirements. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
2400 – 2483.5	6.3	4.27	26.19	415.9	11.9	20
5725 - 5850	8.3	6.76	28.42	695.02	19.3	20
5150 - 5250	8.3	6.76	27.68	586.13	17.8	20

Assessment for simultaneous operation in 5.15-5.25 GHz and 5.8 GHz bands

The Actiontec R3000 has two different radio modules. The device is DBDC “Dual Band Dual Concurrent” (autonomous transmission). The following assessment is based on simultaneous operation in the 5.15-5.25 GHz and 5.8 GHz (worst case) bands.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
5725 - 5850	8.3	6.76	28.42	695.02	19.3	20
5150 - 5250	8.3	6.76	27.68	586.13	17.8	20
			EIRP Total			
			8660.6 mW		26.3	26.3



Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification
Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1
Ref FCC KDB 447498 **General RF Exposure Guidance**

RSS-Gen §5.6 Category I and Category II equipment shall comply with the applicable requirements of RSS-102.

Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------