5 FCC §15.247(i), §1.1310, § 2.1091 - Maximum Permissible Exposure (MPE)

5.1 Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

No.: RXZ190708006-00B

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

RF Exposure Evaluation Result

No.: RXZ190708006-00B

MPE evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation	Power	MPE
		(dBi)	(numeric)	(dBm)	(mW)	Distance (cm)	Density (mW/cm ²)	Limit (mW/cm ²)
2.4G WIFI	2412-2462	4.85	3.055	30	1000	30	0.2701	1.0
5G WIFI B1	5150-5250	5.52	3.565	29.5	891.251	30	0.2809	1.0
5G WIFI B2	5250-5350	5.83	3.828	24	251.189	30	0.0850	1.0
5G WIFI B3	5470-5725	4.85	3.055	24	251.189	30	0.0678	1.0
5G WIFI B4	5725-5825	4.85	3.055	30	1000	30	0.2701	1.0

Note: the maximum antenna gain was used for evaluation.

MPE evaluation for simultaneous transmission:

2.4G WIFI and 5G WIFI can transmit at the same time, MPE evaluation is as below formula: PD1/Limit1+PD2/Limit2+...... < 1, PD (Power Density)

MPE evaluation=MPE of 2.4G WIFI/1 + MPE of 5G WIFI/1= 0.2701/1+0.2809/1=0.551 < 1.0

Result: MPE evaluation of single and simultaneous transmission meet 30cm the requirement of standard.