



# MEASUREMENT REPORT

## FCC PART 15.247 WLAN 802.11b/g/n

---

**FCC ID:** LNQWXB6X00Q

**APPLICANT:** Actiontec Electronics, Inc.

**Application Type:** Certification

**Product:** WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA  
WCB6000Q - 802.11ac Wireless Ethernet Bridge with LAN MoCA  
WEB6000Q - 802.11ac Wireless Ethernet Bridge

**Model No.:** WCB6200Q, WCB6000Q, WEB6000Q

**Trademark:** Actiontec

**FCC Classification:** Digital Transmission System (DTS)

**FCC Rule Part(s):** Part 15.247

**Test Procedure(s):** KDB 558074 D01v03r02, KDB 662911 D01v02r01

**Test Date:** Dec. 01 ~ 14, 2014

Reviewed By : Robin Wu  
( Robin Wu )

Approved By : Marlin Chen  
( Marlin Chen )



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v03r02. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

## Revision History

Report No.	Version	Description	Issue Date
1411RSU02901	Rev. 01	Initial report	12-15-2014
1411RSU02901	Rev. 02	Corrected the radiated emission test procedure	12-19-2014
1411RSU02901	Rev. 03	Corrected the model number of power sensor	03-03-2015

## CONTENTS

Description	Page
<b>§2.1033 General Information</b> .....	<b>5</b>
<b>1. INTRODUCTION</b> .....	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION</b> .....	<b>7</b>
2.1. Equipment Description .....	7
2.2. Frequency / Channel Operation .....	8
2.3. Description of Available Antennas.....	9
2.4. Description of Antenna RF Port.....	10
2.5. Test Mode .....	10
2.6. Test Software .....	11
2.7. Device Capabilities.....	12
2.8. Test Configuration .....	12
2.9. EMI Suppression Device(s)/Modifications.....	12
2.10. Labeling Requirements .....	12
<b>3. DESCRIPTION of TEST</b> .....	<b>13</b>
3.1. Evaluation Procedure .....	13
3.2. AC Line Conducted Emissions.....	13
3.3. Radiated Emissions.....	14
<b>4. ANTENNA REQUIREMENTS</b> .....	<b>15</b>
<b>5. TEST EQUIPMENT CALIBRATION DATE</b> .....	<b>16</b>
<b>6. MEASUREMENT UNCERTAINTY</b> .....	<b>17</b>
<b>7. TEST RESULT</b> .....	<b>18</b>
7.1. Summary .....	18
7.2. 6dB Bandwidth Measurement .....	19
7.2.1. Test Limit .....	19
7.2.2. Test Procedure used .....	19
7.2.3. Test Setting.....	19
7.2.4. Test Setup .....	19
7.2.5. Test Result.....	20
7.3. Output Power Measurement .....	29
7.3.1. Test Limit .....	29
7.3.2. Test Procedure Used.....	29

---

7.3.3.	Test Setting.....	29
7.3.4.	Test Setup .....	29
7.3.5.	Test Result of Output Power.....	30
7.4.	Power Spectral Density Measurement .....	32
7.4.1.	Test Limit .....	32
7.4.2.	Test Procedure Used.....	32
7.4.3.	Test Setting.....	32
7.4.4.	Test Setup .....	33
7.4.5.	Test Result.....	34
7.5.	Conducted Band Edge and Out-of-Band Emissions .....	43
7.5.1.	Test Limit .....	43
7.5.2.	Test Procedure Used.....	43
7.5.3.	Test Setting.....	43
7.5.4.	Test Setup .....	44
7.5.5.	Test Result.....	45
7.6.	Radiated Spurious Emission Measurement .....	62
7.6.1.	Test Limit .....	62
7.6.2.	Test Procedure Used.....	62
7.6.3.	Test Setting.....	62
7.6.4.	Test Setup .....	64
7.6.5.	Test Result.....	66
7.7.	Radiated Restricted Band Edge Measurement .....	90
7.7.1.	Test Result.....	90
7.8.	AC Conducted Emissions Measurement.....	178
7.8.1.	Test Limit .....	178
7.8.2.	Test Setup .....	178
7.8.3.	Test Result.....	179
<b>8.</b>	<b>CONCLUSION.....</b>	<b>181</b>

## §2.1033 General Information

<b>Applicant:</b>	Actiontec Electronics, Inc.
<b>Applicant Address:</b>	760 North Mary Ave. Sunnyvale, CA 94085
<b>Manufacturer:</b>	The First Branch of CIG Shanghai Co. Ltd.
<b>Manufacturer Address:</b>	2-3/FL, Building D, 2059 Duhui Road, Minhang District, Shanghai
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
<b>MRT Registration No.:</b>	809388
<b>FCC Rule Part(s):</b>	Part 15.247
<b>Model No.:</b>	WCB6200Q, WCB6000Q, WEB6000Q
<b>FCC ID:</b>	LNQWXB6X00Q
<b>Test Device Serial No.:</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
<b>FCC Classification:</b>	Digital Transmission System (DTS)

### Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



## 1. INTRODUCTION

### 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA WCB6000Q - 802.11ac Wireless Ethernet Bridge with LAN MoCA WEB6000Q - 802.11ac Wireless Ethernet Bridge
Model No.	WCB6200Q, WCB6000Q, WEB6000Q
Model Difference	WCB6200Q with LAN MoCA "BCM6802" WCB6000Q with LAN MoCA "BCM6803" WEB6000Q without LAN MoCA
Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz
Maximum Output Power	802.11b: 23.39dBm 802.11g: 23.41dBm 802.11n-HT20: 26.08dBm 802.11n-HT40: 23.51dBm
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM
<b>Component</b>	
Adapter #1	M/N: NBS24J120200VU Input: 100-120V ~ 50/60Hz 0.6A OUTPUT: 12Vdc, 2A
Adapter #2	M/N: CDS024-W120U Input: 100-240V ~ 50/60Hz 0.58A OUTPUT: 12Vdc, 2A
Adapter #3	M/N: WA-24Q12FU Input: 100-240V ~ 50/60Hz 0.7A MAX OUTPUT: 12Vdc, 2A

Note:

1. Three model numbers of EUT with the same RF circuit, and assessments were performed the "WCB6200Q" in this report.
2. Three model numbers and adapters assessments were performed in "FCC 15B Report".

## 2.2. Frequency / Channel Operation

### Channel List for 802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	N/A	N/A

### Channel List for 802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	N/A	N/A	N/A	N/A





### 2.3. Description of Available Antennas

Antenna Type	Frequency Band (GHz)	T <sub>x</sub> Paths	Directional Gain (dBi)	
			Non Beam Forming	Beam Forming
PCB Antenna	2.4	2	5.22	--
	5.2	2	--	6.92
	5.8	2	--	7.39

Note:

1. Transmit at 2.4GHz support two antennas, transmit at 5GHz support four antennas.
2. The EUT working on Beam Forming mode, and the Beam Forming support 802.11a/n/ac.
3. Correlated signals include, but are not limited to, signals transmitted in any of the following modes:
  - Any transmit Beam Forming mode, whether fixed or adaptive (e.g., phased array modes, closed loop MIMO modes, Transmitter Adaptive Antenna modes, Maximum Ratio Transmission (MRT) modes, and Statistical Eigen Beam Forming (EBF) modes).
4. Unequal antenna gains, with equal transmit powers. For antenna gains given by  $G_1, G_2, \dots, G_N$  dBi
  - transmit signals are correlated
  - Directional gain =  $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$  dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

## 2.4. Description of Antenna RF Port

Antenna RF Port						
--	2.4GHz RF Port		5GHz RF Port			
Software Control Port	Ant 0	Ant 1	Ant 0	Ant 1	Ant 2	Ant 3
Antenna RF Port Plot						
						

## 2.5. Test Mode

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n-HT20
	Mode 4: Transmit by 802.11n-HT40

## 2.6. Test Software

The test utility software used during testing was "MTOOL\_2.0.07".

Final Power Parameter Value of the test software.

Test Mode	Test Frequency (MHz)	Power Parameter Value Ant 0	Power Parameter Value Ant 1
802.11b	2412	21.0	21.0
	2417	23.0	23.0
	2437	23.0	23.0
	2457	23.0	23.0
	2462	21.0	21.0
802.11g	2412	19.0	19.0
	2417	23.0	23.0
	2437	23.0	23.0
	2457	23.0	23.0
	2462	19.0	19.0

Test Mode	Test Frequency (MHz)	Power Parameter Value Ant 0 + 1
802.11n-HT20	2412	18.0
	2417	23.0
	2437	23.0
	2457	23.0
	2462	18.0
802.11n-HT40	2422	17.0
	2427	20.0
	2437	20.0
	2447	20.0
	2452	17.0

## 2.7. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS) and 5GHz WLAN (UNII)

**Note:** 2.4GHz WLAN (DTS) operation is possible in 20MHz, and 40MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01v03r02. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

- 802.11b - 95.0%
- 802.11g - 95.1%
- 802.11n-HT20 - 91.0%
- 802.11n-HT40 - 83.2%
- 

## 2.8. Test Configuration

The **WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA FCC ID: LNQWXB6X00Q** was tested per the guidance of KDB 558074 D01v03r02. ANSI C63.4-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

## 2.9. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

## 2.10. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### 3. DESCRIPTION of TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009), and the guidance provided in KDB 558074 D01v03r02 were used in the measurement of the **WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA FCC ID: LNQWXB6X00Q.**

**Deviation from measurement procedure.....None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2009 at Clause 4.3.

Line conducted emissions test results are shown in Section 7.8.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(a) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

#### 4. ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of **WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA** is **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The **WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA** FCC ID: **LNQWXB6X00Q** unit complies with the requirement of §15.203.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	101209	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	101683	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	101684	1 year	2015/11/07
Temperature/ Meter Humidity	Anymetre	TH101B	SR2-01	1 year	2015/11/14

### Radiated Emission

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	E4447A	MY45300136	1 year	2015/10/09
EMI Test Receiver	R&S	ESR7	101209	1 year	2015/11/07
Preamplifier	MRT	AP18G40	S-001	1 year	2015/10/06
Preamplifier	MRT	AP01G18	S-001	1 year	2015/12/13
Loop Antenna	Schwarzbeck	FMZB1519	1519-041	1 year	2015/11/08
TRILOG Antenna	Schwarzbeck	VULB9162	9162-047	1 year	2015/11/08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1167	1 year	2015/11/08
Broadband Horn Antenna	Schwarzbeck	BBHA9170	9170-549	1 year	2015/12/12
Temperature/Humidity Meter	Anymetre	TH101B	AC1-01	1 year	2015/11/14

### Conducted Test Equipment

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MY52090106	1 year	2015/01/04
USB Wideband Power Sensor	Boonton	55006	8911	1 year	2015/10/15
Temperature/Humidity Meter	Anymetre	TH101B	TR3-01	1 year	2015/11/14



## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 150kHz~30MHz: $\pm 3.46\text{dB}$
<b>Radiated Emission Measurement</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz ~ 1GHz: $\pm 4.18\text{dB}$ 1GHz ~ 25GHz: $\pm 4.76\text{dB}$

## 7. TEST RESULT

### 7.1. Summary

**Product Name:** WCB6200Q - 802.11ac Wireless Ethernet Bridge with Bonded LAN MoCA  
**FCC ID:** LNQWXB6X00Q  
**FCC Classification:** Digital Transmission System (DTS)  
**Data Rate(s) Tested:** 1Mbps ~ 11Mbps (b);  
6Mbps ~ 54Mbps (g);  
13/14.4Mbps ~ 130/144.4Mbps (n-HT20);  
27/30Mbps ~ 270/300Mbps (n-HT40)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	$\geq 30\text{dBc(Average)}$		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

#### Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 7.2. 6dB Bandwidth Measurement

### 7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 7.2.2. Test Procedure used

KDB 558074 D01v03r02 - Section 8.2 Option 2

### 7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

### 7.2.4. Test Setup




### 7.2.5. Test Result


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
<b>Ant 0</b>						
802.11b	1	01	2412	8.11	≥0.5	Pass
802.11b	1	06	2437	8.10	≥0.5	Pass
802.11b	1	11	2462	8.10	≥0.5	Pass
802.11g	6	01	2412	16.39	≥0.5	Pass
802.11g	6	06	2437	16.40	≥0.5	Pass
802.11g	6	11	2462	16.04	≥0.5	Pass
<b>Ant 0 / Ant 0 + 1</b>						
802.11n-HT20	13	01	2412	17.62	≥0.5	Pass
802.11n-HT20	13	06	2437	17.62	≥0.5	Pass
802.11n-HT20	13	11	2462	17.61	≥0.5	Pass
802.11n-HT40	27	03	2422	35.68	≥0.5	Pass
802.11n-HT40	27	06	2437	35.41	≥0.5	Pass
802.11n-HT40	27	09	2452	35.69	≥0.5	Pass
<b>Ant 1</b>						
802.11b	1	01	2412	8.10	≥0.5	Pass
802.11b	1	06	2437	8.10	≥0.5	Pass
802.11b	1	11	2462	8.10	≥0.5	Pass
802.11g	6	01	2412	16.48	≥0.5	Pass
802.11g	6	06	2437	16.46	≥0.5	Pass
802.11g	6	11	2462	16.42	≥0.5	Pass
<b>Ant 1 / Ant 0 + 1</b>						
802.11n-HT20	13	01	2412	17.65	≥0.5	Pass
802.11n-HT20	13	06	2437	17.63	≥0.5	Pass
802.11n-HT20	13	11	2462	17.64	≥0.5	Pass
802.11n-HT40	27	03	2422	35.95	≥0.5	Pass
802.11n-HT40	27	06	2437	35.75	≥0.5	Pass
802.11n-HT40	27	09	2452	35.46	≥0.5	Pass

802.11b 6dB Bandwidth - Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g 6dB Bandwidth - Ant 0


Channel 01 (2412MHz)






Channel 06 (2437MHz)




Channel 11 (2462MHz)




**802.11n-HT20 6dB Bandwidth - Ant 0 / Ant 0 + 1**
**Channel 01 (2412MHz)**

**Channel 06 (2437MHz)**

**Channel 11 (2462MHz)**


802.11n-HT40 6dB Bandwidth - Ant 0 / Ant 0 + 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)






802.11b 6dB Bandwidth - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




### 802.11g 6dB Bandwidth - Ant 1


#### Channel 01 (2412MHz)



#### Channel 06 (2437MHz)




#### Channel 11 (2462MHz)




802.11n-HT20 6dB Bandwidth - Ant 1 / Ant 0 + 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth - Ant 1 / Ant 0 + 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



### 7.3. Output Power Measurement

#### 7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

#### 7.3.2. Test Procedure Used


KDB 558074 D01v03r02 - Section 9.2.3.2 AVGPM-G Average Power Method

#### 7.3.3. Test Setting

##### Average Power Measurement

Average power measurements were perform only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

#### 7.3.4. Test Setup



### 7.3.5. Test Result of Output Power

Output power at various data rates for Ant 0:

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)
802.11b	20	6	2437	1	21.57
				5.5	21.10
				11	20.88
802.11g	20	6	2437	6	19.34
				24	18.89
				54	18.21
802.11n	20	6	2437	13	20.50
				52	19.95
				130	19.33
802.11n	40	6	2437	27	19.68
				108	19.11
				270	18.76

**Test Result of Average Output Power**

Test Mode	Data Rate (Mbps)	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Limit (dBm)	Result
11b	1	1	2412	21.36	--	21.36	≤30	Pass
11b	1	6	2437	23.12	--	23.12	≤30	Pass
11b	1	11	2462	21.52	--	21.52	≤30	Pass
11b	1	1	2412	--	21.89	21.89	≤30	Pass
11b	1	6	2437	--	23.39	23.39	≤30	Pass
11b	1	11	2462	--	22.13	22.13	≤30	Pass
11g	6	1	2412	19.42	--	19.42	≤30	Pass
11g	6	6	2437	23.23	--	23.23	≤30	Pass
11g	6	11	2462	19.54	--	19.54	≤30	Pass
11g	6	1	2412	--	19.18	19.18	≤30	Pass
11g	6	6	2437	--	23.41	23.41	≤30	Pass
11g	6	11	2462	--	19.33	19.33	≤30	Pass
11n-HT20	13	1	2412	19.22	18.00	21.66	≤30	Pass
11n-HT20	13	6	2437	23.25	22.89	26.08	≤30	Pass
11n-HT20	13	11	2462	19.11	17.99	21.60	≤30	Pass
11n-HT40	27	3	2422	17.55	17.67	20.62	≤30	Pass
11n-HT40	27	6	2437	19.68	21.19	23.51	≤30	Pass
11n-HT40	27	9	2452	17.23	18.36	20.84	≤30	Pass

Note: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Peak Power}/10)} + 10^{(\text{Ant 1 Peak Power}/10)}\}$  (dBm).

## 7.4. Power Spectral Density Measurement

### 7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

### 7.4.2. Test Procedure Used


KDB 558074 D01v03r02 - Section 10.5 Method AVGPSD

### 7.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10kHz
5. VBW = 30kHz
6. Detector = RMS
7. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
8. Sweep time = auto couple
9. Do not use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time.
13. Add Constant Factor =  $10 \cdot \log(3\text{kHz} / 10\text{kHz}) = -5.229$



### 7.4.4. Test Setup



**7.4.5. Test Result**

Test Mode	Data Rate (Mbps)	Channel No.	Freq. (MHz)	Ant 0 AVGPSD (dBm / 10kHz)	Ant 1 AVGPSD (dBm / 10kHz)	Duty Cycle (%)	Constant Factor	Total AVGPSD (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
11b	1	1	2412	-4.856	--	95.0	-5.229	-9.862	≤8.0	Pass
11b	1	6	2437	-2.816	--	95.0	-5.229	-8.045	≤8.0	Pass
11b	1	11	2462	-4.100	--	95.0	-5.229	-9.106	≤8.0	Pass
11b	1	1	2412	--	-3.251	95.0	-5.229	-8.257	≤8.0	Pass
11b	1	6	2437	--	-2.340	95.0	-5.229	-7.569	≤8.0	Pass
11b	1	11	2462	--	-4.096	95.0	-5.229	-9.102	≤8.0	Pass
11g	6	1	2412	-9.018	--	95.1	-5.229	-14.029	≤8.0	Pass
11g	6	6	2437	-6.087	--	95.1	-5.229	-11.316	≤8.0	Pass
11g	6	11	2462	-9.186	--	95.1	-5.229	-14.197	≤8.0	Pass
11g	6	1	2412	--	-9.378	95.1	-5.229	-14.389	≤8.0	Pass
11g	6	6	2437	--	-6.083	95.1	-5.229	-11.312	≤8.0	Pass
11g	6	11	2462	--	-9.802	95.1	-5.229	-14.813	≤8.0	Pass
11n-HT20	13	1	2412	-9.885	-11.117	91.0	-5.229	-12.267	≤8.0	Pass
11n-HT20	13	6	2437	-6.350	-6.372	91.0	-5.229	-8.989	≤8.0	Pass
11n-HT20	13	11	2462	-9.723	-10.754	91.0	-5.229	-12.017	≤8.0	Pass
11n-HT40	27	3	2422	-12.680	-11.940	83.2	-5.229	-13.714	≤8.0	Pass
11n-HT40	27	6	2437	-10.657	-9.646	83.2	-5.229	-11.542	≤8.0	Pass
11n-HT40	27	9	2452	-13.360	-12.225	83.2	-5.229	-14.175	≤8.0	Pass


Note: When EUT duty cycle < 98%, the total PSD =  $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\} + 10 \cdot \log(1/\text{duty cycle}) + \text{Constant Factor}$ .

802.11b AVGPDS - Ant 0

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g AVGPDS - Ant 0


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 AVGPSD - Ant 0 / Ant 0 + 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPSD - Ant 0 / Ant 0 + 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)




802.11AVGb PSD - Ant 1

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g AVGPDS - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)






802.11n-HT20 AVGPSD - Ant 1 / Ant 0 + 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPSD - Ant 1 / Ant 0 + 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



## **7.5. Conducted Band Edge and Out-of-Band Emissions**

### **7.5.1. Test Limit**

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

### **7.5.2. Test Procedure Used**

KDB 558074 D01v03r02 - Section 11.2 & Section 11.3

### **7.5.3. Test Setting**


#### **1. Reference level measurement**

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to  $\geq 1.5$  times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW  $\geq 3 \times$  RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize

#### **2. Emission level measurement**

- (a) Set the center frequency and span to encompass frequency range to be measured
- (b) RBW = 100kHz
- (c) VBW = 300kHz
- (d) Detector = Peak
- (e) Trace mode = max hold
- (f) Sweep time = auto couple
- (g) The trace was allowed to stabilize

### 7.5.4. Test Setup




### 7.5.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
<b>Ant 0</b>					
802.11b	1	01	2412	30dBc	Pass
802.11b	1	06	2437	30dBc	Pass
802.11b	1	11	2462	30dBc	Pass
802.11g	6	01	2412	30dBc	Pass
802.11g	6	06	2437	30dBc	Pass
802.11g	6	11	2462	30dBc	Pass
<b>Ant 0 / Ant 0 + 1</b>					
802.11n-HT20	13	01	2412	30dBc	Pass
802.11n-HT20	13	06	2437	30dBc	Pass
802.11n-HT20	13	11	2462	30dBc	Pass
802.11n-HT40	27	03	2422	30dBc	Pass
802.11n-HT40	27	06	2437	30dBc	Pass
802.11n-HT40	27	09	2452	30dBc	Pass
<b>Ant 1</b>					
802.11b	1	01	2412	30dBc	Pass
802.11b	1	06	2437	30dBc	Pass
802.11b	1	11	2462	30dBc	Pass
802.11g	6	01	2412	30dBc	Pass
802.11g	6	06	2437	30dBc	Pass
802.11g	6	11	2462	30dBc	Pass
<b>Ant 1 / Ant 0 + 1</b>					
802.11n-HT20	13	01	2412	30dBc	Pass
802.11n-HT20	13	06	2437	30dBc	Pass
802.11n-HT20	13	11	2462	30dBc	Pass
802.11n-HT40	27	03	2422	30dBc	Pass
802.11n-HT40	27	06	2437	30dBc	Pass
802.11n-HT40	27	09	2452	30dBc	Pass

### 802.11b Out-of-Band Emissions - Ant 0

#### 100kHz PSD reference Level



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta


Mkr--CF

Mkr--Ref Lvl


More  
1 of 2

### Channel 01 (2412MHz)

#### Low Band Edge




#### Spurious Emission



### Channel 06 (2437MHz)

#### Spurious Emission



Marker

Select Marker

Normal

Delta

Fixed


Off

Properties


More  
1 of 2

### Channel 11 (2462MHz)

#### High Band Edge



#### Spurious Emission



### 802.11g Out-of-Band Emissions - Ant 0

#### 100kHz PSD reference Level




Peak Search


- Next Peak
- Next Pk Right
- Next Pk Left
- Marker Delta
- Mkr--CF
- Mkr--Ref Lvl
- More 1 of 2

### Channel 01 (2412MHz)

#### Low Band Edge




#### Spurious Emission



### Channel 06 (2437MHz)

#### Spurious Emission




Marker

- Select Marker 3
- Normal
- Delta
- Fixed
- Off
- Properties
- More 1 of 2




### Channel 11 (2462MHz)

#### High Band Edge



#### Spurious Emission



### 802.11n-HT20 Out-of-Band Emissions - Ant 0 / Ant 0 + 1

#### 100kHz PSD reference Level



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta


Mkr--CF

Mkr--Ref Lvl


More  
1 of 2

#### Channel 01 (2412MHz)

##### Low Band Edge




##### Spurious Emission



#### Channel 06 (2437MHz)

##### Spurious Emission



Marker

Select Marker

Normal

Delta

Fixed

Off

Properties

More  
1 of 2