

Company: Actiontec Electronics Inc.

Evaluation of: WCB6240Q
To: FCC CFR 47 Part 15 RF Exposure requirements

Report No.: ATEC09-MPE Rev A

MPE TEST REPORT



MPE TEST REPORT

FROM



Evaluation of: Actiontec Electronics Inc. WCB6240Q
to

To: FCC CFR 47 Part 15 RF Exposure Requirements

Test Report Serial No.: ATEC09-MPE Rev A

This report supersedes: NONE

Applicant: Actiontec Electronics Inc.
760 N Mary Avenue
Sunnyvale, 94085
USA

Product Function: Gigabit Wireless Router

Issue Date: 16th November 2015

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 \wedge (\text{G (dBi)}/10)$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ²	Calculated Power Density @ 20cm	Minimum Separation Distance (cm)
2400.0 - 2483.5	3.10	2.04	27.74	594.3	9.8	0.24	20.00
5150.0 - 5250.0	7.00	5.01	26.80	478.6	13.8	0.48	20.00
5250.0 - 5350.0	7.00	5.01	22.11	162.6	8.1	0.16	20.00
5470.0 - 5725.0	6.30	4.27	23.33	215.3	8.5	0.18	20.00
5725.0 - 5850.0	6.30	4.27	27.73	592.9	14.2	0.50	20.00

Assessment for simultaneous operation in 2.4 GHz and 5 GHz bands

The Actiontec MWCB6240Q can transmit simultaneously in the 2.4 GHz and 5 GHz bands. The following assessment is based on simultaneous operation in the 2.4 GHz and 5 GHz bands.

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
2400.0 - 2483.5	3.10	2.04	27.74	594.3	9.8	20.00
5725.0 - 5850.0	6.30	4.27	27.73	592.9	14.2	20.00
			EIRP Total			
			3744.1 mW		17.3	20.00

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.



Title: Actiontec Electronics Inc. WCB6240Q
To: FCC CFR 47 Part 15
Serial #: ATEC09-MPE Rev A
Issue Date: 16th November 2015
Page: 4 of 5

Specification
Maximum Permissible Exposure Limits

FCC §1.1310 Limit = $1\text{mW} / \text{cm}^2$ from 1.310 Table 1

RSS-Gen §3.2 In addition to RSS-Gen, the requirements in Radio Standards Specification RSS-102 shall be met.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com