



THIRD ANGLE PROJECTION



IN

[mm]



THIS DRAWING IS THE EXCLUSIVE PROPERTY OF
MAGNETROL INTERNATIONAL
NO USE WHATSOEVER OF THE INFORMATION
CONTAINED HEREON, NOR REPRODUCTION IN
WHOLE OR IN PART MAY BE MADE WITHOUT
THE EXPRESS WRITTEN PERMISSION OF:
MAGNETROL INTERNATIONAL.

REVISIONS

SYM	DESCRIPTION	BY & DATE	CHANGE NO.
XX	XXXX	XX XX-XX-XX	XXXX-XXX

	Magnetrol® DOWNERS GROVE, IL USA	TYPE 4X	FCC ID: LPN-R82 IC: 2331A-R82	THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION	
<input type="checkbox"/>	MODEL NO. SERIAL NO.	INPUT: OUTPUT:		AMB TEMP: MAX.PRESS:	



005-8066-087

	Magnetrol® DOWNERS GROVE, IL USA	THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION	
MODEL NO: SERIAL NO:		INPUT: 12-28 VDC OUTPUT: 4-20mA	
AMB TEMP: MAX PRESSURE:		FCC ID: LPN-R82 IC: 2331A-R82	

005-9730-023

PRELIMINARY

RICK CAMPBELL 06-26-09

MATERIAL	UNLESS OTHERWISE SPECIFIED:	TITLE:		 Magnetrol® 5300 BELMONT ROAD, DOWNERS GROVE ILLINOIS 60515, AREA CODE 630/969-4000	
RAW MATERIAL PART NO.	DIMENSIONS ARE IN INCHES: [] OR mm DIMENSIONS ARE IN MILLIMETERS REMOVE ALL BURRS AND SHARP EDGES MAX ALLOWED .032 [0.81] INSIDE RADI .032 [0.81]R.	TITLE TITLE TITLE			
HEAT FINISH	ALL FINISHES: 125  OR BETTER	DRAWN: NAME	DATE: DATE	SCALE: 1:1	SHEET 1 OF 1
FINISH	TOLERANCES: 2 PL. DECIMAL ±0.015 IN. [0.4mm] 3 PL. DECIMAL ±0.005 IN. [0.2mm] ANGULAR ±2°	CHECKED: NAME	DATE: DATE	SIZE	000-0000
		APPROVED: NAME	DATE: DATE	A	
		PROJECT NO. NUMBER	SKETCH NO. NUMBER		

Drawing Last Modified: Friday, June 26, 2009 8:55:02 AM



Model: XXXXXXXX-XXXXX-XXXX
Model: XXXXXXXX-XX-001
TEMP: -40°C TO 70°C
INPUT: 12-24 VDC
OUTPUT: XXX
CL II DIV 1 GPS E,F,G
(CSA NO GPS E,F) PER DWG 099-5060



IP67



Exo
INTRINSICALLY
SAFE



