

Advanced
Compliance Laboratory

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT

of

RF CORDLESS HEADPHONE TRANSMITTER
MODEL: STF2010
FCC ID: LPV-STF2010

February 25, 2004

This report concerns (check one): Original grant Class II change
Equipment type: LOW POWER TRANSMITTER

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? yes no
If yes, defer until: _____ (date)
Company agrees to notify the Commission by _____ (date)
of the intended date of announcement of the product so that the grant can be
issued on that date.

Transition Rules Request per 15.37? yes no
If no, assumed Part 15, Subpart B for unintentional radiators - the new 47 CFR
[10-1-90 Edition] provision.

Report prepared for: ALFORD INDUSTRIES LTD.
Report prepared by: Advanced Compliance Lab
Report number: 0048-040217-01-TX

NVLAP®

The test result in this report IS supported and covered by the NVLAP accreditation

Table of Contents

Report Cover Page	1
Table of Contents	2
Figures.....	3
1. GENERAL INFORMATION	4
1.1 Verification of Compliance	4
1.2 Equipment Modifications.....	5
1.3 Product Information.....	6
1.4 Test Methodology	6
1.5 Test Facility	6
1.6 Test Equipment	6
1.7 Statement of the Document Use.....	7
2. PRODUCT LABELING.....	8
3. SYSTEM TEST CONFIGURATION.....	9
3.1 Justification	9
3.2 Special Accessories.....	9
3.3 Configuration of Tested System	9
4. SYSTEM BLOCK DIAGRAM/SCHEMATICS.....	13
5. CONDUCTED EMISSION DATA	14
5.1 Test Methods and Conditions	14
5.2 Test Data	14
6. RADIATED EMISSION DATA	17
6.1 Field Strength Calculation	17
6.2 Test Methods and Conditions	17
6.3 Test Data	18
7. PHOTOS OF TESTED EUT	19

Figures

Figure 2.1 FCC ID Label.....	8
Figure 2.2 Location of Label on Back of the EUT	8
Figure 3.1 Cable Interlink Configuration.....	10
Figure 3.2 Radiated Front.....	11
Figure 3.3 Radiated Rear	11
Figure 3.4 Conducted Front.....	12
Figure 3.5 Conducted Rear	12
Figure 4.1 EUT Block Diagram/Schematics	13
Figure 5.1 Line Conducted.....	14
Figure 5.2 Neutral Conducted	15
Figure 7.1 Top View.....	20
Figure 7.2 Bottom View	21
Figure 7.3 Front View.....	22
Figure 7.4 Rear View	23
Figure 7.5 Open View	24
Figure 7.6 PCB Component Side.....	25
Figure 7.7 PCB Foil Side	26
Figure 7.8 Accessory	27

1. GENERAL INFORMATION

1.1 Verification of Compliance

EUT: RF CORDLESS HEADPHONE TRANSMITTER
 Model: STF2010
 Applicant: ALFORD INDUSTRIES LTD.
 Unit 201, 2nd Fl., Park Building, 476 Castle Peak Rd.,
 Kowloon, Hong Kong
 Test Type: FCC Part 15C CERTIFICATION
 Result: PASS
 Tested by: ADVANCED COMPLIANCE LAB
 Test Date: February 25, 2004
 Report Number: 0048-040217-01-TX

The above equipment was tested by Advanced Compliance Laboratory for compliance with the requirement set forth in the FCC rules and regulations Part 15, subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	±2.36	±2.99	±1.83


 Wei Li
 Lab Manager
 Advanced Compliance Laboratory

Date: February 25, 2004

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC ID	CABLE
Product	TRANSMITTER	LPV-STF2010	
Housing	PLASTICS		
Power Supply	DC12V, 100mA		
Operation Freq.	49.86MHz		
Device Type	Continuous Operation		
FM Receiver	Sony SRF-19W		
Receiver	FCC Part 15 Certificate	LPV-SRF2010	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2001 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Somerset, New Jersey. This site has been accepted by FCC to perform measurements under Part 15 or 18 in a letter dated May 19, 1997 (Refer to: 31040/PRV 1300F2). The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Last Cal dd/mm/yy	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3625A00341	EMI Receiver	23/10/03	23/10/04
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	11/03/03	11/03/04
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	09/02/04	09/02/05
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	03/07/03	03/07/04
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	03/07/03	03/07/04
EMCO	3115	4945	Double Ridge Guide Horn Antenna	15/09/03	15/09/04

All Test Equipment Used are Calibrated Traceable to NIST Standards.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

2. PRODUCT LABELING




Figure 2.1 FCC ID Label




Figure 2.2 Location of the Label

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT with maximum length, 30 inches.

When the power is ON, the red LED in front of the EUT is lit.

Testing was performed as EUT was operated at frequency 49.83~49.89MHz continuously. The worst case of EUT operating frequency as 49.86MHz is recorded for final data on Pg. 19.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 and Figure 3.3 illustrate this system, which is tested standing along.




Figure 3.1 Cable Interlink Configuration




Figure 3.2 Radiated Front



Figure 3.3 Radiated Rear



Figure 3.4 Conducted Front



Figure 3.5 Conducted Rear

4. SYSTEM BLOCK DIAGRAM/SCHEMATICS




Figure 4.1 EUT Block Diagram /Schematics

5. CONDUCTED EMISSION DATA

5.1 Test Methods and Conditions

The EUT was under normal operational mode during the conducted emission test. EMI Receiver was scanned from 150KHz to 30MHz with maximum hold mode for maximum emission. Recorded data was sent to the plotter to generate output in linear format. At the input of the spectrum analyzer, a HP transient limiter is inserted for protective purpose. This limiter has a 10 dB attenuation in the range of 150KHZ to 30MHZ. That factor was automatically compensated by the receiver, so the readings are the corrected readings. The reference of the plot is the CISPR 22 Class B limit in Figure 5.1 through Figure 5.2.

Conducted Emission Technical Requirements				
	Class A		Class B	
Frequency Range	Quasi-Peak dBuV	Average dBuV	Quasi-Peak dBuV	Average dBuV
150kHz -0.5MHz	79 (8912uV)	66 (1995uV)	66-56	56-46
0.5MHz-30MHz	73 (4467uV)	60 (1000uV)	---	---
0.5MHz- 5MHz	---	---	56	46
5MHz-30MHz	---	---	60	50

Emissions that have peak values close to the specification limit (if any) are also measured in the quasi-peak mode to determine compliance.

5.2 Test Data

Figure 5.1 through Figure 5.2 show the neutral and line conducted emissions for the standard operation mode.

Six Highest Data for AC Line Conducted Emissions						
Frequency (MHz)	0.1938	0.1973	16.8	16.87	-	-
Peak Reading (dBuV)	40.28	40.54	50.47	51.99	-	-

Test Personnel:

Tester Signature: 

Date: February 25, 2004

Typed/Printed Name: Edward Lee




Figure 5.1 Line Conducted




Figure 5.2 Neutral Conducted

6. RADIATED EMISSION DATA

6.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in $\text{dB}\mu\text{V/m}$

RA: Amplitude of EMI Receiver before correction in $\text{dB}\mu\text{V}$

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

6.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 120KHz, IF bandwidth / 30KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. The highest radiated emissions below 10GHz are recorded.

6.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Testing was performed as EUT was operated at frequency 49.83~49.89MHz continuously. The worst case of EUT operating frequency as 49.86MHz (CH2) is recorded for final data.

Test Personnel:

Tester Signature:

Typed/Printed Name: Edward Lee

Date: February 25, 2004

Radiated Test Data

Worst Case : operating frequency=49.86MHz

Frequency (MHz)	Polarity [H, V] Position	Height (m)	Azimuth (Degree)	Peak ⁽²⁾ Reading (dBmV/m)	Part 15C ⁽¹⁾ 3m Limit (dBmV/m)	Difference from limit (dB)
49.86	H	1.2	180	56.9	80	-23.1
99.72	H	1.2	90	30.2	43.5	-13.3
149.58	H	1.3	270	27.8	43.5	-15.7
199.44	H	1.1	270	27.7	43.5	-15.8
249.3	H	1.1	270	24.4	46	-21.6
299.16	H	1.2	90	28.4	46	-17.6
49.86	V	1.1	225	61.3	80	-18.7
99.72	V	1.3	270	23.2	43.5	-20.3
149.58	V	1.2	180	28.7	43.5	-14.8
199.44	V	1.2	225	26.3	43.5	-17.2
249.3	V	1.3	180	21.3	46	-24.7
299.16	V	1.1	180	24.2	46	-21.8

(1) The limit for emissions within the 49.82-49.90MHz band is 10,000uV/m(80dBuV). Sec. 15.235. The limits for field harmonics are 150uV/m(43.5dBuV) and 200uV/m(46dBuV) , which are defined in Sec. 15.209.

(2) Because each peak reading is less than the FCC average limit, it is not necessary to show the calculated average reading based on the pulse train characteristics.

7. PHOTOS OF TESTED EUT

The following photos show the inside details of the EUT.